

ToLEDo G9 ToLEDo Retro G9 CL 470LM 827 SL2 0029669



Product features

- LED retrofit replacement for halogen G9 mains voltage capsules
- ToLEDo Retro G9 has the same look and feel as halogen design thanks to glass construction body and wide light distribution
- Compact design
- Omni-directional light distribution
- 470lm = 40W halogen G9 lamp
- 90% energy saving
- Non-dimmable
- Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications










PRODUCT OVERVIEW

Product name ToLEDo Retro G9 CL 470LM 827 SL2 Technology LED Watt (Rated) (W) 4.2 Type LED exchangeable Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 Warranty 3 years Luminous flux (Im) Colour temperature (K) 2700 Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) 4.2 Product Voltage (V) Dimmable No Average life (Nominal) (h) Product EAN number LED extro G9 CL 470LM 827 SL2 LED HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 CL 470LM 827 SL2 HOLL WATO LED EXTRO G9 EXTRO G9 FIXED LED EXTRO G9 EXTRO G9 EXTRO G9 FIXED LED EXTRO G9 EXTRO G9 EXTRO G9 FIXED LED EXTRO G9 EXTRO G9 EXTRO G9 EXTRO G9 FIXED LED EXTRO G9 EXT		
Watt (Rated) (W) Type LED exchangeable Cap/Base G9 Fixture rating General application ETIM Class EC001959 Warranty Luminous flux (Im) Colour temperature (K) Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Average life (Nominal) (h) 4.2 LED exchangeable LED exchangeable LED exchangeable Colour Residential & Consumer ETIM Class EC001959 3 years Luminous flux (Im) 470 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Vattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Product name	ToLEDo Retro G9 CL 470LM 827 SL2
Type LED exchangeable Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Technology	LED
Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Watt (Rated) (W)	4.2
Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Туре	LED exchangeable
General application Hospitality, Residential & Consumer ETIM Class EC001959 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Cap/Base	G9
ETIM Class EC001959 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Fixture rating	Open
Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	General application	Hospitality, Residential & Consumer
Luminous flux (Im) 470 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	ETIM Class	EC001959
Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Warranty	3 years
Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Luminous flux (Im)	470
CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Colour temperature (K)	2700
Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable Average life (Nominal) (h) SDCM6 RG1 4.2 Product Voltage (V) 230 No Average life (Nominal) (h) 12000	Light colour	Homelight
Photobiological Risk Group Wattage (W) 4.2 Product Voltage (V) Dimmable No Average life (Nominal) (h) RG1 8.2 Product Voltage (V) 12000	CRI (Ra)	80
Wattage (W) 4.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Colour Variation Initial (SDCM)	SDCM6
Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 12000	Photobiological Risk Group	RG1
Dimmable No Average life (Nominal) (h) 12000	Wattage (W)	4.2
Average life (Nominal) (h) 12000	Product Voltage (V)	230
, worder me (recomment) (iv)	Dimmable	No
Product EAN number 5410288296692	Average life (Nominal) (h)	12000
	Product EAN number	5410288296692



ToLEDo G9 ToLEDo Retro G9 CL 470LM 827 SL2 0029669

PHOTOMETRY



TECHNICAL DRAWINGS

