Equinox *EQUINOX 165 2100 930 DALI BLACK* 2060588

Product features



Equinox is an elegant and innovative luminaire designed using the latest optical technology. It is a high
quality and efficient lighting solution for office, hospitality, and retail environments. It creates
inspirational halo effects regulated by a unique adjustable optic system. It is DALI dimmable downlight
luminaire, Colour rendering index Ra >90, Colour temperature: 3000K Warm White, Class II, Cut out
dimensions: 165mm. Low Glare UGR<19. Finish Jet Black RAL 9005.


















PRODUCT OVERVIEW

Technology Cap/Base N/A Housing Aluminium Mount Ceiling recessed mounting General application Cffice ETIM Class EC001744 Warranty 5 years Fixture luminous flux (Im) Luminaire efficacy (Im/W) Colour temperature (K) 3000 Light colour Varration Initial (SDCM) SDCM3 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) Glare control Photobiological Risk Group RG1 Total power consumption (W) ELED driver constant current Control gear mounting Remote
Housing Aluminium Mount Ceiling recessed mounting General application Office ETIM Class EC001744 Warranty 5 years Fixture luminous flux (Im) 2100 Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Mount Ceiling recessed mounting General application Office ETIM Class EC001744 Warranty 5 years Fixture luminous flux (Im) 2100 Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
General application ETIM Class EC001744 Warranty 5 years Fixture luminous flux (Im) Luminaire efficacy (Im/W) Colour temperature (K) Light colour Warm White CRI (Ra) Colour Variation Initial (SDCM) Colour Consistency (SDCM) Beam Angle (°) Glare control Photobiological Risk Group RG1 Total power consumption (W) Electrical protection Control gear type CO001744 EC001744 Spears EC001744 Spears EC001744 Spears EC001744 Spears
ETIM Class EC001744 Warranty 5 years Fixture luminous flux (Im) 2100 Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control <19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Warranty 5 years Fixture luminous flux (Im) 2100 Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Fixture luminous flux (Im) 2100 Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control <19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Luminaire efficacy (Im/W) 105 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Colour temperature (K) Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) Beam Angle (°) Glare control Photobiological Risk Group RG1 Total power consumption (W) Electrical protection Control gear type LED driver constant current
Light colour Warm White CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
CRI (Ra) 90 Colour Variation Initial (SDCM) SDCM3 Colour Consistency (SDCM) 3 Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Colour Variation Initial (SDCM) Colour Consistency (SDCM) Beam Angle (°) Glare control Photobiological Risk Group Total power consumption (W) Electrical protection Control gear type Colour Consistency (SDCM) SDCM3 SDCM3 SDCM3 Electrical Colour Colour SDCM3 Colour Colour Colour Colour SDCM3 Colour Colou
Colour Consistency (SDCM) Beam Angle (°) Glare control Photobiological Risk Group Total power consumption (W) Electrical protection Class II Control gear type Control gear type Control SDCM) 64 861 861 861 863 864 864 865 865 865 865 865 865
Beam Angle (°) 64 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Photobiological Risk Group RG1 Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Total power consumption (W) 20 Electrical protection Class II Control gear type LED driver constant current
Electrical protection Class II Control gear type LED driver constant current
Control gear type LED driver constant current
Control gear mounting Remote
Dimmable Yes
Dimming method DALI, Switch-dim (mains-rated)
Minimum dimming level (%)
Housing colour RAL 9005 - Jet black
IP rating IP20
IK rating IK02
Product EAN number 5025768605880



Equinox *EQUINOX 165 2100 930 DALI BLACK* **2060588**

PHOTOMETRY



TECHNICAL DRAWINGS

