

INSAVER SLIM 205 Insaver Slim UGR19 205 IP44 2300lm 830 0030304



Product features

Insaver Slim is a ceiling recessed LED downlight (IP44 from the front),Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 20W; 2300lm; 115lm/W; 3000K; UGR <19 with shallow product depth 60mm. Meets TP(a) requirements.




PRODUCT OVERVIEW


Product name	Insaver Slim UGR19 205 IP44 2300lm 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4276918
Warranty	5 years
Fixture luminous flux (Im)	2300
Luminaire efficacy (Im/W)	115
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Beam Angle (°)	NA
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303048

PHOTOMETRY



INSAVER SLIM 205 Insaver Slim UGR19 205 IP44 2300lm 830 0030304





TECHNICAL DRAWINGS

