

START Flex Low Output

START Flex IP20 840 2850lm
0068101



Product features

- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs; 2850lm per 5m (570lm per 1m); 24V; 4000K; CRI80; SDCM 3; Compatible with emergency packs: 0046600, 0046601



PRODUCT OVERVIEW

Product name	START Flex IP20 840 2850lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276595
Warranty	5 years
Fixture luminous flux (lm)	2850
Luminaire efficacy (lm/W)	119
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
IP rating	IP20
IK rating	IK00
Product EAN number	5410288681016



PHOTOMETRY

START Flex Low Output START Flex IP20 840 2850lm 0068101

0.5	1.91 1.66	E07 E090 E090	191 94 92
1.0	3.01 3.37	E07 E090 E090	188 92 91
1.5	4.52 5.05	E07 E090 E090	182 90 89
2.0	6.02 6.74	E07 E090 E090	177 88 87
2.5	7.53 8.42	E07 E090 E090	172 86 85
3.0	9.03 10.11	E07 E090 E090	167 84 83

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 115.8°)
— C90 - C270 (Half beam angle: 112.8°)



TECHNICAL DRAWINGS

