

START eco Downlight Flat 172 1100lm 830 DIM Surface 0053945



Features

- START eco Downlight Flat DIM Surface is an integrated LED surface mounted downlight with a separate, phase dimmable driver and loop in- out box, 12W; 1100Lm; 92Lm/W; 3000K; IP20.


Product Overview

Product name	START eco Downlight Flat 172 1100lm 830 DIM Surface
Technology	LED
Housing	Aluminium
Max load (A)	120
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278199
Fixture luminous flux (lm)	1100
Luminaire efficacy (lm/W)	92
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes

START eco Downlight Flat 172 1100lm 830 DIM Surface 0053945

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Product EAN number	5410288539454
Warranty	3 years
Dimming method	Mains: leading / trailing edge

Photometry



Technical drawings

