Concord

Lytespan LP single circuit - Starter Track - 1m - White **2019502**





Features

• Lytespan LP - Single circuit Starter Track kit, extruded aluminium body, suitable for surface mounting. Supplied with Track Unit, Push-up Live Feed, End Caps, Surface Mounting screws and screw cap covers, (LxWxH) 1000x45x16mm, 0.60kg, White RAL 9016, Class 1, maximum installed load: 1x3840W (1x3680W), fuse: 1x16A, supply cable: 3 x 1.5mm², 240 (230) VAC supply

Product Overview


Product name	Lytespan LP single circuit - Starter Track - 1m - White
Technology	Accessory
Mount	Ceiling surface mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC000101
E-number FI	4276840
E-number SE	7416000
E-number Norway	3213319
Housing colour	White
Product EAN number	5025768195022
Warranty	5 years



Concord

Lytespan LP single circuit - Starter Track - 1m - White **2019502**

Technical drawings



Data table

GENERAL DATA

Product name	Lytespan LP single circuit - Starter Track - 1m - White
Technology	Accessory
Mount	Ceiling surface mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC000101
E-number FI	4276840
E-number SE	7416000
E-number Norway	3213319
Warranty	5 years

OPTICAL DATA

Adjustable chromaticity N



Concord

Lytespan LP single circuit - Starter Track - 1m - White **2019502**

ELECTRICAL DATA

Mains voltage (V)	230V
Control gear required	No
Transformer required	Yes

PHYSICAL DATA

Housing colour	White
Nominal Product Length (mm)	1000
Weight (kg)	0.6

PACKAGING

Single packaging type	Carton
Product EAN number	5025768195022
Packaging single length / height (cm)	126.6
Packaging single width (cm)	5.4
Packaging single depth (cm)	5.4
Units per outer package	1
Packaging outer length / height (cm)	126.6
Packaging outer width (cm)	5.4
Packaging outer depth (cm)	5.4

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No

