



Features

- START Panel is a range of backlit LED panels used in recessed ceilings. Ideal for general indoor applications such as corridors, breakrooms, offices and meeting rooms. Luminaire dimensions are compatible with common ceiling installation, and the shallow design makes it easy to install in low ceilings. 5900Lm; 58W; 102Lm/W; Drive current: 1250mA; Average lifespan: 100.000Hrs; 4000K; CRI 80; Glare control <19; IK03; IP40 (from the front); SDCM<3; Class II; Loop in loop out connector for quick installation.


Product Overview

Product name	START Panel UGR19 1200x600 5900Lm 840 LILO
Technology	LED
Housing	Aluminium, Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
E-number FI	4278396
Fixture luminous flux (lm)	5900
Luminaire efficacy (lm/W)	102
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	58
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No

START Panel UGR19 1200x600 5900Lm 840 LILO 0042202

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288422022
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

