

Equinox

EQUINOX 165 2500 TRIMLESS 940 SSC
2059939



Product features

- Equinox is an elegant and innovative luminaire designed using the latest optical technology. It is a high quality and efficient lighting solution for office, hospitality, and retail environments. It creates inspirational halo effects regulated by a unique adjustable optic system. It is Sylsmart dimmable downlight luminaire, Colour rendering index Ra >90, Colour temperature: 4000K Neutral White, Class II, Cut out dimensions: 165mm. Low Glare UGR<19.









PRODUCT OVERVIEW

| | |
|---------------------------------|-----------------------------------|
| Product name | EQUINOX 165 2500 TRIMLESS 940 SSC |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| General application | Office |
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 2500 |
| Luminaire efficacy (lm/W) | 125 |
| Colour temperature (K) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Colour Consistency (SDCM) | 3 |
| Beam Angle (°) | 64 |
| Glare control | < 19 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 20 |
| Electrical protection | Class II |
| Control gear type | LED driver constant current |
| Control gear mounting | Remote |
| Dimmable | Yes |
| Dimming method | SylSmart SSC |
| Minimum dimming level (%) | 1 |
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5025768599394 |

Equinox EQUINOX 165 2500 TRIMLESS 940 SSC 2059939

PHOTOMETRY



TECHNICAL DRAWINGS

