

Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Product features



Insaver HE Topper is a ceiling recessed LED downlight with integrated PIR sensor with time (up to 8 mins) and daylight lux level settings. Die-cast aluminium body, Non dimmable LED driver, 8W, 800lm, 100lm/W, 4000K, shallow recessed depth of 55mm. Wieland GST compatible















PRODUCT OVERVIEW

Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
Warranty	3 years
Fixture luminous flux (lm)	800
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	64
Total power consumption (W)	8
Electrical protection	Class II
Control gear type	Electronic ballast
Dimming method	N/A
Housing colour	White
IP rating	IP44/20
IK rating	IK02
Product EAN number	8711971339250

DATA TABLE

General data	
Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External




Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925


General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
Warranty	3 years
Optical data	
Fixture luminous flux (lm)	800
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Adjustable chromaticity	N
Beam Angle (°)	64
Clastrical data	
Electrical data	_
Total power consumption (W)	8
Mains voltage (V)	220-240V
Electrical protection	Class II
Control gear type	Electronic ballast
Transformer required	Yes
Dimming method	N/A
Drive current (mA)	350
Glow Wire Test (°C)	650 E
Energy Efficiency Class (A->G) of contained light source	E
•	
Physical data	
Physical data Housing colour	White
Physical data	IP44/20
Physical data Housing colour IP rating IK rating	*******
Physical data Housing colour IP rating IK rating Diffuser finish	IP44/20 IK02 Opal
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material	IP44/20 IK02 Opal PC Polycarbonate
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish	IP44/20 IK02 Opal PC Polycarbonate Other
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm)	IP44/20 IK02 Opal PC Polycarbonate Other 55
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm)	IP44/20 IK02 Opal PC Polycarbonate Other 55
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or	IP44/20 IK02 Opal PC Polycarbonate Other 55 165
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0 14.0
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0 14.0 18711971339257
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0 14.0 18711971339257 12
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0 14.0 18711971339257 12 78.0
Physical data Housing colour IP rating IK rating Diffuser finish Diffuser material Reflector finish Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	IP44/20 IK02 Opal PC Polycarbonate Other 55 165 145 x 145 0.7 Carton 8711971339250 25.0 17.0 14.0 18711971339257 12



Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

PHOTOMETRY





TECHNICAL DRAWINGS

