## Concord

### EQUINOX 165 2500 940 DALI 2059949















#### **Features**

• Equinox is an elegant and innovative luminaire designed using the latest optical technology. It is a high quality and efficient lighting solution for office, hospitality, and retail environments. It creates inspirational halo effects regulated by a unique adjustable optic system. It is DALI dimmable downlight luminaire, Colour rendering index Ra >90, Colour temperature: 4000K Neutral White, Class II, Cut out dimensions: 165mm. Low Glare UGR<19.



#### **Product Overview**


| Product name                    | EQUINOX 165 2500 940 DALI |
|---------------------------------|---------------------------|
| Technology                      | LED                       |
| Cap/Base                        | N/A                       |
| Housing                         | Aluminium                 |
| Mount                           | Ceiling recessed mounting |
| General application             | Office                    |
| ETIM Class                      | EC001744                  |
| Fixture luminous flux (Im)      | 2500                      |
| Luminaire efficacy (Im/W)       | 125                       |
| Colour temperature (K)          | 4000                      |
| Light colour                    | Neutral White             |
| CRI (Ra)                        | 90                        |
| Colour Consistency (SDCM)       | 3                         |
| Colour Variation Initial (SDCM) | 3                         |
| Beam Angle (°)                  | 64                        |
| Glare control                   | < 19                      |
| Photobiological Risk Group      | RG1                       |
| Total power consumption (W)     | 20                        |

## Concord

# EQUINOX 165 2500 940 DALI **2059949**

| Electrical protection     | Class II                         |
|---------------------------|----------------------------------|
| Control gear type         | LED driver constant current      |
| Control gear mounting     | Remote                           |
| Dimmable                  | Yes                              |
| Minimum dimming level (%) | 1                                |
| Housing colour            | RAL 9016 - Traffic white / Bezel |
| IP rating                 | IP20                             |
| IK rating                 | IK02                             |
| Product EAN number        | 5025768599493                    |
| Warranty                  | 5 years                          |
| Dimming method            | DALI, Switch-dim (mains-rated)   |

### **Photometry**



## **Technical drawings**

