


Features

- A slide diffuser made of acrylic thermoplastic (PP). Operating temperature: -15 - 85 [°C]. IK rating: 08. UV resistant. Fire hazard certificate according to IEC 60695-2-11. Compatible with the following profile: Profile semi deep surface 16 B/U4 (0022588). Transparency level 70%.

Product Overview

Product name	COVER B SLIDE 1M OPAL x10
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC002557
Housing colour	Silver
Product EAN number	5410288226590
Warranty	3 years

Technical drawings



Data table

GENERAL DATA

Product name	COVER B SLIDE 1M OPAL x10
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC002557
Warranty	3 years

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	Silver
Diffuser finish	Opal
Nominal Product Length (mm)	1000
Nominal Product Width (mm)	15.2

COVER B SLIDE 1M OPAL x10 0022659

Nominal Product Height (mm)	0.8
Weight (kg)	0.02

PACKAGING

Single packaging type	Carton
Product EAN number	5410288226590
Packaging single length / height (cm)	100.0
Packaging single width (cm)	1.6
Packaging single depth (cm)	2.0
DUN14 (outer)	15410288226597
Units per outer package	700
Packaging outer length / height (cm)	205.0
Packaging outer width (cm)	16.0
Packaging outer depth (cm)	16.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No