

START eco Downlight Flat 226 1700lm 830 DIM Surface
0053946



Features

- START eco Downlight Flat DIM Surface is an integrated LED surface mounted downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1700Lm; 100Lm/W; 3000K; IP20.


Product Overview

Product name	START eco Downlight Flat 226 1700lm 830 DIM Surface
Technology	LED
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278201
Fixture luminous flux (lm)	1700
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)


START eco Downlight Flat 226 1700lm 830 DIM Surface
0053946

Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Product EAN number	5410288539461
Warranty	3 years
Dimming method	Mains: leading / trailing edge

Photometry



Technical drawings



START eco Downlight Flat 226 1700lm 830 DIM Surface 0053946

Data table

GENERAL DATA

Product name	START eco Downlight Flat 226 1700lm 830 DIM Surface
Technology	LED
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278201
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	1700
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 28
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	17
Mains voltage (V)	220-240V
Lamp power factor	0.9

START eco Downlight Flat 226 1700lm 830 DIM Surface 0053946

THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	450
Inrush Current (A)	4.16
Inrush Duration (μ s)	112
Glow Wire Test ($^{\circ}$ C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	67
Max. Luminaires per 13A C Breaker	87
Max. Luminaires per 16A C Breaker	107
Max. Luminaires per 20A C Breaker	133
Max. Luminaires per 10A B Breaker	67
Max. Luminaires per 13A B Breaker	87
Max. Luminaires per 16A B Breaker	107
Max. Luminaires per 20A B Breaker	133

LIFETIME DATA

Lifespan L70 B50	60000
Lifespan L90 B10	23000

PHYSICAL DATA

Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Diffuser finish	Opal
Diffuser material	PS Polystyrene

START eco Downlight Flat 226 1700lm 830 DIM Surface 0053946

Nominal Product Height (mm)	38
Nominal Product Diameter (mm)	226
Cutout Dimensions (W x L in mm or Diameter in mm)	NA
Weight (kg)	0.664

PACKAGING

Single packaging type	Carton
Product EAN number	5410288539461
Packaging single length / height (cm)	24.7
Packaging single width (cm)	4.2
Packaging single depth (cm)	23.0
DUN14 (outer)	15410288539468
Units per outer package	10
Packaging outer length / height (cm)	48.5
Packaging outer width (cm)	23.9
Packaging outer depth (cm)	29.5

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No