

# PRODUCT DATASHEET

## HALOSTAR OVEN 10 W 12 V G4

HALOSTAR® OVEN | Low-voltage halogen lamps with pin base for oven lighting



---

### Areas of application

- Baking ovens

---

### Product benefits

- Two to three times the luminous efficiency of conventional oven lighting
- Optimum halogen content for high temperatures
- Tempered pins for reliable contact at high temperatures
- Suitable for pyrolysis (permissible ambient temperature 450 °C)
- Contains no mercury


## TECHNICAL DATA

### Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	12 V
Power factor $\lambda$	1.00

### Photometrical data

Luminous flux	130 lm
Luminous efficacy	13 lm/W
Light color (designation)	Warm White
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028
UV protection	Yes



### Light technical data

Starting time	0 s
---------------	-----

### Dimensions & Weight

Overall length	33.00 mm
Light center length (LCL)	21,5 mm
Diameter	10,0 mm
Product weight	1.12 g

### Lifespan

Nominal lamp life time	2000 h <sup>1)</sup>
------------------------	----------------------

<sup>1)</sup> Average lifespan at room temperature / higher temperature can reduce the lifespan

### Additional product data

Base (standard designation)	G4
-----------------------------	----

Mercury-free	Yes
Product remark	Heat-resistant up to 300°C / Lamp suitable for oven with high temperature self cleaning (Lamps must be switched off! Max. ambient temperature 450 °C) / For use in shielded luminaires only

### Capabilities

Dimmable	Yes
Burning position	Any

### Certificates & Standards

Energy efficiency class	G
Energy consumption	10.00 kWh/1000h

### Country-specific categorizations

ILCOS	HS GT/C/UB-10-12-G4-10/21,5
Order reference	64418 OVEN 10W

### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G4
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	33.00 mm
Height	10,0 mm
Width	10,0 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.409
Beam angle	SPHERE_360
EPREL ID	714454,714454
Model number	AC35315,AC35315

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300308081	Folding box 1	25 mm x 23 mm x 70 mm	4.12 g	0.04 dm <sup>3</sup>
4050300942339	Shipping box 40	144 mm x 107 mm x 121 mm	196.00 g	1.86 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.