

# PRODUCT DATASHEET HIGH BAY SENSOR

HIGH BAY SENSOR | Motion sensor with switching contact for up to 13 m height, optional use with DALI HIGHBAY ADAPTER



# Areas of application

- Great installation height
- Industry
- Production halls

#### **Product benefits**

- Energy savings up to 35 % (compared to manual switching)

#### **Product features**

- Motion sensor with switching contact
- 3 to 10 m: detection of motion by people
- 3 to 13 m: detection of vehicle movement (e.g. fork lift truck)
- Adjustable switch-off delay: 30 s to 20 min
- Maximum power consumption in stand-by mode: 0.25 W

# **TECHNICAL DATA**

# **Electrical data**

Nominal wattage	0.60 W
Nominal voltage	120277 V
Mains frequency	50/60 Hz

# **Dimensions & Weight**

Length	115.60 mm
Width	115.60 mm
Height	40.00 mm
Diameter	116,0 mm
Product weight	135.00 g

#### Colors & materials

Product color	White

# Temperatures & operating conditions

# **Capabilities**

Dimmable	No
Maximum installation height	13 m
Detection area	18 m <sup>1)</sup>
Detection angle	100 ° 2)
Load contact	5 A
Type of installation	On-top ceiling mounting

<sup>1)</sup> Maximum diameter

# Certificates & Standards

Approval marks – approval	CE
Protection class	П
Type of protection	IP20

# **EQUIPMENT / ACCESSORIES**

- Suitable for up to 15 electronic control gears
- Installation by means of Mounting Adapter possible

<sup>2)</sup> Approximately

# **DOWNLOAD DATA**

	DOWNLOAD DATA
POF	User instruction
POF	User instruction
POF	User instruction
POF	Declarations of conformity
POF	Declarations of conformity
POF	Advertisements
POF	Advertisements
POF	Advertisements

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321410078	Folding box 1	115 mm x 64 mm x 115 mm	169.00 g	0.85 dm³
4008321410085	Shipping box 20	238 mm x 260 mm x 448 mm	3828.00 g	27.72 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **ADDITIONAL CATALOG INFORMATION**



h 4.0 m 6.0 m 8.0 m 10.0 m 13.0 m A 10.0 m 12.0 m 12.0 m 12.0 m -

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.