

## PRODUCT DATASHEET DULUX S 9 W/840

OSRAM DULUX® S | Short CFLni, with 2-pin base for CCG operation



### Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

### Product benefits

- Improved maintenance

### Product features

- Good color rendering index
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



TECHNICAL DATA

Electrical data


Nominal wattage	9 W
Construction wattage	9.10 W
Nominal voltage	60 V
Nominal current	0.17 A

Photometrical data

Luminous flux	600 lm
Luminous efficacy	66 lm/W
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.75



Dimensions & Weight





Overall length	166.50 mm
Length with base excl. base pins/connection	144,00 mm
Diameter	12.00 mm
Tube diameter	12 mm
Product weight	24.1 g

Temperatures & operating conditions

Ambient temperature range	-5...+40 °C
---------------------------	-------------

Lifespan

Lifespan	10000 h
Service life	6500 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.99
Rated lamp survival factor at 8,000 h	0.81
Lifespan B50	10000 h

Additional product data

Base (standard designation)	G23
Mercury content	1.6 mg

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	G
Energy consumption	10.00 kWh/1000h

Country-specific categorizations

ILCOS	FSD-9/840-I-G23
Order reference	DULUX S 9W/840



### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	CFLNI
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G23
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	166.50 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0,380
Chromaticity coordinate y	0,380
Beam angle correspondence	SPHERE_360
EPREL ID	546490
Model number	AC34265

### EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

### DOWNLOAD DATA

Documents and certificates	
	Declarations Of Conformity CE
	Certificates

Photometric and lighting design files



Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300010588	Folding box 1	36 mm x 23 mm x 171 mm	29.75 g	0.14 dm <sup>3</sup>
4050300240947	Shipping box 10	190 mm x 53 mm x 184 mm	410.00 g	1.85 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.