

PRODUCT DATASHEET

DULUX F 24 W/830 2G10

OSRAM DULUX® F | Flat CFLni, 2 tubes, with 4-pin base for ECG/CCG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Extremely low profile

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G10 base
- Good color rendering index




TECHNICAL DATA

Electrical data


| | |
|----------------------|---------|
| Nominal wattage | 24 W |
| Construction wattage | 24.00 W |
| Nominal voltage | 87 V |
| Nominal current | 0.34 A |

Photometrical data

| | |
|---------------------------|--------------------|
| Luminous flux | 1700 lm |
| Luminous efficacy | 71 lm/W |
| Light color (designation) | LUMILUX Warm White |
| Color temperature | 3000 K |
| Color rendering index Ra | ≥80 |
| Light color | 830 |
| Rated LLMF at 2,000 h | 0.90 |
| Rated LLMF at 4,000 h | 0.86 |
| Rated LLMF at 6,000 h | 0.83 |
| Rated LLMF at 8,000 h | 0.81 |
| Rated LLMF at 12,000 h | 0.77 |



Dimensions & Weight



| | |
|---|-----------|
| Overall length | 170.00 mm |
| Length with base excl. base pins/connection | 162 mm |
| Diameter | 16.30 mm |
| Tube diameter | 17,5 mm |
| Product weight | 85.84 g |

Temperatures & operating conditions

| | |
|---------------------------|-------------|
| Ambient temperature range | -5...+40 °C |
|---------------------------|-------------|

Lifespan

| | |
|--|----------------------|
| Lifespan | 13000 h |
| Service life | 9000 h ¹⁾ |
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 | 0.99 |
| Rated lamp survival factor at 6,000 | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.95 |
| Rated lamp survival factor at 12,000 h | 0.64 |
| Lifespan B50 | 13000 h |

¹⁾ With preheat ECG

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | 2G10 |
| Mercury content | 2.5 mg |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 26.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|--------------------------|
| ILCOS | FSD-24/830-E-2G10-90/165 |
| Order reference | DULUX F 24W/830 |

Energy labelling regulation data acc EU 2019/2015

| | |
|--------------------------|-------|
| Lighting technology used | CFLNI |
|--------------------------|-------|

| | |
|---|--------------|
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | 2G10 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 170.00 mm |
| Height | 16.30 mm |
| Width | 16.30 mm |
| Chromaticity coordinate x | 0,440 |
| Chromaticity coordinate y | 0,403 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 546527 |
| Model number | AC34301 |




EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| Documents and certificates | |
|---|-------------------------------|
|  | Declarations Of Conformity CE |
|  | Certificates |
| Photometric and lighting design files | |
|  | Spectral power distribution |

Photometric and lighting design files

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300333601 | Folding box 1 | 27 mm x 86 mm x 184 mm | 111.00 g | 0.43 dm ³ |
| 4050300333618 | Shipping box 10 | 280 mm x 100 mm x 190 mm | 1319.00 g | 5.32 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.