

## PRODUCT DATASHEET HTM 150/230...240

HALOTRONIC®-COMPACT – HTM, HTN | Electronic transformers for low-voltage halogen lamps



### Areas of application

- Effect and accent lighting
- Living rooms
- Object lighting
- Conference rooms
- Restaurants
- Recessed and surface-mounted furniture luminaires
- Shop lighting
- Event rooms

### Product benefits

- Very low power loss thanks to high efficacy
- Strain relief suitable for different cable types (HTM)
- Suitable for space-critical installation thanks to compact functional design
- Extremely compact transformer for highly space-critical installation conditions (HTN)
- Protective operation throughout the entire partial-load range for long lamp life

### Product features

- Line frequency: 50...60 Hz
- RI suppression: to EN 55015 (A1: 2007)/CISPR 15, EN 55022
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Safety: to EN 61347
- Short-circuit protection, overload protection, overtemperature protection: electronically reversible
- Electrical isolation between the primary side and the secondary side
- Dimmable on the leading edge (without HTN) and trailing edge

## TECHNICAL DATA

### Electrical data

Nominal wattage	157.00 W
Nominal voltage	230...240 V
Nominal output voltage	11.4 V / 11.5 V <sup>1)</sup>
Input voltage range	230...240 V
Input voltage AC	207...264 V
Inrush current	1.1 A <sup>2)</sup>
Mains frequency	50/60 Hz <sup>3)</sup>
Power factor $\lambda$	0.99
ECG efficiency	95 % <sup>4)</sup>
Device power loss	7 W <sup>2)</sup>
Max. ECG no. on circuit breaker 10 A (B)	16
Max. ECG no. on circuit breaker 16 A (B)	26
Operating frequency	40 kHz


1) 150 W / 50 W

2) Maximum

3) Approximately

4) At full load

### Dimensions & Weight



Length	153.00 mm
Mounting hole spacing, length	146,0 mm
Width	54.00 mm
Height	36.00 mm
Cable cross-section, input side	1.5 mm <sup>2</sup>
Cable cross-section, output side	2.5 mm <sup>2</sup>
Wire preparation length, input side	12 mm / 8.0 mm <sup>1)</sup>
Wire preparation length, output side	12 mm / 8.0 mm <sup>1)</sup>

Product weight	185.00 g
----------------	----------

1) Cable sheath / Wire

### Colors & materials

Product color	Grey
Casing material	Plastic
Body material	Plastic

### Temperatures & operating conditions

Ambient temperature range	0...+45 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % 1)

1) Maximum 56 days/year at 85 %

### Additional product data

Encapsulated	No
--------------	----

### Capabilities

Dimmable	Yes
Dimming range	0...100 %
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	II
Type of connection, output side	Screw terminal




### Certificates & Standards

Approval marks – approval	VDE / VDE-EMC / E1 approval / EAC
Standards	Acc. to DIN VDE 0875/CISPR 15/EN 55015 / Acc. to EN 61547/EN 61047 / Acc. to IEC 61000-3-2/EN 61000-3-2 / Acc. to IEC 61347 / Acc. to EN 61000-3-2 / Acc. to EN 61547 / Acc. to EN 61047 / Acc. to EN 61347 / Acc. to EN 55015
Protection class	II
Type of protection	IP20

### LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

## DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE
	Certificates

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300581415	Unpacked 1		192.50 g	
4050300581422	Shipping box 10	276 mm x 98 mm x 166 mm	2046.50 g	4.49 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.