

# PRODUCT DATASHEET

## SPC.T CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



---

### Areas of application

- Baking ovens
- Domestic baking ovens




## TECHNICAL DATA

### Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 15 W    |
| Construction wattage | 15.00 W |
| Nominal voltage      | 230 V   |

### Photometrical data

|                          |        |
|--------------------------|--------|
| Luminous flux            | 85 lm  |
| Luminous efficacy        | 5 lm/W |
| Color temperature        | 2700 K |
| Color rendering index Ra | > 99   |
| Light color              | 927    |



### Light technical data

|               |     |
|---------------|-----|
| Starting time | 0 s |
|---------------|-----|

### Dimensions & Weight

|   |          |
|---|----------|
| Overall length                              | 55.00 mm |
| Length with base excl. base pins/connection | 57.00 mm |
| Light center length (LCL)                   | 45,0 mm  |
| Diameter                                    | 26,0 mm  |
| Product weight                              | 7.6 g    |

### Lifespan

|          |        |
|----------|--------|
| Lifespan | 1000 h |
|----------|--------|

### Additional product data

|                             |     |
|-----------------------------|-----|
| Base (standard designation) | E14 |
|-----------------------------|-----|

|              |     |
|--------------|-----|
| Mercury-free | Yes |
|--------------|-----|

### Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

### Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | G               |
| Energy consumption      | 15.00 kWh/1000h |

### Country-specific categorizations

|                 |                     |
|-----------------|---------------------|
| ILCOS           | IBT/C-15-230-E14-26 |
| Order reference | SPC.T26/57 CL 1     |

### Energy labelling regulation data acc EU 2019/2015

|   |              |
|---|--------------|
| Lighting technology used                            | OTHER        |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | E14          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope  | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | No           |
| Length  | 55.00 mm     |
| Height  | 26,0 mm      |
| Width   | 26,0 mm      |
| Chromaticity coordinate x                           | 0.496        |
| Chromaticity coordinate y                           | 0.416        |
| Beam angle correspondence                           | SPHERE_360   |
| EPREL ID  | 714461       |
| Model number  | AC35396      |

### DOWNLOAD DATA

## Photometric and lighting design files

Spectral power distribution

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300310282 | Folding box<br>1             | 61 mm x 23 mm x 27 mm                | 16.00 g      | 0.04 dm <sup>3</sup> |
| 4050300774558 | Bundle<br>10                 | 82 mm x 62 mm x 110 mm               | 123.00 g     | 0.56 dm <sup>3</sup> |
| 4050300961729 | Shipping box<br>100          | 275 mm x 139 mm x 138 mm             | 1430.00 g    | 5.28 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.