SIEMENS

Data sheet

3SU1900-0GB10-0AA0

RJ45 connection: 22 mm, plastic, black



product brand name product designation RJ45 Cat. 5e product type designation RJ45 Cat. 5e product type designation RJ45 Cat. 5e Plastic, black, 22 mm Actuator Outer diameter of the actuating element Plestic, black, 22 mm Actuator Outer diameter of the actuating element Plestic plack RJ45 Cat. 5e Plastic, black, 22 mm Actuator Outer diameter of the actuating element Plestic plack RJ45 Cat. 5e Plastic product Approval Plastic Plastic conditions ACTUAL TOTAL PLAST CATE RJ45 CATE R			
design of the product product type designation product line Actuator Outer diameter of the actuating element 29.45 mm General technical data protection class IP Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation • during storage and transport shape of the installation opening mounting diameter mounting diameter mounting height installation width installation depth Accessories material of accessory material of accessory Approvals Certificates General Product Approval Plastic Declaration of Con-	product brand name	SIRIUS ACT	
product type designation product line Plastic, black, 22 mm Actuator outer diameter of the actuating element General technical data protection class IP Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature during operation during storage and transport -40 +80 °C Installation/ mounting/ dimensions shape of the installation opening mounting diameter mounting height 11.7 mm installation width 29.45 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory black Approvals Certificates General Product Approval	product designation	RJ45 connection	
product line Plastic, black, 22 mm Actuator outer diameter of the actuating element 29.45 mm General technical data protection class IP IP65 Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation 7025 °C • during storage and transport -40 +80 °C Installation/ mounting/ dimensions shape of the installation opening round mounting diameter 22.3 mm mounting diameter 29.45 mm installation width 29.45 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black General Product Approval	design of the product	RJ-45 Cat. 5e	
Actuator outer diameter of the actuating element 29.45 mm General technical data protection class IP IP65 Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation 7025 °C • during storage and transport -40 +80 °C Installation/ mounting/ dimensions shape of the installation opening round mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black General Product Approval	product type designation	3SU1	
outer diameter of the actuating element General technical data protection class IP Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage and transport Installation/ mounting/ dimensions shape of the installation opening mounting diameter mounting height installation width installation depth Accessories material of accessory Approvals Certificates Pediatr Approvals Declaration of Con-	product line	Plastic, black, 22 mm	
General technical data protection class IP Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage and transport Installation/ mounting/ dimensions shape of the installation opening mounting diameter mounting height installation width 29.45 mm installation depth Accessories material of accessory Approvals Certificates Product Approval	Actuator		
protection class IP Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage and transport Installation/ mounting/ dimensions shape of the installation opening mounting diameter mounting height 11.7 mm installation width 29.45 mm installation depth Accessories material of accessory material of accessory Approvals Certificates Plactic Declaration of Con-	outer diameter of the actuating element	29.45 mm	
Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage and transport Installation/ mounting/ dimensions shape of the installation opening mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth Accessories material of accessory plastic color of accessory Approvals Certificates Declaration of Con-	General technical data		
Ambient conditions ambient temperature • during operation • during storage and transport Installation/ mounting/ dimensions shape of the installation opening mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory plastic color of accessory Approvals Certificates Declaration of Con-	protection class IP	IP65	
ambient temperature • during operation • during storage and transport -40 +80 °C Installation/ mounting/ dimensions shape of the installation opening mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth Accessories material of accessory plastic color of accessory Approvals Certificates Declaration of Con-	Substance Prohibitance (Date)	10/01/2014	
 during operation during storage and transport 40 +80 °C Installation/ mounting/ dimensions shape of the installation opening round mounting diameter 22.3 mm mounting height installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory color of accessory black Approvals Certificates Declaration of Con- 	Ambient conditions		
● during storage and transport -40 +80 °C Installation/ mounting/ dimensions shape of the installation opening round mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates Declaration of Con-	ambient temperature		
Installation/ mounting/ dimensions shape of the installation opening mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates Declaration of Con-	 during operation 	7025 °C	
shape of the installation opening mounting diameter 22.3 mm mounting height 11.7 mm installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates Declaration of Con-	 during storage and transport 	-40 +80 °C	
mounting diameter mounting height installation width installation depth Accessories material of accessory color of accessory Approvals Certificates Plastic Declaration of Con-	Installation/ mounting/ dimensions		
mounting height installation width installation depth 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates Declaration of Con-	shape of the installation opening	round	
installation width 29.45 mm installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates Declaration of Con-	mounting diameter	22.3 mm	
installation depth 28.35 mm Accessories material of accessory Plastic color of accessory black Approvals Certificates General Product Approval Declaration of Con-	mounting height	11.7 mm	
Accessories material of accessory color of accessory black Approvals Certificates Declaration of Con-	installation width	29.45 mm	
material of accessory color of accessory black Approvals Certificates Declaration of Con-	installation depth	28.35 mm	
color of accessory black Approvals Certificates Declaration of Con-	Accessories		
Approvals Certificates General Product Approval Declaration of Con-	material of accessory	Plastic	
General Product Approval	color of accessory	black	
General Product Approval	Approvals Certificates		
	General Product Approval		



Confirmation









Declaration of Conformity

Test Certificates

Marine / Shipping



Type Test Certificates/Test Report









Confirmation

Environmental Confirmations

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1900-0GB10-0AA0

Cax online generator


 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1900-0GB10-0AA0}$


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


https://support.industry.siemens.com/cs/ww/en/ps/3SU1900-0GB10-0AA0


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1900-0GB10-0AA0&lang=en









last modified:

4/4/2022