

### product type designation

### product description

### Connecting cable RS232, Sub-D / M12 tilted / M8

Highly flexible communication line (6-core)

SIMATIC RF200/RF300; connecting cable, pre-assembled, between reader and PC (RS232), PUR, trailing, length 5 m 24 V-end w. M8 connector; reader connector angled



### suitability for use

Plug-in cable for connecting an RS 232 reader to a PC

### cable designation

L-YC11Y 6x1x0.25 6x24AWG CM

### wire length

5 m

### electrical data

#### number of electrical connections

3

#### type of electrical connection

submin-D (female, 9 pin, straight) / M12 (female, 8 pin, tilted) / M8 (male, 3 pin, straight)

#### loop resistance per length / maximum

160 mΩ/m

#### insulation resistance coefficient

20 GΩ·m

#### operating voltage

##### • maximum

300 V

### mechanical data

#### number of electrical cores

6

#### design of the shield

Braided shield made of tin-plated copper wires

#### outer diameter

##### • of cable sheath

5.4 mm

#### symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

#### material

##### • of the wire insulation

PVC

##### • of cable sheath

PUR

#### color

##### • of the insulation of data wires

DIN 47100

##### • of cable sheath

Black

#### bending radius

##### • with single bend / minimum permissible

21.6 mm

##### • with multiple bends / minimum permissible

43 mm

##### • with continuous bending

75 mm

#### number of bending cycles

3000000

#### tensile load / maximum

200 N

#### weight per length

45 kg/km

### ambient conditions

#### ambient temperature

##### • during operation

-30 ... +80 °C

##### • during storage

-30 ... +80 °C

##### • during transport

-30 ... +80 °C

##### • during installation

-30 ... +80 °C

#### fire behavior

flame resistant according to IEC 60332-1-2

#### class of burning behaviour / according to EN 13501-6

Eca

chemical resistance	
<ul style="list-style-type: none"> <li>• to mineral oil</li> <li>• to grease</li> </ul>	resistant resistant
radiological resistance / to UV radiation	resistant
<b>product features, product functions, product components / general</b>	
product feature	
<ul style="list-style-type: none"> <li>• halogen-free</li> <li>• silicon-free</li> </ul>	No Yes
<b>standards, specifications, approvals</b>	
UL/ETL listing / 300 V Rating	Yes; CM (only cable without plug)
certificate of suitability	
<ul style="list-style-type: none"> <li>• EAC approval</li> </ul>	Yes
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul>	WG WGB
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAX-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a> <a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

last modified:

8/29/2023 