

product type designation

product description

IE Connecting Cable IE FC RJ45-180 / IE FC RJ45-180

Flexible plug-in cable (8-wire), preferred length, prefabricated with two IE FC RJ45 connectors 4X2

IE connecting cable IE FC RJ45 Plug-180/IE FC RJ45 Plug-180; IE FC flexible GP 4x2 cable Pre-assembled with 2x IE FC RJ45 plug 180 4 x 2; Length 25 m.



suitability for use

For connecting Industrial Ethernet stations with an RJ45 interface (10/100/1000/10000Mbps)

wire length

25 m

electrical data

number of electrical connections

2

attenuation factor per length

- at 10 MHz / maximum 0.089 dB/m
- at 100 MHz / maximum 0.287 dB/m
- at 250 MHz / maximum 0.466 dB/m
- at 300 MHz / maximum 0.514 dB/m
- at 500 MHz / maximum 0.679 dB/m

impedance

- at 1 MHz ... 100 MHz 100 Ω

near-end crosstalk per length

- at 1 MHz ... 100 MHz 0.453 dB/m
- at 1 MHz ... 250 MHz 0.393 dB/m
- at 1 MHz ... 300 MHz 0.381 dB/m
- at 1 MHz ... 500 MHz 0.348 dB/m

transfer impedance per length / at 10 MHz

20 mΩ/m

loop resistance per length / maximum

180 mΩ/m

insulation resistance coefficient

5000 GΩ·m

operating voltage

- RMS value 80 V

NVP value in percent

68 %

mechanical data

number of electrical cores

8

design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires

type of electrical connection / FastConnect

Yes

core diameter

- of AWG24 insulated conductor 0.51 mm

outer diameter

- of inner conductor 0.6 mm
- of the wire insulation 1.05 mm
- of the inner sheath of the cable 6.4 mm
- of cable sheath 8 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

material

<ul style="list-style-type: none"> • of the wire insulation • of the inner sheath of the cable • of cable sheath 	<p>polyethylene (PE) FRNC PVC</p>
<p>color</p> <ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	<p>white-blue/blue, white-orange/orange, white-green/green, white-brown/brown green</p>
<p>bending radius</p> <ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	<p>24 mm 40 mm</p>
<p>tensile load / maximum</p>	<p>100 N</p>
<p>weight per length</p>	<p>86 kg/km</p>
ambient conditions	
<p>ambient temperature</p> <ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	<p>-40 ... +80 °C -40 ... +80 °C -40 ... +80 °C -40 ... +80 °C</p>
<p>fire behavior</p>	<p>flame resistant according to IEC 60332-3-24 (Category C)</p>
<p>chemical resistance</p> <ul style="list-style-type: none"> • to mineral oil • to grease • to water 	<p>oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance conditional resistance</p>
<p>radiological resistance / to UV radiation</p>	<p>resistant</p>
product features, product functions, product components / general	
<p>product feature</p> <ul style="list-style-type: none"> • halogen-free • silicon-free 	<p>No Yes</p>
<p>wire length / for Industrial Ethernet</p> <ul style="list-style-type: none"> • with 100BaseTX • with 1000BaseT • for 10GBase T 	<p>80 m 80 m 70 m</p>
standards, specifications, approvals	
<p>UL/ETL listing / 300 V Rating</p>	<p>Yes; c(ETL)us, CMG, wiring harness</p>
<p>UL/ETL style / 600 V Rating</p>	<p>No</p>
<p>certificate of suitability</p> <ul style="list-style-type: none"> • EAC approval • CE marking • RoHS conformity 	<p>Yes Yes Yes</p>
<p>product conformity</p> <ul style="list-style-type: none"> • ANSI/TIA-EIA 568-B.2 Cat.5e • IEC 61784-5-2-CP 2/2 (Ethernet/IP) 	<p>Yes Yes</p>
<p>standard for structured cabling</p>	<p>Cat6A, class EA</p>
<p>Marine classification association</p> <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	<p>No No No No No No No</p>
<p>reference code</p> <ul style="list-style-type: none"> • according to IEC 81346-2 • according to IEC 81346-2:2019 	<p>WG WGB</p>
further information / internet links	
<p>internet link</p> <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors 	<p>http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP</p>

- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

5/28/2023 