

product type designation



Figure similar

Antenna ANT 8 incl. antenna cable

SIMATIC RF200/RF300 antenna ANT 8 M8x 38 mm, IP67, -25 to +70 °C, with trailing antenna wire, both ends plug-in PUR, UL 758, Length 3 m Consisting of: 1x 6GT23981CF00 1x 6GT23910AH30.

suitability for operation	RF250R
radio frequencies	
transmission frequency / rated value	13.56 MHz
electrical data	
type of electrical connection / of the antenna	M8, 4-pin
design of plug-in connection	male
mechanical data	
material	Stainless steel V2A
color	Silver
tightening torque / of the screw for securing the equipment / maximum	3 N·m
mounting distance	
• relating to metal surfaces / recommended / minimum	0 m
ambient conditions	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP67, front
shock resistance	according to EN 60721-3-7 Class 7M2
shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
design, dimensions and weights	
depth	38 mm
diameter	8 mm
net weight	140 g
fastening method	2 stainless steel cscrew nuts M8 x 1.0 (included)
wire length / of antenna cable	3 m
standards, specifications, approvals	
certificate of suitability	CE, FCC, IC, cULus
certificate of suitability	
• IECEX	No
reference code / according to IEC 81346-2:2019	TFB
accessories	
accessories	Included: 6GT2391-0AH30 (antenna cable)
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

8/29/2023 