



1) Sensing surface



**Basic features**

<b>Application</b>	Round cylinder Pneumatic cylinder with trapezoidal slot
<b>Approval/Conformity</b>	cULus CE WEEE
<b>Basic standard</b>	IEC 60947-5-2
<b>Principle of operation</b>	Magnetic field sensor

**Display/Operation**

<b>Function indicator</b>	yes
---------------------------	-----

**Electrical connection**

<b>Connection</b>	M12x1-Male, 4-pin, A-coded
<b>Polarity reversal protected</b>	yes
<b>Protection against device mix-ups</b>	yes
<b>Short-circuit protection</b>	yes

**Electrical data**

<b>Assured switching field strength Ha</b>	2 kA/m
<b>Hysteresis H max. (% of Hn)</b>	45 %
<b>Load capacitance max. at Ue</b>	1 µF
<b>Magnetic field frequency, interference field</b>	50...60 Hz
<b>Magnetic field strength, interference field</b>	200 kA/m
<b>No-load current I<sub>o</sub> max., undamped</b>	20 mA
<b>Operating voltage U<sub>b</sub></b>	10...30 VDC
<b>Output resistance R<sub>a</sub></b>	3.0 kOhm + D + LED
<b>Rated insulation voltage U<sub>i</sub></b>	75 V DC
<b>Rated operating current I<sub>e</sub></b>	200 mA
<b>Rated operating voltage U<sub>e</sub> DC</b>	24 V
<b>Rated short circuit current</b>	100 A
<b>Rated switch field strength H<sub>n</sub></b>	1.2 kA/m
<b>Residual current I<sub>r</sub> max.</b>	80 µA
<b>Ripple max. (% of U<sub>e</sub>)</b>	15 %
<b>Switching frequency</b>	10 Hz
<b>Turn-off delay t<sub>off</sub> max.</b>	50 ms
<b>Turn-on delay t<sub>on</sub> max.</b>	50 ms
<b>Utilization category</b>	DC -13
<b>Voltage drop static max.</b>	4 V

Magnetic Sensors  
**BMF 32M-PS-W-2-S4**  
Order Code: BMF008A

**BALLUFF**

**Environmental conditions**

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
ESD	2A (4 kV)
Emission	Group 1, Class B
Magnetic field immune	weld-immune (AC)
Protection degree	IP67

**Material**

Housing material	Aluminum
Material sensing surface	PU

**Remarks**

EMC: Surge resistance  
External protection circuit is required. Document 825345, Section 2.  
The sensor is functional again after the overload has been eliminated.

**Mechanical data**

Dimension	25 x 11.9 x 26 mm
Mounting	with tube cuff

**Output/Interface**

Switching output	PNP normally open (NO)
------------------	------------------------

**Range/Distance**

Temp. drift max. (% of Hn)	0.3 %
----------------------------	-------

**Connector Drawings**



**Wiring Diagrams**

