

### ORIENT CCT SELECTABLE BOLLARD 20W, IP65



## PRODUCT INFORMATION DOCUMENT

### FEATURES

- LED replacement for 120W linear halogen fittings
- Modern and attractive design using high quality materials and technologies
- Complete with switch allowing to select 3000K and 4000K colour temperature
- Removable mounting base providing template for drilling anchor points
- Wide operating ambient temperature range of -25°C to +40°C
- Suitable for switching by PIR, Microwave or Photocell sensors

### CONSTRUCTION

- Die cast aluminium housing with PMMA diffuser
- High quality powder coating process for high corrosion resistance
- Stainless steel fixing screws

--	--	--	--	--	--	--	--	--

Product Code:	ROR20X063-04	ROR20X098-04
Comparable to:	120W linear halogen	120W linear halogen
Total Power (W):	20.1	20.1
Power Factor:	0.95	0.95
Total Light Output (lm):	2020	2020
Total Emergency Light Output (lm):	NA	NA
Efficacy (lm/cctW):	101	101
Lux at 1m (lux):	185	185
Emergency Lux at 1m (lux):	NA	NA
CCT (K):	3000/4000	3000/4000
CRI:	80	80
IP:	65	65
Operation Temperature (°C):	-25 ≤ Ta ≤ +40	-25 ≤ Ta ≤ +40
Inrush Current:	4.8A/3.2us	4.8A/3.2us
RG Value:	0	0
SDCM:	6	6
P <sub>ST</sub> LM:	NA	NA
SVM:	NA	NA
Energy Class:	D	D
Rated Life to L70B50 (Hrs):	50000	50000
Dimensions ØxH (mm):	160x630	160x980
Weight (kg):	3.6	4.9

Separate Control Gear Information		
Type of Light Source:	LED	LED
Full Load Efficiency (%):	88	88
P <sub>NET</sub> (W):	NA	NA
Dimensions (mm):	120x50x31	120x50x31


Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

**PLEASE NOTE:** INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

### ORIENT CCT SELECTABLE BOLLARD 20W, IP65

Cone Illuminance Diagram



Polar Intensity Diagram





Diagram for ROR20X063-04 in 3000K. Other diagrams available on request

Diagram for ROR20X063-04 in 3000K. Other diagrams available on request

Dimension Diagram



	D	H
ROR20X063	160mm	630mm
ROR20X098	160mm	980mm

Sensor Data

Time Off Delay:	NA
Illuminance Switching Range:	NA
Sensitivity Range (%):	NA
Mounting Height (max):	NA
Detection Zone Diameter (max):	NA

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000  
UK: TEL: 0800 973 220  
AUS: TEL: +61 7 3890 5444  
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM  
WEB: ROBUS.COM  
WEB: ROBUS.COM.AU  
WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA