

Big WHITE®

'22

SLV LIGHTING CATALOGUE

OUR PROMISE.



FAST AND
RELIABLE DELIVERY



5 YEAR
WARRANTY*



PRICE AND PERFORMANCE
IN PERFECT HARMONY



GERMAN
ENGINEERING



WE ARE YOUR WAREHOUSE
98% AVAILABILITY

OFFICE

SLV LIGHTING UK LTD
Unit E Chiltern Park,
Boscombe Road
Dunstable
LU5 4LT

Telephone number:
+ 44 (0)203 968 11 00

Fax number:
+ 44 (0)203 968 11 09

sales@uk.slv.com
slv.com

SLV has the right to adapt the relevant price list in line with changes in market conditions, in the event of substantial changes in procurement costs or similar circumstances.

*Please note the warranty conditions under [slv.com](https://www.slv.com) → Service → Downloads → Warranty Conditions

BIG WHITE®

Whether printed or digital – with us, the choice is yours.

SLV.COM – EXPERIENCE LIGHT ONLINE

On our online platform you will find the complete SLV range with all product details, descriptions, availability, and much more. Our filter makes looking for the perfect product easy. Useful design files, 3D data, configurators and calculation tools such as FastCalc by DIAL are there to help you create your perfect lighting design. Always in line with the times, with news from the world of lighting. Visit slv.com



THE DIGITAL BIG WHITE® CATALOG – YOUR FLEXIBLE COMPANION



Our digital catalog is a tool that will make your customer visits more efficient than ever: as well as having a digital copy of our main catalog to hand, you also get additional services offering a quick insight into the specific SLV products you want to see.

SLV EXPERIENCE LIGHT APP: NOW YOU CAN EXPERIENCE REAL INSPIRATION VIRTUALLY TOO.

Understand in advance what SLV lights can do for customers.

With our augmented reality app, SLV EXPERIENCE LIGHT, you can always find the perfect lighting – on the spot, indoors and outdoors. The app is extremely easy to use, making it an important consultation tool for electrical installers and lighting designers. Because where the customer's imagination ends, the possibilities of our app begin: give a virtual presentation of how our lights will work in their future location.



Download the SLV EXPERIENCE LIGHT app for free.

Download our free augmented reality app from the iTunes Apple Store or Google Play Store onto your smartphone or tablet.



SLV – EXPERIENCE LIGHT EVEN BETTER.

Light illuminates, sets the scene, and influences us in all areas. Because digitalization, sustainability and quality are more in focus than ever before, SLV is always reinventing its appeal.

EXPERIENCE LIGHT.

SLV's goal is to make light an experience in all its facets: with products that are progressive, resource-saving and high-quality. We also provide a first-class service, reliable delivery, and easy installation to significantly reduce expenses in terms of time, costs, and effort.



**TRUST SUSTAINABILITY.**

SLV develops its lights in Germany and guarantees satisfaction through consistent quality assurance. In addition, we have a strong focus on sustainability, which we consider holistically across all core processes.

**CERTIFIED QUALITY.**

With its German engineering approach, SLV develops lights and guarantees satisfaction through consistent quality assurance. SLV luminaires are put through their paces in our own laboratories, which are located at SLV's German headquarters in Übach-Palenberg (North Rhine-Westphalia) and in Shanghai, Asia. This means that we don't just offer quality, we guarantee it: for 5 years. We also focus on sustainability, which we consider holistically across all core processes.


As you can see: you can rely on the SLV brand.

**FUTURE-PROOF LIGHTING.**

Constant product development and finding new solutions are what motivate us at SLV. Whether we are developing digital technologies or setting new standards, intelligently networking devices or offering system solutions: SLV stands for modern and future-proof lighting.

**RELIABLE DELIVERY.**

With a constant product availability of 98%, we can supply all customers reliably and quickly from our German logistics centre.

**BOUND BY SUCCESS.**

Success is also always the result of close cooperation - with you as a customer and with strong partners both inside and outside the lighting industry, upon whom SLV can rely.

GOOD FOR THE ENVIRONMENT. GOOD FOR YOU.

Every day, we strive towards our aim of achieving sustainable results across the entire value chain.


With various measures in the areas of production, packaging, logistics, and more.

THE FUTURE IS NOW.

At SLV we focus on avoiding, reducing, reusing and recycling: we design products and packaging in an environmentally friendly way, reduce hidden waste, cut emissions and optimize logistics processes. Today, we are already consistently focusing on sustainability in the development of lighting technology.

SUSTAINABLE PACKAGING SOLUTIONS.

Thanks to packaging solutions on demand (On Demand Packaging), we can save time, packaging material and costs. By using customized boxes from Packsize NOW, we can significantly reduce the amount of corrugated cardboard and filling material used. Our lower transport volume also results in fewer CO₂ emissions during shipping. To this end, we rely on recycled material, limit ourselves to two printing inks, and try to avoid adhesives and glossy varnishes as much as possible.



A LARGE CATALOG WITH A SMALL CO₂-FOOTPRINT.

In addition to our classic DIN A4 catalog size, we offer the BIG WHITE® in a handy DIN A5 format as well as digitally. This helps us to conserve valuable resources but also reduce CO₂ emissions and costs. Our printed BIG WHITE® is FSC Mix certified – in addition to using 100% recycled paper, we also only use paper that is obtained from sustainably managed forests. This allows us to make our catalog production sustainable and environmentally friendly.



**PRODUCTS WITH RECYCLED SECONDARY RESOURCES.**

To preserve resources, we successively replace primary raw materials with secondary raw materials whenever technically possible. Our SAMRINA ground spike light, for example, is partly made using a plastic that contains up to 35% recycled raw materials. The proportion of recycled material in the total mass of the light is 17%. At the same time, SAMRINA impresses customers with the quality and durability they expect from SLV. To protect the environment, we ensure that all our products are easy to recycle at the end of their lifespan.

1004757 592

NEW ENERGY EFFICIENCY CLASSES.

As of September 2021, new rules for the environmentally compatible design (ecodesign) and energy consumption labeling (product information) of energy-relevant products apply. These rules affect lightsources such as LED modules or lamps with pedestals.

NO NEW LABEL FOR LIGHTS.

The implementation of the new regulations for lighting is governed by EU regulations 2019/2015 or 2021/340 (product information) and 2019/2020 or 2021/341 (product design), which replace and supplement the previous requirements. These rules affect lightsources such as lamps with pedestals and LED modules. Lights with integrated non-destructively removable lightbulbs, on the other hand, are regarded as surrounding products and do not receive their own energy label – but the energy class of the integrated lightbulb must be stated in the instructions.

A FUTURE-PROOF SCALE.

The new EU regulation provides for a rescaling of the energy classes. The future energy label scale ranges from A to G and is not related to the previous scale. To ensure that the classification remains sustainable, the legislator has designed the requirements in such a way that the higher classes can only be reached in the future. This means, to give an example, that even a lightbulb with an energy class E has good efficiency.

NEW ENERGY LABELS.

The design of the new energy labels has also changed. To ensure that the energy label can be used in all EU member states, the linguistic components have been removed. The label also features a QR code that refers to a product's corresponding entry in the publicly accessible part of the European product database for energy labelling (EPREL database).

COMMITTED TO EFFICIENCY.

As a company, SLV ensures that all products comply with the new regulations. Stationary traders with a stock of affected products acquired before September 1, 2021 will have a transitional period of 18 months during which the old energy labels may continue to be used.

1004772 443






DO YOU KNOW..?

How to understand the new energy efficiency classes.

Our example – the SLV One 40 Track:



The product continues to show good efficiency: only the classification itself changes. This ensures that the energy efficiency classes remain valid in the long term.

You can find more information about the light in question by using the QR code on the energy label.


Simply scan it!

NEW PRODUCT PRESENTATION.

We have thoroughly revised our product presentation – so that you can offer your customers optimum advice. Clear, detailed, and customer-orientated.

A LOOK AT THE ESSENTIALS

New icons and symbols summarize important technical details for you.



- Integrated LED technology
- Luminous flux
- Colour temperature
- Colour rendering index
- Light with lamp holder
- Lamp
- Maximum wattage

KNOW HOW LONG IT LASTS

All information is marked with new symbols.



PRODUCT DETAILS

All technical product information for the lighting professional.



LAMP DETAILS

Always find the matching lamp



RECOMMENDED LAMP

Complete your pedestal lamp and order the matching lamp at the same time.



RECOMMENDED ACCESSORIES

Expand the function of your light and complement it with matching accessories.



EEC INFORMATION

The energy efficiency of all lightbulbs and variants at a glance.

1001309, 1001310	3700lm 3000K	




WORKLIGHT
FL

NEW





7600lm
4000K
CRI 80










IP 20 IK02 80° 110° 19 L80B10




250

200-240V ~50/60Hz | 2000mA
Total wattage: 79W
Material: aluminium

- Euro plug



		A → G
Up/Down	3800lm 4000K	A B C D E

Options	Prod. no.	EUR
Up: 3800lm 4000K CRI80 Down: 3800lm 4000K CRI80 ■ black	1005390	■

Better readability

Our "NEW", "NEW VARIANT" and "FOLLOWER" products are now even easier to recognize.

At a glance:


The most important information, summarized for your customers.

For the lighting professional

Technical details, accessories, and suitable lamps.

New EEC information

Sustainable and economical LED lighting. For the future, too.





NUMINOS®

014 - 095

N

Lighting system.....	014 - 027
Downlights.....	028 - 061
High-voltage 3-phase track systems.....	062 - 071
Wall and ceiling lights.....	072 - 073
Ceiling lights.....	074 - 087
Pendant lights.....	088 - 095

INDOOR

096 - 507



Table and floor lamps.....	096 - 113
Pendant lights.....	114 - 179
Wall lights.....	180 - 245
Ceiling lights.....	246 - 289
Wall and ceiling lights.....	290 - 341



Recessed lights.....	342 - 423
----------------------	-----------



High-voltage 3-phase track systems.....	424 - 459
High-voltage single-phase track systems.....	460 - 485
High-voltage Easytec® II track system.....	486 - 495
Low-voltage cable system.....	496 - 507

OUTDOOR

508 - 731



Mobile lights and floor lights.....	508 - 583
Spotlights.....	584 - 603
Wall and ceiling lights.....	604 - 693



Recessed wall lights.....	694 - 703
Recessed ceiling lights.....	704 - 713
Recessed floor lights.....	714 - 731

PROFILE SOLUTIONS

732 - 749



LED STRIPS

750 - 763



CONNECTED LIGHTING

764 - 787



DALI – Professionally connected lighting.....	764 - 777
ZIGBEE® 3.0 – The smart wireless system.....	778 - 787

ACCESSORIES

788 - 807

A+

LAMPS

808 - 819



LUMINAIRE FAMILIES, INDEX AND REFERENCES

820 - 866



SLV's luminaire families.....	820 - 835
Numerical.....	838 - 851
Alphabetical.....	855 - 859
References.....	860 - 866

You can find more lights and variants at www.slv.com

All prices are recommended retail prices (RRP) and listed without VAT.





THE PERFECT
LIGHTING
SOLUTION FOR
EVERY CONTEXT.

NUMINOS®

ONE LIGHTING SYSTEM – A THOUSAND POSSIBILITIES.

THE FREELY CONFIGURABLE LIGHTING SYSTEM THAT
CASTS A GOOD LIGHT ON EVERY SETTING.

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers. For every need. For maximum variety with minimum effort.

NUMINOS®

HIGH-PERFORMANCE LED MODULE
WITH BRILLIANT COLOUR RENDERING

WIDE SELECTION OF DOWNLIGHTS
AND SPOTS FOR A HARMONIOUS
DESIGN CONCEPT.



MORE FREEDOM WITH SYSTEM.

WHATEVER YOU'RE PLANNING –
THE NUMINOS® LIGHTING SYSTEM
CREATES SPACE FOR NEW IDEAS.



The NUMINOS® lighting system
offers constant lighting characte-
ristics and modern design for all
uses:

- for office spaces
- shops & boutiques
- hotels & gastronomy
- at home
- and much more

From hotels and offices to commercial or private rooms. From application to technology to detailed design: one great feature is that the modular downlights and spotlights can be configured exactly as required, depending on the design or space in question. And the more multifaceted your project is, the more you benefit from the NUMINOS® lighting system.

Lighting that
won't dominate.



NUMINOS®
GIMBLE M, DL
Product no.
1005945

NUMINOS®
Move S, DL
Product no.
1005340

**Highlights that
shine down.**



NUMINOS® XL, CL
Product no.
1005767

**Free for
all dimensions.**



NUMINOS®
ZOOM M, 3-circuit
Product no.
1006116

**Perfect for
suspending, and
height-adjustable.**



NUMINOS® XL, PD
Product no.
1005783


UNPARALLELED VARIETY, SHARED HIGHLIGHTS.

Choose between:

- Downlight or spotlight
- Various sizes and diameters
- Housing colours (black/white)
- Reflector variants
- Pivoting or rigid versions
- Performance classes

The different variants feature:

- High-performance LED module with the light colours 2700K/3000K/4000K
- Colour quality CRI>90
- Glare rating UGR min. <22



DOWNLIGHTS

Available in seven versions (68-75mm to 176-186mm) with high-performance LED module in three light colours (2700K, 3000K, 4000K) and glare ratings (UGR 16, 19, 22)

Selectable reflectors with half beam angles of 20°, 40° or 55°.

Various effect filters (frosted / prismatic / elliptical / honeycomb) available as accessories.

The decorative ring can be selected in white, black or chrome as a visible border.

NUMINOS® downlights are available as fixed or swivelling versions (4x fixed and 3x swivelling and rotating).



XS S M L XL

Accessories with system:

You can easily add an optional driver (on/off, phase dimming, DALI) and suitable diffusers using the colour coding system.

You can find drivers and diffusers for the SLV NUMINOS® Downlight system on pages 58-61.

A WELL THOUGHT-OUT LIGHTING SYSTEM DOWN TO THE LAST DETAIL.

Thanks to the wide selection of modules, there is a suitable solution to meet every need. Fixed configuration. Fast and safe to install.



SPOTLIGHTS

Available in three housing sizes (65x155mm, 85x175mm, 100x203mm) with high-power LED module in three light colours (2700K, 3000K, 4000K)

Thanks to the built-in LED driver (phase dimming, DALI), all spotlights are suitable for direct connection to 230V mains voltage.

Selectable lenses with half beam angles of 24°, 36° or 60°.

NUMINOS® spotlights are available as swivelling or fixed ceiling spots, pendant lights and as spots for 3-circuit track systems.



Easy to install.

Because efficiency always pays off, SLV lights are easy, quick and safe to install. Connection via mounting plate, rail system, quick-release coupling, spring clips and colour-coded drivers for downlights offers a key advantage: it saves you time and effort – and therefore costs.



A LIGHTING SYSTEM. FOR EVERY SCENARIO.

For success in all conditions, you need team players who shine with individual strengths. Discover the applications for which the individual NUMINOS® lights are particularly well suited.



**Transform objects into
eye-catching features**



NUMINOS®
GIMBLE XS, DL
Product no.
1005817

Downlights.

Unobtrusive, modern and space-saving lighting that directs the gaze to particular objects or the room in general: the downlights in the NUMINOS® lighting system can be used variably in commercial and private settings.



**For elegant
illumination of
lounge areas.**



NUMINOS®
GIMBLE XS, DL
Product no.
1005843

For entrance areas
that really welcome
guests in.



NUMINOS® XS
DL
Product no.
1005520



Guide the way
in hallways.



NUMINOS®
MOVE XS, DL
Product no.
1005584


Individually designed illumination.

Thanks to the large selection of reflectors on offer, the NUMINOS® lighting system is suitable for accent lighting as well as for the illumination of products and sales areas.

To create accents
in sales areas.




NUMINOS®
GIMBLE M, DL
Product no.
1005953



For the perfect
presentation of
objects.



NUMINOS®
GIMBLE S, DL
Product no.
1005899



For the flexible illumination of spaces of all sizes.



NUMINOS® ZOOM M
3Ph., PHASE
Product no.
1006108

Products skilfully showcased.



NUMINOS® ZOOM M
3-circuit., DALI
Product no.
1006119

Spotlights.

Shops and boutiques as well as restaurants, bars, museums, studios, and surgeries – every space depends on expert accent lighting. Spotlights can be used to illuminate larger spaces as well as for targeted lighting.






To create
an appetising
atmosphere.



NUMINOS® M
PD, PHASE
Product no.
1004247
combined with
decorative ring
Product no.
1006168



For a cosier home.



NUMINOS® S, PD, DALI
Prod. no.: 1004439
combined with decorative ring
Prod. no.: 1006167



SYSTEMATICALLY ACHIEVING YOUR OBJECTIVE.

With the NUMINOS® Online Configurator.

Our configurator really is this easy:

the first question is: downlight or spotlight?
You can then choose between preconfigured
and additionally customisable application
scenarios or free configuration.

If you are still unsure about the selection
of attributes, don't worry: we offer suitable
explanations for each selected configuration.

This way to the NUMINOS® Configurator:


www.numinos.SLV.com

Just three steps to reach your goal:

- 1 **TECHNICAL CONFIGURATION**
↓
- 2 **OPTICAL CONFIGURATION**
↓
- 3 **VISUAL REPRESENTATION & COMPLETION**

Reach your goal here and now – configure your lighting with the BIG WHITE® catalogue.


Put together your dream lighting over the next pages. The following product overviews will help you reach your goal just as easily: scroll to your desired light type, follow the columns from left to right and make your individual selection. At the end, you will find the relevant item number for direct ordering.



STEP 1

SPTLIGHT OR DOWNLIGHT?


Choose the most suitable light type for your needs. The diameter (downlights) or housing size (spotlights) are coupled with the total wattage.



STEP 2

TECHNICAL CONFIGURATION & SELECTION OF DETAILS

Column by column, you can select optical and technical attributes such as housing colour or decorative colours, the colour temperature, half beam angle and more.




STEP 3

PRODUCT

Get a visual impression of your fully configured light and order it right away using the relevant item number.

STILL UNSURE ABOUT SOMETHING?



Scan me to view a video that shows how to configure NUMINOS® lights.

In addition to the familiar catalog icons, you will find the following icons in this chapter:



Glare rating



Colour temperature



Beam angle



Lumen



Controller

NUMINOS® XS

NEW VARIANT


DL



XS


Product details:

200mA

Power consumption: 7W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug

Driver not included

Leaf springs are included with the product and can be replaced.

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	640lm	20°	16	1005499	
		620lm	40°	22	1005502	
		640lm	55°	25	1005505	
	3000 K	700lm	20°	16	1005517	
		670 lm	40°	22	1005520	
		690lm	55°	25	1005523	
	4000 K	720lm	20°	16	1005535	
		700lm	40°	22	1005538	
		710lm	55°	25	1005541	
	2700 K	670 lm	20°	16	1005500	
		650lm	40°	22	1005503	
		670 lm	55°	25	1005506	
	3000 K	730lm	20°	16	1005518	
		700lm	40°	22	1005521	
		720lm	55°	25	1005524	
	4000 K	750lm	20°	16	1005536	
		730lm	40°	22	1005539	
		740lm	55°	25	1005542	
	2700 K	670 lm	20°	16	1005501	
		650lm	40°	22	1005504	
		670 lm	55°	25	1005507	
	3000 K	730lm	20°	16	1005519	
		700lm	40°	22	1005522	
		720lm	55°	25	1005525	
	4000 K	750lm	20°	16	1005537	
		730lm	40°	22	1005540	
		740lm	55°	25	1005543	
	2700 K	640lm	20°	16	1005508	
		620lm	40°	22	1005511	
		640lm	55°	25	1005514	
	3000 K	700lm	20°	16	1005526	
		670 lm	40°	22	1005529	
		690lm	55°	25	1005532	
	4000 K	720lm	20°	16	1005544	
		700lm	40°	22	1005547	
		710lm	55°	25	1005550	
	2700 K	670 lm	20°	16	1005509	
		650lm	40°	22	1005512	
		670 lm	55°	25	1005515	
	3000 K	730lm	20°	16	1005527	
		700lm	40°	22	1005530	
		720lm	55°	25	1005533	
	4000 K	750lm	20°	16	1005545	
		730lm	40°	22	1005548	
		740lm	55°	25	1005551	
	2700 K	670 lm	20°	16	1005510	
		650lm	40°	22	1005513	
		670 lm	55°	25	1005516	
	3000 K	730lm	20°	16	1005528	
		700lm	40°	22	1005531	
		720lm	55°	25	1005534	
	4000 K	750lm	20°	16	1005546	
		730lm	40°	22	1005549	
		740lm	55°	25	1005552	

NUMINOS® S



DL

S





Product details:

250mA

Power consumption: 8.6W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 6.8 cm D: 5.5 cm



Tip:

Low-voltage plug

Driver not included

Leaf springs are included with the product and can be replaced.

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

A ↑ G ↓ F	2700 K	670 lm	20°	19	1003769	
		670 lm	40°	18,5	1003772	
		670 lm	55°	22	1003775	
A ↑ G ↓ E	3000 K	690lm	20°	19	1003793	
		690lm	40°	19	1003796	
		690lm	55°	22	1003799	
A ↑ G ↓ E	4000 K	730lm	20°	19	1003817	
		730lm	40°	19	1003820	
		730lm	55°	22	1003823	
A ↑ G ↓ F	2700 K	720lm	20°	18,5	1003770	
		720lm	40°	19	1003773	
		720lm	55°	22	1003776	
A ↑ G ↓ E	3000 K	730lm	20°	19	1003794	
		730lm	40°	19	1003797	
		730lm	55°	22	1003800	
A ↑ G ↓ E	4000 K	790lm	20°	19	1003818	
		790lm	40°	19	1003821	
		790lm	55°	22	1003824	
A ↑ G ↓ F	2700 K	690lm	20°	19	1003771	
		690lm	40°	19	1003774	
		690lm	55°	22	1003777	
A ↑ G ↓ E	3000 K	700lm	20°	19	1003795	
		700lm	40°	19	1003798	
		700lm	55°	19	1003801	
A ↑ G ↓ E	4000 K	750lm	20°	19	1003819	
		750lm	40°	19	1003822	
		750lm	55°	22	1003825	
A ↑ G ↓ F	2700 K	670 lm	20°	19	1003781	
		670 lm	40°	19	1003784	
		670 lm	55°	22	1003787	
A ↑ G ↓ E	3000 K	690lm	20°	19	1003805	
		690lm	40°	19	1003808	
		690lm	55°	22	1003811	
A ↑ G ↓ E	4000 K	730lm	20°	19	1003829	
		730lm	40°	19	1003832	
		730lm	55°	22	1003835	
A ↑ G ↓ F	2700 K	720lm	20°	18,5	1003782	
		720lm	40°	19	1003785	
		720lm	55°	22	1003788	
A ↑ G ↓ E	3000 K	730lm	20°	19	1003806	
		730lm	40°	19	1003809	
		730lm	55°	22	1003812	
A ↑ G ↓ E	4000 K	790lm	20°	19	1003830	
		790lm	40°	19	1003833	
		790lm	55°	22	1003836	
A ↑ G ↓ F	2700 K	690lm	20°	19	1003783	
		690lm	40°	19	1003786	
		690lm	55°	22	1003789	
A ↑ G ↓ E	3000 K	700lm	20°	19	1003807	
		700lm	40°	19	1003810	
		700lm	55°	22	1003813	
A ↑ G ↓ E	4000 K	750lm	20°	19	1003831	
		750lm	40°	19	1003834	
		750lm	55°	22	1003837	

NUMINOS® M



DL

M





Product details:

500mA

Power consumption: 17.5W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 9 cm D: 7.5 cm



Tip:

Low-voltage plug

Driver not included

Leaf springs are included with the product and can be replaced.

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black



white



chrome



black



white



white



chrome



PROD. NO.

		2700 K	1460lm	20°	19	1003841	
			1460lm	40°	22	1003844	
			1460lm	55°	22	1003847	
		3000 K	1500lm	20°	19	1003865	
			1500lm	40°	22	1003868	
			1500lm	55°	22	1003871	
		4000 K	1600lm	20°	19	1003889	
			1600lm	40°	22	1003892	
			1600lm	55°	22	1003895	
		2700 K	1600lm	20°	22	1003842	
			1600lm	40°	19,4	1003845	
			1600lm	55°	22	1003848	
		3000 K	1600lm	20°	22	1003866	
			1600lm	40°	22	1003869	
			1600lm	55°	22	1003872	
		4000 K	1750lm	20°	22	1003890	
			1750lm	40°	22	1003893	
			1750lm	55°	22	1003896	
		2700 K	1550lm	20°	19	1003843	
			1550lm	40°	19	1003846	
			1550lm	55°	19	1003849	
		3000 K	1550lm	20°	19	1003867	
			1550lm	40°	19	1003870	
			1550lm	55°	19	1003873	
		4000 K	1660lm	20°	19	1003891	
			1660lm	40°	19	1003894	
			1660lm	55°	19	1003897	
		2700 K	1460lm	20°	19	1003853	
			1460lm	40°	22	1003856	
			1460lm	55°	22	1003859	
		3000 K	1500lm	20°	19	1003877	
			1500lm	40°	22	1003880	
			1500lm	55°	22	1003883	
		4000 K	1600lm	20°	19	1003901	
			1600lm	40°	22	1003904	
			1600lm	55°	22	1003907	
		2700 K	1600lm	20°	22	1003854	
			1600lm	40°	19	1003857	
			1600lm	55°	22	1003860	
		3000 K	1600lm	20°	22	1003878	
			1600lm	40°	22	1003881	
			1600lm	55°	22	1003884	
		4000 K	1750lm	20°	22	1003902	
			1750lm	40°	22	1003905	
			1750lm	55°	22	1003908	
		2700 K	1550lm	20°	19	1003855	
			1550lm	40°	19	1003858	
			1550lm	55°	19	1003861	
		3000 K	1550lm	20°	19	1003879	
			1550lm	40°	19	1003882	
			1550lm	55°	19	1003885	
		4000 K	1660lm	20°	19	1003903	
			1660lm	40°	19	1003906	
			1660lm	55°	19	1003909	

NUMINOS® L



DL





Product details:

700mA

Power consumption: 25.4W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 11.7 cm D: 9 cm



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	2150lm	20°	22	1003913	
		2150lm	40°	22	1003916	
		2150lm	55°	22	1003919	
	3000 K	2150lm	20°	22	1003937	
		2150lm	40°	22	1003940	
		2150lm	55°	25	1003943	
	4000 K	2350lm	20°	22	1003961	
		2350lm	40°	22	1003964	
		2350lm	55°	25	1003967	
	2700 K	2250lm	20°	19	1003914	
		2250lm	40°	19	1003917	
		2250lm	55°	22	1003920	
	3000 K	2300lm	20°	19	1003938	
		2300lm	40°	19	1003941	
		2300lm	55°	20	1003944	
	4000 K	2450lm	20°	19	1003962	
		2450lm	40°	19	1003965	
		2450lm	55°	22	1003968	
	2700 K	2150lm	20°	19	1003915	
		2150lm	40°	19	1003918	
		2150lm	55°	19	1003921	
	3000 K	2200lm	20°	19	1003939	
		2200lm	40°	19	1003942	
		2200lm	55°	19	1003945	
	4000 K	2350lm	20°	19	1003963	
		2350lm	40°	19	1003966	
		2350lm	55°	19	1003969	
	2700 K	2150lm	20°	22	1003925	
		2150lm	40°	22	1003928	
		2150lm	55°	22	1003931	
	3000 K	2150lm	20°	22	1003949	
		2150lm	40°	22	1003952	
		2150lm	55°	25	1003955	
	4000 K	2350lm	20°	22	1003973	
		2350lm	40°	22	1003976	
		2350lm	55°	25	1003979	
	2700 K	2250lm	20°	19	1003926	
		2250lm	40°	19	1003929	
		2250lm	55°	22	1003932	
	3000 K	2300lm	20°	19	1003950	
		2300lm	40°	19	1003953	
		2300lm	55°	22	1003956	
	4000 K	2450lm	20°	19	1003974	
		2450lm	40°	19	1003977	
		2450lm	55°	22	1003980	
	2700 K	2150lm	20°	19	1003927	
		2150lm	40°	19	1003930	
		2150lm	55°	19	1003933	
	3000 K	2200lm	20°	19	1003951	
		2200lm	40°	19	1003954	
		2200lm	55°	19	1003957	
	4000 K	2350lm	20°	19	1003975	
		2350lm	40°	19	1003978	
		2350lm	55°	19	1003981	

NUMINOS® XL



DL

XL





Product details:

1050mA

Power consumption: 37.4W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 14.5 cm D: 11.5 cm



Tip:

Low-voltage plug
Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

A ↑ G F	2700 K	3300lm	20°	22	1003985	
		3300lm	40°	22	1003988	
		3300lm	55°	22	1003991	
A ↑ G E	3000 K	3300lm	20°	22	1004009	
		3300lm	40°	22	1004012	
		3300lm	55°	22	1004015	
A ↑ G E	4000 K	3600lm	20°	22	1004033	
		3600lm	40°	22	1004036	
		3600lm	55°	25	1004039	
A ↑ G F	2700 K	3500lm	20°	19	1003986	
		3500lm	40°	19	1003989	
		3500lm	55°	19	1003992	
A ↑ G E	3000 K	3550lm	20°	19	1004010	
		3550lm	40°	19	1004013	
		3550lm	55°	19	1004016	
A ↑ G E	4000 K	3800lm	20°	19	1004034	
		3800lm	40°	19	1004037	
		3800lm	55°	19	1004040	
A ↑ G F	2700 K	3400lm	20°	19	1003987	
		3400lm	40°	19	1003990	
		3400lm	55°	19	1003993	
A ↑ G E	3000 K	3500lm	20°	19	1004011	
		3500lm	40°	19	1004014	
		3500lm	55°	19	1004017	
A ↑ G E	4000 K	3750lm	20°	19	1004035	
		3750lm	40°	19	1004038	
		3750lm	55°	19	1004041	
A ↑ G F	2700 K	3300lm	20°	22	1003997	
		3300lm	40°	22	1004000	
		3300lm	55°	22	1004003	
A ↑ G E	3000 K	3300lm	20°	22	1004021	
		3300lm	40°	22	1004024	
		3300lm	55°	22	1004027	
A ↑ G E	4000 K	3600lm	20°	22	1004045	
		3600lm	40°	22	1004048	
		3600lm	55°	25	1004051	
A ↑ G F	2700 K	3500lm	20°	19	1003998	
		3500lm	40°	19	1004001	
		3500lm	55°	19	1004004	
A ↑ G E	3000 K	3550lm	20°	19	1004022	
		3550lm	40°	19	1004025	
		3550lm	55°	19	1004028	
A ↑ G E	4000 K	3800lm	20°	19	1004046	
		3800lm	40°	19	1004049	
		3800lm	55°	19	1004052	
A ↑ G F	2700 K	3400lm	20°	19	1003999	
		3400lm	40°	19	1004002	
		3400lm	55°	19	1004005	
A ↑ G E	3000 K	3500lm	20°	19	1004023	
		3500lm	40°	19	1004026	
		3500lm	55°	19	1004029	
A ↑ G E	4000 K	3750lm	20°	19	1004047	
		3750lm	40°	19	1004050	
		3750lm	55°	19	1004053	

NUMINOS® MOVE XS

NEW VARIANT


DL


XS


Product details:

200mA

Power consumption: 7W

Material: aluminium/polycarbonate (PC)


Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

A ↑ G F	2700 K	640lm	20°	16	1005553	
		620lm	40°	22	1005556	
		640lm	55°	25	1005559	
A ↑ G E	3000 K	700lm	20°	16	1005571	
		670lm	40°	22	1005574	
		690lm	55°	25	1005577	
A ↑ G E	4000 K	720lm	20°	16	1005589	
		700lm	40°	22	1005592	
		710lm	55°	25	1005595	
A ↑ G F	2700 K	670lm	20°	16	1005554	
		650lm	40°	22	1005557	
		670lm	55°	25	1005560	
A ↑ G E	3000 K	730lm	20°	16	1005572	
		700lm	40°	22	1005575	
		720lm	55°	25	1005578	
A ↑ G E	4000 K	750lm	20°	16	1005590	
		730lm	40°	22	1005593	
		740lm	55°	25	1005596	
A ↑ G F	2700 K	670lm	20°	16	1005555	
		650lm	40°	22	1005558	
		670lm	55°	25	1005561	
A ↑ G E	3000 K	730lm	20°	16	1005573	
		700lm	40°	22	1005576	
		720lm	55°	25	1005579	
A ↑ G E	4000 K	750lm	20°	16	1005591	
		730lm	40°	22	1005594	
		740lm	55°	25	1005597	
A ↑ G F	2700 K	640lm	20°	16	1005562	
		620lm	40°	22	1005565	
		640lm	55°	25	1005568	
A ↑ G E	3000 K	700lm	20°	16	1005580	
		670lm	40°	22	1005583	
		690lm	55°	25	1005586	
A ↑ G E	4000 K	720lm	20°	16	1005598	
		700lm	40°	22	1005603	
		710lm	55°	25	1005606	
A ↑ G F	2700 K	670lm	20°	16	1005563	
		650lm	40°	22	1005566	
		670lm	55°	25	1005569	
A ↑ G E	3000 K	730lm	20°	16	1005581	
		700lm	40°	22	1005584	
		720lm	55°	25	1005587	
A ↑ G E	4000 K	750lm	20°	16	1005599	
		730lm	40°	22	1005604	
		740lm	55°	25	1005607	
A ↑ G F	2700 K	670lm	20°	16	1005564	
		650lm	40°	22	1005567	
		670lm	55°	25	1005570	
A ↑ G E	3000 K	730lm	20°	16	1005582	
		700lm	40°	22	1005585	
		720lm	55°	25	1005588	
A ↑ G E	4000 K	750lm	20°	16	1005600	
		730lm	40°	22	1005605	
		740lm	55°	25	1005608	

NUMINOS® MOVE S

NEW VARIANT


DL


S


Product details:

250 mA

Power consumption: 8.6W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug
Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	670 lm	20°	19	1005319	
		670 lm	40°	19	1005322	
		670 lm	55°	22	1005325	
	3000 K	690lm	20°	19	1005337	
		690lm	40°	19	1005340	
		690lm	55°	22	1005343	
	4000 K	730lm	20°	19	1005355	
		730lm	40°	19	1005358	
		730lm	55°	22	1005361	
	2700 K	720lm	20°	19	1005320	
		720lm	40°	19	1005323	
		720lm	55°	22	1005326	
	3000 K	730lm	20°	19	1005338	
		730lm	40°	19	1005341	
		730lm	55°	22	1005344	
	4000 K	790lm	20°	19	1005356	
		790lm	40°	19	1005359	
		790lm	55°	22	1005362	
	2700 K	690lm	20°	19	1005321	
		690lm	40°	19	1005324	
		690lm	55°	22	1005327	
	3000 K	700lm	20°	19	1005339	
		700lm	40°	19	1005342	
		700lm	55°	22	1005345	
	4000 K	750lm	20°	19	1005357	
		750lm	40°	19	1005360	
		750lm	55°	22	1005363	
	2700 K	670 lm	20°	19	1005328	
		670 lm	40°	19	1005331	
		670 lm	55°	22	1005334	
	3000 K	690lm	20°	19	1005346	
		690lm	40°	19	1005349	
		690lm	55°	22	1005352	
	4000 K	730lm	20°	19	1005364	
		730lm	40°	19	1005367	
		730lm	55°	22	1005370	
	2700 K	720lm	20°	19	1005329	
		720lm	40°	19	1005332	
		720lm	55°	22	1005335	
	3000 K	730lm	20°	19	1005347	
		730lm	40°	19	1005350	
		730lm	55°	22	1005353	
	4000 K	790lm	20°	19	1005365	
		790lm	40°	19	1005368	
		790lm	55°	22	1005371	
	2700 K	690lm	20°	19	1005330	
		690lm	40°	19	1005333	
		690lm	55°	22	1005336	
	3000 K	700lm	20°	19	1005348	
		700lm	40°	19	1005351	
		700lm	55°	22	1005354	
	4000 K	750lm	20°	19	1005366	
		750lm	40°	19	1005369	
		750lm	55°	22	1005372	

NUMINOS® MOVE M



DL

M




Product details:

500mA

Power consumption: 17.5W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 12 cm D: 10 cm



Tip:

Low-voltage plug
Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

		2700 K	1460lm	20°	19	1003553	
			1460lm	40°	22	1003556	
			1460lm	55°	22	1003559	
		3000 K	1500lm	20°	19	1003577	
			1500lm	40°	22	1003580	
			1500lm	55°	22	1003583	
		4000 K	1600lm	20°	19	1003601	
			1600lm	40°	22	1003604	
			1600lm	55°	22	1003607	
		2700 K	1600lm	20°	22	1003554	
			1600lm	40°	19	1003557	
			1600lm	55°	22	1003560	
		3000 K	1600lm	20°	22	1003578	
			1600lm	40°	22	1003581	
			1600lm	55°	22	1003584	
		4000 K	1750lm	20°	22	1003602	
			1750lm	40°	22	1003605	
			1750lm	55°	22	1003608	
		2700 K	1550lm	20°	19	1003555	
			1550lm	40°	19	1003558	
			1550lm	55°	19	1003561	
		3000 K	1550lm	20°	19	1003579	
			1550lm	40°	19	1003582	
			1550lm	55°	19	1003585	
		4000 K	1660lm	20°	19	1003603	
			1660lm	40°	19	1003606	
			1660lm	55°	19	1003609	
		2700 K	1460lm	20°	19	1003565	
			1460lm	40°	22	1003568	
			1460lm	55°	22	1003571	
		3000 K	1500lm	20°	19	1003589	
			1500lm	40°	22	1003592	
			1500lm	55°	22	1003595	
		4000 K	1600lm	20°	19	1003613	
			1600lm	40°	22	1003616	
			1600lm	55°	22	1003619	
		2700 K	1600lm	20°	22	1003566	
			1600lm	40°	22	1003569	
			1600lm	55°	22	1003572	
		3000 K	1600lm	20°	22	1003590	
			1600lm	40°	22	1003593	
			1600lm	55°	22	1003596	
		4000 K	1750lm	20°	22	1003614	
			1750lm	40°	22	1003617	
			1750lm	55°	22	1003620	
		2700 K	1550lm	20°	19	1003567	
			1550lm	40°	19	1003570	
			1550lm	55°	19	1003573	
		3000 K	1550lm	20°	19	1003591	
			1550lm	40°	19	1003594	
			1550lm	55°	19	1003597	
		4000 K	1660lm	20°	19	1003615	
			1660lm	40°	19	1003618	
			1660lm	55°	19	1003621	

NUMINOS® MOVE L



DL




Product details:

750mA

Power consumption: 25.4W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 14.5 cm D: 10.5 cm



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

		2700 K	2150lm	20°	22	1003625	
			2150lm	40°	22	1003628	
			2150lm	55°	22	1003631	
		3000 K	2150lm	20°	22	1003649	
			2150lm	40°	22	1003652	
			2150lm	55°	25	1003655	
		4000 K	2350lm	20°	22	1003673	
			2350lm	40°	22	1003676	
			2350lm	55°	25	1003679	
		2700 K	2250lm	20°	19	1003626	
			2250lm	40°	19	1003629	
			2250lm	55°	22	1003632	
		3000 K	2300lm	20°	19	1003650	
			2300lm	40°	19	1003653	
			2300lm	55°	22	1003656	
		4000 K	2450lm	20°	19	1003674	
			2450lm	40°	19	1003677	
			2450lm	55°	22	1003680	
		2700 K	2150lm	20°	19	1003627	
			2150lm	40°	19	1003630	
			2150lm	55°	19	1003633	
		3000 K	2200lm	20°	19	1003651	
			2200lm	40°	19	1003654	
			2200lm	55°	19	1003657	
		4000 K	2350lm	20°	19	1003675	
			2350lm	40°	19	1003678	
			2350lm	55°	19	1003681	
		2700 K	2150lm	20°	22	1003637	
			2150lm	40°	22	1003640	
			2150lm	55°	22	1003643	
		3000 K	2150lm	20°	22	1003661	
			2150lm	40°	22	1003664	
			2150lm	55°	25	1003667	
		4000 K	2350lm	20°	22	1003685	
			2350lm	40°	22	1003688	
			2350lm	55°	25	1003691	
		2700 K	2250lm	20°	19	1003638	
			2250lm	40°	19	1003641	
			2250lm	55°	22	1003644	
		3000 K	2300lm	20°	19	1003662	
			2300lm	40°	19	1003665	
			2300lm	55°	22	1003668	
		4000 K	2450lm	20°	19	1003686	
			2450lm	40°	19	1003689	
			2450lm	55°	22	1003692	
		2700 K	2150lm	20°	19	1003639	
			2150lm	40°	19	1003642	
			2150lm	55°	19	1003645	
		3000 K	2200lm	20°	19	1003663	
			2200lm	40°	19	1003666	
			2200lm	55°	19	1003669	
		4000 K	2350lm	20°	19	1003687	
			2350lm	40°	19	1003690	
			2350lm	55°	19	1003693	

NUMINOS® MOVE XL



DL

XL




Product details:

1050mA

Power consumption: 37.4W

Material: aluminium/polycarbonate (PC)

Installation dimensions: Diameter: 17.5 cm D: 13 cm



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

A F	2700 K	3300lm	20°	22	1003697	
		3300lm	40°	22	1003700	
		3300lm	55°	22	1003703	
A E	3000 K	3300lm	20°	22	1003721	
		3300lm	40°	22	1003724	
		3300lm	55°	22	1003727	
A E	4000 K	3600lm	20°	22	1003745	
		3600lm	40°	22	1003748	
		3600lm	55°	25	1003751	
A F	2700 K	3500lm	20°	19	1003698	
		3500lm	40°	19	1003701	
		3500lm	55°	19	1003704	
A E	3000 K	3550lm	20°	19	1003722	
		3550lm	40°	19	1003725	
		3550lm	55°	19	1003728	
A E	4000 K	3800lm	20°	19	1003746	
		3800lm	40°	19	1003749	
		3800lm	55°	19	1003752	
A F	2700 K	3400lm	20°	19	1003699	
		3400lm	40°	19	1003702	
		3400lm	55°	19	1003705	
A E	3000 K	3500lm	20°	19	1003723	
		3500lm	40°	19	1003726	
		3500lm	55°	19	1003729	
A E	4000 K	3750lm	20°	19	1003747	
		3750lm	40°	19	1003750	
		3750lm	55°	19	1003753	
A F	2700 K	3300lm	20°	22	1003709	
		3300lm	40°	22	1003712	
		3300lm	55°	22	1003715	
A E	3000 K	3300lm	20°	22	1003733	
		3300lm	40°	22	1003736	
		3300lm	55°	22	1003739	
A E	4000 K	3600lm	20°	22	1003757	
		3600lm	40°	22	1003760	
		3600lm	55°	25	1003763	
A F	2700 K	3500lm	20°	19	1003710	
		3500lm	40°	19	1003713	
		3500lm	55°	19	1003716	
A E	3000 K	3550lm	20°	19	1003734	
		3550lm	40°	19	1003737	
		3550lm	55°	19	1003740	
A E	4000 K	3800lm	20°	19	1003758	
		3800lm	40°	19	1003761	
		3800lm	55°	19	1003764	
A F	2700 K	3400lm	20°	19	1003711	
		3400lm	40°	19	1003714	
		3400lm	55°	19	1003717	
A E	3000 K	3500lm	20°	19	1003735	
		3500lm	40°	19	1003738	
		3500lm	55°	19	1003741	
A E	4000 K	3750lm	20°	19	1003759	
		3750lm	40°	19	1003762	
		3750lm	55°	19	1003765	

NUMINOS® GIMBLE XS

NEW

LED
INSIDE



DL

XS





Product details:

200mA

Power consumption: 7W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug
Driver not included

You can find suitable drivers,
diffusers, and reducer rings
on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	640lm	20°	16	1005813	
		620lm	40°	22	1005816	
		640lm	55°	25	1005819	
	3000 K	700lm	20°	16	1005831	
		670 lm	40°	22	1005834	
		690lm	55°	25	1005837	
	4000 K	720lm	20°	16	1005849	
		700lm	40°	22	1005852	
		710lm	55°	25	1005855	
	2700 K	670 lm	20°	16	1005814	
		650lm	40°	22	1005817	
		670 lm	55°	25	1005820	
	3000 K	730lm	20°	16	1005832	
		700lm	40°	22	1005835	
		720lm	55°	25	1005838	
	4000 K	750lm	20°	16	1005850	
		730lm	40°	22	1005853	
		740lm	55°	25	1005856	
	2700 K	670 lm	20°	16	1005815	
		650lm	40°	22	1005818	
		670 lm	55°	25	1005821	
	3000 K	730lm	20°	16	1005833	
		700lm	40°	22	1005836	
		720lm	55°	25	1005839	
	4000 K	750lm	20°	16	1005851	
		730lm	40°	22	1005854	
		740lm	55°	25	1005857	
	2700 K	640lm	20°	16	1005822	
		620lm	40°	22	1005825	
		640lm	55°	25	1005828	
	3000 K	700lm	20°	16	1005840	
		670 lm	40°	22	1005843	
		690lm	55°	25	1005846	
	4000 K	720lm	20°	16	1005858	
		700lm	40°	22	1005861	
		710lm	55°	25	1005864	
	2700 K	670 lm	20°	16	1005823	
		650lm	40°	22	1005826	
		670 lm	55°	25	1005829	
	3000 K	730lm	20°	16	1005841	
		700lm	40°	22	1005844	
		720lm	55°	25	1005847	
	4000 K	750lm	20°	16	1005859	
		730lm	40°	22	1005862	
		740lm	55°	25	1005865	
	2700 K	670 lm	20°	16	1005824	
		650lm	40°	22	1005827	
		670 lm	55°	25	1005830	
	3000 K	730lm	20°	16	1005842	
		700lm	40°	22	1005845	
		720lm	55°	25	1005848	
	4000 K	750lm	20°	16	1005860	
		730lm	40°	22	1005863	
		740lm	55°	25	1005866	

NUMINOS® GIMBLE S

NEW
LED
INSIDE


DL


S


Product details:

250mA

Power consumption: 8.6W


Material: aluminium/polycarbonate (PC)



355°

60°

10



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	670 lm	20°	19	1005867	
		670 lm	40°	19	1005870	
		670 lm	55°	22	1005873	
	3000 K	690lm	20°	19	1005885	
		690lm	40°	19	1005888	
		690lm	55°	22	1005891	
	4000 K	730lm	20°	19	1005903	
		730lm	40°	19	1005906	
		730lm	55°	22	1005909	
	2700 K	720lm	20°	19	1005868	
		720lm	40°	19	1005871	
		720lm	55°	22	1005874	
	3000 K	730lm	20°	19	1005886	
		730lm	40°	19	1005889	
		730lm	55°	22	1005892	
	4000 K	790lm	20°	19	1005904	
		790lm	40°	19	1005907	
		790lm	55°	22	1005910	
	2700 K	690lm	20°	19	1005869	
		690lm	40°	19	1005872	
		690lm	55°	22	1005875	
	3000 K	700lm	20°	19	1005887	
		700lm	40°	19	1005890	
		700lm	55°	22	1005893	
	4000 K	750lm	20°	19	1005905	
		750lm	40°	19	1005908	
		750lm	55°	22	1005911	
	2700 K	670 lm	20°	19	1005876	
		670 lm	40°	19	1005879	
		670 lm	55°	22	1005882	
	3000 K	690lm	20°	19	1005894	
		690lm	40°	19	1005897	
		690lm	55°	22	1005900	
	4000 K	730lm	20°	19	1005912	
		730lm	40°	19	1005915	
		730lm	55°	22	1005918	
	2700 K	720lm	20°	19	1005877	
		720lm	40°	19	1005880	
		720lm	55°	22	1005883	
	3000 K	730lm	20°	19	1005895	
		730lm	40°	19	1005898	
		730lm	55°	22	1005901	
	4000 K	790lm	20°	19	1005913	
		790lm	40°	19	1005916	
		790lm	55°	22	1005919	
	2700 K	690lm	20°	19	1005878	
		690lm	40°	19	1005881	
		690lm	55°	22	1005884	
	3000 K	700lm	20°	19	1005896	
		700lm	40°	19	1005899	
		700lm	55°	22	1005902	
	4000 K	750lm	20°	19	1005914	
		750lm	40°	19	1005917	
		750lm	55°	22	1005920	

NUMINOS® GIMBLE M

NEW
LED
INSIDE


DL



M


Product details:

500mA

Power consumption: 17.5W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

	2700 K	1460lm	20°	22	1005921	
		1460lm	40°	22	1005924	
		1460lm	55°	22	1005927	
	3000 K	1500lm	20°	22	1005939	
		1500lm	40°	22	1005942	
		1500lm	55°	22	1005945	
	4000 K	1600lm	20°	22	1005957	
		1600lm	40°	22	1005960	
		1600lm	55°	22	1005963	
	2700 K	1600lm	20°	22	1005922	
		1600lm	40°	22	1005925	
		1600lm	55°	22	1005928	
	3000 K	1600lm	20°	22	1005940	
		1600lm	40°	22	1005943	
		1600lm	55°	22	1005946	
	4000 K	1750lm	20°	22	1005958	
		1750lm	40°	22	1005961	
		1750lm	55°	22	1005964	
	2700 K	1550lm	20°	22	1005923	
		1550lm	40°	22	1005926	
		1550lm	55°	22	1005929	
	3000 K	1550lm	20°	22	1005941	
		1550lm	40°	22	1005944	
		1550lm	55°	22	1005947	
	4000 K	1660lm	20°	22	1005959	
		1660lm	40°	22	1005962	
		1660lm	55°	22	1005965	
	2700 K	1460lm	20°	22	1005930	
		1460lm	40°	22	1005933	
		1460lm	55°	22	1005936	
	3000 K	1500lm	20°	22	1005948	
		1500lm	40°	22	1005951	
		1500lm	55°	22	1005954	
	4000 K	1600lm	20°	22	1005966	
		1600lm	40°	22	1005969	
		1600lm	55°	22	1005972	
	2700 K	1600lm	20°	22	1005931	
		1600lm	40°	22	1005934	
		1600lm	55°	22	1005937	
	3000 K	1600lm	20°	22	1005949	
		1600lm	40°	22	1005952	
		1600lm	55°	22	1005955	
	4000 K	1750lm	20°	22	1005967	
		1750lm	40°	22	1005970	
		1750lm	55°	22	1005973	
	2700 K	1550lm	20°	22	1005932	
		1550lm	40°	22	1005935	
		1550lm	55°	22	1005938	
	3000 K	1550lm	20°	22	1005950	
		1550lm	40°	22	1005953	
		1550lm	55°	22	1005956	
	4000 K	1660lm	20°	22	1005968	
		1660lm	40°	22	1005971	
		1660lm	55°	22	1005974	

NUMINOS® GIMBLE L

NEW
LED
INSIDE


DL



L


Product details:

700mA

Power consumption: 25.4W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

		2700 K	2150lm	20°	22	1005975	
			2150lm	40°	22	1005978	
			2150lm	55°	22	1005981	
		3000 K	2150lm	20°	22	1005993	
			2150lm	40°	22	1005996	
			2150lm	55°	22	1005999	
		4000 K	2350lm	20°	22	1006011	
			2350lm	40°	22	1006014	
			2350lm	55°	22	1006017	
		2700 K	2250lm	20°	22	1005976	
			2250lm	40°	22	1005979	
			2250lm	55°	22	1005982	
		3000 K	2300lm	20°	22	1005994	
			2300lm	40°	22	1005997	
			2300lm	55°	22	1006000	
		4000 K	2450lm	20°	22	1006012	
			2450lm	40°	22	1006015	
			2450lm	55°	22	1006018	
		2700 K	2150lm	20°	22	1005977	
			2150lm	40°	22	1005980	
			2150lm	55°	22	1005983	
		3000 K	2200lm	20°	22	1005995	
			2200lm	40°	22	1005998	
			2200lm	55°	22	1006001	
		4000 K	2350lm	20°	22	1006013	
			2350lm	40°	22	1006016	
			2350lm	55°	22	1006019	
		2700 K	2150lm	20°	22	1005984	
			2150lm	40°	22	1005987	
			2150lm	55°	22	1005990	
		3000 K	2150lm	20°	22	1006002	
			2150lm	40°	22	1006005	
			2150lm	55°	22	1006008	
		4000 K	2350lm	20°	22	1006020	
			2350lm	40°	22	1006023	
			2350lm	55°	22	1006026	
		2700 K	2250lm	20°	22	1005985	
			2250lm	40°	22	1005988	
			2250lm	55°	22	1005991	
		3000 K	2300lm	20°	22	1006003	
			2300lm	40°	22	1006006	
			2300lm	55°	22	1006009	
		4000 K	2450lm	20°	22	1006021	
			2450lm	40°	22	1006024	
			2450lm	55°	22	1006027	
		2700 K	2150lm	20°	22	1005986	
			2150lm	40°	22	1005989	
			2150lm	55°	22	1005992	
		3000 K	2200lm	20°	22	1006004	
			2200lm	40°	22	1006007	
			2200lm	55°	22	1006010	
		4000 K	2350lm	20°	22	1006022	
			2350lm	40°	22	1006025	
			2350lm	55°	22	1006028	

NUMINOS® GIMBLE XL

NEW

**LED
INSIDE**



DL

XL





Product details:

1000/1050mA

Power consumption: 37.4W

Material: aluminium/polycarbonate (PC)



Tip:

Low-voltage plug

Driver not included

You can find suitable drivers, diffusers, and reducer rings on pages 58-61.



black



black




white



chrome



black



white



white



chrome



PROD. NO.

A ↑ G F	2700 K	3300lm	20°	22	1006029	
		3300lm	40°	22	1006032	
		3300lm	55°	22	1006035	
A ↑ G E	3000 K	3300lm	20°	22	1006047	
		3300lm	40°	22	1006050	
		3300lm	55°	22	1006053	
A ↑ G E	4000 K	3600lm	20°	22	1006065	
		3600lm	40°	22	1006068	
		3600lm	55°	22	1006071	
A ↑ G F	2700 K	3500lm	20°	22	1006030	
		3500lm	40°	22	1006033	
		3500lm	55°	22	1006036	
A ↑ G E	3000 K	3550lm	20°	22	1006048	
		3550lm	40°	22	1006051	
		3550lm	55°	22	1006054	
A ↑ G E	4000 K	3800lm	20°	22	1006066	
		3800lm	40°	22	1006069	
		3800lm	55°	22	1006072	
A ↑ G F	2700 K	3400lm	20°	22	1006031	
		3400lm	40°	22	1006034	
		3400lm	55°	22	1006037	
A ↑ G E	3000 K	3500lm	20°	22	1006049	
		3500lm	40°	22	1006052	
		3500lm	55°	22	1006055	
A ↑ G E	4000 K	3750lm	20°	22	1006067	
		3750lm	40°	22	1006070	
		3750lm	55°	22	1006073	
A ↑ G F	2700 K	3300lm	20°	22	1006038	
		3300lm	40°	22	1006041	
		3300lm	55°	22	1006044	
A ↑ G E	3000 K	3300lm	20°	22	1006056	
		3300lm	40°	22	1006059	
		3300lm	55°	22	1006062	
A ↑ G E	4000 K	3600lm	20°	22	1006074	
		3600lm	40°	22	1006077	
		3600lm	55°	22	1006080	
A ↑ G F	2700 K	3500lm	20°	22	1006039	
		3500lm	40°	22	1006042	
		3500lm	55°	22	1006045	
A ↑ G E	3000 K	3550lm	20°	22	1006057	
		3550lm	40°	22	1006060	
		3550lm	55°	22	1006063	
A ↑ G E	4000 K	3800lm	20°	22	1006075	
		3800lm	40°	22	1006078	
		3800lm	55°	22	1006081	
A ↑ G F	2700 K	3400lm	20°	22	1006040	
		3400lm	40°	22	1006043	
		3400lm	55°	22	1006046	
A ↑ G E	3000 K	3500lm	20°	22	1006058	
		3500lm	40°	22	1006061	
		3500lm	55°	22	1006064	
A ↑ G E	4000 K	3750lm	20°	22	1006076	
		3750lm	40°	22	1006079	
		3750lm	55°	22	1006082	




Accessories

Perfect driver assignment

						
	LED Driver, 200mA, 10W QC	LED Driver, 200mA, 10W, PHASE QC	LED Driver 200mA, 30W, DALI QC	LED driver 250mA, 10W	LED driver 250mA, 10W, PHASE	LED driver 250mA, 20W, DALI
	XS	XS	XS	S	S	S
	    	    	    	    	    	    
	200mA	200mA	200mA	250mA	250mA	250/350/500/700mA
Material	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)
Colour	white	white	white	white	white	white
Voltage prim.	200-240V ~50/60Hz	200-240V ~50/60Hz	200-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Voltage sec.	29-42V DC	30-42V DC	15-54V DC	26-40V	30-42V	6-60V
Output current	200mA	200mA	200mA	250mA	250mA	250mA
Number of outputs sec.	1	1	1	1	1	1
Wattage of	5.8W	6W	3.8W	6.5W	7.5W	1.5W
Wattage up to	8.4W	8.4W	13.5W	10W	10W	15W
Environmental temp. min.	–	–	–	-20°C	-20°C	-20°C
Environmental temp. max.	–	–	–	45°C	50°C	50°C
Thermal protection	110°C	110°C	110°C	110°C	110°C	110°C
IP protection rating	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
Dimmable	–	PHASE C	DALI	–	PHASE C	DALI
Length	6.5 cm	8.5 cm	18 cm	6.5 cm	8.5 cm	15 cm
Width	3.9 cm	4.1cm	4.5 cm	3.9 cm	3.9 cm	5.2 cm
Height	3.5cm	3 cm	3 cm	2 cm	2.2 cm	2.8 cm
Prod. no.	1005610	1005609	1005611	1004058	1004055	1004067

Diffusers

	XS				S				
									
	Diffuser elliptical	Diffuser prismatic	Diffuser frosted	Diffuser honeycomb	Diffuser elliptical	Diffuser prismatic	Diffuser frosted	Diffuser honeycomb	
Prod. no.	1005612	1005613	1005614	1005615	1004786	1004787	1004788	1004789	

			
	LED driver 500mA, 30W	LED driver 500mA, 30W, PHASE	LED driver 500mA, 40W, DALI
			
			
	500/600/700mA	500mA	250/350/500/700mA
Material	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)
Colour	white	white	white
Voltage prim.	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Voltage sec.	30-42V	25-42V	6-58V
Output current	500mA	500mA	500mA
Number of outputs sec.	1	1	1
Wattage of	15W	12.5W	1.5W
Wattage up to	29.5W	21W	40.6W
Environmental temp. min.	-20°C	-25°C	-25°C
Environmental temp. max.	50°C	50°C	50°C
Thermal protection	110°C	110°C	110°C
IP protection rating	IP 20	IP 20	IP 20
Dimmable	–	PHASE C	DALI
Length	14.7 cm	11.5W	12.3 cm
Width	4.3 cm	4.1cm	7.9 cm
Height	3 cm	2.5 cm	2.4 cm
Prod. no.	1004064	1004054	1004069

				
				
	Diffuser elliptical	Diffuser prismatic	Diffuser frosted	Diffuser honeycomb
Prod. no.	1004790	1004791	1004792	1004793

Accessories

Perfect driver assignment

						
	LED driver 1050mA, 40W	LED driver 700mA, 30W, PHASE	LED driver 700mA, 40W, DALI	LED driver 1050mA, 40W	LED driver 1000mA, 40W, PHASE	LED driver 1050mA, 50W, DALI
						
	  	  	  	  	  	  
	500/600/700mA	700mA	700mA	800/900/1050mA	1000mA	1050mA
Material	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)	Polycarbonate (PC)
Colour	white	white	white	white	white	white
Voltage prim.	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Voltage sec.	30-42V	30-42V	6-58V	30-42V	25-40V DC	6-58V
Output current	700mA	700mA	250/350/500/700mA	1050mA	1050mA	1050mA
Number of outputs sec.	1	1	1	1	1	1
Wattage of	15W	21W	1.5W	24W	26.3W	4.2W
Wattage up to	29.5W	29.4W	40.6W	44W	42W	50W
Environmental temp. min.	-20°C	-20°C	-25°C	-20°C	-20°C	-25°C
Environmental temp. max.	50°C	50°C	50°C	50°C	50°C	50°C
Thermal protection	110°C	110°C	110°C	110°C	110°C	110°C
IP protection rating	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
Dimmable	–	PHASE C	DALI	–	PHASE C	DALI
Length	14.7 cm	11.5W	12.3 cm	9.7 cm	14.5 cm	12.3 cm
Width	4.3 cm	4.4 cm	7.9 cm	4.3 cm	4 cm	7.9 cm
Height	3 cm	3 cm	2.4 cm	3 cm	3 cm	2.4 cm
Prod. no.	1004062	1004065	1004070	1004059	1004066	1004071

Diffusers

								
								
	Diffuser elliptical	Diffuser prismatic	Diffuser frosted	Diffuser honeycomb	Diffuser elliptical	Diffuser prismatic	Diffuser frosted	Diffuser honeycomb
Prod. no.	1004794	1004795	1004796	1004797	1004798	1004799	1004800	1004801

NEW

TIME FOR A CHANGE. TIME FOR AN UPDATE.

An old recessed ceiling light, often still fitted with conventional bulbs, should give way to an energy-efficient and cost-effective alternative. When removing the old fitting, a larger ceiling cut-out will often be required than before.

Here SLV offers the appropriate solution – our new reducer rings.

The reducer rings completely cover the larger ceiling cut-out, while at the same time providing perfect support for your new, compact, recessed ceiling light.

Neat, time-saving, uncomplicated.

And also perfectly tailored to the NUMINOS® Downlight and Spotlight system.



1. Old recessed ceiling light with larger ceiling cut-out.



2. Removal of the old recessed ceiling light.



3. Installation of the reducer ring.



4. Reducer ring installed. Larger ceiling cut-out fully covered.



5. Electrical connection and installation of the new recessed ceiling light.



6. New recessed ceiling light placed into the reducer ring.

Reducer ring, round



					
Material	steel	steel	steel	steel	steel
External Ø	16 cm	16 cm	24 cm	24 cm	24 cm
Height	5.3 cm	5.3 cm	5.3 cm	5.3 cm	5.3 cm
Internal Ø	7 cm	9 cm	12 cm	15 cm	18 cm
Ceiling cut-out	8.5 - 13 cm	12 - 15 cm	14 - 18 cm	17 - 20 cm	20 - 22 cm
Material thickness	3 cm	3 cm	3 cm	3 cm	3 cm
Prod. no. black	1006135	1006139	1006143	1006147	1006151
Prod. no. white	1006136	1006140	1006144	1006148	1006152

Reducer ring, square



					
Material	steel	steel	steel	steel	steel
Length	16 cm	16 cm	24 cm	24 cm	24 cm
Width	16 cm	16 cm	24 cm	24 cm	24 cm
Height	5.3 cm	5.3 cm	5.3 cm	5.3 cm	5.3 cm
Internal Ø	7 cm	9 cm	12 cm	15 cm	18 cm
Ceiling cut-out	8.5 - 13 cm	12 - 15 cm	14 - 18 cm	17 - 20 cm	20 - 22 cm
Material thickness	3 cm	3 cm	3 cm	3 cm	3 cm
Prod. no. black	1006137	1006141	1006145	1006149	1006153
Prod. no. white	1006138	1006142	1006146	1006150	1006154

NUMINOS® S




3-circuit

Product details:

220-240V ~50/60Hz | 250mA

Total wattage: 11W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative ring S

white

Prod. no. 1006167



black



white



PROD. NO.



2700 K

985lm

24°

16

1004074



3000 K

985lm

36°

16

1004075

980lm

60°

19

1004076

1020lm

24°

13

1004082

1020lm

36°

13

1004083

1020lm

60°

19

1004084

1100lm

24°

16

1004090



4000 K

1100lm

36°

16

1004091

1100lm

60°

19

1004092



2700 K

985lm

24°

16

1004362

985lm

36°

16

1004363

980lm

60°

19

1004364

1020lm

24°

13

1004370



3000 K

1020lm

36°

13

1004371

1020lm

60°

19

1004372

1100lm

24°

16

1004378



4000 K

1100lm

36°

16

1004379

1100lm

60°

19

1004380



2700 K

985lm

24°

16

1004078

985lm

36°

16

1004079

980lm

60°

19

1004080

1020lm

24°

13

1004086



3000 K

1020lm

36°

13

1004087

1020lm

60°

19

1004088

1100lm

24°

16

1004094



4000 K

1100lm

36°

16

1004095

1100lm

60°

19

1004096



2700 K

985lm

24°

16

1004366

985lm

36°

16

1004367

980lm

60°

19

1004368

1020lm

24°

13

1004374



3000 K

1020lm

36°

13

1004375

1020lm

60°

19

1004376

1100lm

24°

16

1004382



4000 K

1100lm

36°

16

1004383

1100lm

60°

19

1004384

NUMINOS® M




3-circuit

Product details:

220-240V ~50/60Hz | 500mA

Total wattage: 20W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring M

white

Prod. no. 1006168



black



white



PROD. NO.



2700 K

1925lm

24°

16

1004170



3000 K

1935lm

36°

16

1004171

1885lm

60°

22

1004172

1955lm

24°

16

1004178



3000 K

1970lm

36°

13

1004179

1880lm

60°

22

1004180



4000 K

2125lm

24°

19

1004186

2120lm

36°

16

1004187

2060lm

60°

25

1004188



2700 K

1925lm

24°

16

1004458



2700 K

1935lm

36°

16

1004459

1885lm

60°

22

1004460

1955lm

24°

16

1004466



3000 K

1970lm

36°

13

1004467

1880lm

60°

22

1004468

2125lm

24°

19

1004474



4000 K

2120lm

36°

16

1004475

2060lm

60°

25

1004476



2700 K

1925lm

24°

16

1004174



2700 K

1935lm

36°

16

1004175

1885lm

60°

22

1004176

1955lm

24°

16

1004182



3000 K

1970lm

36°

13

1004183

1880lm

60°

22

1004184

2125lm

24°

19

1004190



4000 K

2120lm

36°

16

1004191

2060lm

60°

25

1004192



2700 K

1925lm

24°

16

1004462



2700 K

1935lm

36°

16

1004463

1885lm

60°

22

1004464

1955lm

24°

16

1004470



3000 K

1970lm

36°

13

1004471

1880lm

60°

22

1004472

2125lm

24°

19

1004478



4000 K

2120lm

36°

16

1004479

2060lm

60°

25

1004480



NUMINOS® L




3-circuit

Product details:

220-240V ~50/60Hz | 700mA

Total wattage: 28W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring L

white

Prod. no. 1006169



black



white



PROD. NO.



2700 K

2440lm

24°

19

1004266



3000 K

2400lm

36°

19

1004267

2475lm

60°

22

1004268

2430lm

24°

13

1004274



3000 K

2340lm

36°

13

1004275

2400lm

60°

22

1004276

2675lm

24°

19

1004282



4000 K

2620lm

36°

19

1004283

2715lm

60°

22

1004284



2700 K

2440lm

24°

19

1004554

2400lm

36°

19

1004555

2475lm

60°

22

1004556

2430lm

24°

13

1004562



3000 K

2340lm

36°

13

1004563

2400lm

60°

22

1004564

2675lm

24°

19

1004570



4000 K

2620lm

36°

19

1004571

2715lm

60°

22

1004572



2700 K

2440lm

24°

19

1004270

2400lm

36°

19

1004271

2475lm

60°

22

1004272

2430lm

24°

13

1004278



3000 K

2340lm

36°

13

1004279

2400lm

60°

22

1004280

2675lm

24°

19

1004286



4000 K

2620lm

36°

19

1004287

2715lm

60°

22

1004288



2700 K

2440lm

24°

19

1004558

2400lm

36°

19

1004559

2475lm

60°

22

1004560

2430lm

24°

13

1004566



3000 K

2340lm

36°

13

1004567

2400lm

60°

22

1004568

2675lm

24°

19

1004574



4000 K

2620lm

36°

19

1004575

2715lm

60°

22

1004576



NUMINOS® XL

NEW VARIANT




3-circuit

Product details:

220-240V ~50/60Hz | 900mA

System output: 36W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative ring XL

white

Prod. no. 1006170



black



white



PROD. NO.



2700 K

3290lm

24°

19

1005723



2700 K

3250lm

36°

19

1005724

2980lm

60°

25

1005725



3000 K

3530lm

24°

19

1005729



3000 K

3490lm

36°

19

1005730

3210lm

60°

25

1005731



4000 K

3800lm

24°

19

1005735



4000 K

3760lm

36°

19

1005736

3460lm

60°

25

1005737



2700 K

3290lm

24°

19

1005795



2700 K

3250lm

36°

19

1005796

2980lm

60°

25

1005797



3000 K

3530lm

24°

19

1005801



3000 K

3490lm

36°

19

1005802

3210lm

60°

25

1005803



4000 K

3800lm

24°

19

1005807



4000 K

3760lm

36°

19

1005808

3460lm

60°

25

1005809



2700 K

3290lm

24°

19

1005726



2700 K

3250lm

36°

19

1005727

2980lm

60°

25

1005728



3000 K

3530lm

24°

19

1005732



3000 K

3490lm

36°

19

1005733

3210lm

60°

25

1005734



4000 K

3800lm

24°

19

1005738



4000 K

3760lm

36°

19

1005739

3460lm

60°

25

1005740



2700 K

3290lm

24°

19

1005798



2700 K

3250lm

36°

19

1005799

2980lm

60°

25

1005800



3000 K

3530lm

24°

19

1005804



3000 K

3490lm

36°

19

1005805

3210lm

60°

25

1005806



4000 K

3800lm

24°

19

1005810



4000 K

3760lm

36°

19

1005811

3460lm

60°

25

1005812



NUMINOS® ZOOM M

NEW
LED
INSIDE


3-circuit


Product details:

220-240V ~50/60Hz | 500mA

Total wattage: 20W



Material: aluminium/polycarbonate (PC)

- Half-peak divergence adjustable from 15°-60°.




350°

90°



black



white



							PROD. NO.	
		2700 K	680-1650lm	15°-60°	25		1006108	
		3000 K	750-1800lm	15°-60°	25		1006110	
		4000 K	780-1900lm	15°-60°	25		1006112	
		2700 K	680-1650lm	15°-60°	25		1006114	
		3000 K	750-1800lm	15°-60°	25		1006116	
		4000 K	780-1900lm	15°-60°	25		1006118	
		2700 K	680-1650lm	15°-60°	25		1006109	
		3000 K	750-1800lm	15°-60°	25		1006111	
		4000 K	780-1900lm	15°-60°	25		1006113	
		2700 K	680-1650lm	15°-60°	25		1006115	
		3000 K	750-1800lm	15°-60°	25		1006117	
		4000 K	780-1900lm	15°-60°	25		1006119	



NUMINOS® S




CW

Product details:

220-240V ~50/60Hz | 250mA

Total wattage: 11W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring S

white

Prod. no. 1006167



black



white



PROD. NO.



2700 K

985lm

24°

16

1004098



3000 K

1020lm

24°

13

1004106



3000 K

1020lm

36°

13

1004107



3000 K

1020lm

60°

19

1004108



4000 K

1100lm

24°

16

1004114



4000 K

1100lm

36°

16

1004115



4000 K

1100lm

60°

19

1004116



2700 K

985lm

24°

16

1004386



2700 K

985lm

36°

16

1004387



2700 K

980lm

60°

19

1004388



3000 K

1020lm

24°

13

1004394



3000 K

1020lm

36°

13

1004395



3000 K

1020lm

60°

19

1004396



4000 K

1100lm

24°

16

1004402



4000 K

1100lm

36°

16

1004403



4000 K

1100lm

60°

19

1004404



2700 K

985lm

24°

16

1004102



2700 K

985lm

36°

16

1004103



2700 K

980lm

60°

19

1004104



3000 K

1020lm

24°

13

1004110



3000 K

1020lm

36°

13

1004111



3000 K

1020lm

60°

19

1004112



4000 K

1100lm

24°

16

1004118



4000 K

1100lm

36°

16

1004119



4000 K

1100lm

60°

19

1004120



2700 K

985lm

24°

16

1004390



2700 K

985lm

36°

16

1004391



2700 K

980lm

60°

19

1004392



3000 K

1020lm

24°

13

1004398



3000 K

1020lm

36°

13

1004399



3000 K

1020lm

60°

19

1004400



4000 K

1100lm

24°

16

1004406



4000 K

1100lm

36°

16

1004407



4000 K

1100lm

60°

19

1004408



NUMINOS® M




CL

Product details:

220-240V ~50/60Hz | 500mA

Total wattage: 20W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring M

white

Prod. no. 1006168



black



white



PROD. NO.



2700 K

1925lm

24°

16

1004194



2700 K

1935lm

36°

16

1004195

1885lm

60°

22

1004196



3000 K

1955lm

24°

16

1004202



3000 K

1970lm

36°

13

1004203

1880lm

60°

22

1004204



4000 K

2125lm

24°

19

1004210



4000 K

2120lm

36°

16

1004211

2060lm

60°

25

1004212



2700 K

1925lm

24°

16

1004482



2700 K

1935lm

36°

16

1004483

1885lm

60°

22

1004484



3000 K

1955lm

24°

16

1004490



3000 K

1970lm

36°

13

1004491

1880lm

60°

22

1004492



4000 K

2125lm

24°

19

1004498



4000 K

2120lm

36°

16

1004499

2060lm

60°

25

1004500



2700 K

1925lm

24°

16

1004198



2700 K

1935lm

36°

16

1004199

1885lm

60°

22

1004200



3000 K

1955lm

24°

16

1004206



3000 K

1970lm

36°

13

1004207

1880lm

60°

22

1004208



4000 K

2125lm

24°

19

1004214



4000 K

2120lm

36°

16

1004215

2060lm

60°

25

1004216



2700 K

1925lm

24°

16

1004486



2700 K

1935lm

36°

16

1004487

1885lm

60°

22

1004488



3000 K

1955lm

24°

16

1004494



3000 K

1970lm

36°

13

1004495

1880lm

60°

22

1004496



4000 K

2125lm

24°

19

1004502



4000 K

2120lm

36°

16

1004503

2060lm

60°

25

1004504



NUMINOS® L





CL

Product details:

220-240V ~50/60Hz | 700mA

Total wattage: 28W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring L

white

Prod. no. 1006169



black



white



PROD. NO.



2700 K

2440lm

24°

19

1004290



2700 K

2400lm

36°

19

1004291

2475lm

60°

22

1004292



3000 K

2430lm

24°

13

1004298



3000 K

2340lm

36°

13

1004299

2400lm

60°

22

1004300



4000 K

2675lm

24°

19

1004306



4000 K

2620lm

36°

19

1004307

2715lm

60°

22

1004308



2700 K

2440lm

24°

19

1004578



2700 K

2400lm

36°

19

1004579

2475lm

60°

22

1004580



3000 K

2430lm

24°

13

1004586



3000 K

2340lm

36°

13

1004587

2400lm

60°

22

1004588



4000 K

2675lm

24°

19

1004594



4000 K

2620lm

36°

19

1004595

2715lm

60°

22

1004596



2700 K

2440lm

24°

19

1004294



2700 K

2400lm

36°

19

1004295

2475lm

60°

22

1004296



3000 K

2430lm

24°

13

1004302



3000 K

2340lm

36°

13

1004303

2400lm

60°

22

1004304



4000 K

2675lm

24°

19

1004310



4000 K

2620lm

36°

19

1004311

2715lm

60°

22

1004312



2700 K

2440lm

24°

19

1004582



2700 K

2400lm

36°

19

1004583

2475lm

60°

22

1004584



3000 K

2430lm

24°

13

1004590



3000 K

2340lm

36°

13

1004591

2400lm

60°

22

1004592



4000 K

2675lm

24°

19

1004598



4000 K

2620lm

36°

19

1004599

2715lm

60°

22

1004600



NUMINOS® XL

NEW VARIANT




CL

Product details:

220-240V ~50/60Hz | 900mA

System output: 36W

Material: aluminium/polycarbonate (PC)



Tip:


Decorative ring also available in white




Decorative
ring XL

white

Prod. no. 1006170



black



white



PROD. NO.



2700 K

3290lm

24°

19

1006083



3250lm

36°

19

1006084

2980lm

60°

25

1006085



3000 K

3530lm

24°

19

1006089



3490lm

36°

19

1006090

3210lm

60°

25

1006091



4000 K

3800lm

24°

19

1006095



3760lm

36°

19

1006096

3460lm

60°

25

1006097



2700 K

3290lm

24°

19

1005741



3250lm

36°

19

1005742

2980lm

60°

25

1005743



3000 K

3530lm

24°

19

1005747



3490lm

36°

19

1005748

3210lm

60°

25

1005749



4000 K

3800lm

24°

19

1005753



3760lm

36°

19

1005754

3460lm

60°

25

1005755



2700 K

3290lm

24°

19

1006086



3250lm

36°

19

1006087

2980lm

60°

25

1006088



3000 K

3530lm

24°

19

1006092



3490lm

36°

19

1006093

3210lm

60°

25

1006094



4000 K

3800lm

24°

19

1006098



3760lm

36°

19

1006099

3460lm

60°

25

1006100



2700 K

3290lm

24°

19

1005744



3250lm

36°

19

1005745

2980lm

60°

25

1005746



3000 K

3530lm

24°

19

1005750



3490lm

36°

19

1005751

3210lm

60°

25

1005752



4000 K

3800lm

24°

19

1005756



3760lm

36°

19

1005757

3460lm

60°

25

1005758



NUMINOS® S




CL

Product details:

220-240V ~50/60Hz | 250mA

Total wattage: 11W

Material: aluminium/polycarbonate (PC)



Tip:

Decorative ring also available in white




Decorative
ring S

□ white

Prod. no. **1006167**



■ black



□ white



PROD. NO.



2700 K

985lm

24°

16

1004122



3000 K

1020lm

24°

13

1004130



3000 K

1020lm

36°

13

1004131



3000 K

1020lm

60°

19

1004132



4000 K

1100lm

24°

16

1004138



4000 K

1100lm

36°

16

1004139



4000 K

1100lm

60°

19

1004140



2700 K

985lm

24°

16

1004410



2700 K

985lm

36°

16

1004411



2700 K

980lm

60°

19

1004412



3000 K

1020lm

24°

13

1004418



3000 K

1020lm

36°

13

1004419



3000 K

1020lm

60°

19

1004420



4000 K

1100lm

24°

16

1004426



4000 K

1100lm

36°

16

1004427



4000 K

1100lm

60°

19

1004428



2700 K

985lm

24°

16

1004126



2700 K

985lm

36°

16

1004127



2700 K

980lm

60°

19

1004128



3000 K

1020lm

24°

13

1004134



3000 K

1020lm

36°

13

1004135



3000 K

1020lm

60°

19

1004136



4000 K

1100lm

24°

16

1004142



4000 K

1100lm

36°

16

1004143



4000 K

1100lm

60°

19

1004144



2700 K

985lm

24°

16

1004414



2700 K

985lm

36°

16

1004415



2700 K

980lm

60°

19

1004416



3000 K

1020lm

24°

13

1004422



3000 K

1020lm

36°

13

1004423



3000 K

1020lm

60°

19

1004424



4000 K

1100lm

24°

16

1004430



4000 K

1100lm

36°

16

1004431



4000 K

1100lm

60°

19

1004432



NUMINOS® M




CL

Product details:

220-240V ~50/60Hz | 500mA

Total wattage: 20W

Material: aluminium/polycarbonate (PC)



Tip:

Decorative ring also available in white




Decorative
ring M

☐ white

Prod. no. **1006168**



☒ black



☐ white



PROD. NO.



2700 K

1925lm

24°

16

1004218



3000 K

1935lm

36°

16

1004219

1885lm

60°

22

1004220

1955lm

24°

16

1004226



3000 K

1970lm

36°

13

1004227

1880lm

60°

22

1004228

2125lm

24°

19

1004234



4000 K

2120lm

36°

16

1004235

2060lm

60°

25

1004236



2700 K

1925lm

24°

16

1004506



2700 K

1935lm

36°

16

1004507

1885lm

60°

22

1004508

1955lm

24°

16

1004514



3000 K

1970lm

36°

13

1004515

1880lm

60°

22

1004516

2125lm

24°

19

1004522



4000 K

2120lm

36°

16

1004523

2060lm

60°

25

1004524



2700 K

1925lm

24°

16

1004222



2700 K

1935lm

36°

16

1004223

1885lm

60°

22

1004224

1955lm

24°

16

1004230



3000 K

1970lm

36°

13

1004231

1880lm

60°

22

1004232

2125lm

24°

19

1004238



4000 K

2120lm

36°

16

1004239

2060lm

60°

25

1004240



2700 K

1925lm

24°

16

1004510



2700 K

1935lm

36°

16

1004511

1885lm

60°

22

1004512

1955lm

24°

16

1004518



3000 K

1970lm

36°

13

1004519

1880lm

60°

22

1004520

2125lm

24°

19

1004526



4000 K

2120lm

36°

16

1004527

2060lm

60°

25

1004528



NUMINOS® L



CL

Product details:


220-240V ~50/60Hz | 700mA

Total wattage: 28W

Material: aluminium/polycarbonate (PC)



L80B50



Tip:

Decorative ring also available in white




Decorative
ring L

☐ white

Prod. no. **1006169**



☒ black



☐ white



PROD. NO.



2700 K

2440lm

24°

19

1004314



3000 K

2430lm

24°

13

1004322

2340lm

36°

13

1004323

2400lm

60°

22

1004324



4000 K

2675lm

24°

19

1004330

2620lm

36°

19

1004331

2715lm

60°

22

1004332



2700 K

2440lm

24°

19

1004602

2400lm

36°

19

1004603

2475lm

60°

22

1004604



3000 K

2430lm

24°

13

1004610

2340lm

36°

13

1004611

2400lm

60°

22

1004612



4000 K

2675lm

24°

19

1004618

2620lm

36°

19

1004619

2715lm

60°

22

1004620



2700 K

2440lm

24°

19

1004318

2400lm

36°

19

1004319

2475lm

60°

22

1004320



3000 K

2430lm

24°

13

1004326

2340lm

36°

13

1004327

2400lm

60°

22

1004328



4000 K

2675lm

24°

19

1004334

2620lm

36°

19

1004335

2715lm

60°

22

1004336



2700 K

2440lm

24°

19

1004606

2400lm

36°

19

1004607

2475lm

60°

22

1004608



3000 K

2430lm

24°

13

1004614

2340lm

36°

13

1004615

2400lm

60°

22

1004616



4000 K

2675lm

24°

19

1004622

2620lm

36°

19

1004623

2715lm

60°

22

1004624



NUMINOS® XL

NEW VARIANT



CL

Product details:


220-240V ~50/60Hz | 900mA

System output: 36W

Material: aluminium/polycarbonate (PC)



L80B50



Tip:

Decorative ring also available in white




Decorative ring XL

☐ white

Prod. no. 1006170



☒ black



☐ white



PROD. NO.



2700 K

3290lm

24°

19

1005687



3250lm

36°

19

1005688

2980lm

60°

25

1005689



3000 K

3530lm

24°

19

1005693



3490lm

36°

19

1005694

3210lm

60°

25

1005695



4000 K

3800lm

24°

19

1005699



3760lm

36°

19

1005700

3460lm

60°

25

1005701



2700 K

3290lm

24°

19

1005759



3250lm

36°

19

1005760

2980lm

60°

25

1005761



3000 K

3530lm

24°

19

1005765



3490lm

36°

19

1005766

3210lm

60°

25

1005767



4000 K

3800lm

24°

19

1005771



3760lm

36°

19

1005772

3460lm

60°

25

1005773



2700 K

3290lm

24°

19

1005690



3250lm

36°

19

1005691

2980lm

60°

25

1005692



3000 K

3530lm

24°

19

1005696



3490lm

36°

19

1005697

3210lm

60°

25

1005698



4000 K

3800lm

24°

19

1005702



3760lm

36°

19

1005703

3460lm

60°

25

1005704



2700 K

3290lm

24°

19

1005762



3250lm

36°

19

1005763

2980lm

60°

25

1005764



3000 K

3530lm

24°

19

1005768



3490lm

36°

19

1005769

3210lm

60°

25

1005770



4000 K

3800lm

24°

19

1005774



3760lm

36°

19

1005775

3460lm

60°

25

1005776



NUMINOS® S



PD

Product details:

220-240V ~50/60Hz | 250mA


Total wattage: 11W

Material: aluminium/polycarbonate (PC)



L80B50

250



Tip:

Decorative ring also available in white




Decorative
ring S

white

Prod. no. 1006167



black



white



PROD. NO.



2700 K

985lm

24°

16

1004146



3000 K

985lm

36°

16

1004147

980lm

60°

19

1004148

1020lm

24°

13

1004154

1020lm

36°

13

1004155

1020lm

60°

19

1004156



4000 K

1100lm

24°

16

1004162

1100lm

36°

16

1004163

1100lm

60°

19

1004164



2700 K

985lm

24°

16

1004434

985lm

36°

16

1004435

980lm

60°

19

1004436

1020lm

24°

13

1004442



3000 K

1020lm

36°

13

1004443

1020lm

60°

19

1004444

1100lm

24°

16

1004450



4000 K

1100lm

36°

16

1004451

1100lm

60°

19

1004452



2700 K

985lm

24°

16

1004150

985lm

36°

16

1004151

980lm

60°

19

1004152

1020lm

24°

13

1004158



3000 K

1020lm

36°

13

1004159

1020lm

60°

19

1004160

1100lm

24°

16

1004166



4000 K

1100lm

36°

16

1004167

1100lm

60°

19

1004168



2700 K

985lm

24°

16

1004438

985lm

36°

16

1004439

980lm

60°

19

1004440

1020lm

24°

13

1004446



3000 K

1020lm

36°

13

1004447

1020lm

60°

19

1004448

1100lm

24°

16

1004454



4000 K

1100lm

36°

16

1004455

1100lm

60°

19

1004456



NUMINOS® M



PD

Product details:

220-240V ~50/60Hz | 500mA


Total wattage: 20W

Material: aluminium/polycarbonate (PC)



L80B50

250



Tip:

Decorative ring also available in white




Decorative
ring M

white

Prod. no. 1006168



black



white



PROD. NO.



2700 K

1925lm

24°

16

1004242



3000 K

1935lm

36°

16

1004243

1885lm

60°

22

1004244

1955lm

24°

16

1004250



3000 K

1970lm

36°

13

1004251

1880lm

60°

22

1004252

2125lm

24°

19

1004258



4000 K

2120lm

36°

16

1004259

2060lm

60°

25

1004260



2700 K

1925lm

24°

16

1004530



2700 K

1935lm

36°

16

1004531

1885lm

60°

22

1004532

1955lm

24°

16

1004538



3000 K

1970lm

36°

13

1004539

1880lm

60°

22

1004540

2125lm

24°

19

1004546



4000 K

2120lm

36°

16

1004547

2060lm

60°

25

1004548



2700 K

1925lm

24°

16

1004246



2700 K

1935lm

36°

16

1004247

1885lm

60°

22

1004248

1955lm

24°

16

1004254



3000 K

1970lm

36°

13

1004255

1880lm

60°

22

1004256

2125lm

24°

19

1004262



4000 K

2120lm

36°

16

1004263

2060lm

60°

25

1004264



2700 K

1925lm

24°

16

1004534



2700 K

1935lm

36°

16

1004535

1885lm

60°

22

1004536

1955lm

24°

16

1004542



3000 K

1970lm

36°

13

1004543

1880lm

60°

22

1004544

2125lm

24°

19

1004550



4000 K

2120lm

36°

16

1004551

2060lm

60°

25

1004552



NUMINOS® L




PD

Product details:

220-240V ~50/60Hz| 700mA


Total wattage: 28W

Material: aluminium/polycarbonate (PC)



L80B50

250



Tip:

Decorative ring also available in white




Decorative
ring L

white

Prod. no. 1006169



black



white



PROD. NO.



2700 K

2440lm

24°

19

1004338



3000 K

2400lm

36°

19

1004339

2475lm

60°

22

1004340

2430lm

24°

13

1004346



3000 K

2340lm

36°

13

1004347

2400lm

60°

22

1004348

2675lm

24°

19

1004354



4000 K

2620lm

36°

19

1004355

2715lm

60°

22

1004356



2700 K

2440lm

24°

19

1004626

2400lm

36°

19

1004627

2475lm

60°

22

1004628

2430lm

24°

13

1004634



3000 K

2340lm

36°

13

1004635

2400lm

60°

22

1004636

2675lm

24°

19

1004642



4000 K

2620lm

36°

19

1004643

2715lm

60°

22

1004644



2700 K

2440lm

24°

19

1004342

2400lm

36°

19

1004343

2475lm

60°

22

1004344

2430lm

24°

13

1004350



3000 K

2340lm

36°

13

1004351

2400lm

60°

22

1004352

2675lm

24°

19

1004358



4000 K

2620lm

36°

19

1004359

2715lm

60°

22

1004360



2700 K

2440lm

24°

19

1004630

2400lm

36°

19

1004631

2475lm

60°

22

1004632

2430lm

24°

13

1004638



3000 K

2340lm

36°

13

1004639

2400lm

60°

22

1004640

2675lm

24°

19

1004646



4000 K

2620lm

36°

19

1004647

2715lm

60°

22

1004648



NUMINOS® XL

NEW VARIANT




PD

Product details:

220-240V ~50/60Hz | 900mA

System output: 36W

Material: aluminium/polycarbonate (PC)



Tip:

Decorative ring also available in white




Decorative ring XL

white

Prod. no. 1006170



black



white



A → G



UGR

PROD. NO.

A
t
g F

2700 K

3290lm

24°

19

1005705

3250lm

36°

19

1005706

2980lm

60°

25

1005707

A
t
g E

3000 K

3530lm

24°

19

1005711

3490lm

36°

19

1005712

3210lm

60°

25

1005713

A
t
g E

4000 K

3800lm

24°

19

1005717

3760lm

36°

19

1005718

3460lm

60°

25

1005719

A
t
g F

2700 K

3290lm

24°

19

1005777

3250lm

36°

19

1005778

2980lm

60°

25

1005779

A
t
g E

3000 K

3530lm

24°

19

1005783

3490lm

36°

19

1005784

3210lm

60°

25

1005785

A
t
g E

4000 K

3800lm

24°

19

1005789

3760lm

36°

19

1005790

3460lm

60°

25

1005791

A
t
g F

2700 K

3290lm

24°

19

1005708

3250lm

36°

19

1005709

2980lm

60°

25

1005710

A
t
g E

3000 K

3530lm

24°

19

1005714

3490lm

36°

19

1005715

3210lm

60°

25

1005716

A
t
g E

4000 K

3800lm

24°

19

1005720

3760lm

36°

19

1005721

3460lm

60°

25

1005722

A
t
g F

2700 K

3290lm

24°

19

1005780

3250lm

36°

19

1005781

2980lm

60°

25

1005782

A
t
g E

3000 K

3530lm

24°

19

1005786

3490lm

36°

19

1005787

3210lm

60°

25

1005788

A
t
g E

4000 K

3800lm

24°

19

1005792

3760lm

36°

19

1005793

3460lm

60°

25

1005794





TIMELESS CLASSICS

PERFECT TABLE AND FLOOR LAMPS
FOR EVERY ROOM.

Classic lamps: our table and floor lamps blend seamlessly into any interior thanks to their simple, slimline design, making them the perfect elegant choice for an office, living room or retail outlet.





155540 + 155592 105 + 107




1002146 109



1003029 + 1000764 99 + 107



TABLE AND FLOOR LAMPS



You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808

WORKLIGHT
TL

NEW



200-240V ~50/60Hz | 2000mA
Total wattage: 79W
Material: aluminium

- Euro plug
- Clamping range: 6–40 mm






Up/Down	3800lm 4000K	

Options Prod. no.

Up: 3800lm | 4000K | CRI80
Down: 3800lm | 4000K | CRI80
■ black 1005392 ■

WORKLIGHT
TL

NEW



200-240V ~50/60Hz | 2000mA
Total wattage: 79W
Material: aluminium

- Euro plug
- Clamping range: 6–40 mm



Up/Down	3800lm 4000K	

Options Prod. no.

Up: 3800lm | 4000K | CRI80
Down: 3800lm | 4000K | CRI80
□ white 1005394 ■








1005392 100



1005390 101

WORKLIGHT
FL

NEW



200-240V ~50/60Hz | 2000mA
Total wattage: 79W
Material: aluminium

- Euro plug



		A → G
Up/Down	3800lm 4000K	A ↑ G E



Options

Prod. no.

Up: 3800lm | 4000K | CRI80
Down: 3800lm | 4000K | CRI80
■ black 1005390 ■

WORKLIGHT
FL

NEW



200-240V ~50/60Hz | 2000mA
Total wattage: 79W
Material: aluminium

- Euro plug



		A → G
Up/Down	3800lm 4000K	A ↑ G E

Options

Prod. no.

Up: 3800lm | 4000K | CRI80
Down: 3800lm | 4000K | CRI80
□ white 1005391 ■



SLV FENDA. MIX & MATCH.



MIX & MATCH

MIX&MATCH Video



bit.ly/slv-mix-match








1003029 + 100763 99 + 106



1004773 + 155780 155 + 104



1003032 + 1004774 104 + 107

FENDA
TL, E27

220-240V ~50/60Hz
Material: steel

- Euro plug and switch



E27 <60W





LED E27 | 7,5W | 320°
2700K | 700lm | EEK=F
8kWh/1000h



Prod. no. 1005304

Options	Prod. no.
1xE27	
■ black	155780
1xE27	
□ white	1003030 ▼
1xE27	
■ metal	155785

FENDA
FL, E27

220-240V ~50/60Hz
Material: steel

- Euro plug and switch



E27 <60W



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h



Prod. no. 1005301

Options	Prod. no.
1xE27	
■ black	155790
1xE27	
□ white	1003031 ▼
1xE27	
■ metal	155795

1003030 + 1004773 104 + 107






155790 + 156110 104 + 107







155540 + 155592 105 + 107

FENDA
TL, E27220-240V ~50/60Hz
Material: aluminium

- Euro plug

FENDA
FL, E27220-240V ~50/60Hz
Material: aluminium

- Euro plug

155490 + 1004775 105 + 107



E27 <40W

LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005265



Options	Prod. no.
1xE27	
■ black	155540
1xE27	
□ white	1003032 ▼



E27 <40W

LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302




Options	Prod. no.
1xE27	
■ black	155490
1xE27	
□ white	1003033 ▼
1xE27	
■ chrome	155492 ▼

FENDA BOW BASIS
FL, E27

SOCKET
INSIDE



<25
W



IP 20



IK03



180°



200

220-240V ~50/60Hz
Material: steel

- Max. shade weight 900g
- Euro plug and switch



E27 <25W L: 17.5 cm



LED E27 | 7.5W | 320°
2700K | 700lm | EEK=F
8kWh/1000h



Prod. no. 1005304

Options	Prod. no.
1xE27 ■ black	1003029
1xE27 □ white	1003028 ▼
1xE27 ■ chrome	1000763



1003028 + 156111 106 + 107


FENDA
 15 cm, round

NEW VARIANT


H: 40 cm
 Diameter: 15 cm
 Material: textile/steel

Options	Prod. no.
black/copper	156152
white	156141
beige	156143
grey	1004773

FENDA
 30 cm, round

NEW VARIANT


H: 20 cm
 Diameter: 30 cm
 Material: textile/steel

Options	Prod. no.
black/copper	155592
white	155582
beige	155583
grey	1004774

FENDA
 45 cm, round

NEW VARIANT


H: 28 cm
 Diameter: 45.5 cm
 Material: textile/steel

Options	Prod. no.
black/copper	156122
white	156111
beige	156113
grey	1004775

FENDA
 Diameter 70 cm, round


IP 20

H: 36 cm
 Diameter: 70 cm
 Material: textile/steel

- Max. 20W

Options	Prod. no.
black/copper	1000580
white	1000579


FENDA
 Diameter 40 cm, round




IP 20

H: 30 cm
 Diameter: 40 cm
 Material: poly (methyl methacrylate) (PMMA)

- Max. 40W




Options	Prod. no.
white	1000764



KARPO
TL

100-240V ~50/60Hz | 500mA
Total wattage: 6.5W
Material: aluminium

- Plug-in power supply

KARPO
FL

100-240V ~50/60Hz | 500mA
Total wattage: 6.5W
Material: aluminium


- Plug-in power supply



Options	Prod. no.
330lm 3000K CRI80	
black	1001461
400lm 3000K CRI90	
white	1001460



Options	Prod. no.
330lm 3000K CRI80	
black	1001463
400lm 3000K CRI90	
white	1001462







1001676 109




1002146 109

FITU
TL, E27FITU
FL, E27<10
W

IP 20 IK03 200

220-240V ~50/60Hz
Material: aluminium

- Euro plug and switch

<24
W

IP 20 IK03 200

220-240V ~50/60Hz
Material: aluminium/steel

- Euro plug and switch





E27 <10W

LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005265

Options	Prod. no.
1xE27	
■ black	1001676

Options	Prod. no.
1xE27	
■ black	1002146

PHELIA
TL, QPAR51PHELIA
FL, E27

230V ~50/60Hz
Material: aluminium/steel

- Safety plug and switch



GU10 <35W
Diameter: 5 cm L: 10.5 cm






LED GU10 | 3.2W
2700K | 270lm | EEC=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ black	146000



230V ~50/60Hz
Material: aluminium/steel

- Safety plug and switch

Options	Prod. no.
1xE27	
■ black	146010



146000

110



146010





110



1002404 111



1002405 111

MECANICA PLUS
TL




220-240V ~50/60Hz | 12V
Total wattage: 7.9W
Material: aluminium

- Plug-in power supply



1002404	520-610lm 2700-6500K	

Options	Prod. no.
520-610lm 2700-6500K CRI80	
■ black	1002404

MECANICA PLUS
FL




220-240V ~50/60Hz | 12V
Total wattage: 7.9W
Material: aluminium

- Plug-in power supply



1002405	520-610lm 2700-6500K	

Options	Prod. no.
520-610lm 2700-6500K CRI80	
■ black	1002405

TONILA
TL

5V battery operation
Total wattage: 1.6W
Material: aluminium/plastic

- Battery 3.6V 2000mAh included
- Power adapter excl. USB charger 5V DC/1-2A required
- For MINI-USB charging cable
- Can be dimmed to 3 different levels using the switch



		A → G
1002583	90lm 2700K	A G

Options Prod. no.

90lm | 2700K | CRI80
■ black

1002583





1002583 112



1002583 112



1004970 113

MAGANDA
TL

IP 44

IK 02

L70B50

340°

90°

200

100-240V ~50/60Hz | 12V

Total wattage: 4.8W

Material: steel/glass

- Safety plug
- 3 colour temperature options via button



		A → G
1004970	45/48/51lm 2700/3000/4000K	A ↑ G F

Options

Prod. no.

45/48/51lm | 2700/3000/4000K | CRI90

■ chrome/frosted **1004970**



ATTENTION- GRABBING HIGHLIGHTS.

PENDANT LIGHTS ADD EMPHASIS.

Give every room an individual feel: with pendant lights, you can immerse selected areas in atmospheric light, adding optical highlights thanks to a wide variety of styles. Be it in restaurants, cafés, bars or at home, these lights create pleasant environments and make a tasteful statement.





135120


131




Pendant lights from the NUMINOS® down and spotlight system can be found on pages 88 to 95. Or for easy online configuration, visit:
www.numinos.slv.com

1005715 + 1006170 95 + 94

PENDANT LIGHTS






NEW		NEW						NEW VARIANT		
	118		118	119	120	120	121		121	122
		NEW VARIANT								
	123		123	128	128	129	130	131	131	
										
	131	132	133	133	134	134	134	134	135	
										
	136	136	136	137	138	139	140	140	140	
										
	141	141	142	143	143	144	144	144	145	



You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808

ONE LINEAR 100
PD, PHASE, up/down

NEW







180

220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel

ONE LINEAR 140
PD, PHASE, up/down

NEW



180

220-240V ~50/60Hz | 900mA
Total wattage: 35W
Material: aluminium/steel



		A → G
Up	550/580lm 2700/3000K	A ↑ G F
Down	670/700lm 2700/3000K	A ↑ G F


Options	Prod. no.
Up: 550/580lm 2700/3000K CRI90 Down: 700/670lm 2700/3000K CRI90	
■ black	1006185
Up: 550/580lm 2700/3000K CRI90 Down: 700/670lm 2700/3000K CRI90	
□ white	1006186
Up: 550/580lm 2700/3000K CRI90 Down: 700/670lm 2700/3000K CRI90	
■ brass	1006187




		A → G
Up	830/860lm 2700/3000K	A ↑ G F
Down	980/1015lm 2700/3000K	A ↑ G F

Options	Prod. no.
Up: 830/860lm 2700/3000K CRI90 Down: 980/1015lm 2700/3000K CRI90	
■ black	1006188
Up: 830/860lm 2700/3000K CRI90 Down: 980/1015lm 2700/3000K CRI90	
□ white	1006189
Up: 830/860lm 2700/3000K CRI90 Down: 980/1015lm 2700/3000K CRI90	
■ brass	1006190







1006188 118



1002913 119





ONE TRIPLE
PD, DALI

220-240V ~50/60Hz | 1700mA
Total wattage: 64W
Material: aluminium/steel






		A → G
1002913, 1002914	4040/4200lm 3000/4000K	A E

Options	Prod. no.
4040/4200lm 3000/4000K CRI90	
■ black	1002913
4040/4200lm 3000/4000K CRI90	
□ white	1002914

ONE 60
PD, DALI

220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel

ONE 80
PD, DALI

220-240V ~50/60Hz | 800mA
Total wattage: 32W
Material: aluminium/steel



Options	Prod. no.
1480/1550lm 3000/4000K CRI90	
■ black	1002909
1480/1550lm 3000/4000K CRI90	
□ white	1002910




Options	Prod. no.
1930/2140lm 3000/4000K CRI90	
■ black	1002911
1930/2140lm 3000/4000K CRI90	
□ white	1002912

Options	Prod. no.
1480/1550lm 3000/4000K CRI90	
■ black	1002909
1480/1550lm 3000/4000K CRI90	
□ white	1002910




Options	Prod. no.
1930/2140lm 3000/4000K CRI90	
■ black	1002911
1930/2140lm 3000/4000K CRI90	
□ white	1002912



1004759 121



1005177 121

ONE 60
PD, DALI, up/down

220-240V ~50/60Hz | 600mA
Total wattage: 25W
Material: aluminium/steel



Up/Down	400/410lm 3000/4000K	

Options

Prod. no.

Up: 400/410lm | 3000/4000K | CRI90
Down: 400/410lm | 3000/4000K | CRI90




■ black 1004761

Up: 400/410lm | 3000/4000K | CRI90
Down: 400/410lm | 3000/4000K | CRI90

□ white 1004762

ONE 60
PD, PHASE, up/down

NEW VARIANT



220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel



Up/Down	410/415lm 2700/3000K	

Options

Prod. no.

Up: 410/415lm | 2700/3000K | CRI90
Down: 410/415lm | 2700/3000K | CRI90



■ black 1004759

Up: 410/415lm | 2700/3000K | CRI90
Down: 410/415lm | 2700/3000K | CRI90

□ white 1004760

Up: 410/415lm | 2700/3000K | CRI90
Down: 410/415lm | 2700/3000K | CRI90

■ brass 1005177

**ONE 80**
PD, DALI, up/down

130°

130°

300

220-240V ~50/60Hz | 800mA
Total wattage: 34W
Material: aluminium/steel



Up/Down	615/635lm 3000/4000K	

Options**Prod. no.**

Up: 615/635lm | 3000/4000K | CRI90
Down: 615/635lm | 3000/4000K | CRI90

■ black **1004763**

Up: 615/635lm | 3000/4000K | CRI90
Down: 615/635lm | 3000/4000K | CRI90

□ white **1004764**







1004767 123



1005178 123

ONE DOUBLE
PD, DALI, up/down

220-240V ~50/60Hz | 1400mA
Total wattage: 55W
Material: aluminium/steel



		A → G
Up/Down	1050/1060lm 3000/4000K	A G E

Options

Prod. no.

Up: 1050/1060lm | 3000/4000K | CRI90
Down: 1050/1060lm | 3000/4000K | CRI90




■ black 1004767

Up: 1050/1060lm | 3000/4000K | CRI90
Down: 1050/1060lm | 3000/4000K | CRI90

□ white 1004768

ONE DOUBLE
PD, PHASE, up/down

NEW VARIANT



220-240V ~50/60Hz | 900mA
Total wattage: 35W
Material: aluminium/steel



		A → G
Up/Down	615/635lm 2700/3000K	A G E

Options

Prod. no.

Up: 615/635lm | 2700/3000K | CRI90
Down: 615/635lm | 2700/3000K | CRI90

■ black 1004765

Up: 615/635lm | 2700/3000K | CRI90
Down: 615/635lm | 2700/3000K | CRI90

□ white 1004766

Up: 615/635lm | 2700/3000K | CRI90
Down: 615/635lm | 2700/3000K | CRI90

■ brass 1005178



MEDO LUMINAIRE FAMILY.

PENDANT OR CEILING LIGHTS.

	MEDO 30 CL, 1-10V	MEDO 40 CL, 1-10V	MEDO 60 CL, 1-10V	MEDO 90 CL, 1-10V
Example				
Lamp				
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm
Light strength	1000lm	2000lm	3500lm	11000lm
UGR	25	25	22	25
Dimmable	1-10V	1-10V	1-10V	1-10V
Suspension set (not included)	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m

	MEDO 30 CL, PHASE	MEDO 40 CL, PHASE	
Example			
Lamp			
Size	Diameter: 30 cm	Diameter: 40 cm	
Light strength	1200lm	2125lm	
UGR	25	25	
Dimmable	C, L	C, L	
Suspension set (not included)	1.5 m 5 m	1.5 m 5 m	



		MEDO 60 CL, square, 1-10V	MEDO 60 CL, square, DALI	
Example				
Lamp				
Size		W L: 60 cm	W L: 60 cm	
Light strength		3300 lm	3300 lm	
UGR		22	22	
Dimmable		1-10V		
Suspension set (not included)		1.5 m 5 m	1.5 m 5 m	


		MEDO RING 60 PD, 1-10V	MEDO RING 90 PD, 1-10V	MEDO RING 60 PD, DALI
Example				
Lamp				
Size		Diameter: 60 cm	Diameter: 90 cm	Diameter: 60 cm
Light strength		2000lm	3945lm	2000lm
UGR		–	–	22
Dimmable		1-10V	1-10V	
Suspension kit		not necessary, (incl.) – pure pendant light	not necessary, (incl.) – pure pendant light	not necessary, (incl.) – pure pendant light

MEDO LUMINAIRE FAMILY.

PENDANT OR CEILING LIGHTS.

	MEDO 30 AMBIENT CW, PHASE	MEDO 40 AMBIENT CW, PHASE	MEDO 60 AMBIENT CW, PHASE	MEDO 90 AMBIENT CL, PHASE	
Example					
Lamp					
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm	
Light strength	Down: 1230/1280lm Up: 20lm	Down: 2750/2900lm Up: 50lm	Down: 4350/4750lm Up: 120lm	Down: 9500/10100lm Up: 125lm	
UGR	25	25	25	25	
Dimmable	C	C	C	C	
Suspension set (not included)	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	



	MEDO 30 AMBIENT CW, DALI	MEDO 40 AMBIENT CW, DALI	MEDO 60 AMBIENT CW, DALI	MEDO 90 AMBIENT CL, DALI	
Example					
Lamp					
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm	
Light strength	Down: 1230/1280lm Up: 20lm	Down: 2750/2900lm Up: 50lm	Down: 4350/4750lm Up: 120lm	Down: 9500/10100lm Up: 125lm	
UGR	25	25	25	25	
Dimmable					
Suspension set (not included)	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	






Ambient effect – These MEDO variants produce even and indirect light in an upwards direction.



Colour temperature – With this MEDO variant, you can select the colour temperature yourself. The switch on the reverse can be used to choose between 3000k and 4000k.

MEDO RING 60
PD, 1-10V

220-240V ~50/60Hz | 700mA
Total wattage: 33W
Material: aluminium/poly (methyl methacrylate) (PMMA)

MEDO RING 90
PD, 1-10V

120-277V ~50/60Hz | 1200mA
Total wattage: 56W
Material: aluminium/poly (methyl methacrylate) (PMMA)

Lighting options		
		A → G
133840, 133841	2200lm 3000K	A G E


1-10V dimming
Prod. no. 470505

Options	Prod. no.
2200lm 3000K CRI80 ■ black	133840
2200lm 3000K CRI80 □ white	133841

Lighting options		
		A → G
133850, 133851	4900lm 3000K	A G E

1-10V dimming
Prod. no. 470505

Options	Prod. no.
4900lm 3000K CRI80 ■ black	133850
4900lm 3000K CRI80 □ white	133851



133840 128





133850 128



1002890 129

MEDO RING 60 PD, DALI



220-240V ~50/60Hz | 700mA

Total wattage: 34W

Material: aluminium/poly (methyl methacrylate) (PMMA)





		A → G
1002890, 1002891	2000lm 2095lm 3000K	A → G E

Options	Prod. no.
2000lm 3000K CRI80	
■ black	1002890
2095lm 3000K CRI80	
□ white	1002891



1000864 131

135174 131

MEDO 30
CL, 1-10V

220-240V ~50/60Hz | 350mA
 Total wattage: 15W
 Material: aluminium/poly (methyl methacrylate) (PMMA)
 • Suspension set not included





		A → G
1000855, 1000856, 1000857	1000lm 3000K	A G D



☒ Suspension set 1.5m Prod. no. 135250	
☐ Suspension set 1.5m Prod. no. 135251	
☒ Suspension set 1.5m Prod. no. 135254	
☐ 1-10V dimming Prod. no. 470505	
☐ Suspension set 5m Prod. no. 1001950	
☒ Suspension set 5m Prod. no. 1001951	
☒ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
1000lm 3000K CRI80	
☒ black	1000855
1000lm 3000K CRI80	
☐ white	1000856
1000lm 3000K CRI80	
☒ grey	1000857

MEDO 40
CL, 1-10V

220-240V ~50/60Hz | 700mA
Total wattage: 28W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included






		A → G
1000864, 1000865, 1000866	2450lm 3000K	A G E



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
2450lm 3000K CRI80	
■ black	1000864
2450lm 3000K CRI80	
□ white	1000865
2450lm 3000K CRI80	
■ grey	1000866

MEDO 60
CL, 1-10V

220-240V ~50/60Hz | 1000mA
Total wattage: 38W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included





		A → G
135120, 135121, 135124	4000lm 3000K	A G D



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
4000lm 3000K CRI80	
■ black	135120
4000lm 3000K CRI80	
□ white	135121
4000lm 3000K CRI80	
■ grey	135124

MEDO 90
CL, 1-10V

220-240V ~50/60Hz | 2900mA
Total wattage: 109W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included



		A → G
135170, 135171, 135174	11560lm 3000K	A G D






■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
11560lm 3000K CRI80	
■ black	135170
11560lm 3000K CRI80	
□ white	135171
11560lm 3000K CRI80	
■ grey	135174



MEDO 60

CL, square, 1-10V



220-240V ~50/60Hz | 1000mA

Total wattage: 39W

Material: aluminium/acrylic

• Suspension set not included



1000725, 1000726, 1000727	3800lm 3000K	



■ Suspension set 1.5m Prod. no. 135250		
□ Suspension set 1.5m Prod. no. 135251		
■ Suspension set 1.5m Prod. no. 135254		
□ 1-10V dimming Prod. no. 470505		
□ Suspension set 5m Prod. no. 1001950		
■ Suspension set 5m Prod. no. 1001951		
■ Suspension set 5m Prod. no. 1001952		




Options	Prod. no.
3800lm 3000K CRI80	
■ black	1000725
3800lm 3000K CRI80	
□ white	1000726
3800lm 3000K CRI80	
■ grey	1000727





135074

133

MEDO 30
CL, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 16W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included






		A → G
135020, 135021, 135024	1200lm 3000K	A D



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
1200lm 3000K CRI80 ■ black	135020
1200lm 3000K CRI80 □ white	135021
1200lm 3000K CRI80 ■ grey	135024

MEDO 40
CL, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 28W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included






		A → G
135070, 135071, 135074	2450lm 3000K	A E



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
2450lm 3000K CRI80 ■ black	135070
2450lm 3000K CRI80 □ white	135071
2450lm 3000K CRI80 ■ grey	135074




MEDO 30 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	1270/1320lm 3000/4000K	A → G
		A ↑ G

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
■ black	1001877
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
□ white	1001881
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
■ grey	1001882




MEDO 40 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	2750/3000lm 3000/4000K	A → G
		A ↑ G

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
■ black	1001883
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
□ white	1001884
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
■ grey	1001885



MEDO 60 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 1050mA
Total wattage: 40W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	4720/5240lm 3000/4000K	A → G
		A ↑ G

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
■ black	1001886
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
□ white	1001887
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
■ grey	1001888

MEDO 90 AMBIENT
CL, PHASE

220-240V ~50/60Hz | 1050mA

Total wattage: 78W

Material: aluminium/polycarbonate (PC)

• Suspension set not included



		A → G
Up/Down	9750/10350lm 3000/4000K	A T G D



■ Suspension set 1.5m

Prod. no. 135250

□ Suspension set 1.5m

Prod. no. 135251

■ Suspension set 1.5m

Prod. no. 135254

□ Suspension set 5m

Prod. no. 1001950

■ Suspension set 5m

Prod. no. 1001951

■ Suspension set 5m




Prod. no. 1001952

Options	Prod. no.
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
■ black	1001878
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
□ white	1001879
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
■ grey	1001880



1001886

135




MEDO 30 AMBIENT
CW, DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	1230/1280lm 3000/4000K	A → G C
---------	---------------------------	------------

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
■ black	1001889
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
□ white	1001893
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
■ grey	1001894




MEDO 40 AMBIENT
CW, DALI

220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	2800/2950lm 3000/4000K	A → G C
---------	---------------------------	------------

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
■ black	1001895
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
□ white	1001896
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
■ grey	1001897

MEDO 60 AMBIENT
CW, DALI

220-240V ~50/60Hz | 1000mA
Total wattage: 37W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	4470/4870lm 3000/4000K	A → G C
---------	---------------------------	------------




■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
■ black	1001898
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
□ white	1001900
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
■ grey	1001899



1001898 136

MEDO 90 AMBIENT CL, DALI



220-240V ~50/60Hz | 1000mA
Total wattage: 78W
Material: aluminium/polycarbonate (PC)
• Suspension set not included






		A → G
Up/Down	9625/10225lm 3000/4000K	A G



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
■ black	1001890
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
□ white	1001891
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
■ grey	1001892

**MEDO 60**
CL, square, DALI

220-240V ~50/60Hz | 1000mA
Total wattage: 39W
Material: aluminium/acrylic




		A → G
1002882	3800lm 3000K	A G E



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
3800lm 3000K CRI80	
□ white	1002882




1002882 138



1002858 139



1002858 139

MALANG
CW

100-240V ~50/60Hz | 24V
Total wattage: 39W
Material: aluminium / polyethylene (PE)

- Can be controlled and dimmed with SLV VALETO remote control 1002994 or Gateway 1002411
- Ring light and panel can be controlled separately (Zigbee 3.0)







The energy efficiency class information for this product was not available at the time of printing. The latest product data can always be found at www.slv.com







■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	
□ SLV VALETO® remote control, CCT/RGBW Prod. no. 1002994	

Options	Prod. no.
Ring: 350lm RGB+W (3000K) CRI80	
Panel: 2100-2400lm 2700-6500K CRI80	
□ white	1002858

**I-PENDANT PRO**
PD, 1195x295mm, DALI

100-277V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate)
(PMMA)

I-PENDANT PRO
PD, 1195x295mm, DALI



100-240V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate)
(PMMA)



Options	Prod. no.
3750lm 3000K CRI80 white	1003048
3750lm 3000K CRI80 grey	1003050



Options	Prod. no.
3800lm 4000K CRI90 white	1003049
3800lm 4000K CRI90 grey	1003051






1003047 141





1003044 141

PANEL 60 PD, round, DALI



100-277V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate) (PMMA)

PANEL 60 PD, round, DALI



100-277V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate) (PMMA)






		A → G
1003046, 1003047	3150lm 3350lm 3000K 4000K	A ↑ G E

Options	Prod. no.
3150lm 3000K CRI90 ■ grey	1003046
3350lm 4000K CRI90 ■ grey	1003047



		A → G
1003044, 1003045	3150lm 3350lm 3000K 4000K	A ↑ G E

Options	Prod. no.
3150lm 3000K CRI80 □ white	1003044
3350lm 4000K CRI80 □ white	1003045

NOYA
PD, PHASE


220-240V ~50/60Hz | 700mA
Total wattage: 32W
Material: aluminium/polycarbonate (PC)



1003530, 1003532	1861/2025lm 2700/3000K	

Options	Prod. no.
1861/2025lm 2700/3000K CRI90	
■ black	1003530
1861/2025lm 2700/3000K CRI90	
□ white	1003532








1001403 143



1001406 143

GLENOS
PD, 1m, 1-10V

220-240V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/plastic

GLENOS
PD, 2m, 1-10V

220-240V ~50/60Hz | 1000mA
Total wattage: 85W
Material: aluminium/plastic



		A → G
1001400, 1001403	2850lm 3300lm 3000 4000K	A f G E



1-10V dimming
Prod. no. 470505

Options	Prod. no.
2850lm 3000K CRI80	
■ black	1001400
3300lm 4000K CRI80	
■ black	1001403



		A → G
1001406, 1001409	5700lm 6600lm 3000 4000K	A f G E





1-10V dimming
Prod. no. 470505

Options	Prod. no.
5700lm 3000K CRI80	
■ black	1001406
6600lm 4000K CRI80	
■ black	1001409






Q-LINE® PD, 1m, BAP, PHASE



220-240V ~50/60Hz | 900mA
Total wattage: 46W
Material: aluminium/plastic

Q-LINE® PD, 2m, BAP, PHASE



220-240V ~50/60Hz | 900mA
Total wattage: 93W
Material: aluminium/plastic



Options	Prod. no.
1000927, 1000926	2100lm 3000K
	A → G
	A → F

Options	Prod. no.
2100lm 3000K CRI90	
■ black	1000927
2100lm 3000K CRI90	
□ white	1000926



Options	Prod. no.
1000930, 1000929	4200lm 3000K
	A → G
	A → F




Options	Prod. no.
4200lm 3000K CRI90	
■ black	1000930
4200lm 3000K CRI90	
□ white	1000929






1000927 144






1000930 144

Q-LINE®
PD, 1m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 46W
Material: aluminium/plastic

Q-LINE®
PD, 2m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 93W
Material: aluminium/plastic

Q-LINE®
PD, DALI, single

220-240V ~50/60Hz | 700mA
Total wattage: 47W
Material: aluminium/acrylic



Options	Prod. no.
1000933, 1000932	2300lm 4000K
■ black	1000933
□ white	1000932

Options	Prod. no.
2300lm 4000K CRI90	
■ black	1000933
2300lm 4000K CRI90	
□ white	1000932



Options	Prod. no.
1000936, 1000935	4600lm 4000K
■ black	1000936
□ white	1000935

Options	Prod. no.
4600lm 4000K CRI90	
■ black	1000936
4600lm 4000K CRI90	
□ white	1000935





Options	Prod. no.
1001309, 1001310	3700lm 3000K
■ black	1001309
□ white	1001310

Options	Prod. no.
3700lm 3000K CRI80	
■ black	1001309
3700lm 3000K CRI80	
□ white	1001310

WORKLIGHT
PD, DALI

NEW

CRI
80

L80B10 250

200-240V ~50/60Hz | 1500mA

Total wattage: 57W

Material: aluminium



Up	2000lm 4000K	A → G
Down	3000lm 4000K	A → G

Options

Prod. no.

Up: 2000lm | 4000K | CRI80
Down: 3000lm | 4000K | CRI80

■ black 1005395 ■

Up: 2000lm | 4000K | CRI80
Down: 3000lm | 4000K | CRI80

□ white 1005396 ■







1004744 + 1004672 151 + 147



1004744 + 1004672 151 + 147

OCULUS

PD, single, PHASE



220-240V ~50/60Hz | 250mA

Total wattage: 11W



Material: aluminium/glass

- Additional frosted lens included
- Matching accessories can be found on page 151




1004672, 1004673	36-780lm 2000-3000K	A → G F
------------------	------------------------	------------


Options	Prod. no.
36-780lm 2000-3000K CRI90	
■ black	1004672
36-780lm 2000-3000K CRI90	
□ white	1004673

SUPROS 78
PD

220-240V ~50/60Hz | 250mA
Total wattage: 12W
Material: aluminium

SUPROS
PD

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium

SUPROS
PD

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium



Product	Light Output	Color Temperature
133120, 133121	700lm	3000K



□ Lens 20°
Prod. no. 116302
□ Lens 40°
Prod. no. 116304



Product	Light Output	Color Temperature
1003275, 1003276	2600lm	3000K



■ Reflector 20°
Prod. no. 114102
■ Reflector 40°
Prod. no. 114104



Product	Light Output	Color Temperature
1003277, 1003278	2700lm	3000K






■ Reflector 20°
Prod. no. 114102
■ Reflector 40°
Prod. no. 114104




Options	Prod. no.
700lm 3000K CRI80	
■ black	133120
700lm 3000K CRI80	
□ white	133121

Options	Prod. no.
2600lm 3000K CRI90	
■ black	1003275
2600lm 3000K CRI80	
□ white	1003276

Options	Prod. no.
2700lm 4000K CRI90	
■ black	1003277
2700lm 4000K CRI90	
□ white	1003278

SUPROS
PD

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium

SUPROS
PD

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium



133121

148



1003275

148



Product	Light Output	Color Temperature
1003279, 1003280	3380lm	3000K



Reflector 20° Prod. no. 114102	
Reflector 40° Prod. no. 114104	

Options	Prod. no.
3380lm 3000K CRI90	
■ black	1003279
3380lm 3000K CRI90	
□ white	1003280





Product	Light Output	Color Temperature
1003281, 1003282	3520lm	3000K



Reflector 20° Prod. no. 114102	
Reflector 40° Prod. no. 114104	

Options	Prod. no.
3520lm 4000K CRI90	
■ black	1003281
3520lm 4000K CRI90	
□ white	1003282

FITU PD, E27



IP 20 500

220-240V ~50/60Hz
Material: aluminium

- Textile cable
- Open cable end






E27 <60W


LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h


Prod. no. 1005303

Options	Prod. no.
1xE27	
■ black	132690
1xE27	
□ white	132691
1xE27	
■ gold	1002168

FITU PD, E27



IP 20 500

220-240V ~50/60Hz
Material: aluminium

- Textile cable
- Open cable end




E27 <60W


LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h


Prod. no. 1005265

Options	Prod. no.
1xE27	
■ black	1002558
1xE27	
□ white	1002562
1xE27	
■ gold	1002564
1xE27	
□ aluminium	1002563



132691 150



1002558 150



FITU MIX & MATCH ACCESSORIES

Fitu single ceiling rose

16A max.
steel
H: 3.9 cm
Diameter: 8.5 cm
Incl. strain relief



Options	Prod. no.
■ black	132600
□ white	132601
■ chrome	132605
■ gold	1002163

Fitu triple ceiling rose

16A max.
steel
H: 5.4 cm
Diameter: 22 cm
Incl. strain relief



Options	Prod. no.
■ black	132610
□ white	132611
■ chrome	132615 ▼
■ gold	1002164

Fitu quintuple ceiling rose

16A max.
steel
H: 6 cm
Diameter: 33 cm
Incl. strain relief



Options	Prod. no.
■ black	132620
□ white	132621
■ chrome	132625 ▼
■ gold	1002165

Ceiling rose 3-piece

16A max.
steel
L: 60 cm W: 8.5 cm H: 5 cm
Incl. strain relief



Options	Prod. no.
■ black	1001818
□ white	1001819
■ gold	1002264

Ceiling rose 5-piece

16A max.
steel
L: 120 cm W: 8.5 cm H: 5 cm



Options	Prod. no.
■ black	1001820
□ white	1001821
■ gold	1002265

Ceiling rose structure

16A max.
steel
H: 2.6 cm
Diameter: 9 cm



Options	Prod. no.
■ black	1004744
□ white	1004745
■ chrome	1004746

Built-in ceiling rose

16A max.
Steel/polyamide 66 (PA 66)
H: 3.3 cm
Diameter: 8.5 cm



Options	Prod. no.
■ black	1004674
□ white	1004675
■ chrome	1004676

Ceiling hook

aluminium
L: 4.6 cm
Diameter: 1.8 cm



Options	Prod. no.
■ black	132670
□ white	132671

Cable hook

aluminium
L: 3.1 cm
Diameter: 1.4 cm



Options	Prod. no.
■ black	132680
□ white	132681

1-phase light adapter

6A max.
Polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 4.2 cm
Max. mechanical load 2 kg




Options	Prod. no.
■ black	143120
□ white	143121
■ grey	143124

3-phase light adapter

10A max.
plastic
Max. mechanical load 5 kg



Options	Prod. no.
■ black	145990
□ white	1001542
■ grey	145994



132690 150


SLV FENDA. MIX & MATCH.

MIX & match


MIX&MATCH Video

bit.ly/slv-mix-match





FENDA
PD, E27



IP 20

150

220-240V ~50/60Hz
Material: steel/plastic

- Open cable end
- Matching accessories can be found on page 151



E27 <60W



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



Options	Prod. no.
1xE27 ■ black	132660
1xE27 □ white	132661
1xE27 ■ chrome	132662

FENDA
Glass shade



IP 20

H: 20 cm
Diameter: 12.5 cm
Material: glass

- Max. 25W

Options	Prod. no.
 brown	1000773
 white	1002217

FENDA
Diameter 40cm, round



IP 20

H: 30 cm
Diameter: 40 cm
Material: poly (methyl methacrylate) (PMMA)

- Max. 40W

Options	Prod. no.
☐ white	1000764





132662 + 156113 154 + 155

FENDA 15 cm, round



NEW VARIANT



H: 40 cm
Diameter: 15 cm
Material: textile/steel

Options	Prod. no.
☒ black/copper	156152
☐ white	156141
☐ beige	156143
☐ grey	1004773

FENDA 30 cm, round



NEW VARIANT



H: 20 cm
Diameter: 30 cm
Material: textile/steel

Options	Prod. no.
☒ black/copper	155592
☐ white	155582
☐ beige	155583
☐ grey	1004774



132660 + 1002217 154

FENDA 45 cm, round



NEW VARIANT



H: 28 cm
Diameter: 45.5 cm
Material: textile/steel



☐ Acrylic glass cover
Prod. no. 156100

Options	Prod. no.
☒ black/copper	156122
☐ white	156111
☐ beige	156113
☐ grey	1004775

FENDA Diameter 70 cm, round







H: 36 cm
Diameter: 70 cm
Material: textile/steel

• Max. 20W



☐ Acrylic glass cover
Prod. no. 1000957

Options	Prod. no.
☒ black/copper	1000580
☐ white	1000579

ACCANTO
PD, E27TRIADEM
PD, E27

220-240V ~50/60Hz
Material: steel/textile

220-240V ~50/60Hz
Material: steel/textile



E27 <40W L: 13 cm



E27 <60W L: 14 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h



Prod. no. 1005301



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h



Prod. no. 1005302




Options	Prod. no.
3xE27	
■ black	1002946 ▼
3xE27	
□ white	1002947 ▼

Options	Prod. no.
3xE27	
■ black	155870 ▼
3xE27	
□ white	155871 ▼






1003436 157

HELIA AMBIENT 35
PD, PHASEHELIA AMBIENT 35
PD

220-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/acrylic



500mA
Total wattage: 7.5W
Material: aluminium/acrylic

- Incl. built-in rose
- Diameter built-in rose 68 mm



Options	Prod. no.
425lm 3000K CRI90	1003436
■ black	



Options	Prod. no.
425lm 3000K CRI90	1003435
■ black	

Options	Prod. no.
425lm 3000K CRI90	1003436
■ black	


Options	Prod. no.
425lm 3000K CRI90	1003435
■ black	

HELIA 30
PD, PHASE

590|620|670lm



3000K




220-240V ~50/60Hz | 500mA
Total wattage: 9.2W
Material: aluminium

HELIA 30
PD

500|550lm



3000K

3.0
cm

500mA
Total wattage: 7.5W
Material: aluminium

- LED driver not included
- Material thickness of mounting surface:
max. 12 mm



Options	Prod. no.
152360, 152361, 1002172	590lm 670lm 620lm 3000K
	152360
	152361
	1002172



Options	Prod. no.
158400, 158401, 1002170	500lm 550lm 3000K
	158400
	158401
	1002170



LED Driver 500mA |
15W dimmable
Prod. no. 464144




Options	Prod. no.
590lm 3000K CRI90	
black	152360
670lm 3000K CRI90	
white	152361
620lm 3000K CRI90	
gold	1002172

Options	Prod. no.
500lm 3000K CRI90	
black	158400
550lm 3000K CRI90	
white	158401
550lm 3000K CRI90	
gold	1002170



158400

158





158401

158



HELIA 40 PD, PHASE





220-240V ~50/60Hz | 500mA
Total wattage: 10W
Material: aluminium



Options	Prod. no.
730lm 3000K CRI90	
■ black	152370
830lm 3000K CRI90	
□ white	152371
790lm 3000K CRI90	
■ gold	1002171

HELIA 40 PD



500mA
Total wattage: 9W
Material: aluminium

- LED driver not included
- Material thickness of mounting surface: max. 12 mm



Options	Prod. no.
700lm 3000K CRI90	
■ black	158410
720lm 3000K CRI90	
□ white	158411
720lm 3000K CRI90	
■ gold	1002169





□ LED Driver 500mA |
15W dimmable
Prod. no. 464144



Options	Prod. no.
730lm 3000K CRI90	
■ black	152370
830lm 3000K CRI90	
□ white	152371
790lm 3000K CRI90	
■ gold	1002171

Options	Prod. no.
700lm 3000K CRI90	
■ black	158410
720lm 3000K CRI90	
□ white	158411
720lm 3000K CRI90	
■ gold	1002169

ASTINA
PD, QPAR51

220-240V ~50/60Hz
Material: aluminium

- Open cable end
- Matching accessories can be found on page 151



GU10 <10W




LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004972

Options	Prod. no.
1xGU10 ■ black	1002939
1xGU10 □ white	1002937
1xGU10 ■ grey	1002938





IP 20 150





IP 20 150



Prod. no. 1005302

Options	Prod. no.
1xE27	
■ black	149388
1xE27	
□ white	149381
1xE27	
■ gold	149387

PANTILO 20
PD, E27<15
W

IP 20 250

200-240V ~50/60Hz
Material: glass

- Open cable end
- Matching accessories can be found on page 151






E27 <15W

LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h

Prod. no. 1005303

Options	Prod. no.
1xE27	
chrome	1003004
1xE27	
copper	1003005

PANTILO 28
PD, E27<15
W

IP 20 250

200-240V ~50/60Hz
Material: glass

- Open cable end
- Matching accessories can be found on page 151




E27 <15W

LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005265

Options	Prod. no.
1xE27	
chrome	1003006
1xE27	
copper	1003007








1003443 163



1003444 163

PANTILO CONVEX 29
PD, E27

SOCKET INSIDE                             

ANELA
PD, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 10W
Material: aluminium

- Reflector not included
- Luminous flux with reflector 1000809 = 500lm
Luminous flux with reflector 1000810 = 620lm
Luminous flux with reflector 1000811 = 200lm
Luminous flux with reflector 1000812 = 600lm





		A → G
1000813	220-750lm 3000K	A → G E



Reflector 28°	
Prod. no. 1000809	
Reflector 28°	
Prod. no. 1000810	
Reflector 28°	
Prod. no. 1000811	
Reflector 28°	
Prod. no. 1000812	

Options	Prod. no.
220-750lm 3000K CRI90	
glossy black	1000813

LISENNE
PD, E27

220-240V ~50/60Hz
Material: basalt/glass



E27 <23W
Diameter: 5.9 cm L: 15 cm




LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h

Prod. no. 1005268



Options	Prod. no.
1xE27	
grey	155714






133444 165



1003432 165

TONGA®
PD, E14

SOCKET INSIDE **<60 W**



IP 20 150

220-240V ~50/60Hz
Material: aluminium/glass



E14 <60W
Diameter: 5 cm L: 13 cm



LED E14 | 4.2W | 320°
2700K | 350lm | EEK=G
5kWh/1000h


Prod. no. 1005285



Options	Prod. no.
1xE14	
grey	133444

QUADRASS
PD, E27

SOCKET INSIDE **<40 W**



IP 20 250

220-240V ~50/60Hz
Material: steel/glass

- Open cable end
- Matching accessories can be found on page 151



E27 <40W
Diameter: 6.5 cm L: 18 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



Options	Prod. no.
1xE27	
chrome	1003432





PARA CONE GL **PD, GU10**

**NEW**

SOCKET
INSIDE



<25 W



220-240V ~50/60Hz
 Material: aluminium/glass

- Matching accessories can be found on page 151



GU10 <25W





LED GU10 | 3,2W
 2700K | 270lm | EEC=G
 4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ black	1006159
1xGU10	
□ white	1006160






133019 167

PARA CONE 30 PD, E27



SOCKET INSIDE **<60 W**



IP 20

150

220-240V ~50/60Hz
 Material: aluminium/steel

- Textile cable
- Black/gold version with golden reflector
- All other versions with white reflector



E27 <15W



LED E27 | 7.5W | 320°
 2700K | 800lm | EEK=F
 8kWh/1000h




Prod. no. 1005303

Options	Prod. no.
1xE27	
glossy black/gold	133060
1xE27	
copper	133019



1002949 169





133310 169

133320 169




133310 169

PHELIA 25 PD, E27



SOCKET INSIDE                             

FORCHINI 50
PD, E27



230V ~50Hz
Material: fiberglass



E27 <40W L: 20 cm




LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h



Prod. no. 1005301

Options	Prod. no.
1xE27	
 black/gold	155530

FORCHINI 70
PD, E27



220-240V ~50/60Hz
Material: fiberglass



E27 <40W L: 20 cm



G125 | 7.5W | 180°
2700K | 720lm | EEK=F
8kWh/1000h



Prod. no. 1005306

Options	Prod. no.
1xE27	
 black/gold	1001701





FORCHINI M 40 PD, E27





FORCHINI M 50 PD, E27



SOCKET INSIDE **<40 W**

SOCKET INSIDE **<40 W**



IP 20 150

230V ~50Hz
Material: aluminium/steel



IP 20 150

230V ~50Hz
Material: aluminium/steel



E27 <40W L: 15.2 cm



A60 | 7.5W | 180°
2700K | 720lm | EEK=F
8kWh/1000h



Prod. no. 1005305



E27 <40W L: 18 cm



G125 | 7.5W | 180°
2700K | 720lm | EEK=F
8kWh/1000h




Prod. no. 1005306

Options	Prod. no.
1xE27	
black/gold	155910

Options	Prod. no.
1xE27	
black/gold	155930

LIGHT EYE® 90

PD, GU10



220-240V ~50/60Hz
Material: steel

- Textile cable



GU10 <6W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972




- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151040
- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151041
- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151049



Options	Prod. no.
1xGU10	
■ black	133490
1xGU10	
□ white	133491

LIGHT EYE® 150

PD, QPAR111



220-240V ~50/60Hz
Material: steel

- Textile cable



GU10 <75W



LED GU10 | 12.5W | 60°
2700K | 1000lm | EEK=F
13kWh/1000h

Prod. no. 1005277



Options	Prod. no.
1xGU10	
■ white/chrome	133481
1xGU10	
■ chrome	133482
1xGU10	
■ copper	133489







1002045 173

SUN / BIG SUN
PD, E27

SOCKET INSIDE **<60 W**



IP 20



170

230V ~50Hz
Material: steel/glass

- Open cable end
- Matching accessories can be found on page 151



E27 <60W
Diameter: 7 cm L: 12 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEC=F
13kWh/1000h



Prod. no. 1005302

Options	Prod. no.
1xE27 Diameter: 19.5 cm	
white/chrome	1002045
1xE27 Diameter: 30 cm	
white/chrome	1002046




PLASTRA 25
PD, round, TCR-TSE



Socket Inside

<11 W



IP 20

150

230V ~50Hz
Material: plaster/steel



GX53 <11W



LED GX53 | 6.1W | 120°
4000K | 520lm | EEK=F
6kWh/1000h




Prod. no. 1005269

Options	Prod. no.
1xGX53	
☐ white	1002047

PARA DOME
PD, E27

SOCKET INSIDE **<150 W**



220-240V ~50/60Hz
Material: aluminium



E27 <150W
Diameter: 7 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301

Options	Prod. no.
1xE27	
■ black	1005214
1xE27	
■ grey	1005215

PARA DOME
Shade

H: 20.6 cm
Diameter: 30.8 cm
Material: aluminium

Options	Prod. no.
■ black	1005216
■ grey	1005217

PARA DOME
Shade

H: 20 cm
Diameter: 31.5 cm
Material: polycarbonate (PC)

Options	Prod. no.
■ transparent	1005218





1005214

176

1005218

176






165359

179



1000827 + 1000918 179

PARA 380 **PD, E27**



220-240V ~50/60Hz
Material: aluminium




E27 <20W



Prod. no. 1005302

Options	Prod. no.
1xE27	
■ black	165359
1xE27	
■ aluminium	165358

PARA FLAC **PD/CL, DALI**



220-240V ~50/60Hz | 1600mA
Total wattage: 104W
Material: aluminium/polycarbonate (PC)




- This product is supplied without a chain and can be hung with standard chains
- Open cable end

Prod. no.	12800lm 4000K	A → G
1003107		A → G E

Options	Prod. no.
■ Connection box IP68, 3-pole	
Prod. no. 228730	
■ Reflector	
Prod. no. 1000918	
■ Reflector	
Prod. no. 1001691	
■ Reflector cover	
Prod. no. 1001692	

Options	Prod. no.
12800lm 4000K CRI80	
■ black	1003107

PARA FLAC **PD/CL**



220-240V ~50/60Hz | 1600mA
Total wattage: 100W
Material: aluminium/polycarbonate (PC)

- This product is supplied without a chain and can be hung with standard chains
- Open cable end

Prod. no.	12800lm 4000K	A → G
1000827		A → G E

Options	Prod. no.
■ Connection box IP68, 3-pole	
Prod. no. 228730	
■ Reflector	
Prod. no. 1000918	
■ Reflector	
Prod. no. 1001691	
■ Reflector cover	
Prod. no. 1001692	

Options	Prod. no.
12800lm 4000K CRI80	
■ black	1000827



SURPRISINGLY VERSATILE.

WALL LIGHTS ADD INDIVIDUAL LIGHT SPOTS.

An eye-catching wall feature and a genuine highlight for the room: wall lights are an ideal, space-saving way to create spots of light. And there is something to suit every taste in the large range of designs and colours available.





1004729 233






1004682 214

WALL LIGHTS

 185	 185	 185	 185	 186	 186	 186	 187
 187	 187	 187	 188	 189	 190	 190	 190
 191	 193	 193	 193	 194	 194	 194	 196
 196	 197	 197	 198	 198	 199	 199	 200
 201	 201	 201	 202	 202	 203	 203	 204



You can find more lights and variants at www.slv.com

Manufacturer's details for our recommended lamps can be found in the chapter 'Lamps', from page 808






1004969 + 1004660 185

1004657 + 1004663 185



MANA BASE
WL, round, PHASE




220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/polycarbonate (PC)



1004657	800/820lm 2700/3000K	

Options	Prod. no.
800/820lm 2700/3000K CRI90	
■ anthracite	1004657

MANA BASE
round



Material: aluminium/polycarbonate (PC)
• Non-illuminated base for round MANA shades

Options	Prod. no.
■ anthracite	1004969

MANA 40
Shade, round



H: 6 cm
Diameter: 40 cm
Material: felt/aluminium

Options	Prod. no.
■ beige	1004660
■ grey	1004661

MANA 60
Shade, round






H: 6 cm
Diameter: 60 cm
Material: felt/aluminium

Options	Prod. no.
■ beige	1004662
■ grey	1004663



MANA WL, base, PHASE



220-240V ~50/60Hz | 350mA
 Total wattage: 8.3W
 Material: aluminium/steel

MANA Shade



IP 20

L: 12 cm H: 10 cm T: 9.0 cm
 Material: wood/aluminium

- Suitable only with 1000613

Options	Prod. no.
wood grey/brown	1000616
aluminium white	1000618
aluminium aluminium	1000619

MANA Shade



IP 20

W: 13.6 cm H: 10 cm D: 9.5 cm
 Material: plaster/steel


- Suitable only with 1000613




		A → G
1000613	520lm 2000-3000K	A G F

Options	Prod. no.
520lm 2000-3000K CRI90	
white	1000613

Options	Prod. no.
white	1000824






1000613 + 1000824 186





1000615 + 1000624 187

MANA WL, base, PHASE



220-240V ~50/60Hz | 350mA
 Total wattage: 15W
 Material: aluminium/steel

MANA WL, base



220-240V ~50/60Hz | 350/500mA
 Total wattage: 11W
 Material: aluminium/steel

- Spot can be switched separately

MANA Shade



L: 29 cm H: 9.5 cm D: 7.0 cm
 Material: wood / aluminium

- Suitable only with 1000614/1000615

Options	Prod. no.
wood grey/brown	1000621
aluminium white	1000623
aluminium aluminium	1000624

MANA Shade



W: 30.9 cm H: 9.5 cm D: 7.4 cm
 Material: plaster/steel

- Suitable only with 1000614/1000615



Options	Prod. no.
700lm 2000-3000K CRI90	
white	1000614



Options	Prod. no.
Indirect: 650lm 3000K CRI80	
Spot: 80lm 3000K CRI80	
white/chrome	1000615






W: 30.9 cm H: 9.5 cm D: 7.4 cm
 Material: plaster/steel

- Suitable only with 1000614/1000615

Options	Prod. no.
white	1000825

OCULUS UP/DOWN
WL, PHASE






220-240V ~50/60Hz | 700mA
Total wattage: 15W
Material: aluminium/glass

- Additional frosted lens included

		A → G
Up/Down	22-555lm 2000-3000K	A F

Options	Prod. no.
Up: 22-555lm 2000-3000K CRI90 Down: 22-555lm 2000-3000K CRI90	
■ black	1004670
Up: 22-555lm 2000-3000K CRI90 Down: 22-555lm 2000-3000K CRI90	
□ white	1004671



SUPROS 78 UP/DOWN
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium




Up/Down	700lm 3000K		



☐ Lens 20°	
Prod. no. 116302	
☐ Lens 40°	
Prod. no. 116304	

Options	Prod. no.
Up: 700lm 3000K CRI80 Down: 700lm 3000K CRI80	
■ black	116340
Up: 700lm 3000K CRI80 Down: 700lm 3000K CRI80	
□ white	116341



Material: plaster/steel





G9 <42W



3000K | 400lm | EEK=E
4kWh/1000h

Prod. no. 1005286

Options	Prod. no.
1xG9	
☐ white	148018



220-240V ~50/60Hz
Material: plaster/steel



G9 15W
Diameter: 7 cm L: 4 cm



LED G9 | 3.6W | 300°
3000K | 400lm | EEK=E
4kWh/1000h

Prod. no. 1005286

Options	Prod. no.
2xG9	
☐ white	1004733






1002238 191



148010 191

PLASTRA WL, rectangular, QT-DE12



IP 20

220-240V ~50/60Hz
Material: plaster/steel



R7s 118mm <20W





LED R7s | 15W | 330°
3000K | 2000lm | EEK=E
15kWh/1000h

Prod. no. 1005288



Options	Prod. no.
1xR7s 118mm	
☐ white	1002238

PLASTRA WL, E14



IP 20

220-240V ~50/60Hz
Material: plaster/steel



E14 <40W



C35 | 4.2W | 320°
2700K | 350lm | EEK=G
5kWh/1000h

Prod. no. 1005285



Options	Prod. no.
1xE14	
☐ white	148010



148060 193




148091 193



1004732 193



PLASTRA 101
WL, E14

230V ~50Hz
Material: plaster/steel




E14 <40W
Diameter: 4.5 cm L: 11 cm



LED E14 | 4.2W | 320°
2700K | 370lm | EEK=F
4kWh/1000h



Prod. no. 1005284

PLASTRA
WL, curve, QT-DE12

230V ~50Hz
Material: plaster/steel




R7s 78mm <100W



LED R7s | 9W | 330°
3000K | 1050lm | EEK=E
9kWh/1000h



Prod. no. 1005287

PLASTRA 104
WL, QT14

220-240V ~50/60Hz
Material: plaster/steel



G9 <42W



LED G9 | 4.2W | 320°
2700K | 370lm | EEK=F
4kWh/1000h

Prod. no. 1005284

Options	Prod. no.
1xE14	
☐ white	148013

Options	Prod. no.
1xR7s 78mm	
☐ white	148012


Options	Prod. no.
1xG9	
☐ white	148016






148012 194




148013 194



148016 194

LOGS IN
WLLOGS IN
WL, PHASE

100-240V ~50/60Hz | 500mA
Total wattage: 6W
Material: aluminium



220-240V ~50/60Hz | 250mA
Total wattage: 11W
Material: aluminium




Options	Prod. no.
151320, 151321, 151325	151320
300lm 470lm 3000K	151321
aluminium/white	151325




Options	Prod. no.
1000638, 1000639, 1000640	1000638
430lm 690lm 2000-3000K	1000639
aluminium/white	1000640

Options	Prod. no.
300lm 3000K CRI90	
black/gold	151320
470lm 3000K CRI90	
white	151321
470lm 3000K CRI90	
aluminium/white	151325

Options	Prod. no.
430lm 2000-3000K CRI90	
black/gold	1000638
690lm 2000-3000K CRI90	
white	1000639
690lm 2000-3000K CRI90	
aluminium/white	1000640



151325 196





1000639 196






1002928 197

LOGS IN L WL, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium

LOGS IN L WL, PHASE






220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium






Options	Prod. no.
1100lm 1600lm 3000K	1002842, 1002843, 1002844
1100lm 1600lm 3000K	1002842
1600lm 3000K CRI90	1002844
1600lm 3000K CRI90	1002843



Options	Prod. no.
1000lm 1390lm 2000-3000K	1002928, 1002929, 1002930
1000lm 1390lm 2000-3000K	1002928
1390lm 2000-3000K CRI90	1002929
1390lm 2000-3000K CRI90	1002930

QUAD FRAME 14
WL

100-277V ~50/60Hz | 350mA
Total wattage: 4W
Material: aluminium

QUAD FRAME 19
WL

100-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium



Options	Prod. no.
1003467	130/165lm 2700/3000K
	A → G F

Options Prod. no.
130/165lm | 2700/3000K | CRI90
□ white 1003467



Options	Prod. no.
1003468	540/640lm 2700/3000K
	A → G F

Options Prod. no.
540/640lm | 2700/3000K | CRI90
□ white 1003468





1000422 199




1003467 198



1000423 199

SHELL 15
WL, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/acrylic

SHELL 30
WL, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 54W
Material: aluminium/acrylic



1000422	1400lm 3000K	A → G D
---------	-----------------	------------

Options **Prod. no.**
1400lm | 3000K | CRI80
□ white **1000422**





1000423	5600lm 3000K	A → G D
---------	-----------------	------------

Options **Prod. no.**
5600lm | 3000K | CRI80
□ white **1000423**

ASSO 70

WL



⚙️

⚡

💧

🕒

🔄

IP 20

L70B50

100-240V ~50/60Hz | 500mA

Total wattage: 6W

Material: aluminium/steel

💡	🌈	A → G
151311, 151315	440lm 3000K	A ↑ G ↓ E

Options	Prod. no.
440lm 3000K CRI90	
white	151311
440lm 3000K CRI90	
aluminium/white	151315






1000636

201







1000635





201

ASSO
WL, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 11W
Material: aluminium/steel

ASSO 300
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 12W
Material: aluminium/steel

ASSO 300
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/steel



Options	Prod. no.
1000636, 1000637	700lm 2000-3000K
	1000636
	1000637

Options	Prod. no.
700lm 2000-3000K CRI90	
white	1000636
700lm 2000-3000K CRI90	
aluminium/white	1000637



Options	Prod. no.
151271, 151275	975lm 3000K
	151271
	151275

Options	Prod. no.
975lm 3000K CRI80	
white	151271
975lm 3000K CRI80	
aluminium/white	151275





Options	Prod. no.
1000634, 1000635	1340lm 2000-3000K
	1000634
	1000635

Options	Prod. no.
1340lm 2000-3000K CRI90	
white	1000634
1340lm 2000-3000K CRI90	
aluminium/white	1000635





OSSA 180
WL, QT-DE12



230V ~50Hz
Material: aluminium/steel

OSSA 300
WL, QT-DE12



230V ~50Hz
Material: aluminium/steel



R7s 78mm <100W



LED R7s | 9W | 330°
3000K | 1050lm | EEK=E
9kWh/1000h



Prod. no. 1005287

Options	Prod. no.
1xR7s 78mm	
■ black	151450
1xR7s 78mm	
□ white	151451
1xR7s 78mm	
▒ aluminium	151456



R7s 118mm <120W



LED R7s | 15W | 330°
3000K | 1960lm | EEK=E
15kWh/1000h




Prod. no. 1005288




Options	Prod. no.
1xR7s 118mm	
■ black	151410
1xR7s 118mm	
□ white	151411
1xR7s 118mm	
▒ aluminium	151416







151710 203



151740 203

CARISO
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 9.2W
Material: aluminium/steel

CARISO
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/steel



		A → G
151710, 151711	250lm 560lm 2700 3000K	A → G D


Options	Prod. no.
250lm 2700K CRI80 black/gold	151710
560lm 3000K CRI80 white	151711



		A → G
151740, 151741	580lm 1030lm 1700-2700 2000-3000K	A → G F

Options	Prod. no.
580lm 1700-2700K CRI90 black/gold	151740
1030lm 2000-3000K CRI90 white	151741

© 2006 The Authors



		
1003316, 1003317	590lm 3000K	









149511 205



149511 205

WL 149
WL, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: steel/glass

WL 149
WL, QT-DE12

220-240V ~50/60Hz
Material: steel/glass



149511	1050lm 3000K	



R7s 78mm <60W



LED R7s | 9W | 330°
3000K | 1050lm | EEK=E
9kWh/1000h



Prod. no. 1005287

Options Prod. no.



1050lm | 3000K | CRI80
□ white

149511



Options Prod. no.

R7s 78mm
□ white

149471

DIRETO 60
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 14W
Material: aluminium

DIRETO 90
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium



Up/Down	590/625lm 2700/3000K	

Options	Prod. no.
Up: 590/625lm 2700/3000K CRI90 Down: 590/625lm 2700/3000K CRI90	
■ black	1004740
Up: 590/625lm 2700/3000K CRI90 Down: 590/625lm 2700/3000K CRI90	
□ white	1004741




Up/Down	840/880lm 2700/3000K	



Options	Prod. no.
Up: 840/880lm 2700/3000K CRI90 Down: 840/880lm 2700/3000K CRI90	
■ black	1004742
Up: 840/880lm 2700/3000K CRI90 Down: 840/880lm 2700/3000K CRI90	
□ white	1004743





1004743 206





1002964 207

SEDO 7
WL

220-240V ~50/60Hz | 350mA
Total wattage: 11.5W
Material: aluminium/glass

SEDO 14
WL

220-240V ~50/60Hz | 500mA
Total wattage: 16W
Material: aluminium/glass

SEDO 21
WL

220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/glass






Options	Prod. no.
1020lm 3000K CRI80	
white	1002962
1020lm 3000K CRI80	
aluminium	1002964






Options	Prod. no.
1300lm 3000K CRI80	
white	151781
1300lm 3000K CRI80	
aluminium	151786



Options	Prod. no.
2500lm 3000K CRI80	
white	151791
2500lm 3000K CRI80	
aluminium	151796

ARLINA 60
WL

220-240V ~50/60Hz | 500mA
Total wattage: 23W
Material: aluminium/glass

ARLINA 130
WL

220-240V ~50/60Hz | 700mA
Total wattage: 28W
Material: aluminium/glass



Options	Prod. no.
1550lm 3000K CRI80	1002239
aluminium	



Options	Prod. no.
2400lm 3000K CRI90	1002240
aluminium	




1002239 208








1002240 208



1003023 209

NEW FLAT
WL, RGB-W

IP 20

110°

110°

L70B50

220-240V ~50/60Hz | 24V

Total wattage: 11.3W

Material: aluminium/acrylic

- Can be controlled with Gateway prod. no. 1002411 or remote control prod. no. 1002994.



		A → G
Up	300lm 3000K	A t G
Down	280lm 3000K	A t G

Options

Prod. no.



Up: RGB-W (300lm | 3000K | CRI>80)
Down: RGB-W (280lm | 3000K | CRI>80)

white 1003022

Up: RGB-W (300lm | 3000K | CRI>80)
Down: RGB-W (280lm | 3000K | CRI>80)

aluminium 1003023

ANDREAS
WL, QT-DE12



220-240V ~50/60Hz
Material: aluminium/steel



R7s 118mm <80W




LED R7s | 15W | 330°
3000K | 2000lm | EEK=E
15kWh/1000h



Prod. no. 1005288

Options	Prod. no.
1xR7s 118mm	
■ black	1002927
1xR7s 118mm	
□ white	1002925
1xR7s 118mm	
■ grey	1002926

1002926 210




151591 211



DENA 30
WL, E14

SOCKET INSIDE                                                        



IP 20

Material: steel/glass





E27 <40W
Diameter: 6.5 cm L: 18 cm



Prod. no. 1005301

Options	Prod. no.
1xE27	
☒ black	1003430
1xE27	
☐ white	1003431



100-240V ~50/60Hz | 700mA
Total wattage: 2W
Material: steel/glass



		
Spot	200lm 3000K	



E27 <40W
Diameter: 6.5 cm L: 18 cm



Prod. no. 1005289


Options	Prod. no.
1xE27 200lm 3000K CRI80 ■ black/milky	1003428
1xE27 200lm 3000K CRI80 □ white/milky	1003429




220-240V ~50/60Hz
Material: basalt/glass



155752

FITU
Wall bracket

Material: steel

FITU
WL, E27<24
W220-240V ~50/60Hz
Material: aluminium/steel


E27 <24W

LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h


Prod. no. 1005265

Options	Prod. no.
■ black	1004682
□ white	1004683

Options	Prod. no.
1xE27	
■ black	1002148
1xE27	
□ white	1002147
1xE27	
■ gold	1002149



1004682 214



1002149 214




FITU CUBE
WL, E27



Socket Inside

Icons representing different light bulb types: incandescent, CFL, LED, and others.

<20 W



IP 20

220-240V ~50/60Hz
Material: steel



E27 <20W
Diameter: 12.5 cm



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=E
8kWh/1000h




Prod. no. 1005309

Options	Prod. no.
1xE27	
☒ black	1004738
1xE27	
☐ white	1004739



THEO UP/DOWN WL, QPAR51



230V ~50Hz
Material: aluminium



GU10 <50W




LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h



Prod. no. 1004973

Options	Prod. no.
2xGU10	
■ anthracite	1000330
2xGU10	
□ white	1000327
2xGU10	
■ aluminium	1000329

SOLID CUBE WL, QT14



230V ~50Hz
Material: concrete



G9 <25W




LED G9 | 3.6W | 300°
3000K | 400lm | EEK=E
4kWh/1000h



Prod. no. 1005286

Options	Prod. no.
1xG9	
■ black	1000911
1xG9	
■ grey	1000910





FENDA
WL, base, E27



SOCKET INSIDE                                                             



1001450 + 1001452 218 + 219




1001272 + 1001273 218

FENDA WL, base, E27



SOCKET INSIDE



230V ~50Hz
Material: steel



E27 <40W L: 12 cm



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h





Prod. no. 1005303

Options	Prod. no.
1xE27	
■ black	1001450 ▼
1xE27	
■ chrome	1001449 ▼

FENDA WL, E27



SOCKET INSIDE



220-240V ~50/60Hz
Material: steel/aluminium



E27 <40W






LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h



Prod. no. 1005301

Options	Prod. no.
1xE27	
■ black	1003034 ▼
1xE27	
□ white	1003035 ▼

KENKUA SPOT
WL, E27

100-240V ~50/60Hz | 700mA
Total wattage: 2W
Material: steel/glass

- Light sources can be switched on/off separately at the light



		A → G
Spot	200lm 3000K	A F

E27 <40W
Diameter: 6.5 cm L: 12 cm

LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301

Options	Prod. no.
1xE27 200lm 3000K CRI80 chrome/milky	1002855

KENKUA
WL, E27

220-240V ~50/60Hz
Material: steel/glass

E27 <40W


LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302

Options	Prod. no.
1xE27 chrome/milky	1002856




155670 221




1002856 220



ACCANTO WL, E27




SOCKET INSIDE **<40 W**



IP 20

220-240V ~50/60Hz
Material: steel/textile



E27 <40W
Diameter: 8 cm L: 14 cm






LED E27 | 7.5W | 320°
2700K | 700lm | EEK=F
8kWh/1000h



Prod. no. 1005304

Options	Prod. no.
1xE27	
■ black	1002942 ▼
1xE27	
□ white	1002943 ▼

COUPA FLEX
WL

220-240V ~50/60Hz | 700mA
Total wattage: 3.4W
Material: steel/glass

- Light sources can be switched on/off separately at the light



Spot	175lm 3000K	A → G
------	----------------	-------




G9 <42W L: 9 cm



LED G9 | 3.6W | 300°
3000K | 400lm | EEK=E
4kWh/1000h

Prod. no. 1005286

Options	Prod. no.
1xG9 175 lm 3000K CRI80 chrome/milky	149452

COUPA
WL, QT14

220-240V ~50/60Hz
Material: steel/glass



G9 <42W L: 9 cm



LED G9 | 3.6W | 300°
3000K | 400lm | EEK=E
4kWh/1000h

Prod. no. 1005286

Options	Prod. no.
1xG9 chrome/milky	1002859

149452

222



1002859




222





PLASTRA

WL, square



IP 20 L70B50

100-240V ~50/60Hz | 12V

Total wattage: 10.5W

Material: plaster/steel



		A → G
148019	650lm 3000K	A F

Options

Prod. no.

650lm | 3000K | CRI80





□ white

148019



KARPO MAGN

CW, single, PHASE






220-240V ~50/60Hz | 500mA
Total wattage: 6.2W
Material: steel/aluminium

KARPO GOOSE

WL



NEW



220-240V ~50/60Hz | 12V
Total wattage: 5.8W
Material: aluminium/steel


- Light can be dimmed via switch on the lamp head




Options	Prod. no.
350lm 3000K CRI90	
black	1004706
430lm 3000K CRI90	
white	1004707




Options	Prod. no.
380lm 3000K CRI90	
black	1006162
420lm 3000K CRI90	
white	1006161





1004706 224



1006162 224

KARPO 30
WL, single

100-240V ~50/60Hz | 500mA
Total wattage: 6W
Material: aluminium/steel

KARPO
WL

220-240V ~50/60Hz | 500mA
Total wattage: 6.6W
Material: aluminium

- 2 USB connections 1.5 A max.
- 3 dimming levels via switch on base



1002140 225



		A → G
152340, 152341	370lm 400lm 3000K	A f G E

Options	Prod. no.
370lm 3000K CRI90	
■ black	152340
400lm 3000K CRI90	
□ white	152341





		A → G
1002140	390lm 3000K	A f G E

Options	Prod. no.
390lm 3000K CRI90	
□ white	1002140





SOMNILA SPOT WL, left



100-240V ~50/60Hz | 12V
Total wattage: 15W
Material: aluminium/steel

- 1 USB connection
- Light sources can be switched on/off separately on the housing

SOMNILA SPOT WL, right



100-240V ~50/60Hz | 12V
Total wattage: 15W
Material: aluminium/steel

- 1 USB connection
- Light sources can be switched on/off separately on the housing



Spot	120lm 3000K	
Indirect	370lm 650lm 3000K	

Options	Prod. no.
Spot: 120lm 3000K CRI90 Indirect: 370lm 3000K CRI90	
■ black	1003455
Spot: 120lm 3000K CRI90 Indirect: 650lm 3000K CRI90	
□ white	1003457




Spot	120lm 3000K	
Indirect	370lm 650lm 3000K	

Options	Prod. no.
Spot: 120lm 3000K CRI90 Indirect: 370lm 3000K CRI90	
■ black	1003456
Spot: 120lm 3000K CRI90 Indirect: 650lm 3000K CRI90	
□ white	1003458

1003455 226



1003457 226








1003459 227



1003460 227

SOMNILA FLEX
WL, left

100-240V ~50/60Hz | 12V
Material: aluminium/textile

- 1 USB connection
- Light sources can be switched on/off separately on the housing



		A → G
Spot	120lm 3000K	A ↑ G






E27 40W L: 18 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301

Options	Prod. no.
1xE27 120lm 3000K CRI90 □ white	1003459

SOMNILA FLEX
WL, right

100-240V ~50/60Hz | 12V
Material: aluminium/textile

- 1 USB connection
- Light sources can be switched on/off separately on the housing



		A → G
Spot	120lm 3000K	A ↑ G



E27 40W L: 18 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302

Options	Prod. no.
1xE27 120lm 3000K CRI90 □ white	1003460

DIO FLEX PLATE
WL



100-240V ~50/60Hz | 350mA
Total wattage: 1.9W
Material: aluminium

		A → G
146682, 1002116	100lm 3000K 2700K	A → G F

Options	Prod. no.
100lm 3000K CRI80 chrome	146682
100lm 2700K CRI80 chrome	1002116



1002117 228



1002116 229




PHELIA
WL, QPAR51



SOCKET
INSIDE



<35
W



IP 20



350°



90°

230V ~50/60Hz
Material: aluminium/steel



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEC=G
4kWh/1000h

Prod. no. 1004972






Options	Prod. no.
1xGU10	
■ black	148540



148540 230



1001468 231



MERADO FLOOD
WL, PHASE

220-240V ~50/60Hz | 1000mA
Total wattage: 40W
Material: aluminium



		A → G
1001468, 1001472	3000lm 3200lm 3000K 4000K	A t G E

Options	Prod. no.
3000lm 3000K CRI80	
□ white	1001468
3200lm 4000K CRI80	
□ white	1001472



MAGANDA
WL

100-240V ~50/60Hz | 12V
Total wattage: 4.8W
Material: steel/glass



1004971	45.4/48/51lm 2700/3000/4000K	




Options	Prod. no.
45.4/48/51lm 2700/3000/4000K CRI90 chrome/white	1004971



TRUKKO

WL, rectangular

NEW VARIANT





220-240V ~50/60Hz | 24V
Total wattage: 24W
Material: glass/aluminium

- Incl. mirror heating

TRUKKO

WL, rectangular






220-240V ~50/60Hz | 24V
Total wattage: 25W
Material: glass/plastic

- Incl. mirror heating

TRUKKO

WL, round



220-240V ~50/60Hz | 24V
Total wattage: 25W
Material: glass/plastic

- Incl. mirror heating



1004729	1310/1320/ 1340lm 3000/4000/ 6500K		

Options **Prod. no.**
1310/1320/1340lm | 3000/4000/6500K | CRI90
silver/milky **1004729**




1004730	1080/1290/ 1250lm 3000/4000/ 6500K		

Options **Prod. no.**
1080/1290/1250lm | 3000/4000/6500K | CRI90
silver/milky **1004730**




1004731	1270/1260/ 1260lm 3000/4000/ 6500K		

Options **Prod. no.**
1270/1260/1260lm | 3000/4000/6500K | CRI90
silver/milky **1004731**

TRUKKO 60
WL

220-240V ~50/60Hz | 500mA
Total wattage: 9.2W
Material: aluminium/plastic

TRUKKO 90
WL

220-240V ~50/60Hz | 500mA
Total wattage: 12W
Material: aluminium/plastic



		A → G
149762	750lm 3000K	A → G E

Options	Prod. no.
750lm 3000K CRI90 chrome/milky	149762



		A → G
149772	1040lm 3000K	A → G D

Options	Prod. no.
1040lm 3000K CRI90 chrome/milky	149772







1002192 235

MARYLIN 40/60/90
WL

890|1170|1800lm / 980|1280|1990lm



IP 44

120°

35 000

Hours

L70B50

220-240V ~50/60Hz | 350mA

Total wattage: 11W



Material: aluminium/polycarbonate (PC)



		A → G
1002190, 1002191, 1002192	890/980lm 1170/1280lm 1800/1990lm 3000/4000K	A E

Options	Prod. no.
890/980lm 3000/4000K CRI80 L: 40 cm chrome/milky	1002190
1170/1280lm 3000/4000K CRI80 L: 60 cm chrome/milky	1002191
1800/1990lm 3000/4000K CRI80 L: 90 cm chrome/milky	1002192



WL 106
E14

220-240V ~50/60Hz
Material: aluminium/glass




E14 <40W
Diameter: 3.6 cm L: 11 cm



LED E14 | 4.2W | 320°
2700K | 370lm | EEK=F
4kWh/1000h

Prod. no. 1005284

Options	Prod. no.
1xE14 chrome	1002228

WL 106
E14

220-240V ~50/60Hz
Material: aluminium/glass





E14 <40W
Diameter: 3.6 cm L: 11 cm



LED E14 | 4.2W | 320°
2700K | 370lm | EEK=F
4kWh/1000h

Prod. no. 1005284

Options	Prod. no.
2xE14 chrome	1002229

MIBO UP/DOWN
WL, QT14

220-240V ~50/60Hz
Material: aluminium/glass



G9 <25W






LED G9 | 3.6W | 300°
3000K | 400lm | EEK=E
4kWh/1000h

Prod. no. 1005286

Options	Prod. no.
2xG9 chrome	151282



DORISA 30



200-240V ~50Hz | 340mA
Total wattage: 5.2W
Material: aluminium/plastic

- Clamping range: 0-6 mm. Can be converted to a mirror light by removing the bracket



		A → G
1000777	300lm 4000K	A ↑ G E

Options	Prod. no.
300lm 4000K CRI80 chrome	1000777



1000780 239

1000780 239




DORISA 50

LED
INSIDE

370lm

4000K

CRI
80

IP 44

110°

30 000
Hours

L70B50

200-240V ~50Hz | 340mA

Total wattage: 6.6W

Material: aluminium/plastic

- Clamping range: 0-6 mm. Can be converted to a mirror light by removing the bracket



		
1000780	370lm 4000K	

Options	Prod. no.
370lm 4000K CRI80 chrome	1000780



MIRROR LIGHT HIGHLIGHTS.

OUR PERFECT LIGHTING FOR YOUR BATHROOM.



GLENOS® 60 | 241




L-LINE 60 | 242






L-LINE 120 | 242



Q-LINE® | 243



1003508 241

GLENOS® 60
WL

IP 20 120° L70B50


220-240V ~50/60Hz | 500mA

Total wattage: 12W

Material: aluminium/polycarbonate (PC)




1003507 241

1003506,
1003507,
10035081170lm
3000/4000K

Options	Prod. no.
1170lm 3000/4000K CRI80	
■ black	1003506
1170lm 3000/4000K CRI80	
□ white	1003507
1170lm 3000/4000K CRI80	
■ grey	1003508





L-LINE 60 WL



220-240V ~50/60Hz | 350mA
Total wattage: 10W
Material: aluminium/polycarbonate (PC)

L-LINE 120 WL




220-240V ~50/60Hz | 350mA
Total wattage: 18.5W
Material: aluminium/polycarbonate (PC)



Options	Prod. no.
820lm 3000K CRI80	
white	1001299
silver	1001300
grey	1001301




Options	Prod. no.
1650lm 3000K CRI80	
white	1001303
silver	1001304
grey	1001305





1000668 243

Q-LINE®
WL

IP 20 110° L70B50

220-240V ~50/60Hz | 700mA
Total wattage: 45W
Material: aluminium/acrylic






1000669, 1000668, 1000670	3800lm 3000K	A → G A t G E
---------------------------------	-----------------	---------------------------

Options	Prod. no.
3800lm 3000K CRI80 ■ black	1000669
3800lm 3000K CRI80 □ white	1000668
3800lm 3000K CRI80 ■ grey	1000670



RETRATO WL, PHASE




220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/steel



1002960, 1002961	750lm 3000K	

Options	Prod. no.
750lm 3000K CRI90 white/chrome	1002960
750lm 3000K CRI90 silver	1002961

1002961 244



1002860 245



ALL GOOD THINGS COME FROM ABOVE.

CEILING LIGHTS FOR FLEXIBLE LIGHTING.

Ceiling lights are the key component for any room lighting. Their radiance creates a warm atmosphere in any area. You can customize the lights to suit the room design, adding impressive lighting highlights from above.





1001886 258



Ceiling lights from the NUMINOS® down and spotlight system can be found on pages 72 to 86. Or for easy online configuration, visit: www.numinos.slv.com

1004519 83

CEILING LIGHTS

							
250	251	254	255	255	255	257	258
							
258	258	259	260	260	260	261	261
							
262	262	263	263	264	264	265	265
							
266	266	266	269	269	269	270	270
							
271	273	273	274	274	275	275	276
NEW VARIANT	NEW VARIANT						
							
277	277	277	278	278	279	280	281
							
281	281	282	282	282	283	284	285
							
287	287	287	288	288	289	289	289




You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808

MEDO LUMINAIRE FAMILY.

CEILING OR PENDANT LIGHTS.

	MEDO 30 CL, 1-10V	MEDO 40 CL, 1-10V	MEDO 60 CL, 1-10V	MEDO 90 CL, 1-10V
Example				
Lamp				
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm
Light strength	1000lm	2000lm	3500lm	11000lm
UGR	25	25	22	25
Dimmable	1-10V	1-10V	1-10V	1-10V
Suspension set	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m

	MEDO 30 CL, PHASE	MEDO 40 CL, PHASE	
Example			
Lamp			
Size	Diameter: 30 cm	Diameter: 40 cm	
Light strength	1200lm	2125lm	
UGR	25	25	
Dimmable	C, L	C, L	
Suspension set (not included)	1.5 m 5 m	1.5 m 5 m	

		MEDO 60 CL, square, 1-10V	MEDO 60 CL, square, DALI	
Example				
Lamp				
Size		W L: 60 cm	W L: 60 cm	
Light strength		3300 lm	3300 lm	
UGR		22	22	
Dimmable		1-10V		
Suspension set		1.5 m 5 m	1.5 m 5 m	




MEDO LUMINAIRE FAMILY.

CEILING OR PENDANT LIGHTS.

	MEDO 30 AMBIENT CW, PHASE	MEDO 40 AMBIENT CW, PHASE	MEDO 60 AMBIENT CW, PHASE	MEDO 90 AMBIENT CL, PHASE	
Example					
Lamp					
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm	
Light strength	Down: 1230/1280lm Up: 20lm	Down: 2750/2900lm Up: 50lm	Down: 4350/4750lm Up: 120lm	Down: 9500/10100lm Up: 125lm	
UGR	25	25	25	25	
Dimmable	C	C	C	C	
Suspension set	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	

	MEDO 30 AMBIENT CW, DALI	MEDO 40 AMBIENT CW, DALI	MEDO 60 AMBIENT CW, DALI	MEDO 90 AMBIENT CL, DALI	
Example					
Lamp					
Size	Diameter: 30 cm	Diameter: 40 cm	Diameter: 60 cm	Diameter: 90 cm	
Light strength	Down: 1230/1280lm Up: 20lm	Down: 2750/2900lm Up: 50lm	Down: 4350/4750lm Up: 120lm	Down: 9500/10100lm Up: 125lm	
UGR	25	25	25	25	
Dimmable					
Suspension set	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	




Ambient effect – These MEDO variants produce even and indirect light in an upwards direction.



Colour temperature – With this MEDO variant, you can select the colour temperature yourself. The switch on the reverse can be used to choose between 3000k and 4000k.

135121 255

1000864 255

MEDO 30
CL, 1-10V

1-10V IP 20 105° 25 L70B50

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included





		A → G
1000855, 1000856, 1000857	1000lm 3000K	A G D



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
1000lm 3000K CRI80	
■ black	1000855
1000lm 3000K CRI80	
□ white	1000856
1000lm 3000K CRI80	
■ grey	1000857

MEDO 40
CL, 1-10V

220-240V ~50/60Hz | 700mA
Total wattage: 28W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included





		A → G
1000864, 1000865, 1000866	2450lm 3000K	A E



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
2450lm 3000K CRI80 ■ black	1000864
2450lm 3000K CRI80 □ white	1000865
2450lm 3000K CRI80 ■ grey	1000866

MEDO 60
CL, 1-10V

220-240V ~50/60Hz | 1000mA
Total wattage: 38W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included





		A → G
135120, 135121, 135124	4000lm 3000K	A D



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
4000lm 3000K CRI80 ■ black	135120
4000lm 3000K CRI80 □ white	135121
4000lm 3000K CRI80 ■ grey	135124

MEDO 90
CL, 1-10V

220-240V ~50/60Hz | 2900mA
Total wattage: 109W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included



		A → G
135170, 135171, 135174	11560lm 3000K	A D






■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
11560lm 3000K CRI80 ■ black	135170
11560lm 3000K CRI80 □ white	135171
11560lm 3000K CRI80 ■ grey	135174

MEDO 60

CL, square, 1-10V



220-240V ~50/60Hz | 1000mA
Total wattage: 39W
Material: aluminium/acrylic
• Suspension set not included



		A → G
1000725, 1000726, 1000727	3800lm 3000K	A G E



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ 1-10V dimming Prod. no. 470505	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
3800lm 3000K CRI80 ■ black	1000725
3800lm 3000K CRI80 □ white	1000726
3800lm 3000K CRI80 ■ grey	1000727

1000725 256



135021 257




135171 255

135121 255





135071 257

MEDO 30
CL, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 16W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included





135020, 135021, 135024	1200lm 3000K	A → G D
------------------------------	-----------------	------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
1200lm 3000K CRI80 ■ black	135020
1200lm 3000K CRI80 □ white	135021
1200lm 3000K CRI80 ■ grey	135024

MEDO 40
CL, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 28W
Material: aluminium/poly (methyl methacrylate) (PMMA)
• Suspension set not included






135070, 135071, 135074	2450lm 3000K	A → G E
------------------------------	-----------------	------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
2450lm 3000K CRI80 ■ black	135070
2450lm 3000K CRI80 □ white	135071
2450lm 3000K CRI80 ■ grey	135074





MEDO 30 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	1270/1320lm 3000/4000K	A → G C
---------	---------------------------	------------

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
■ black	1001877
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
□ white	1001881
Up: 20/20lm 3000/4000K CRI80 Down: 1250/1300lm 3000/4000K CRI80	
■ grey	1001882





MEDO 40 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	2750/3000lm 3000/4000K	A → G C
---------	---------------------------	------------

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
■ black	1001883
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
□ white	1001884
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2950lm 3000/4000K CRI80	
■ grey	1001885




MEDO 60 AMBIENT
CW, PHASE

220-240V ~50/60Hz | 1050mA
Total wattage: 40W
Material: aluminium/polycarbonate (PC)
• Suspension set not included

Up/Down	4720/5240lm 3000/4000K	A → G C
---------	---------------------------	------------

■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
■ black	1001886
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
□ white	1001887
Up: 120/120lm 3000/4000K CRI80 Down: 4600/5120lm 3000/4000K CRI80	
■ grey	1001888

MEDO 90 AMBIENT
CL, PHASE

220-240V ~50/60Hz | 1050mA

Total wattage: 78W

Material: aluminium/polycarbonate (PC)

• Suspension set not included



		A → G
Up/Down	9750/10350lm 3000/4000K	A ↑ G



■ Suspension set 1.5m

Prod. no. 135250

□ Suspension set 1.5m

Prod. no. 135251

■ Suspension set 1.5m

Prod. no. 135254

□ Suspension set 5m

Prod. no. 1001950

■ Suspension set 5m

Prod. no. 1001951

■ Suspension set 5m



Prod. no. 1001952

Options	Prod. no.
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
■ black	1001878
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
□ white	1001879
Up: 125/125lm 3000/4000K CRI80 Down: 9625/10225lm 3000/4000K CRI80	
■ grey	1001880

1001887 258

1001881 258



MEDO 30 AMBIENT
CW, DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/polycarbonate (PC)
• Suspension set not included






Up/Down	1230/1280lm 3000/4000K	A → G A ↑ C ↓
---------	---------------------------	------------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
■ black	1001889
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
□ white	1001893
Up: 20/20lm 3000/4000K CRI80 Down: 1230/1280lm 3000/4000K CRI80	
■ grey	1001894

MEDO 40 AMBIENT
CW, DALI

220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/polycarbonate (PC)
• Suspension set not included







Up/Down	2800/2950lm 3000/4000K	A → G A ↑ C ↓
---------	---------------------------	------------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
■ black	1001895
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
□ white	1001896
Up: 50/50lm 3000/4000K CRI80 Down: 2750/2900lm 3000/4000K CRI80	
■ grey	1001897

MEDO 60 AMBIENT
CW, DALI

220-240V ~50/60Hz | 1000mA
Total wattage: 37W
Material: aluminium/polycarbonate (PC)
• Suspension set not included






Up/Down	4470/4870lm 3000/4000K	A → G A ↑ C ↓
---------	---------------------------	------------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
■ black	1001898
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
□ white	1001900
Up: 120/120lm 3000/4000K CRI80 Down: 4350/4750lm 3000/4000K CRI80	
■ grey	1001899

MEDO 90 AMBIENT
CL, DALI

220-240V ~50/60Hz | 1000mA
Total wattage: 78W
Material: aluminium/polycarbonate (PC)
• Suspension set not included






Up/Down	9625/10225lm 3000/4000K	A → G D
---------	----------------------------	------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
■ black	1001890
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
□ white	1001891
Up: 125/125lm 3000/4000K CRI80 Down: 9500/10100lm 3000/4000K CRI80	
■ grey	1001892

MEDO 60
CL, square, DALI

220-240V ~50/60Hz | 1000mA
Total wattage: 39W
Material: aluminium/acrylic



1002882	3800lm 3000K	A → G E
---------	-----------------	------------



■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	

Options	Prod. no.
3800lm 3000K CRI80	
□ white	1002882






1001891/93/96 + 1001900 260 + 261



1002882 261

PANEL 60





CL, round, PHASE



220-240V ~50/60Hz | 1000mA
Total wattage: 42W
Material: aluminium/poly (methyl methacrylate) (PMMA)

PANEL

CL, 1200x300mm, PHASE



220-240V ~50/60Hz | 1000mA
Total wattage: 45W
Material: aluminium/poly (methyl methacrylate) (PMMA)

Options	Prod. no.
3150lm 3000K CRI80	
white	1000783
3350lm 4000K CRI80	
white	1000784
3150lm 3000K CRI80	
grey	1000785
3350lm 4000K CRI80	
grey	1000786

Options	Prod. no.
3100lm 3000K CRI80	
white	1001505
3400lm 4000K CRI80	
white	1001506
3100lm 3000K CRI80	
grey	1001508
3400lm 4000K CRI80	
grey	1001509

Options	Prod. no.
3150lm 3000K CRI80	
white	1000783
3350lm 4000K CRI80	
white	1000784
3150lm 3000K CRI80	
grey	1000785
3350lm 4000K CRI80	
grey	1000786




Options	Prod. no.
3100lm 3000K CRI80	
white	1001505
3400lm 4000K CRI80	
white	1001506
3100lm 3000K CRI80	
grey	1001508
3400lm 4000K CRI80	
grey	1001509

1000783 262



PANEL 60

CL, round, DALI



100-277V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate) (PMMA)






		A → G
1003040, 1003041, 1003042, 1003043	3150lm 3350lm 3000K 4000K	A ↑ G E

Options	Prod. no.
3150lm 3000K CRI80 □ white	1003040
3350lm 4000K CRI80 □ white	1003041
3150lm 3000K CRI80 ■ grey	1003042
3350lm 4000K CRI80 ■ grey	1003043

PANEL

CL, 1200x300mm, DALI





100-277V ~50/60Hz | 1000mA
Total wattage: 43W
Material: aluminium/poly (methyl methacrylate) (PMMA)






		A → G
1003052, 1003053, 1003054, 1003055	3100lm 3400lm 3000K 4000K	A ↑ G F

Options	Prod. no.
3100lm 3000K CRI90 □ white	1003052
3400lm 4000K CRI80 □ white	1003053
3100lm 3000K CRI80 ■ grey	1003054
3400lm 4000K CRI80 ■ grey	1003055

Q-LINE®
CL, 1m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 46W
Material: aluminium/plastic

Q-LINE®
CL, 1m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 46W
Material: aluminium/plastic



Options	Prod. no.
2100lm 3000K CRI90	
■ black	1000686
2100lm 3000K CRI90	
□ white	1000685





Options	Prod. no.
2300lm 4000K CRI90	
■ black	1000689
2300lm 4000K CRI90	
□ white	1000688




1000689 264



1000692 265

Q-LINE®
CL, 2m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 93W
Material: aluminium/plastic

Q-LINE®
CL, 2m, BAP, PHASE

220-240V ~50/60Hz | 900mA
Total wattage: 93W
Material: aluminium/plastic





		A → G
1000692, 1000691	4200lm 3000K	A F

Options	Prod. no.
4200lm 3000K CRI90	
■ black	1000692
4200lm 3000K CRI90	
□ white	1000691






		A → G
1000695, 1000694	4600lm 4000K	A F



Options	Prod. no.
4600lm 4000K CRI90	
■ black	1000695
4600lm 4000K CRI90	
□ white	1000694

TRILEDO
 CL, single, square, QPAR51


220-240V ~50/60Hz
Material: aluminium

TRILEDO
 CL, double, square, QPAR51


220-240V ~50/60Hz
Material: aluminium

TRILEDO
 CL, single, round, QPAR51


220-240V ~50/60Hz
Material: aluminium



GU10 <10W
Diameter: 5 cm L: 5.5 cm



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973



GU10 <10W
Diameter: 5 cm L: 5.5 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



GU10 <10W
Diameter: 5 cm L: 5.5 cm



LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h

Prod. no. 1005075




Options	Prod. no.
1xGU10	
■ black	1002013
1xGU10	
□ white	1002015
1xGU10	
■ aluminium	1002004

Options	Prod. no.
2xGU10	
■ black	1002005
2xGU10	
□ white	1002006


Options	Prod. no.
1xGU10	
■ black	1002010
1xGU10	
□ white	1002011
1xGU10	
■ aluminium	1002012






TRILEDO
 CL, single, square


100-240V ~50/60Hz | 350mA
 Total wattage: 7.6W
 Material: aluminium

TRILEDO
 CL, double, square


220-240V ~50/60Hz | 350mA
 Total wattage: 14W
 Material: aluminium

TRILEDO
 CL, single, round


100-240V ~50/60Hz | 350mA
 Total wattage: 7.6W
 Material: aluminium



		A → G
113940, 113941	640lm 3000K	A E

Options	Prod. no.
640lm 3000K CRI80	
■ black	113940
640lm 3000K CRI80	
□ white	113941





		A → G
1002003, 1002008	1300lm 3000K	A E

Options	Prod. no.
1300lm 3000K CRI80	
■ black	1002003
1300lm 3000K CRI80	
□ white	1002008





		A → G
113930, 113931	640lm 3000K	A E

Options	Prod. no.
640lm 3000K CRI80	
■ black	113930
640lm 3000K CRI80	
□ white	113931

SUPROS
CL, MOVE

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium

SUPROS
CL, MOVE

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium



Product Code	Light Output & Color	Energy Efficiency
1003283, 1003284, 1003285, 1003286	3380lm 3000K 4000K	A → G
		A+ G E



Reflector 20°
Prod. no. 114102

Reflector 40°
Prod. no. 114104



Product Code	Light Output & Color	Energy Efficiency
1003289, 1003290, 1003287, 1003288	2600lm 2700lm 3000K 4000K	A → G
		A+ G E



Reflector 20°
Prod. no. 114102

Reflector 40°
Prod. no. 114104



Options	Prod. no.
3380lm 3000K CRI90	
■ black	1003283
3380lm 3000K CRI90	
□ white	1003284
3520lm 4000K CRI90	
■ black	1003285
3520lm 4000K CRI90	
□ white	1003286


Options	Prod. no.
2600lm 3000K CRI90	
■ black	1003289
2600lm 3000K CRI90	
□ white	1003290
2700lm 4000K CRI90	
■ black	1003287
2700lm 4000K CRI90	
□ white	1003288

1003284 270





116331 271

SUPROS 78
CL, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 12W
Material: aluminium



		A → G
116330, 116331	700lm 3000K	A G E



☐ Lens 20°

Prod. no. 116302

☐ Lens 40°

Prod. no. 116304

Options	Prod. no.
700lm 3000K CRI80	
black	116330
700lm 3000K CRI80	
white	116331

117321 273

DESIGNED BY
David Morgan






David Morgan




“Excellent light quality
from innovative,
distinctive and attractive
luminaire designs.”



117351 273

OCCULDAS 13
DL, indirect, PHASEOCCULDAS 23
DL, indirect, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium



220-240V ~50/60Hz | 700mA
Total wattage: 24W
Material: aluminium/steel



117351	810lm 3000K	A → G A ↑ G E

Options

810lm | 3000K | CRI80
□ white

Prod. no.

117351




117321	1500lm 3000K	A → G A ↑ G E

Options

1500lm | 3000K | CRI80
□ white

Prod. no.

117321

ALTRA DICE
CL, QPAR51

220-240V ~50/60Hz
Material: aluminium/steel



GU10 <35W





LED GU10 51mm | 6W | 38°
2700K | 450lm | EEC=G
6kWh/1000h



Prod. no. 1005075

Options	Prod. no.
1xGU10	
■ black	1002216
1xGU10	
□ white	151511
1xGU10	
■ grey/black	151514

ALTRA DICE
CW, double, QPAR51

220-240V ~50/60Hz
Material: aluminium/steel



GU10 <50W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEC=F
4kWh/1000h



Prod. no. 1004973

Options	Prod. no.
2xGU10	
■ black	1002215
2xGU10	
□ white	151531
2xGU10	
■ grey/black	151534

151514

274



1002215




274





117110 275

KARDAMOD
CL, double, square, QPAR111



220-240V ~50/60Hz
Material: steel



GU10 <75W



QPAR111 | 12.5W | 30°
4000K | 1000lm | EEK=F
13kWh/1000h




Prod. no. 1005282

Options	Prod. no.
2xGU10	
■ black	117110
2xGU10	
□ white	117111

SLV FENDA. MIX & MATCH.


MIX & MATCH



FENDA
Ceiling rose, E27



SOCKET INSIDE **<60 W**



220-240V ~50/60Hz
Material: steel



E27 <60W



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h


Prod. no. 1005302



Options	Prod. no.
1xE27	
■ black	155550
1xE27	
□ white	155551
1xE27	
■ chrome	155552

155552 + 156122 276 + 277





155552 + 156122 276 + 277

FENDA
30 cm, round

NEW VARIANT



H: 20 cm
Diameter: 30 cm
Material: textile/steel

FENDA
45 cm, round

NEW VARIANT



H: 28 cm
Diameter: 45.5 cm
Material: textile/steel

FENDA
70 cm, round



H: 36 cm
Diameter: 70 cm
Material: textile/steel

• Max. 20W



☐ Acrylic glass cover
Prod. no. 156100





Options	Prod. no.
☒ black/copper	155592
☐ white	155582
☐ beige	155583
☐ grey	1004774



☐ Acrylic glass cover
Prod. no. 1000957



Options	Prod. no.
☒ black/copper	1000580
☐ white	1000579

TENORA
CL, E27

220-240V 50/60Hz
Material: steel/textile




E27 <23W L: 14.8 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301

SOPRANA
CL, E27

220-240V ~50/60Hz
Material: steel/textile



E27 <60W




LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302



Options	Prod. no.
3xE27	
■ black	156050
3xE27	
□ white	156051

Options	Prod. no.
3xE27	
■ beige	155373



156050 278




155373 278



1002945 279

ACCANTO
CL, E27

SOCKET INSIDE **<40 W**



IP 20

220-240V ~50/60Hz
Material: steel/textile



E27 <40W L: 13 cm






LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h



Prod. no. 1005301

Options	Prod. no.
2xE27	
■ black	1002944 ▼
2xE27	
□ white	1002945 ▼

OCULUS
CL, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 11W
Material: aluminium/glass


- Additional frosted lens included




		A → G
1004666, 1004667	36-780lm 2000-3000K	A F

Options	Prod. no.
36-780lm 2000-3000K CRI90	
■ black	1004666
36-780lm 2000-3000K CRI90	
□ white	1004667


1004666 280



151811 281



PLASTRA 104
CL, E27



IP 20

220-240V ~50/60Hz
Material: plaster/glass



E27 <25W
Diameter: 5 cm L: 14 cm






LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289



Options	Prod. no.
2xE27	
☐ white	148002



FERA 25
CL, DALI

220-240V ~50/60Hz | 500mA
Total wattage: 19.5W
Material: polycarbonate (PC)/poly (methyl methacrylate) (PMMA)




		A → G
1002968, 1002967	1580/1650lm 3000/4000K	A G D

Options	Prod. no.
1580/1650lm 3000/4000K CRI80	
■ black	1002968
1580/1650lm 3000/4000K CRI80	
□ white/frosted	1002967

1002968 284



161461 285

FERA 25
CL

IP 20

100°

20 000
Hours

L70B50

220-240V ~50/60Hz | 550mA
Total wattage: 23W
Material: aluminium/polystyrene (PS)



1001939, 161461	1800lm 3000K	A → G A T G E

Options

Prod. no.

1800lm | 3000K | CRI80

■ black




1001939

1800lm | 3000K | CRI80




□ white

161461



MARONA
WL, PHASE

200-240V ~50/60Hz | 430mA
Total wattage: 15W
Material: poly (methyl methacrylate) (PMMA)/steel

BATO 45
CW, E27

220-240V ~50/60Hz
Material: aluminium/steel



Options	Prod. no.
1200lm 3000K CRI80	
grey	155156



E27 <60W




LED E27 | 7.5W | 180°
2700K | 720lm | EEK=F
8kWh/1000h



Prod. no. 1005305



Options	Prod. no.
1xE27	
black	1000443
1xE27	
gold	1000445



1000443 288


ROTOBALL 25
CL, E27ROTOBALL 40
CL, E27

230V ~50Hz
Material: steel/polyethylene (PE)



230V ~50Hz
Material: steel/polyethylene (PE)

1002051 289



1002052 289



E27 <24W
Diameter: 6.5 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



E27 <24W
Diameter: 9.5 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302

Options	Prod. no.
1xE27	
□ white	1002051

Options	Prod. no.
1xE27	
□ white	1002052 ▼



FOR A RADIANT PERFORMANCE.

COMBINE WALL AND CEILING LIGHTS.

While ceiling lights set the tone for a lighting scheme, wall lights offer individual focus. That is why a combination offers the ideal holistic lighting solution, enabling so many options that there really is no limit to your creativity.



1002919 294



Wall and ceiling lights from the NUMINOS® down and spotlight system can be found on pages 72 to 73. Or for easy online configuration, visit: www.numinos.slv.com

1006093 + 1006170 78 + 79





WALL AND CEILING LIGHTS

							
294	294	295	296	296	296	298	299
							
299	300	300	300	303	303	303	303
							
304	304	304	304	307	307	307	308
							
308	308	311	311	311	312	312	312
							
312	315	315	315	315	316	316	316
							
316	318	319	319	319	320	320	320
							
322	322	323	323	326	326	326	329
							
329	329	330	330	332	332	333	334
							
334	336	337	337	339	339	340	340
							
341							






You can find more lights and variants at www.slv.com

You can find manufacturer's details for our recommended lamps in the chapter 'Lamps', from page 808






ONE 40
CW, DALI



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium/steel

ONE 60
WL, DALI



220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel



1002915 294



1002919 294



Options	Prod. no.
1350/1430lm 3000/4000K CRI90 Diameter: 40 cm	
■ black	1002915
1350/1430lm 3000/4000K CRI90 Diameter: 40 cm	
□ white	1002917





Options	Prod. no.
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
■ black	1002918
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
□ white	1002919

Options	Prod. no.
1350/1430lm 3000/4000K CRI90 Diameter: 40 cm	
■ black	1002915
1350/1430lm 3000/4000K CRI90 Diameter: 40 cm	
□ white	1002917

Options	Prod. no.
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
■ black	1002918
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
□ white	1002919



1002915 294

MALANG
CW

100-240V ~50/60Hz | 24V
Total wattage: 39W
Material: aluminium / polyethylene (PE)

- Can be controlled and dimmed with SLV VALETO remote control 1002994 or Gateway 1002411
- Ring light and panel can be controlled separately (Zigbee 3.0)



The energy efficiency class information for this product was not available at the time of printing. The latest product data can always be found at www.slv.com






■ Suspension set 1.5m Prod. no. 135250	
□ Suspension set 1.5m Prod. no. 135251	
■ Suspension set 1.5m Prod. no. 135254	
□ Suspension set 5m Prod. no. 1001950	
■ Suspension set 5m Prod. no. 1001951	
■ Suspension set 5m Prod. no. 1001952	
□ SLV VALETO® Remote control, CCT/RGBW Prod. no. 1002994	

Options	Prod. no.
Ring: 350lm RGB+W (3000K) CRI>80	
Panel: 2100-2400lm 2700-6500K CRI>80	
□ white	1002858





1002858 295



OCULUS
CW, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 11W
Material: aluminium/glass

- Additional frosted lens included

KARPO 30
CW, single

220-240V ~50/60Hz | 500mA
Total wattage: 9.3W
Material: aluminium/steel

KARPO 30
CW, single, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/steel



Options	Prod. no.
1004664, 1004665	36-780lm 2000-3000K CRI90
■ black	1004664
□ white	1004665



Options	Prod. no.
152330, 152331	560lm 680lm 3000K CRI90
■ black	152330
□ white	152331



Options	Prod. no.
1001495, 1001496	580lm 660lm 3000K CRI90
■ black	1001495
□ white	1001496

Options	Prod. no.
36-780lm 2000-3000K CRI90	
■ black	1004664
36-780lm 2000-3000K CRI90	
□ white	1004665

Options	Prod. no.
560lm 3000K CRI90	
■ black	152330
680lm 3000K CRI90	
□ white	152331

Options	Prod. no.
580lm 3000K CRI90	
■ black	1001495
660lm 3000K CRI90	
□ white	1001496



1004664 296





1004665 296



1001495 296



TOTHEE
CW, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 17W
Material: aluminium/plastic



		A → G
1000426, 1000427	1250lm 3000K	A ↑ G ↓ E

Options	Prod. no.
1250lm 3000K CRI80	
■ black	1000426
1250lm 3000K CRI80	
■ white/black	1000427



1000247 298






156501 299



156510 299

HELIA CW, single, PHASE






220-240V ~50/60Hz | 500mA
Total wattage: 10W
Material: aluminium



		A → G
156500, 156501	700lm 820lm 3000K	A ↑ G ↓ E

Options	Prod. no.
700lm 3000K CRI90	
■ black	156500
820lm 3000K CRI90	
□ white	156501

HELIA CW, double, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 17W
Material: aluminium





		A → G
156510, 156511	1200lm 3000K	A ↑ G ↓ E

Options	Prod. no.
1200lm 3000K CRI90	
■ black	156510
1200lm 3000K CRI90	
□ white	156511




NOBLO CW, PHASE



220-240V ~50/60Hz | 350mA
Material: aluminium




NOBLO CW, single, PHASE



		A → G
1002969, 1002970, 1002971	600lm 2700K	A G E

Options	Prod. no.
600lm 2700K CRI80 ■ black	1002969
600lm 2700K CRI80 □ white	1002970
600lm 2700K CRI80 ■ silver	1002971


NOBLO CW, double, PHASE



		A → G
1002973, 1002974, 1002975	1200lm 2700K	A G E

Options	Prod. no.
1200lm 2700K CRI80 ■ black	1002973
1200lm 2700K CRI80 □ white	1002974
1200lm 2700K CRI80 ■ silver	1002975

NOBLO CW, triple, PHASE



		A → G
1002976, 1002977, 1002978	1800lm 2700K	A G E

Options	Prod. no.
1800lm 2700K CRI80 ■ black	1002976
1800lm 2700K CRI80 □ white	1002977
1800lm 2700K CRI90 ■ silver	1002978



1002974 300






1000136 303

1000130 303

KALU
CW, PHASE

220-240V ~50/60Hz | 350mA
Material: aluminium/polycarbonate (PC)


KALU
CW, single, PHASE

		A → G
1000127, 1000128	1000lm 3000K	A t G E

Options

Prod. no.

1000lm 3000K 60° CRI80	
■ black	1000127
■ white/black	1000128


KALU
CW, double, PHASE

		A → G
1000129, 1000130	2000lm 3000K	A t G E

Options

Prod. no.

2000lm 3000K 60° CRI80	
■ black	1000129
■ white/black	1000130


KALU
CW, triple, PHASE

		A → G
1000131, 1000132	3000lm 3000K	A t G E

Options

Prod. no.

3000lm 3000K 60° CRI80	
■ black	1000131
■ white/black	1000132

KALU
CW, quad, PHASE

		A → G
1000135, 1000136	4000lm 3000K	A t G E


Options

Prod. no.

4000lm 3000K 60° CRI80	
■ black	1000135
■ white/black	1000136



KALU
CW, QPAR111



220-240V ~50/60Hz
Material: aluminium




GU10 <75W



QPAR111 | 8W | 38°
2700K | 680lm | EEC=F
8kWh/1000h




KALU
CW, single, QPAR111




Options	Prod. no.
1xGU10 ■ black	1000702
1xGU10 □ white	147301
1xGU10 ■ aluminium	147306

KALU
CW, double, QPAR111




Options	Prod. no.
2xGU10 ■ black	1000703
2xGU10 □ white	147311
2xGU10 ■ aluminium	147316

KALU
CW, triple, QPAR111



Options	Prod. no.
3xGU10 ■ black	1000704
3xGU10 □ white	147321
3xGU10 ■ aluminium	147326

KALU
CW, quad, QPAR111



Options	Prod. no.
4xGU10 ■ black	1002023
4xGU10 □ white	1002024
4xGU10 ■ aluminium	1002025




1002024 304



1000702 304







152013 307



152023 307

ENOLA B

CW, single, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Decorative ring in light colour included
- Optional black decorative ring available as an accessory



GU10 <50W L: 6.7 cm



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973





■ Decorative ring, black
Prod. no. 151840



Options	Prod. no.
1xGU10	
■ black	152010
1xGU10	
□ white	152011
1xGU10	
■ gold	152013

ENOLA B

CW, double, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Decorative ring in light colour included
- Optional black decorative ring available as an accessory



GU10 <50W L: 6.7 cm



LED GU10 51mm | 4W | 36°
4000K | 290lm | EEK=F
4kWh/1000h

Prod. no. 1004974





■ Decorative ring, black
Prod. no. 151840



Options	Prod. no.
2xGU10	
■ black	152020
2xGU10	
□ white	152021
2xGU10	
■ gold	152023

ENOLA B

CW, double, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Decorative ring in light colour included
- Optional black decorative ring available as an accessory



GU10 <50W L: 8 cm



LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h



Prod. no. 1005079





■ Decorative ring, black
Prod. no. 151840





Options	Prod. no.
2xGU10	
■ black	151830
2xGU10	
□ white	151831

**ALTRA DICE**
CW, double, QPAR51

220-240V ~50/60Hz
Material: aluminium/steel

SPOT 79
CW, QPAR51

220-240V ~50/60Hz
Material: aluminium

INDA
CW, QPAR51

220-240V ~50/60Hz
Material: aluminium



GU10 <50W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973



GU10 <50W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



GU10 <50W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h

Prod. no. 1005078



Options	Prod. no.
2xGU10	
■ black	1002215
2xGU10	
□ white	151531
2xGU10	
■ grey/black	151534

Options	Prod. no.
1xGU10	
■ black	132020
1xGU10	
□ white	132021
1xGU10	
■ grey	132024

Options	Prod. no.
1xGU10	
■ black	147550
1xGU10	
□ white	147551
1xGU10	
■ aluminium	147559





147414 311





ASTO TUBE



SOCKET
INSIDE



<50
W



IP 20



350°



90°

230V ~50Hz

Material: aluminium



GU10 50W

Diameter: 6.4 cm L: 8.1 cm




LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973



ASTO TUBE


CW, single, QPAR51



Options	Prod. no.
1xGU10	
□ white	147411 ▼

ASTO TUBE


CW, double, QPAR51






Options	Prod. no.
2xGU10	
□ white	147412 ▼

ASTO TUBE



CW, triple, QPAR51



Options	Prod. no.
3xGU10	
□ white	147414 ▼



Options	Prod. no.
2xGU10	
■ black	147370
2xGU10	
□ white	147371



Options	Prod. no.
4xGU10	
■ black	1002029
4xGU10	
□ white	1002030



1002030 312



1000892 315



1000887 315



AVO
CW, QPAR51

**SECRET
INSIDE**

<50
W



IP 20

 320° 90°

230V ~50Hz
Material: steel



GU10 <50W




LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004972

AVO
CW, single, QPAR51




Options	Prod. no.
1xGU10	
☒ black	1000886
1xGU10	
☐ white	1000887

AVO
CW, double, QPAR51




Options	Prod. no.
2xGU10	
■ black	1000889
2xGU10	
□ white	1000890




1000894 315

AVO
CW, triple, QPAR51



Options	Prod. no.
3xGU10	
☒ black	1000892
3xGU10	
☐ white	1000893


AVO
CW, quad, QPAR51



Options	Prod. no.
4xGU10	
 black	1000895
4xGU10	
 white	1000896



ASTO
CW, QPAR51



220-240V ~50/60Hz
Material: aluminium

- Decorative ring included



GU10 <75W




LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h




Prod. no. 1004973

ASTO
CW, single, QPAR51



ASTO
CW, double, QPAR51




Options	Prod. no.
1xGU10	
■ brushed aluminium	147441

Options	Prod. no.
2xGU10	
■ brushed aluminium	147442




ASTO
CW, triple, QPAR51



Options	Prod. no.
3xGU10	
■ brushed aluminium	147443

ASTO
CW, quad, QPAR51



Options	Prod. no.
4xGU10	
■ brushed aluminium	147444



147443



316



FITU
CW, E27



SOCKET INSIDE <60 W



220-240V ~50/60Hz
Material: aluminium/steel



E27 <60W



LED E27 | 7,5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h



Prod. no. 1005265

Options	Prod. no.
1xE27	
■ black	1002585
1xE27	
□ white	1002584 ▼






1002584 318



1004705 319

SENDER 12




CW, square, PHASE



220-240V ~50/60Hz | 200mA
Total wattage: 8.2W
Material: aluminium

SENDER 18




CW, square, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 12W
Material: aluminium

SENDER 24

CW, square, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 15W
Material: aluminium






Options	Prod. no.
480lm 3000K CRI80	
□ white	1003017
440lm 4000K CRI80	
□ white	1004703






Options	Prod. no.
880lm 3000K CRI80	
□ white	1003018
880lm 4000K CRI90	
□ white	1004704






Options	Prod. no.
1200lm 3000K CRI90	
□ white	1003019
1240lm 4000K CRI90	
□ white	1004705

**SENDER 12**
CW, round, PHASE**SENDER 18**
CW, round, PHASE**SENDER 24**
CW, round, PHASE

220-240V ~50/60Hz | 200mA
Total wattage: 8.2W
Material: aluminium



220-240V ~50/60Hz | 350mA
Total wattage: 12W
Material: aluminium



220-240V ~50/60Hz | 500mA
Total wattage: 15W
Material: aluminium



Options	Prod. no.
1003014, 1004700	480lm 470lm 3000K 4000K



Options	Prod. no.
1003015, 1004701	880lm 990lm 3000K 4000K



Options	Prod. no.
1003016, 1004702	1200lm 1300lm 3000K 4000K

Options	Prod. no.
480lm 3000K CRI80 ☐ white	1003014
470lm 4000K CRI90 ☐ white	1004700

Options	Prod. no.
880lm 3000K CRI80 ☐ white	1003015
990lm 4000K CRI90 ☐ white	1004701

Options	Prod. no.
1200lm 3000K CRI80 ☐ white	1003016
1300lm 4000K CRI90 ☐ white	1004702







1004700/01/02 320



SIMA
CW, round, sensor



SIMA
CW, round, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 24W
Material: polycarbonate (PC)



220-240V ~50/60Hz | 350mA
Total wattage: 24W
Material: polycarbonate (PC)



Options	Prod. no.
2150lm 3000K CRI90 □ white	1005086






Options	Prod. no.
2150lm 3000K CRI90 □ white	1005085



1005085 322



1005088 323

SIMA
CW, square, sensor

220-240V ~50/60Hz | 350mA
Total wattage: 24W
Material: polycarbonate (PC)

SIMA
CW, square, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 24W
Material: polycarbonate (PC)



		A → G
1005088	2150lm 3000K	A D

Options

2150lm | 3000K | CRI90
□ white

Prod. no.

1005088



		A → G
1005087	2150lm 3000K	A D

Options

2150lm | 3000K | CRI90
□ white

Prod. no.

1005087



LIPSY® LUMINAIRE FAMILY.




THE COLOURS YOU WANT.

	LIPSY® 30 Dome	LIPSY® 40 Dome	LIPSY® 50 Dome	
Example				
Lamp				
Sensor	–	–	–	
Size	Diameter: 30 cm	Diameter: 35 cm	Diameter: 40 cm	
Colour temperature	3000K 4000K	3000K 4000K	3000K 4000K	
Light colour	1400/1600lm	1800/2000lm	2200/2400lm	
Control dimmable	–	–	–	
				With this LIPSY® variant you can select/change the colour temperature yourself!




	LIPSY® 40 CW, Drum, DALI	LIPSY® 50 CW, Drum, DALI	
Example			
Lamp			
Sensor	–	–	
Size	Diameter: 35 cm	Diameter: 40 cm	
Colour temperature	3000K 4000K	3000K 4000K	
Light colour	1800/2000lm	2200/2400lm	
Control dimmable			






		LIPSY® 30 Drum	LIPSY® 40 Drum	LIPSY® 50 Drum	
Example					  With this LIPSY® variant you can select/change the colour temperature yourself!
Lamp					
Sensor		–	–	–	
Size		Diameter: 30 cm	Diameter: 35 cm	Diameter: 40 cm	
Colour temperature		3000K 4000K	3000K 4000K	3000K 4000K	
Light colour		1400/1600lm	1800/2000lm	2200/2400lm	
Control dimmable		–	–	–	

LIPSY® 30
CW, Dome

220-240V ~50/60Hz | 350mA
Total wattage: 13.5W
Material: aluminium/polycarbonate (PC)

LIPSY® 40
CW, Dome

220-240V ~50/60Hz | 500mA
Total wattage: 17.5W
Material: aluminium/polycarbonate (PC)

LIPSY® 50
CW, Dome

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium/polycarbonate (PC)




Options	Prod. no.
1550/1600lm 3000/4000K CRI80 □ white	1002020



Options	Prod. no.
2050/2200lm 3000/4000K CRI80 □ white	1002021



Options	Prod. no.
2500/2700lm 3000/4000K CRI80 □ white	1002022






1002022 326






1002076 329






LIPSY® 30
CW, Drum

220-240V ~50/60Hz | 350mA
Total wattage: 13.5W
Material: aluminium/polycarbonate (PC)

LIPSY® 40
CW, Drum

220-240V ~50/60Hz | 500mA
Total wattage: 17.5W
Material: aluminium/polycarbonate (PC)

LIPSY® 50
CW, Drum

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium/polycarbonate (PC)



1002075	1600/1650lm 3000/4000K	

Options **Prod. no.**
1600/1650lm | 3000/4000K | CRI80
□ white **1002075**



1002076	2100/2300lm 3000/4000K	

Options **Prod. no.**
2100/2300lm | 3000/4000K | CRI80
□ white **1002076**





1002077	2450/2600lm 3000/4000K	

Options **Prod. no.**
2450/2600lm | 3000/4000K | CRI80
□ white **1002077**






LIPSY® 40
CW, Drum, DALI



220-240V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/polycarbonate (PC)

LIPSY® 50
CW, Drum, DALI



220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/polycarbonate (PC)

1002940	1800/2000lm 3000/4000K	A → G C


Options	Prod. no.
1800/2000lm 3000/4000K CRI90 white	1002940

1002941	2200/2400lm 3000/4000K	A → G C

Options	Prod. no.
2200/2400lm 3000/4000K CRI80 white	1002941

1002940 330









1002940 330



MELAN
CW, E27

GLASSA
CW, square, E27



230V ~50Hz
Material: aluminium/glass

220-240V ~50/60Hz
Material: steel/glass



E27 <60W
Diameter: 7 cm L: 16 cm



E27 <60W
Diameter: 4.8 cm L: 14.8 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h



Prod. no. 1005302



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289

Options	Prod. no.
1xE27	
aluminium	155236

Options	Prod. no.
2xE27	
silver	155180






1000746 333

BATO 35 CW, E27



SOCKET INSIDE **<60 W**



IP 20

220-240V ~50/60Hz
Material: aluminium/steel



E27 <60W



LED E27 | 7.5W | 180°
2700K | 720lm | EEK=F
8kWh/1000h







Prod. no. 1005305

Options	Prod. no.
1xE27	
■ black	1000746
1xE27	
■ brass	1000748



BATTEN 60
CW




NEW



220-240V ~50/60Hz | 110mA
Total wattage: 9W
Material: polycarbonate (PC)

BATTEN 120
CW

NEW



220-240V ~50/60Hz | 220mA
Total wattage: 18W
Material: polycarbonate (PC)

Feed-in cable

Polyvinyl chloride (PVC)
150 cm cable length



Options

Prod. no.

☐ white

1006125

Mounting clips

Polyvinyl chloride (PVC)



Options

Prod. no.

☐ white

1006126

Cable connector

Polyvinyl chloride (PVC)
60 cm cable length



Options

Prod. no.

☐ white

1006127

Direct connector

Polyvinyl chloride (PVC)
60 cm cable length



1006123	940/980lm 3000/4000K	

Options

Prod. no.

940/980lm | 3000/4000K | CRI90
☐ white

1006123



1006124	1900/1960lm 3000/4000K	

Options

Prod. no.

1900/1960lm | 3000/4000K | CRI90
☐ white

1006124





1006124 334



LONG GRILL
CW



1001020 336



IP 20

110°

L70B50

30 000
Hours

270°

220-240V ~50/60Hz | 700mA
Total wattage: 20W
Material: aluminium/acrylic






1001020, 1001019	1600lm 3000K	

Options	Prod. no.
1600lm 3000K CRI80	
■ black	1001020
1600lm 3000K CRI80	
□ white	1001019








1001286 337

SIGHT 60
CW

220-240V ~50/60Hz | 700mA
Total wattage: 20W
Material: aluminium/acrylic

SIGHT 115
CW

220-240V ~50/60Hz | 700mA
Total wattage: 38W
Material: aluminium/acrylic



		A → G
1001283, 1001284, 1001285	1490lm 3000K	A E

Options	Prod. no.
1490lm 3000K CRI80	
■ black	1001283
1490lm 3000K CRI80	
□ white	1001284
1490lm 3000K CRI80	
■ grey	1001285



		A → G
1001286, 1001287, 1001288	3100lm 3000K	A E

Options	Prod. no.
3100lm 3000K CRI80	
■ black	1001286
3100lm 3000K CRI80	
□ white	1001287
3100lm 3000K CRI80	
■ grey	1001288



BENA Video



bit.ly/slv-bena







631337

339



631339

339



BENA 120
CW

IP 20 120° L70B50

220-240V ~50/60Hz | 700mA

Total wattage: 28W

Material: Polymethylacrylate (PMMA)/steel

BENA 150
CW

IP 20 120° L70B50

220-240V ~50/60Hz | 700mA

Total wattage: 36W

Material: Polymethylacrylate (PMMA)/steel



631337, 631347	3800lm 4000lm 3000K 4000K	

Options Prod. no.

3800lm | 3000K | CRI80

☐ white 631337

4000lm | 4000K | CRI80

☐ white 631347

631339, 631349	5000lm 5400lm 3000K 4000K	

Options Prod. no.

5000lm | 3000K | CRI80

☐ white 631339

5400lm | 4000K | CRI80



☐ white 631349



P-LIGHT
CW




P-LIGHT
CW



220-240V ~50Hz
Total wattage: 3.5W
Material: ABS / polycarbonate (PC)

- Perception distance 24 m. 3 escape route signs (right/left/down) and 1 white foil included. Emergency light with built-in Ni-Mh battery. With automatic self-test. Emergency operating time 3 hrs. Luminance >15cd/ m². Operating mode: continuous operation/standby



220-240V ~50/60Hz
Total wattage: 4W
Material: ABS / polycarbonate (PC)

- Perception distance 30 m. 3 escape route signs (right/left/down) and 1 white foil included. Emergency light with built-in Ni-Mh battery. With automatic self-test. Emergency operating time 3 hrs. Luminance >15cd/ m². Operating mode: continuous operation/standby



Pictogram foil
Prod. no. 240007
Accumulator
Prod. no. 240020



Pictogram foil
Prod. no. 240008
Accumulator
Prod. no. 240021




Options	Prod. no.
32lm 6000K CRI80 □ white	240000

Options	Prod. no.
32lm 6000K CRI70 □ white	240002





P-LIGHT CW



IP 65 110° L70B50

220-240V ~50Hz
Total wattage: 6.5W
Material: polycarbonate (PC)

- Perception distance 30 m. For use as emergency lighting. Auto-test function. Ni-Mh battery 2x 3.6V 1.0Ah included. Emergency operation via battery 2 hrs. Escape route sign optionally available and can be used as emergency sign light.

Pictogram foil

Material: polypropylene (PP)
W: 24 cm H: 13.1 cm



4-part pictogram set for insertion

Options	Prod. no.
■ green	240007

Pictogram foil

Material: polypropylene (PP)
W: 35.3 cm H: 16.5 cm



3-part pictogram set for insertion
(up, down, right)

Options	Prod. no.
■ green	240009

Pictogram foil

Material: polypropylene (PP)
W: 30 cm H: 16.1 cm



3-part pictogram set for insertion

Options	Prod. no.
■ green	240008

Pictogram foil

Material: polypropylene (PP)
W: 35.3 cm H: 16.5 cm



2-part pictogram set for insertion
(right diagonal up/right diagonal down)

Options	Prod. no.
■ green	240010



■ Pictogram foil	Prod. no. 240009	
■ Pictogram foil	Prod. no. 240010	
■ Accumulator	Prod. no. 240022	

Options	Prod. no.
100lm 6000K CRI70	
□ white	240004



DEEPLY ROOTED.

RECESSED LIGHTS OFFER IMPRESSIVE RADIANCE.

Be it focused or wide angle, fixed or pivoting, recessed lights are a key component in many lighting concepts and a great alternative to free-hanging lights. Why? Because they adapt to any environment, ensuring plenty of design flexibility.







OUR QUALITY PROMISE

INNOVATION AND DEVELOPMENT



German engineering



Customer and product feedback



High innovative power



The latest trends in design and technology



MANUFACTURE



Qualified suppliers



Strict compliance with regulations



Long-term collaboration



QUALITY ASSURANCE



State-of-the-art laboratories



Extensive safety and performance tests



Multi-level product release standards



Would you like to find out more about the topic of quality? Watch the video now: bit.ly/slv-quality





RECESSED LIGHTS


NEW		NEW		NEW				
								
349	349	349	350	350	351	351	352	
								
352	352	353	354	355	355	355	356	
								
								
356	357	357	358	358	359	359	360	
								
								
361	361	361	362	362	362	363	364	
								
								
365	366	366	366	367	368	368	369	
						NEW VARIANT		
								
369	370	370	371	371	371	372	373	
								
								
374	375	376	376	376	378	378	379	
								
								
379	379	380	380	382	383	384	384	
								
								
384	385	386	386	387	387	389	389	
								
								
389	390	390	390	393	393	393	394	
								
								
394	395	395	396	397	397	398	398	



Recessed lights from the NUMINOS® down and spotlight system can be found on pages 28 to 57.
Or for easy online configuration, visit:
www.numinos.slv.com



1003809 31



You can find more lights and variants at www.slv.com

You can find manufacturer's details for our recommended lamps in the chapter 'Lamps', from page 808






1005407 349



MILANDOS 4
DL

NEW



700mA
Power consumption: 8W
Material: aluminium/polycarbonate (PC)



		A → G
1005407, 1005409	510lm 640lm 2700K	A ↑ F
1005408, 1005410	520lm 650lm 3000K	A ↑ F






□ LED driver 700mA | 10.5W dimmable | incl. strain relief
Prod. no. 464142

□ LED driver 20W | 350mA | 1-10V/ DALI dimmable | incl. strain relief
Prod. no. 1002423

Options	Prod. no.
510lm 2700K CRI90 UGR16	
■ black	1005407
640lm 2700K CRI90 UGR23	
□ white	1005409
520lm 3000K CRI90 UGR16	
■ black	1005408
650lm 3000K CRI90 UGR23	
□ white	1005410

MILANDOS 6
DL

NEW



700mA
Power consumption: 12W
Material: aluminium/polycarbonate (PC)



		A → G
1005415, 1005417	770lm 960lm 2700K	A ↑ F
1005416, 1005418	780lm 980lm 3000K	A ↑ F






□ LED driver 15W | 700mA | incl. strain relief
Prod. no. 464147

□ LED driver 20W | 350mA | 1-10V/ DALI dimmable | incl. strain relief
Prod. no. 1002423

Options	Prod. no.
770lm 2700K CRI90 UGR16	
■ black	1005415
960lm 2700K CRI90 UGR23	
□ white	1005417
780lm 3000K CRI90 UGR16	
■ black	1005416
980lm 3000K CRI90 UGR23	
□ white	1005418

MILANDOS 8
DL

NEW



700mA
Power consumption: 16W
Material: aluminium/polycarbonate (PC)



		A → G
1005423, 1005425	1030lm 1280lm 2700K	A ↑ F
1005424, 1005426	1040lm 1300lm 3000K	A ↑ F



□ LED driver 20W | 350mA | 1-10V/ DALI dimmable | incl. strain relief
Prod. no. 1002423

□ LED driver 20W | 700mA | dimmable | incl. strain relief
Prod. no. 1006202

Options	Prod. no.
1030lm 2700K CRI90 UGR16	
■ black	1005423
1280lm 2700K CRI90 UGR23	
□ white	1005425
1040lm 3000K CRI90 UGR16	
■ black	1005424
1300lm 3000K CRI90 UGR23	
□ white	1005426





NEW TRIA 68

DL, round, QPAR51





NEW TRIA 68

DL, square, QPAR51






230V ~50Hz
Material: aluminium

- Products are delivered with spring clips. Leaf springs are included with the product and can be replaced.
- Material thickness of mounting surface: 20 mm



230V ~50Hz
Material: aluminium

- Products are delivered with spring clips. Leaf springs are included with the product and can be replaced.
- Material thickness of mounting surface: 20 mm



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Options	Prod. no.
1xGU10	
■ black	1001980
1xGU10	
□ white	1001981
1xGU10	
■ aluminium	1001982



GU10 <50W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973







Options	Prod. no.
1xGU10	
■ black	1001994
1xGU10	
□ white	1001995
1xGU10	
■ aluminium	1001996




113456

351

NEW TRIA 78 XL
DL, round, QPAR51NEW TRIA 78 XL
DL, square, QPAR51

113440

351

230V ~50Hz
Material: aluminium

- Material thickness of mounting surface: 18 mm




GU10 <50W

LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ black	113440
1xGU10	
□ white	113441
1xGU10	
■ aluminium	113446

230V ~50Hz
Material: aluminium

- Material thickness of mounting surface: 18 mm



GU10 <50W



LED GU10 | 6W | 36°
2700K | 900lm | EEK=G
6kWh/1000h

Prod. no. 1005273

Options	Prod. no.
1xGU10	
■ black	113450
1xGU10	
□ white	113451
1xGU10	
■ aluminium	113456





NEW TRIA 78 DL, round, QPAR51



220-240V ~50/60Hz
Material: aluminium

- Leaf springs
- Material thickness of mounting surface: max. 20mm



NEW TRIA 78 DL, square, QPAR51



220-240V ~50/60Hz
Material: aluminium

- Leaf springs
- Material thickness of mounting surface: max. 20mm

NEW TRIA 78 DL, round, QPAR51



220-240V ~50/60Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 18mm



GU10 <50W



LED GU10 | 6W | 36°
2700K | 900lm | EEK=G
6kWh/1000h

Prod. no. 1005273



Options	Prod. no.
1xGU10	
■ black	111710
1xGU10	
□ white	111711
1xGU10	
■ aluminium	111716



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Options	Prod. no.
1xGU10	
■ black	111720
1xGU10	
□ white	111721
1xGU10	
■ aluminium	111726



GU10 <50W




LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973



Options	Prod. no.
1xGU10	
■ black	113490
1xGU10	
□ white	113510
1xGU10	
■ aluminium	111360




111711 352

NEW TRIA 78
DL, square, QPAR51

Socket Inside

<50 W



IP 2

 360° 30°

220-240V ~50/60Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 18mm



GU10 <50W




LED GU10 | 6W | 10°
3000K | 450lm | EEK=G
6kWh/1000h




Prod. no. 1005278

Options	Prod. no.
1xGU10	
■ black	113491
1xGU10	
□ white	113511
1xGU10	
■ aluminium	111361



133511 353

NEW TRIA 155
DL, double, QPAR51

220-240V ~50/60Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 30mm



GU10 <50W




LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h





Prod. no. 1004972

Options	Prod. no.
2xGU10 ■ black	113492
2xGU10 □ white	113512
2xGU10 ▒ aluminium	111362



NEW TRIA 150

DL, round, QPAR111



230V ~50Hz
Material: aluminium

- Leaf springs
- Material thickness of mounting surface: max. 30 mm





QPAR111 | 12,5W | 30°
4000K | 1000lm | EEK=F
13kWh/1000h

Prod. no. 1005282

Options	Prod. no.
1xGU10	
■ black	113550
1xGU10	
□ white	113540
1xGU10	
■ aluminium	111380

NEW TRIA 150

DL, square, QPAR111



230V ~50Hz
Material: aluminium

- Leaf springs
- Material thickness of mounting surface: max. 30 mm



GU10 <75W






QPAR111 | 8W | 38°
2700K | 680lm | EEK=F
8kWh/1000h

Prod. no. 1005274

Options	Prod. no.
1xGU10	
■ black	113830
1xGU10	
□ white	113541
1xGU10	
■ aluminium	111381

NEW TRIA 300

DL, double, QPAR111



230V ~50Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 30 mm





GU10 <75W



LED E27 | 7,3W | 25°
3000K | 530lm | EEK=F
7kWh/1000h




Prod. no. 1005292

Options	Prod. no.
2xGU10	
■ black	113840
2xGU10	
□ white	113841
2xGU10	
■ aluminium	111382

NEW TRIA 45
DL, round

220-240V ~50/60Hz | 700mA
Total wattage: 4.2W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 20mm

NEW TRIA 45
Single, square, CS

220-240V ~50/60Hz | 700mA
Total wattage: 4.2W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 20mm



Options	Prod. no.
113970, 113971, 113976	155lm 3000K
	A → G

Options	Prod. no.
155lm 3000K CRI80	
■ black	113970
□ white	113971
■ aluminium	113976



Options	Prod. no.
114400, 114401, 114406	155lm 3000K
	A → G

Options	Prod. no.
155lm 3000K CRI80	
■ black	114400
□ white	114401
■ aluminium	114406







113956 357



113966 357




NEW TRIA 68
DL, round

100-240V ~50/60Hz | 350mA
Total wattage: 5.3W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 20 mm



Options	Prod. no.
300lm 3000K CRI80	
■ black	1003057
300lm 3000K CRI80	
□ white	113951
300lm 3000K CRI80	
▒ brushed aluminium	113956



NEW TRIA 68
DL, square

100-240V ~50/60Hz | 350mA
Total wattage: 5.3W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 20 mm






Options	Prod. no.
300lm 3000K CRI80	
■ black	1003061
300lm 3000K CRI80	
□ white	113961
300lm 3000K CRI80	
▒ brushed aluminium	113966

NEW TRIA 68
DL, round

100-240V ~50/60Hz | 350mA
Total wattage: 5.3W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm

NEW TRIA 68
DL, round, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm



Options	Prod. no.
1003058, 1003059, 1003060	1003058
300lm 2700K CRI80	1003059
300lm 2700K CRI80	1003060

Options	Prod. no.
300lm 2700K CRI80	1003058
300lm 2700K CRI80	1003059
300lm 2700K CRI80	1003060



Options	Prod. no.
1003065, 1003066, 1003067	1003065
800lm 2700K CRI80	1003066
800lm 2700K CRI80	1003067

Options	Prod. no.
800lm 2700K CRI80	1003065
800lm 2700K CRI80	1003066
800lm 2700K CRI80	1003067





1003059 358



1003066 358




1003059 358

NEW TRIA 68
DL, square, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm

NEW TRIA 68
DL, square

100-240V ~50/60Hz | 350mA
Total wattage: 5.3W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm

1003066 358




Options	Prod. no.
800lm 2700K CRI80	
■ black	1003068
800lm 2700K CRI80	
□ white	1003069
800lm 2700K CRI80	
■ brushed aluminium	1003070

Options	Prod. no.
800lm 2700K CRI80	
■ black	1003068
800lm 2700K CRI80	
□ white	1003069
800lm 2700K CRI80	
■ brushed aluminium	1003070




Options	Prod. no.
300lm 2700K CRI80	
■ black	1003062
300lm 2700K CRI80	
□ white	1003063
300lm 2700K CRI80	
■ brushed aluminium	1003064

Options	Prod. no.
300lm 2700K CRI80	
■ black	1003062
300lm 2700K CRI80	
□ white	1003063
300lm 2700K CRI80	
■ brushed aluminium	1003064





114380 360



114391 361

NEW TRIA 68
DL, round, PHASE






220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm



		A → G
114380, 114381, 114386	890lm 3000K	A E

Options	Prod. no.
890lm 3000K CRI80	
■ black	114380
890lm 3000K CRI80	
□ white	114381
890lm 3000K CRI80	
▒ brushed aluminium	114386

NEW TRIA 68
DL, square, PHASE




220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm



Options	Prod. no.
890lm 3000K CRI80	
■ black	114390
□ white	114391
■ brushed aluminium	114396

Options	Prod. no.
890lm 3000K CRI80	
■ black	114390
□ white	114391
■ brushed aluminium	114396

NEW TRIA 68
DL, round, PHASE




220-240V ~50/60Hz | 350mA
Total wattage: 7.2W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm



Options	Prod. no.
430lm 1800-3000K CRI95	
■ black	1001978
□ white	1001989
■ brushed aluminium	1001990

Options	Prod. no.
430lm 1800-3000K CRI95	
■ black	1001978
□ white	1001989
■ brushed aluminium	1001990

NEW TRIA 68
DL, square, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 7.2W
Material: aluminium

- Spring clips and leaf springs
- Material thickness of mounting surface: 20 mm






Options	Prod. no.
430lm 1800-3000K CRI80	
■ black	1001991
□ white	1001992
■ brushed aluminium	1001993

Options	Prod. no.
430lm 1800-3000K CRI80	
■ black	1001991
□ white	1001992
■ brushed aluminium	1001993

NEW TRIA 77
DL, round



220-240V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm

NEW TRIA 77
DL, square

220-240V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm

NEW TRIA 77
DL, round

220-240V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm



Options	Prod. no.
113870, 113871, 113876	645lm 2700K
■ black	113870
□ white	113871
■ aluminium	113876



Options	Prod. no.
113880, 113881, 113886	645lm 2700K
■ black	113880
□ white	113881
■ aluminium	113886





Options	Prod. no.
113900, 113901, 113906	700lm 3000K
■ black	113900
□ white	113901
■ aluminium	113906

Options	Prod. no.
645lm 2700K CRI80	
■ black	113870
645lm 2700K CRI80	
□ white	113871
645lm 2700K CRI80	
■ aluminium	113876

Options	Prod. no.
645lm 2700K CRI80	
■ black	113880
645lm 2700K CRI80	
□ white	113881
645lm 2700K CRI80	
■ aluminium	113886

Options	Prod. no.
700lm 3000K CRI80	
■ black	113900
700lm 3000K CRI80	
□ white	113901
700lm 3000K CRI80	
■ aluminium	113906

NEW TRIA 77
DL, square



220-240V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm



		A → G
113910, 113911, 113916	700lm 3000K	A G E

Options	Prod. no.
700lm 3000K CRI80	
■ black	113910
700lm 3000K CRI80	
□ white	113911
700lm 3000K CRI80	
■ aluminium	113916








NEW TRIA 155
DL, double



113891 364



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 30 mm



		A → G
113890, 113891, 113896	1160lm 2700K	A E

Options	Prod. no.
1160lm 2700K CRI80	
black	113890
1160lm 2700K CRI80	
white	113891
1160lm 2700K CRI80	
aluminium	113896







NEW TRIA 155

DL, double



113890 364






220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 30 mm






		A → G
113920, 113921, 113926	1250lm 3000K	A G E

Options	Prod. no.
1250lm 3000K CRI80 ■ black	113920
1250lm 3000K CRI80 □ white	113921
1250lm 3000K CRI80 ■ aluminium	113926

NEW TRIA 110
DL, round, PHASENEW TRIA 110
DL, round, PHASENEW TRIA 110
DL, square, PHASE




220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm



Options	Prod. no.
114220, 114221	1010lm 1030lm 2700K
■ black	114220
□ white	114221



Options	Prod. no.
114230, 114231	1100lm 1120lm 3000K
■ black	114230
□ white	114231





Options	Prod. no.
114240, 114241	1010lm 1030lm 2700K
■ black	114240
□ white	114241

Options	Prod. no.
1010lm 2700K CRI80	
■ black	114220
1030lm 2700K CRI80	
□ white	114221

Options	Prod. no.
1100lm 3000K CRI80	
■ black	114230
1120lm 3000K CRI80	
□ white	114231

Options	Prod. no.
1010lm 2700K CRI80	
■ black	114240
1030lm 2700K CRI80	
□ white	114241

NEW TRIA 110
DL, square, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 20mm

Options		
114250, 114251	1100lm 1120lm 3000K	A → G A t G E




Options	Prod. no.
1100lm 3000K CRI80	
■ black	114250
1120lm 3000K CRI80	
□ white	114251





NEW TRIA 150

DL, round, 1-10V






100-240V ~50/60Hz | 700mA
Total wattage: 29W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm

NEW TRIA 150

DL, round, 1-10V



100-240V ~50/60Hz | 700mA
Total wattage: 29W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 20mm

Options	Prod. no.
2210lm 2700K CRI80	
■ black	114260
2275lm 2700K CRI80	
□ white	114261


Options	Prod. no.
2425lm 3000K CRI80	
■ black	114270
2500lm 3000K CRI80	
□ white	114271

Options	Prod. no.
2210lm 2700K CRI80	
■ black	114260
2275lm 2700K CRI80	
□ white	114261

Options	Prod. no.
2425lm 3000K CRI80	
■ black	114270
2500lm 3000K CRI80	
□ white	114271

114271

368







114271

369

NEW TRIA 150

DL, square, 1-10V



100-240V ~50/60Hz | 700mA
Total wattage: 29W
Material: aluminium



- Spring clips
- Material thickness of mounting surface: max. 20mm



Options	Prod. no.
2210lm 2700K CRI80	
■ black	114280
2275lm 2700K CRI80	
□ white	114281

NEW TRIA 150

DL, square, 1-10V



100-240V ~50/60Hz | 700mA
Total wattage: 29W
Material: aluminium



- Spring clips
- Material thickness of mounting surface: max. 20mm



Options	Prod. no.
2425lm 3000K CRI80	
■ black	114290
2500lm 3000K CRI80	
□ white	114291

Options	Prod. no.
2210lm 2700K CRI80	
■ black	114280
2275lm 2700K CRI80	
□ white	114281

Options	Prod. no.
2425lm 3000K CRI80	
■ black	114290
2500lm 3000K CRI80	
□ white	114291

HORN MINI
EL

350mA
Power consumption: 1W
Material: aluminium/polycarbonate (PC)

- Driver not included
- AMP plug included
- Different light colour with golden reflector



		A → G
1000915, 1000917, 1000914	70lm 2900 3000K	A F






■ Connector strip, 3 outlets
Prod. no. 111850

□ LED driver 250mA |
15W incl. strain relief
Prod. no. 464031



Options	Prod. no.
70lm 3000K CRI90	
■ black	1000915
70lm 2900K CRI90	
■ black / gold	1000917
70lm 3000K CRI90	
□ white	1000914

HORN
DL, single, QPAR51

220-240V ~50/60Hz
Material: aluminium



GU10 <25W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h



Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ black	113140
1xGU10	
□ white	113141

113141

370





113110

371

HORN



DL, double, QPAR51



220-240V ~50/60Hz
Material: aluminium

HORN

DL, single, asymmetric, QPAR51



220-240V ~50/60Hz
Material: aluminium



113151

371



GU10 <25W



LED GU10 | 6W | 36°
2700K | 900lm | EEK=G
6kWh/1000h

Prod. no. 1005273



GU10 <25W






LED GU10 | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h

Prod. no. 1005077



Options	Prod. no.
2xGU10	
■ black	1006121
2xGU10	
□ white	1006122

Options	Prod. no.
1xGU10	
■ black	113150
1xGU10	
□ white	113151

**HORN**
DL, single, QPAR51

220-240V ~50/60Hz
Material: aluminium




GU10 <25W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ black	113160
1xGU10	
□ white	113161

HORN
EL, single, QPAR51

220-240V ~50/60Hz
Material: steel

- Material thickness of mounting surface:
max. 45mm



GU10 <50W




LED GU10 51mm | 4W | 36°
4000K | 290lm | EEK=F
4kWh/1000h

Prod. no. 1004974

Options	Prod. no.
1xGU10	
■ black	112910
1xGU10	
□ white	112911







113160 372

HORN DL, GU10, blower door tested

NEW VARIANT




SOCKET INSIDE **<25 W**



220-240V ~50/60Hz
Material: aluminium

- The downlight meets the RT2012 standards



113160 372



GU10 <25W



LED GU10 | 6W | 38°
3000K | 450lm | EEK=G
6kWh/1000h



Prod. no. 1005080

Options	Prod. no.
1xGU10	
black	1005435
1xGU10	
white	1005436




HORN-T
EL, QPAR111



SOCKET INSIDE                                              



HORN MAGNA



500mA
Power consumption: 6W
Material: aluminium/polycarbonate (PC)

- Spring clips
- Driver not included
- Different light colour with golden reflector



1002592, 1002594, 1002591	440/470/550lm 2900K 3000K	



■ Honeycomb module
Prod. no. 1002596




Options	Prod. no.
445lm 3000K CRI80	
■ black	1002592
470lm 2900K CRI90	
■ black / gold	1002594
550lm 3000K CRI80	
□ white	1002591



KADUX

EL, single, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm



GU10 <50W



LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h




Prod. no. 1005075

Options	Prod. no.
1xGU10	
■ black	115510
1xGU10	
□ white	115511

KADUX

EL, double, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004972

Options	Prod. no.
2xGU10	
■ black	115520
2xGU10	
□ white	115521

KADUX

EL, triple, QPAR51



220-240V ~50/60Hz
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm



GU10 <50W



LED GU10 | 6W | 36°
2700K | 900lm | EEK=G
6kWh/1000h




Prod. no. 1005273

Options	Prod. no.
3xGU10	
■ black	115530
3xGU10	
□ white	115531





KADUX
EL, single, QPAR111



220-240V ~50/60Hz
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 25mm



GU10 <75W





QPAR111 | 8W | 38°
2700K | 680lm | EEK=F
8kWh/1000h

Prod. no. 1005274

Options	Prod. no.
1xGU10	
■ black	115540
1xGU10	
□ white	115541

KADUX
EL, double, QPAR111



220-240V ~50/60Hz
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 25mm




GU10 <75W





LED GU10 | 12.5W | 10°
2700K | 900lm | EEK=F
13kWh/1000h

Prod. no. 1005275



Options	Prod. no.
2xGU10	
■ black	115550
2xGU10	
□ white	115551



KADUX
EL, single, PHASE




220-240V ~50/60Hz | 350mA
Total wattage: 7.5W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm

KADUX
EL, double, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm

KADUX
EL, triple, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 20W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 30 mm






Options	Prod. no.
115700, 115701	650lm 3000K CRI80
■ black	115700
□ white	115701



Options	Prod. no.
115710, 115711	1290lm 3000K CRI80
■ black	115710
□ white	115711



Options	Prod. no.
115720, 115721	1920lm 3000K CRI80
■ black	115720
□ white	115721

KADUX
DL, single, 1-10V




100-240V ~50/60Hz | 700mA
Total wattage: 29W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 25mm

Lighting options		
		A → G
115730, 115731	2425lm 2500lm 3000K	A ↑ G E

1-10V dimming
Prod. no. 470505

Options	Prod. no.
2425lm 3000K CRI80	
■ black	115730
2500lm 3000K CRI80	
□ white	115731

KADUX
EL, double, 1-10V

100-240V ~50/60Hz | 1400mA
Total wattage: 54W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 25mm


Lighting options		
		A → G
115740, 115741	5200lm 5300lm 3000K	A ↑ G E

1-10V dimming
Prod. no. 470505

Options	Prod. no.
5200lm 3000K CRI80	
■ black	115740
5300lm 3000K CRI80	
□ white	115741





SUPROS 78
EL, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 12W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 25mm



		A → G
116310, 116311	700lm 3000K	A E



- ☐ Lens 20°
Prod. no. 116302
- ☐ Lens 40°
Prod. no. 116304



Options	Prod. no.
700lm 3000K CRI80 60°	
■ black	116310
700lm 3000K CRI80 60°	
□ white	116311

116310 382





116320 383

SUPROS 78
EL, MOVE, PHASE

220-240V ~50/60Hz | 250mA
Total wattage: 12W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 25mm





		A → G
116320, 116321	700lm 3000K	A t G E



- ☐ Lens 20°
Prod. no. 116302
- ☐ Lens 40°
Prod. no. 116304






Options	Prod. no.
700lm 3000K CRI80 60°	
■ black	116320
700lm 3000K CRI80 60°	
□ white	116321

SUPROS
DL




220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 25mm

SUPROS
DL

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 25mm

SUPROS
DL

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 25mm



Product Code	Light Output	Color Temperature
1003299, 1003300	2600lm	3000K



Options	Prod. no.
Reflector 20°	Prod. no. 114102
Reflector 40°	Prod. no. 114104



Product Code	Light Output	Color Temperature
1003301, 1003302	3380lm	3000K



Options	Prod. no.
Reflector 20°	Prod. no. 114102
Reflector 40°	Prod. no. 114104



Product Code	Light Output	Color Temperature
1003303, 1003304	2700lm	4000K



Options	Prod. no.
Reflector 20°	Prod. no. 114102
Reflector 40°	Prod. no. 114104

Options	Prod. no.
2600lm 3000K CRI90 60°	
black	1003299
2600lm 3000K CRI90 60°	
white	1003300


Options	Prod. no.
3380lm 3000K CRI90 60°	
black	1003301
3380lm 3000K CRI90 60°	
white	1003302

Options	Prod. no.
2700lm 4000K CRI90 60°	
black	1003303
2700lm 4000K CRI90 60°	
white	1003304

SUPROS
DLLED
INSIDE

3520lm

4000K

CRI
9010,7
cm

IP 20



60°



L70B50



30°



LED

220-240V ~50/60Hz | 950mA

Total wattage: 36W

Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 25mm

1003305,
10033063520lm
4000K

A → G

A
T
G E

Reflector 20°

Prod. no. 114102





Reflector 40°

Prod. no. 114104





Options	Prod. no.
3520lm 4000K CRI90 60°	
■ black	1003305
3520lm 4000K CRI90 60°	
□ white	1003306



SUPROS
DL, MOVE

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 25 mm

SUPROS
DL, MOVE

220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 25 mm



Product	Light Output	Color Temperature
1003307, 1003308	2600lm	3000K
		A → G



Options	Prod. no.
Reflector 20°	Prod. no. 114102
Reflector 40°	Prod. no. 114104



Product	Light Output	Color Temperature
1003311, 1003312	2700lm	4000K
		A → G



Options	Prod. no.
Reflector 20°	Prod. no. 114102
Reflector 40°	Prod. no. 114104

Options	Prod. no.
2600lm 3000K CRI90 60°	
■ black	1003307
2600lm 3000K CRI90 60°	
□ white	1003308



Options	Prod. no.
2700lm 4000K CRI90 60°	
■ black	1003311
2700lm 4000K CRI90 60°	
□ white	1003312



1003308 386



1003310 387

SUPROS
DL, MOVE

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 25 mm





		A → G
1003309, 1003310	3380lm 3000K	A E



Reflector 20°
Prod. no. 114102
Reflector 40°
Prod. no. 114104



Options	Prod. no.
3380lm 3000K CRI90 60°	
black	1003309
3380lm 3000K CRI90 60°	
white	1003310

SUPROS
DL, MOVE

220-240V ~50/60Hz | 950mA
Total wattage: 36W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 25 mm



		A → G
1003313, 1003314	3520lm 4000K	A E



Reflector 20°
Prod. no. 114102
Reflector 40°
Prod. no. 114104





Options	Prod. no.
3520lm 4000K CRI90 60°	
black	1003313
3520lm 4000K CRI90 60°	
white	1003314




1003008 389

Nº10
HAIRROOM

SENDER 12
EL, round




200mA
Power consumption: 7W
Material: aluminium

- Spring clips
- Driver not included

SENDER 18
EL, round

350mA
Power consumption: 12W
Material: aluminium

- Spring clips
- Driver not included

SENDER 24
EL, round

500mA
Power consumption: 13W
Material: aluminium

- Spring clips
- Driver not included



		A → G
1003008, 1004694	470lm 3000K 440lm 4000K	A → G D



□ LED driver 10W | 200mA |
dimmable | incl. strain relief
Prod. no. 1003254



Options	Prod. no.
470lm 3000K CRI80 □ white	1003008
470lm 4000K CRI90 □ white	1004694



		A → G
1003009, 1004695	940lm 3000K 990lm 4000K	A → G D



□ LED driver 15W | 350mA |
dimmable | incl. strain relief
Prod. no. 1002803



Options	Prod. no.
940lm 3000K CRI80 □ white	1003009
990lm 4000K CRI90 □ white	1004695



		A → G
1003010, 1004696	1200lm 3000K 1300lm 4000K	A → G D



□ LED driver 15W | 500mA |
dimmable | incl. strain relief
Prod. no. 464144



Options	Prod. no.
1200lm 3000K CRI80 □ white	1003010
1300lm 4000K CRI90 □ white	1004696



SENDER 12

EL, round









SENDER 18

EL, round



SENDER 24

EL, round



200mA
Power consumption: 7W
Material: aluminium

- Spring clips
- Driver not included



350mA
Power consumption: 12W
Material: aluminium

- Spring clips
- Driver not included



500mA
Power consumption: 13W
Material: aluminium

- Spring clips
- Driver not included



Product	Light Output	Color Temperature
1003011, 1004697	440lm	3000K 4000K



□ LED driver 10W | 200mA | dimmable | incl. strain relief
Prod. no. 1003254



Product	Light Output	Color Temperature
1003012, 1004698	820lm 880lm	3000K 4000K



□ LED driver 15W | 350mA | dimmable | incl. strain relief
Prod. no. 1002803



Product	Light Output	Color Temperature
1003013, 1004699	1200lm 1240lm	3000K 4000K



□ LED driver 15W | 500mA | dimmable | incl. strain relief
Prod. no. 464144




Options	Prod. no.
440lm 3000K CRI80 □ white	1003011
440lm 4000K CRI90 □ white	1004697

Options	Prod. no.
820lm 3000K CRI80 □ white	1003012
880lm 4000K CRI90 □ white	1004698

Options	Prod. no.
1200lm 3000K CRI80 □ white	1003013
1240lm 4000K CRI90 □ white	1004699



1003011 390









112682 393






112702 393



VERLUX
 EL, square, PHASE





220-240V ~50/60Hz | 500mA
 Total wattage: 12W
 Material: aluminium/plastic

- Spring clips
- Material thickness of mounting surface: max. 30 mm

VERLUX
 EL, square, PHASE


220-240V ~50/60Hz | 500mA
 Total wattage: 22W
 Material: aluminium/plastic

- Spring clips
- Material thickness of mounting surface: max. 30 mm

VERLUX
 EL, square, PHASE


220-240V ~50/60Hz | 700mA
 Total wattage: 31W
 Material: aluminium/plastic

- Spring clips
- Material thickness of mounting surface: max. 30 mm



		A → G
112682	880lm 3000K	A → G E

Options **Prod. no.**
 880lm | 3000K | CRI80
☐ white **112682**






		A → G
112692	1800lm 3000K	A → G E

Options **Prod. no.**
 1800lm | 3000K | CRI80
☐ white **112692**






		A → G
112702	2360lm 3000K	A → G F

Options **Prod. no.**
 2360lm | 3000K | CRI80
☐ white **112702**

DL 126
EL

12V DC
Power consumption: 2.8W
Material: aluminium/plastic

- Mounting spring

DL 126
EL

12V DC
Power consumption: 2.8W
Material: aluminium/plastic

- Mounting spring



Options	Prod. no.
112161, 112165, 112162	160lm 2700K
white	112161
grey	112165
chrome	112162




Options	Prod. no.
112221, 112225, 112222	160lm 3000K
white	112221
grey	112225
chrome	112222

Options	Prod. no.
160lm 2700K CRI80	
white	112161
160lm 2700K CRI80	
grey	112165
160lm 2700K CRI80	
chrome	112162

Options	Prod. no.
160lm 3000K CRI80	
white	112221
160lm 3000K CRI80	
grey	112225
160lm 3000K CRI80	
chrome	112222



112222 394





1000716 395



1000714 395



PIKA
DL, round, QPAR51, rigid



220-240V ~50/60Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 13mm



GU10 <50W





LED GU10 | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h

Prod. no. 1005077



Options	Prod. no.
1xGU10  white	1000714
1xGU10  grey	1000717
1xGU10  chrome	1000715
1xGU10  brass	1000716

PIKA
DL, round, QPAR51, pivoting



220-240V ~50/60Hz
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 15mm



GU10 <50W



LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h



Prod. no. 1005075



Options	Prod. no.
1xGU10  white	1000718
1xGU10  grey	1000721
1xGU10  chrome	1000719
1xGU10  brass	1000720



OCULUS
CL, MOVE, PHASE



220-240V ~50/60Hz | 250mA
Total wattage: 11W
Material: aluminium/glass

- Mounting spring
- Material thickness of mounting surface: 7-20 mm
- Additional frosted lens included



		A → G
1004668, 1004669	36-780lm 2000-3000K	A F

Options	Prod. no.
36-780lm 2000-3000K CRI90	
■ black	1004668
36-780lm 2000-3000K CRI90	
□ white	1004669

1004668 396





117331 397







117311 397

OCCULDAS 14 EL, indirect, PHASE




OCCULDAS 23 EL, indirect, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium/steel

- Mounting spring
- Material thickness of mounting surface:
max. 10-30 mm



200-240V ~50/60Hz | 700mA
Total wattage: 26W
Material: aluminium/steel

- Mounting spring
- Material thickness of mounting surface:
max. 10-30 mm



		A → G
117331	810lm 3000K	A 1 G E

Options **Prod. no.**
810lm | 3000K | CRI80
□ white **117331**







		A → G
117311	1500lm 3000K	A 1 G E

Options **Prod. no.**
1500lm | 3000K | CRI80
□ white **117311**



CONTONE®
DL, round, adjustable,
PHASE

CONTONE®
DL, round, rigid, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 16W
Material: aluminium

220-240V ~50/60Hz | 350mA
Total wattage: 16W
Material: aluminium

- Material thickness of mounting surface:
max. 25mm

- Material thickness of mounting surface:
max. 25mm

Options	Prod. no.
890lm 3000K CRI90	
white	161271

Options	Prod. no.
890lm 3000K CRI70	
white	161291






114481 399



H-LIGHT DL, round, PHASE





220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 30 mm



Options	Prod. no.
265lm 2700K CRI80	
■ black	114480
265lm 2700K CRI80	
□ white	114481

H-LIGHT DL, oval, PHASE





220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium

- Spring clips
- Material thickness of mounting surface:
max. 30 mm





Options	Prod. no.
395lm 2700K CRI80	
■ black	114490
395lm 2700K CRI80	
□ white	114491



KARPO 30
EL

500mA
Power consumption: 7.5W
Material: aluminium/steel

- Spring clips
- Material thickness of mounting surface: max. 12 mm
- Driver not included

HELIA
EL

500mA
Power consumption: 9W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 15 mm
- Driver not included




Options	Prod. no.
152380, 152381	152380
450lm 470lm 3000K	152381

Options	Prod. no.
450lm 3000K CRI90	
black	152380
470lm 3000K CRI90	
white	152381




Options	Prod. no.
156530, 156531	156530
700lm 800lm 3000K	156531

Options	Prod. no.
700lm 3000K CRI90	
black	156530
800lm 3000K CRI90	
white	156531




152380 400



156531 400



1001156 401

LIGHTPOINT
EL

IP 20

L70B50

50

350mA

Power consumption: 1W

Material: aluminium/polymethylacrylate (PMMA)

- Material thickness of mounting surface:
- Driver not included



1001156, 1001155	100lm 3000K	



■ Connector strip, 3 outlets

Prod. no. 111850

□ LED driver 3W | 350mA |
incl. strain relief

Prod. no. 464107




Options	Prod. no.
100lm 3000K CRI80	
□ white	1001156
100lm 3000K CRI90	
■ chrome	1001155



PLASTRA
RL, round, QPAR51



SOCKET INSIDE            <35 W



13,5 cm



IP 20

220-240V ~50/60Hz
Material: plaster/steel

- Spring clips and mounting plate
- Material thickness of mounting surface: max. 25mm



GU10 <35W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEC=F
4kWh/1000h



Prod. no. 1004973

Options	Prod. no.
1xGU10	
☐ white	148070

148070

402






PLASTRA
RL, square, QPAR51



<35
W



IP 20

220-240V ~50/60Hz
Material: plaster/steel

- Spring clips and mounting plate
- Material thickness of mounting surface:
max. 25mm



GU10 <35W






LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972

Options	Prod. no.
1xGU10	
☐ white	148071

DEKLED
EL

350mA
Material: aluminium/polycarbonate (PC)

- Spring clips
- Material thickness of mounting surface: 10 mm





112242	60lm 3000K	A → G
--------	---------------	-------



□ LED driver 320mA |
3W incl. strain relief
Prod. no. 464108



Options	Prod. no.
60lm 3000K CRI80 ■ aluminium	112242

VARU
EL, QPAR51

220-240V ~50/60Hz
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 15 mm



GU10 <5W
Diameter: 5 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972

Options	Prod. no.
1xGU10 ■ black	1001930
1xGU10 ■ white/black	1001931

112242 404





1001931 404





1001172 405



- Spring clips
- Material thickness of mounting surface:
max. 20mm




GU10 <50W



Prod. no. 1005273





Options	Prod. no.
1xGU10	
 white	1001169
1xGU10	
 chrome	1001170
1xGU10	
 grey	1001171
1xGU10	
 silver	1001172

**KAMUELA ECO**
EL, round, PHASE

220-240V ~50Hz
Total wattage: 6.5W
Material: aluminium/plastic

- Spring clips
- Material thickness of mounting surface: max. 40mm
- Fire resistant for at least 90 minutes compliant with BS 476-21

KAMUELA ECO
EL, round, PHASE

220-240V ~50Hz
Total wattage: 6.5W
Material: aluminium/plastic


- Spring clips
- Material thickness of mounting surface: max. 40mm
- Fire resistant for at least 90 minutes compliant with BS 476-21



Options	Prod. no.
400lm 3000K CRI80	
■ black	1001015
400lm 3000K CRI80	
□ white	1001016



Options	Prod. no.
400lm 4000K CRI80	
■ black	1001017
400lm 4000K CRI80	
□ white	1001018










1001264 407

KINI EL, PHASE

AKALO D83 EL, PHASE



220-240V ~50/60Hz | 260mA
Total wattage: 12W
Material: aluminium/polycarbonate (PC)

- Spring clips
- Material thickness of mounting surface: 5-20mm



220-240V ~50/60Hz | 120mA
Total wattage: 9W
Material: aluminium/polycarbonate (PC)

- Spring clips
- Material thickness of mounting surface: 20 mm
- Kelvin value can be configured via rear switch







		A → G
1000833	850lm 3000K	A → G E



		A → G
1001264	800/880/850lm 3000/4200/5700K	A → G F



Options **Prod. no.**
850lm | 3000K | CRI80
□ white **1000833**

Options **Prod. no.**
800/880/850lm | 3000/4200/5700K | CRI80
□ white **1001264**

FRAME BASIC SET
RL

220-240V ~50/60Hz | 350mA
Total wattage: 8.3W
Material: aluminium/acrylic

- Spring clips
- Material thickness of mounting surface: max. 20mm

FRAME CURVE
EL, HV

100-277V ~50/60Hz | 350mA
Total wattage: 3.1W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 10-30 mm



		A → G
1000574, 1000575	100lm 2700K	A ↑ G F





■ Flush frame
Prod. no. 112780
■ Panel connection
Prod. no. 112781



		A → G
112720, 112721	445lm 3000K	A ↑ G E

Options	Prod. no.
600lm 3000K CRI80 ■ black	112720
600lm 3000K CRI80 □ white	112721

FRAME CURVE
EL

350mA
Total wattage: 1W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: max. 10-30 mm
- AMP connector incl. / driver excl.



		A → G
113292, 111292	60lm 3000K	A ↑ G F




■ Connector strip, 3 outlets
Prod. no. 111850
■ Cable extension, 1m
Prod. no. 111861
■ Flush frame
Prod. no. 112780
■ Panel connection
Prod. no. 112781
□ LED driver 350mA | 3W
incl. strain relief
Prod. no. 464107



Options	Prod. no.
100lm 2700K CRI80 □ white	1000574
100lm 2700K CRI90 ■ grey	1000575


Options	Prod. no.
60lm 3000K CRI90 □ white	113292
60lm 3000K CRI90 ■ grey	111292



111292 408



1000577 409

FRAME BASIC
RL, HV

100-277V ~50/60Hz | 350mA
Total wattage: 3.1W
Material: aluminium

- Spring clips
- Material thickness of mounting surface: 10-30 mm





		A → G
1000576, 1000577	140lm 2700K	A ↑ G ↓ F



- Flush frame
Prod. no. 112780
- Panel connection
Prod. no. 112781



Options	Prod. no.
140lm 2700K CRI80 □ white	1000576
140lm 2700K CRI90 ■ grey	1000577

FRAME BASIC
RL

350mA
Total wattage: 1W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: max. 10-30 mm
- AMP connector incl. / driver excl.





		A → G
113262, 111262	40lm 3000K	A ↑ G ↓ F



- Connector strip, 3 outlets
Prod. no. 111850
- Cable extension, 1m
Prod. no. 111861
- Flush frame
Prod. no. 112780
- Panel connection
Prod. no. 112781
- LED driver 350mA | 3W
incl. strain relief
Prod. no. 464107





Options	Prod. no.
40lm 3000K CRI90 □ white	113262
40lm 3000K CRI90 ■ grey	111262

QUAD FRAME 9
WL



100-240V ~50/60Hz | 350mA
Total wattage: 3W
Material: aluminium/aluminium

- Spring clips
- Material thickness of mounting surface: 10-30 mm

NOTAPO S
RL

700mA
Total wattage: 2W
Material: aluminium

- Spring clips
- Open cable end

NOTAPO L
RL

700mA
Total wattage: 2W
Material: aluminium

- Spring clips
- Open cable end



1003466	75lm 3000K	



■ Flush frame
Prod. no. 112780
■ Panel connection
Prod. no. 112781



1002979	6lm 3000K	



☐ LED driver 700mA | 10.5W
dimmable incl. strain relief
Prod. no. 464142
☐ LED driver 700mA | 30W
incl. strain relief
Prod. no. 464200
■ NOTAPO | mounting frame
Prod. no. 1002981



1002980	6lm 3000K	




☐ LED driver 700mA | 10.5W
dimmable incl. strain relief
Prod. no. 464142
☐ LED driver 700mA | 30W
incl. strain relief
Prod. no. 464200
■ NOTAPO | mounting frame
Prod. no. 1002981




Options	Prod. no.
75lm 3000K CRI90 ☐ white	1003466

Options	Prod. no.
6lm 3000K CRI90 H: 10.5 cm ☐ white	1002979



Options	Prod. no.
6lm 3000K CRI90 H: 18 cm ☐ white	1002980



DOWNUNDER PUR 80
EL

350mA
Total wattage: 3.6W
Material: aluminium/steel

- Mounting spring
- Material thickness of mounting surface: max. 15mm

DOWNUNDER PUR 150
EL

500mA
Total wattage: 5.2W
Material: aluminium/steel

- Mounting spring
- Material thickness of mounting surface: max. 15mm



151950	180lm 3000K	A → G A G E
--------	----------------	----------------------



■ Mounting frame
Prod. no. 151960
□ LED driver 320mA | 10W
Prod. no. 464140



151952	230lm 3000K	A → G A G E
--------	----------------	----------------------




■ Mounting frame
Prod. no. 151962
□ LED driver 500mA |
15W dimmable
Prod. no. 464144



Options	Prod. no.
180lm 3000K CRI80 □ white	151950



Options	Prod. no.
230lm 3000K CRI80 □ white	151952






1002982 413

MOBALA EL



100-240V ~50/60Hz | 24V
Total wattage: 1.3W
Material: aluminium

WORO EL



350mA
Total wattage: 1.2W
Material: steel

- This product is suitable for installation in cavity walls and flush-mounted sockets for switches/sockets
- Open cable end



		A → G
1002982	14lm 3000K	A → G



■ MOBALA | panel connection
Prod. no. 1002983

■ MOBALA | mounting frame
Prod. no. 1002984



		A → G
1002922	50lm 3000K	A → G



□ LED driver 320mA |
3W incl. strain relief
Prod. no. 464108





Options	Prod. no.
14lm 3000K CRI80 □ white	1002982

Options	Prod. no.
50lm 3000K CRI80 □ white	1002922



MEDO 30
EL, frameless



13,0
cm



350mA
Total wattage: 14W
Material: aluminium/polymethylacrylate
(PMMA)

- Open cable end




		A → G
1001901	1500/1600lm 3000/4000K	A G C





LED driver 20W | 350mA | 1-10V/
DALI dimmable | incl. strain relief
Prod. no. 1002423



Options	Prod. no.
1500/1600lm 3000/4000K CRI80	
white	1001901



MEDO 40
EL, frameless

700mA
Total wattage: 28W
Material: aluminium/polymethylacrylate (PMMA)

- Open cable end



		A → G
1001902	3100/3300lm 3000/4000K	A ↑ G C





□ LED driver 40W | 700/900/1000mA
incl. strain relief
Prod. no. 1006120

□ LED driver 40W | 700mA |
dimmable
Prod. no. 1005446

□ LED driver 40W | 700mA | 1-10V/
DALI dimmable | incl. strain relief
Prod. no. 1002424

Options **Prod. no.**
3100/3300lm | 3000/4000K | CRI80
□ white **1001902**

MEDO 60
EL, frameless

1000/1050mA
Total wattage: 36W
Material: aluminium/polymethylacrylate (PMMA)

- Open cable end



		A → G
1001903	4700/5000lm 3000/4000K	A ↑ G C






□ LED driver 40W | 700/900/1000mA
incl. strain relief
Prod. no. 1006120

□ LED driver 40W | 700mA |
dimmable
Prod. no. 1005446

□ LED driver 40W | 700mA | 1-10V/
DALI dimmable | incl. strain relief
Prod. no. 1002424

Options **Prod. no.**
4700/5000lm | 3000/4000K | CRI80
□ white **1001903**

MEDO 90
EL, frameless

1000/1050mA
Total wattage: 72W
Material: aluminium/polymethylacrylate (PMMA)

- 2 LED drivers are required.
- Open cable end



		A → G
1001904	9550/10150lm 3000/4000K	A ↑ G D






□ LED driver 40W | 700/900/1000mA
incl. strain relief
Prod. no. 1006120

□ LED driver 40W | 700mA |
dimmable
Prod. no. 1005446




□ LED driver 40W | 700mA | 1-10V/
DALI dimmable | incl. strain relief
Prod. no. 1002424

Options **Prod. no.**
9550/10150lm | 3000/4000K | CRI90
□ white **1001904**

MEDO 30
EL, mounting frame




350mA
Total wattage: 14W
Material: aluminium/polymethylacrylate (PMMA)

- Open cable end

MEDO 40
EL, mounting frame

700mA
Total wattage: 28W
Material: aluminium/polymethylacrylate (PMMA)

- Open cable end

MEDO 60
EL, mounting frame

1000/1050mA
Total wattage: 36W
Material: aluminium/polymethylacrylate (PMMA)

- Open cable end

Lighting	Color Temperature	Beam Angle
1001905	1500/1600lm 3000/4000K	A → G

Options	Prod. no.
□ LED driver 20W 350mA 1-10V/ DALI dimmable incl. strain relief	
Prod. no. 1002423	

Lighting	Color Temperature	Beam Angle
1001906	3100/3300lm 3000/4000K	A → G

Options	Prod. no.
□ LED driver 40W 700/900/1000mA incl. strain relief	
Prod. no. 1006120	
□ LED driver 40W 700mA dimmable	
Prod. no. 1005446	
□ LED driver 40W 700mA 1-10V/ DALI dimmable incl. strain relief	
Prod. no. 1002424	

Lighting	Color Temperature	Beam Angle
1001907	4700/5000lm 3000/4000K	A → G

Options	Prod. no.
□ LED driver 40W 700/900/1000mA incl. strain relief	
Prod. no. 1006120	
□ LED driver 40W 700mA dimmable	
Prod. no. 1005446	
□ LED driver 40W 700mA 1-10V/ DALI dimmable incl. strain relief	
Prod. no. 1002424	



Options	Prod. no.
1500/1600lm 3000/4000K CRI90	
□ white	1001905

Options	Prod. no.
3100/3300lm 3000/4000K CRI80	
□ white	1001906

Options	Prod. no.
4700/5000lm 3000/4000K CRI90	
□ white	1001907



MEDO 90 EL, mounting frame



1000/1050mA
Total wattage: 72W
Material: aluminium/polymethylacrylate (PMMA)

- 2 LED drivers are required
- Open cable end



1001908	9550/10150lm 3000/4000K	A → G D






- ☐ LED driver 40W | 700/900/1000mA incl. strain relief
Prod. no. 1006120
- ☐ LED driver 40W | 700mA | dimmable
Prod. no. 1005446
- ☐ LED driver 40W | 700mA | 1-10V/ DALI dimmable | incl. strain relief
Prod. no. 1002424



Options	Prod. no.
9550/10150lm 3000/4000K CRI80	
☐ white	1001908

CONNECTED LED PANEL

595x595mm, UGR<19






100-240V ~50/60Hz | 1050mA
Total wattage: 43W
Material: aluminium/acrylic

- Remote control and dimming with Remote Control CCT/DIM [1002994] or Gateway [1002411]

CONNECTED LED PANEL

620x620mm, UGR<19



100-240V ~50/60Hz | 1050mA
Total wattage: 43W
Material: aluminium/acrylic

- Remote control and dimming with Remote Control CCT/DIM [1002994] or Gateway [1002411]





Options	Prod. no.
3200-3600lm 2700-6500K CRI90	
□ white	1001250



Options	Prod. no.
3200-3600lm 2700-6500K CRI80	
□ white	1001251

1001251 418

1003084 419

LED PANEL
600x600mm

1050mA
Power consumption: 35W
Material: aluminium/polystyrene (PS)




- Open cable end



		A → G
1003083, 1003084	4000lm 3000 4000K	A E



□ LED driver 1050mA | 40W Triac
phase-control dimmable
Prod. no. 464804
□ LED driver 50W | 700-1400mA |
1-10V/DALI dimmable |
incl. strain relief
Prod. no. 1002425

LED PANEL
620x620mm

1050mA
Power consumption: 35W
Material: aluminium/polystyrene (PS)

- Open cable end









		A → G
1003073, 1003074	4000lm 3000 4000K	A E



□ LED driver 1050mA | 40W Triac
phase-control dimmable
Prod. no. 464804
□ LED driver 50W | 700-1400mA |
1-10V/DALI dimmable |
incl. strain relief
Prod. no. 1002425


Options	Prod. no.
4000lm 3000K CRI90 □ white	1003083
4000lm 4000K CRI90 □ white	1003084

Options	Prod. no.
4000lm 3000K CRI90 □ white	1003073
4000lm 4000K CRI90 □ white	1003074

P-LIGHT
ELPATTA-I
EL, round, PHASEPATTA-I
DL, square, PHASE

220-240V ~50Hz
Total wattage: 5W
Material: ABS / Polycarbonate (PC)

- Spring clips
- Material thickness of mounting surface: max. 25mm
- Can be used as emergency lighting. Auto test function. Ni-Mh battery 2x 3.6V 1.5Ah included. Emergency operation via battery 3 hrs. Beam angle 90°



220-240V ~50/60Hz | 350mA
Total wattage: 7.3W
Material: aluminium/glass

- Products are delivered with spring clips. Leaf springs are included with the product and can be replaced
- Material thickness of mounting surface: 20 mm



220-240V ~50/60Hz | 350mA
Total wattage: 7.3W
Material: aluminium/glass

- Products are delivered with spring clips. Leaf springs are included with the product and can be replaced
- Material thickness of mounting surface: 20 mm



Accumulator
Prod. no. 240024



Options	Prod. no.
1002098, 1002099, 1002100	440lm 1800-3000K CRI95
■ black	1002098
□ white	1002099
■ brushed aluminium	1002100




Options	Prod. no.
1002101, 1002102, 1002103	440lm 1800-3000K CRI95
■ black	1002101
□ white	1002102
■ brushed aluminium	1002103




Options	Prod. no.
120lm 6000K CRI70	
□ white	240006

Options	Prod. no.
440lm 1800-3000K CRI95	
■ black	1002098
440lm 1800-3000K CRI95	
□ white	1002099
440lm 1800-3000K CRI95	
■ brushed aluminium	1002100

Options	Prod. no.
440lm 1800-3000K CRI95	
■ black	1002101
440lm 1800-3000K CRI95	
□ white	1002102
440lm 1800-3000K CRI95	
■ brushed aluminium	1002103






PATTA-I EL, round, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 25 mm

PATTA-I EL, square, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 25 mm



Options	Prod. no.
114420, 114421, 114426	910lm 3000K
■ black	114420
□ white	114421
■ brushed aluminium	114426

Options	Prod. no.
910lm 3000K CRI80	
■ black	114420
910lm 3000K CRI80	
□ white	114421
910lm 3000K CRI80	
■ brushed aluminium	114426





Options	Prod. no.
114430, 114431, 114436	910lm 3000K
■ black	114430
□ white	114431
■ brushed aluminium	114436

Options	Prod. no.
910lm 3000K CRI80	
■ black	114430
910lm 3000K CRI80	
□ white	114431
910lm 3000K CRI80	
■ brushed aluminium	114436





PATTA-F EL, round, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 20 mm

PATTA-F EL, square, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 20 mm



Options	Prod. no.
745lm 3000K CRI80	
■ black	114440
860lm 3000K CRI80	
□ white	114441



Options	Prod. no.
745lm 3000K CRI80	
■ black	114450
860lm 3000K CRI80	
□ white	114451

Options	Prod. no.
745lm 3000K CRI80	
■ black	114440
860lm 3000K CRI80	
□ white	114441



Options	Prod. no.
745lm 3000K CRI80	
■ black	114450
860lm 3000K CRI80	
□ white	114451





OUT 65

EL, round, PHASE



C₀L

IP 20 / IP 65

38°

L70B50

40 000 Hours

LED

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Spring clips
- Material thickness of mounting surface: 20 mm




		A → G
114460, 114461	510lm 640lm 3000K	A F G E

Options	Prod. no.
510lm 3000K CRI80	
■ black	114460
640lm 3000K CRI80	
□ white	114461

A PROFESSIONAL SET-UP.

HIGH-VOLTAGE 3-PHASE TRACK SYSTEMS FOR NEW LIGHTING ACCENTS.

Well-designed lighting is essential, especially where there's plenty to see. High-voltage 3-phase track systems are perfect for shops and exhibition stands. They create the perfect illumination and present products and exhibits in just the right light.



1001865 458




1004267

67

3-phase spots from the NUMINOS® down and spotlight system can be found on pages 62 to 71.
Or for easy online configuration, visit:
www.numinos.slv.com





1006157 444

HIGH-VOLTAGE 3-PHASE TRACK SYSTEMS

NEW						NEW	NEW		
	440	441	441	443	443	444	444	444	445
						NEW			
	445	446	446	447	448	448	450	451	451
	451	452	452	453	453	453	454	454	454
	454	456	456	457	457	458	459	459	459
	459								

Suitable mounting rails and accessories can be found on pages 431-439






You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808




COMPATIBILITY

3-phase track systems

Compatible with lights/adapters from:

 tracks and track components 	Use	SLV	Global/Nordic	EUTRAC®
				
	without DALI	✓	✓	★
	with DALI	✓	✓	✗

Compatible with tracks and track components from:

 lights and adapters 	Use	SLV S-TRACK	Global/Nordic	EUTRAC®
				
	without DALI	✓	✓	✓
	with DALI	✓	✓	✓★★

- ★ Subject to prior testing using light and track samples
- ★★ But without DALI functionality

Details not guaranteed.
 Technical data and dimensions are subject to change without notice.
 During the planning phase of the project, check the project using samples to ensure functionality.
 Compatibility refers only to tracks/lights.
 Tracks and track components from different manufacturers should not be combined.


The SLV track systems and components are highly compatible with lights and adapters from: EUTRAC®, Staff/Zumtobel, Neuco, Lytespan 3, Mela and Nordlux. Subject to prior testing using lights and track samples.





S-TRACK

3-phase surface-mounted track DALI



Nominal voltage (V)

1 m

220-240V ~50/60Hz

1 m

220-240V ~50/60Hz

Max. current (A)

16

16

Max. mech. load

30 kg

30 kg

Material

aluminium

aluminium

Colour

■ black

□ white

L x W x H (cm)

100 x 3.6 x 3.6

100 x 3.6 x 3.6

Prod. no.

1004937

1004938

2 m

220-240V ~50/60Hz

2 m

220-240V ~50/60Hz

16

16

30 kg

30 kg

aluminium

aluminium

■ black

□ white

200 x 3.6 x 3.6

200 x 3.6 x 3.6

1002631

1002632



Nominal voltage (V)

3 m

220-240V ~50/60Hz

3 m

220-240V ~50/60Hz

Max. current (A)

16

16

Max. mech. load

30 kg

30 kg

Material

aluminium

aluminium

Colour

■ black

□ white

L x W x H (cm)

300 x 3.6 x 3.6

300 x 3.6 x 3.6

Prod. no.

1002633

1002634

4 m

220-240V ~50/60Hz

4 m

220-240V ~50/60Hz

16

16

30 kg

30 kg

aluminium

aluminium

■ black

□ white

400 x 3.6 x 3.6

400 x 3.6 x 3.6





1002635






1002636

S-TRACK

3-phase DALI surface-mounted track
Planning assistance and accessories at a glance

View of components from above on the
installation side




	Feed-in, DALI, earth left 10 A max. polycarbonate (PC) L: 13.9 cm W: 3.5 cm H: 3.3 cm ■ black Prod. no.: 1002637 □ white 1002639		Insulating connector Polycarbonate (PC) L: 6.8 cm W: 3.1 cm H: 2.6 cm ■ black Prod. no.: 175080 □ white 1001382
	Feed-in, DALI, earth right 16 A max. polycarbonate (PC) L: 13.9 cm W: 3.5 cm H: 3.3 cm ■ black Prod. no.: 1002638 □ white 1002640		Mounting bracket Steel L: 4 cm W: 3.4 cm H: 1.25 cm ■ black Prod. no.: 1002657 □ white 1002658
	Feed-in, DALI, earth external 16 A max. polycarbonate (PC) L: 11.9 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1002647 □ white 1002649		3-phase adapter, DALI 10 A max. polycarbonate (PC) L: 11.3 cm W: 5.5 cm H: 3.3 cm ■ black Prod. no.: 1002660 □ white 1002659
	Feed-in, DALI, earth internal 16 A max. polycarbonate (PC) L: 11.9 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1002648 □ white 1002650		Mech. 3-phase adapter Aluminium / polycarbonate (PC) L: 6.6 cm W: 6.6 cm H: 3.1 cm ■ black Prod. no.: 175210 □ white 1001395
	T-connector, DALI, earth external, left* 16 A max. polycarbonate (PC) L: 20.3 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1002652 □ white 1002654		Cover Polycarbonate (PC) L: 200 cm W: 2.2 cm H: 0.75 cm ■ black Prod. no.: 1004939 □ white 1004940
	T-connector, DALI, earth external, right* 16 A max. polycarbonate (PC) L: 20.3 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1002651 □ white 1002653		End cap Polycarbonate (PC) L: 3.5 cm W: 3.3 cm H: 3.2 cm ■ black Prod. no.: 175060 □ white 1001380
	T-connector, DALI, earth internal left* 16 A max. polycarbonate (PC) L: 20.3 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1004941 □ white 1004942		Pendant suspension Aluminium / polycarbonate (PC) L: 6 cm W: 6 cm H: 4 cm max. 10 kg ■ black Prod. no.: 175160 □ white 1001390
	T-connector, DALI, earth internal right* 16 A max. polycarbonate (PC) L: 20.3 cm W: 11.9 cm H: 3.3 cm ■ black Prod. no.: 1004943 □ white 1004944		Joint connector Aluminium L: 18.2 cm W: 3.3 cm H: 2.1 cm ■ black Prod. no.: 175180 □ white 1001392
	X-connector, DALI* 16 A max. polycarbonate (PC) L: 20.3 cm W: 20.3 cm H: 3.3 cm ■ black Prod. no.: 1002655 □ white 1002656		Hook Polycarbonate (PC) / steel H: 5.2 cm diameter: 2.6 cm max. 10 kg ■ black Prod. no.: 175190 □ white 1001393
	Longitudinal connector: DALI 16 A max. polycarbonate (PC) L: 10.6 cm W: 2.5 cm H: 2.8 cm ■ black Prod. no.: 1002641 □ white 1002642		Ceiling rose 16 A max. polycarbonate (PC) H: 3.56 cm diameter: 14.32 cm ■ black Prod. no.: 1004684 □ white 1004685
	Longitudinal connector, DALI* 10 A max. polycarbonate (PC) L: 20.3 cm W: 3.5 cm H: 3.3 cm ■ black Prod. no.: 1002643 □ white 1002644		Wire rope suspension, 2-piece Stainless steel/brass L: 500 cm max. 10 kg ■ nickel Prod. no.: 1002845
	Flexible connector, DALI 16 A max. polycarbonate (PC) L: 28.5 cm W: 3.5 cm H: 3.3 cm ■ black Prod. no.: 1002645 □ white 1002646	* with feed-in capacity	



EUTRAC®

3-phase surface-mounted track




	1 m	1 m	1 m	2 m	2 m	2 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16	16	16	16	16
Material	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)
Colour	■ black	□ white	■ grey	■ black	□ white	■ grey
L x W x H (cm)	100 x 3.6 x 3.2	100 x 3.6 x 3.2	100 x 3.6 x 3.2	200 x 3.6 x 3.2	200 x 3.6 x 3.2	200 x 3.6 x 3.2
Prod. no.	145100	1001510	145102	145200	1001511	145202

Manufacturer: EUTRAC® Stromschienen GmbH

	3 m	3 m	3 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16	16
Material	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)
Colour	■ black	□ white	■ grey
L x W x H (cm)	300 x 3.6 x 3.2	300 x 3.6 x 3.2	300 x 3.6 x 3.2
Prod. no.	145300	1001512	145302

Manufacturer: EUTRAC® Stromschienen GmbH




EUTRAC®

Manufacturer: EUTRAC® Stromschienen GmbH

3-phase surface-mounted track Planning assistance and accessories at a glance

View of components from above on the
installation side



145510
1001513
145514



145520
1001514
145524




145670
1001520
145674




145680
1001521
145684




145630
1001518
145634



145640
1001519
145644



145690
1001522
145694



Example: earth external

145670
1001520
145674

145510
1001513
145514


145670
1001520
145674

145680
1001521
145684

145520
1001514
145524

Example: earth internal

145510
1001513
145514



145630
1001518
145634

145680
1001521
145684

145690
1001522
145694

145680
1001521
145684

145520
1001514
145524

145680
1001521
145684

**Feed-in, earth left**

16 A max. | polycarbonate (PC)
L: 11.2 cm W: 3.6 cm H: 3.2 cm

■ black Prod. no.: **145510**
□ white **1001513**
■ grey **145514**

**Joint connector**

Polycarbonate (PC)
L: 10 cm W: 3.6 cm H: 1.9 cm

■ black Prod. no.: **145600**
□ white **1001523**
■ grey **145604**

**Feed-in, earth right**

16 A max. | polycarbonate (PC)
L: 11.2 cm W: 3.6 cm H: 3.2 cm

■ black Prod. no.: **145520**
□ white **1001514**
■ grey **145524**

**Flex connector**

16 A max. | polycarbonate (PC)/steel
L: 22 cm W: 3.6 cm H: 3.2 cm

■ black Prod. no.: **145580**
□ white **1001524**
■ grey **145584**

**Centre feed-in**

16 A max. | polycarbonate (PC)
L: 13 cm W: 3.6 cm H: 3.6 cm

■ black Prod. no.: **145530**
□ white **1001515**
■ grey **145534**

**Socket**

6.3 A max. | polycarbonate (PC)
L: 9.6 cm W: 6.5 cm H: 9 cm

■ black Prod. no.: **145700**
□ white **1001525**

**Longitudinal connector***

16 A max. | polycarbonate (PC)/steel
L: 26 cm W: 3.6 cm H: 3.2 cm

■ black Prod. no.: **145660**
□ white **1001517**
■ grey **145664**

**3-phase light adapter**

10 A max. | polycarbonate (PC)

■ black Prod. no.: **145990**
□ white **1001542**
■ grey **145994**

**Longitudinal connector**

16 A max. | polycarbonate (PC)
L: 5.8 cm W: 1.5 cm H: 2.6 cm

■ black Prod. no.: **145660**
□ white **1001516**
■ grey **145664**

**Pendant clip**


Aluminium
L: 5 cm W: 3.6 cm H: 1.9 cm

■ black Prod. no.: **145730**
□ white **1001530**
■ grey **145734**

**L-connector, earth internal***

16 A max. | polycarbonate (PC) / steel
L: 15 cm W: 15 cm H: 3.2 cm

■ black Prod. no.: **145680**
□ white **1001521**
■ grey **145684**

**Point outlet**

16 A max. | polycarbonate (PC)
H: 3.1 cm diameter: 11.9 cm

■ black Prod. no.: **145830**
□ white **1001526**
■ grey **145834**

**L-connector, earth external***


16 A max. | polycarbonate (PC)/steel
L: 15 cm W: 15 cm H: 3.2 cm

■ black Prod. no.: **145670**
□ white **1001520**
■ grey **145674**

**End cap**

Polycarbonate (PC)
L: 3.6 cm W: 1.7 cm H: 3.2 cm

■ black Prod. no.: **145590**
□ white **1001527**
■ grey **145594**

**T-connector, earth internal left***


16 A max. | polycarbonate (PC)/steel
L: 26 cm W: 18.5 cm H: 3.2 cm

■ black Prod. no.: **145630**
□ white **1001518**
■ grey **145634**

**Pendant suspension**


Polycarbonate (PC)/steel
L: 60 cm H: 63.5 cm diameter: 7 cm

■ black Prod. no.: **145720**
□ white **1001529**
■ grey **145724**

**T-connector, earth internal right***

16 A max. | polycarbonate (PC)/steel
L: 26 cm W: 18.5 cm H: 3.2 cm

■ black Prod. no.: **145640**
□ white **1001519**
■ grey **145644**

**Pendant suspension**


Polycarbonate (PC)/steel
L: 120 cm H: 122 cm diameter: 7 cm

■ black Prod. no.: **145710**
□ white **1001528**
■ grey **145714**

**X-connector***

16 A max. | polycarbonate (PC)/steel
L: 26 cm W: 26 cm H: 3.2 cm
2 separate power circuits

■ black Prod. no.: **145690**
□ white **1001522**
■ grey **145694**

**Wire rope suspension 2 piece**

Stainless steel/brass
L: 500 cm | max. 10 kg


■ nickel Prod. no.: **1002845**

* with feed-in capacity



EUTRAC®

3-phase recessed track with matching accessories



	2 m	3 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16
Material	aluminium/ polycarbonate (PC)	aluminium/ polycarbonate (PC)
Colour	☐ white	☐ white
L x W x H (cm)	200 x 5.9 x 4.1	300 x 5.9 x 4.1
Recessed W (cm)	4	4
Prod. no.	1001531	1001532


Manufacturer: EUTRAC® Stromschienen GmbH



Feed-in, earth left

16 A max. | polycarbonate (PC)/steel
L: 12.2 cm W: 6 cm H: 3.4 cm

☐ white Prod. no. 1001533



End cap

Polycarbonate (PC)
L: 2.7 cm W: 6 cm H: 3.2 cm

☐ white Prod. no. 1001538



Feed, earth right

16 A max. | polycarbonate (PC)/steel
L: 12.2 cm W: 6 cm H: 3.4 cm

☐ white Prod. no. 1001534



Longitudinal connector with stabilizer

16 A max. | polycarbonate (PC)/steel
L: 6.2 cm W: 2.5 cm H: 2.7 cm


☐ white Prod. no. 1001539



Recessed L-connector with feed-in

16 A max. | polycarbonate (PC)/steel
L: 16 cm W: 16 cm H: 3.2 cm
Earth external, with feed-in capability


☐ white Prod. no. 1001536



Spring clip

Steel
L: 2 cm W: 1 cm H: 2.5 cm

☒ grey Prod. no. 145551



Recessed L-connector with feed-in

16 A max. | polycarbonate (PC)/steel
L: 16 cm W: 16 cm H: 3.2 cm
Earth internal, with feed-in capability

☐ white Prod. no. 1001537



3-phase light adapter

10 A max. | polycarbonate (PC)




☐ white Prod. no. 1001542

SIGHT TRACK
3Ph., DALI



NEW

CCT



220-240V ~50/60Hz | 700mA
Total wattage: 39W
Material: aluminium/acrylic



hV	Color temperature	A → G
1005397, 1005399	3000/3000lm 3000/4000K	A F

Options	Prod. no.
3000/3000lm 3000/4000K CRI 90	
black	1005397
3000/3000lm 3000/4000K CRI 90	
white	1005399










1004691 441



1004690 441

SIGHT MOVE
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)

SIGHT MOVE
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)



hv		A → G
1004690, 1004691	2700lm 3000K	A f G E

Options	Prod. no.
2700lm 3000K CRI90	
■ black	1004690
2700lm 3000K CRI90	
□ white	1004691



hv		A → G
1004692, 1004693	3100lm 4000K	A f G E

Options	Prod. no.
3100lm 4000K CRI90	
■ black	1004692
3100lm 4000K CRI90	
□ white	1004693

1004769 443








1004770 443



1004771 443



ONE 40 TRACK
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15.2W
Material: aluminium



hV	Color temperature	A → G
1004769, 1004770	650lm 3000K	A f G E

Options	Prod. no.
650lm 3000K CRI90	
■ black	1004769
650lm 3000K CRI90	
□ white	1004770

ONE 40 TRACK
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15.2W
Material: aluminium





hV	Color temperature	A → G
1004771, 1004772	670lm 4000K	A f G E

Options	Prod. no.
670lm 4000K CRI90	
■ black	1004771
670lm 4000K CRI90	
□ white	1004772

PARA CONE GL
3Ph., GU10



NEW




220-240V ~50/60Hz
Material: aluminium/glass

PARA CONE GL
PD, GU10



NEW



220-240V ~50/60Hz
Material: aluminium/glass



GU10 <25W



LED GU10 | 3,2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ black	1006157 ■
1xGU10	
□ white	1006158 ■



GU10 <25W








LED GU10 | 3,2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ black	1006159 ■
1xGU10	
□ white	1006160 ■



- Textile cable
- Black/gold version with golden reflector
- All other versions with white reflector



Prod. no. 1005080

Options	Prod. no.
1xGU10 ■ black	153140
1xGU10 □ white	153141
1xGU10 ■ copper	1002686

LIGHT EYE® 150 TRACK
3Ph. QPAR111



LIGHT EYE® 150
3Ph. PD, QPAR111



SOCKET INSIDE                                                      




153130 447

FORCHINI M 40 TRACK

3Ph., PD, E27



SOCKET INSIDE **<40 W**



IP 20

150

230V ~50Hz
Material: aluminium/steel



E27 <40W
Diameter: 6.8 cm L: 15.2 cm



LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h








Prod. no. 1005265

Options	Prod. no.
1xE27	
■ black/gold	153130

SIGHT MOVE
3Ph.



SIGHT MOVE
3Ph.



220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)



220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)




Options	Prod. no.
2700lm 3000K CRI90	
black	1004686
2700lm 3000K CRI90	
white	1004687



Options	Prod. no.
3100lm 4000K CRI90	
black	1004688
3100lm 4000K CRI90	
white	1004689

Options	Prod. no.
2700lm 3000K CRI90	
black	1004686
2700lm 3000K CRI90	
white	1004687





Options	Prod. no.
3100lm 4000K CRI90	
black	1004688
3100lm 4000K CRI90	
white	1004689



1004686 448



SIGHT TRACK
3Ph.



220-240V ~50/60Hz | 700mA
Total wattage: 37W
Material: aluminium/acrylic

		A → G
1005400, 1005401, 1005402	3000/3000lm 3000/4000K	A F

Options	Prod. no.
3000/3000lm 3000/4000K CRI 90 ■ black	1005400 ■
3000/3000lm 3000/4000K CRI 90 □ white	1005401 ■
3000/3000lm 3000/4000K CRI 90 ■ grey	1005402 ■








152751 451



152781 451

EURO CUBE
3Ph.

220-240V ~50/60Hz | 700mA
Total wattage: 28.5W
Material: aluminium

EURO CUBE
3Ph.

220-240V ~50/60Hz | 700mA
Total wattage: 28.5W
Material: aluminium



hv		A → G
152750, 152751	2100lm 3000K	A F

Options Prod. no.

2100lm | 3000K | CRI90 | 60°
■ black 152750
2100lm | 3000K | CRI90 | 60°
□ white 152751







hv		A → G
152780, 152781	2150lm 4000K	A F

Options Prod. no.

2150lm | 4000K | CRI90 | 60°
■ black 152780
2150lm | 4000K | CRI90 | 60°
□ white 152781

EURO SPOT TRACK
3Ph., QPAR111

EURO SPOT TRACK
3Ph., QPAR51



220-240V ~50Hz
Material: aluminium

220-240V ~50Hz
Material: aluminium/glass

GU10 <75W


GU10 <25W

QPAR111 | 12,5W | 30°
4000K | 1000lm | EEK=F
13kWh/1000h
Prod. no. 1005282

LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h
Prod. no. 1005076

Options	Prod. no.
1xGU10	
■ black	153420
1xGU10	
□ white	153421

Options	Prod. no.
1xGU10	
■ black	153850
1xGU10	
□ white	153851











KALU TRACK 3Ph., PHASE



KALU TRACK 3Ph., QPAR111



KALU TRACK 3Ph., QR111



220-240V ~50/60Hz
Total wattage: 13W
Material: aluminium

220-240V ~50/60Hz | 12V
Material: aluminium/plastic

220-240V ~50/60Hz | 12V
Material: aluminium/plastic

• Product cannot be used with our ceiling roses
(145830/1001527/145834)



Options	Prod. no.
860lm 3000K CRI90	
■ black	152600
860lm 3000K CRI80	
□ white	152601

Options	Prod. no.
1xGU10	
■ black	152610
1xGU10	
□ white	152611

Options	Prod. no.
1xG53	
■ black	153580
1xG53	
□ white	153581



BIMA
3Ph., single, QPAR51



220-240V ~50/60Hz
Material: aluminium



GU10 <50W
Diameter: 5 cm L: 5.7 cm





LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ black	152240
1xGU10	
□ white	152241
1xGU10	
■ grey	152242

BIMA
3Ph., double, QPAR51



220-240V ~50/60Hz
Material: aluminium



GU10 <50W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
2xGU10	
■ black	152230
2xGU10	
□ white	152231
2xGU10	
■ grey	152232

1000657 457









152960 457

STRUCTEC ZOOM

3 Ph,


HELIA 50 TRACK

3Ph.



220-240V ~50/60Hz | 900mA
Total wattage: 34W
Material: aluminium

- Beam angle can be adjusted from 25°-60° via zoom function



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium



Options	Prod. no.
1000656, 1000657	2800lm 3000K
	1000656
	1000657






Options	Prod. no.
152960, 152961	810lm 880lm 3000K
	152960
	152961

Options	Prod. no.
2800lm 3000K CRI90	
■ black	1000656
2800lm 3000K CRI90	
□ white	1000657

Options	Prod. no.
810lm 3000K CRI90	
■ black	152960
880lm 3000K CRI90	
□ white	152961



NOBLO SPOT 3Ph.



IP 20

36°

L70B50

320°

90°




220-240V ~50/60Hz | 350mA
Total wattage: 7.5W
Material: aluminium



hV		A → G
1001865, 1001866	620lm 2700K	A ↑ G E

Options	Prod. no.
620lm 2700K CRI80	
■ black	1001865
620lm 2700K CRI80	
□ white	1001866



ENOLA C TRACK
3Ph.

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium



hV	Light spectrum	A → G
152430, 152431	1040lm 3000K	A ↑ G E

Options	Prod. no.
1040lm 3000K CRI80 55°	
■ black	152430
1040lm 3000K CRI80 55°	
□ white	152431




TEC KALU TRACK
3Ph., double, PHASE

220-240V ~50/60Hz | 700mA
Total wattage: 31W
Material: aluminium/polycarbonate (PC)



hV	Light spectrum	A → G
1001419, 1001420	1900lm 3000K	A ↑ G E

Options	Prod. no.
1900lm 3000K CRI80 60°	
■ black	1001419
1900lm 3000K CRI80 60°	
■ white/black	1001420

AVO TRACK
3Ph., QPAR51

230V ~50/60Hz
Material: steel



GU10 <50W
Diameter: 5 cm



LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h



Prod. no. 1005078

Options	Prod. no.
1xGU10	
■ black	152640
1xGU10	
□ white	152641

STAY ON TRACK.

SIMPLY GREAT ILLUMINATION WITH HIGH-VOLTAGE SINGLE-PHASE TRACK SYSTEMS.

Thanks to the drilled holes in their cross-section, these flat aluminium tracks can be attached to your wall or ceiling quickly and easily. You can choose between a recessed version and a surface-mounted version, both of which are available in multiple colours.






1006159 472


1004935 471

143450 478





HIGH-VOLTAGE SINGLE-PHASE TRACK



You can find suitable mounting rails and accessories on pages 465-469



You can find more lights and variants at www.slv.com
You can find manufacturer's details for our recommended lamps in the chapter 'Lamps', from page 808

1000713 476




SINGLE-PHASE

MOUNTING TRACK



	1 m	1 m	1 m	2 m	2 m	2 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16	16	16	16	16
Material	aluminium	aluminium	aluminium	aluminium	aluminium	aluminium
Colour	■ black	□ white	■ grey	■ black	□ white	■ grey
L x W x H (cm)	100 x 3.5 x 1.8	100 x 3.5 x 1.8	100 x 3.5 x 1.8	200 x 3.5 x 1.8	200 x 3.5 x 1.8	200 x 3.5 x 1.8
Prod. no.	143010	143011	143012	143020	143021	143022

	3 m	3 m	3 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16	16
Material	aluminium	aluminium	aluminium
Colour	■ black	□ white	■ grey
L x W x H (cm)	300 x 3.5 x 1.8	300 x 3.5 x 1.8	300 x 3.5 x 1.8
Prod. no.	1002151	1002152	1002153







SINGLE-PHASE

Mounting track

Planning assistance and accessories at a glance

View of components from above on the
installation side



**Feed-in, earth left**

16 A max. | polycarbonate (PC)
L: 6.5 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143030**
□ white **143031**
■ grey **143032**

**Stabilising longitudinal connector**

Steel
L: 19.7 cm W: 3.2 cm H: 1.3 cm
For reinforcement when mounting several tracks with ceiling suspension (1002845)

■ nickel Prod. no.: **143151**

**Feed-in, earth right**

16 A max. | polycarbonate (PC)
L: 10.4 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143040**
□ white **143041**
■ grey **143042**

**Stabilising corner connector**


Steel
L: 11.5 cm W: 11.5 cm H: 0.5 cm
For reinforcement when mounting several tracks with ceiling suspension (1002845)

■ nickel Prod. no.: **143152**

**Longitudinal connector***

16 A max. | polycarbonate (PC)
L: 17.2 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143100**
□ white **143101**
■ grey **143102**

**Stabilising X-connector**

Steel
L: 19.7 cm W: 19.7 cm H: 0.5 cm
For reinforcement when mounting several tracks with ceiling suspension (1002845).

■ grey Prod. no.: **143169**

**Longitudinal connector**

16 A max. | polycarbonate (PC)
L: 6.4 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143090**
□ white **143091**
■ grey **143092**

**Single-phase light adapter**

6 A max. | polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 4.2 cm

■ black Prod. no.: **143120**
□ white **143121**
■ grey **143124**

**Corner connector, earth inside**

16 A max. | polycarbonate (PC)
L: 10.4 cm W: 10.4 cm H: 1.8 cm

■ black Prod. no.: **143060**
□ white **143061**
■ grey **143062**

**Single-phase light adapter with hooks**

6 A max. | polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 7.4 cm

■ black Prod. no.: **143170**
□ white **143171**
■ grey **143172**

**Corner connector, earth outside**

16 A max. | polycarbonate (PC)
L: 10.4 cm W: 10.4 cm H: 1.8 cm

■ black Prod. no.: **143050**
□ white **143051**
■ grey **143052**

**Cover**

Polycarbonate (PC)
L: 200 cm W: 1.8 cm H: 0.75 cm

■ black Prod. no.: **1004783**
□ white **1004785**
■ grey **1004784**

**T-connector, earth external, left**

16 A max. | polycarbonate (PC)
L: 17.2 cm W: 10.4 cm H: 1.8 cm

■ black Prod. no.: **143070**
□ white **143071**
■ grey **143072**

**End cap**


Polycarbonate (PC)
L: 0.4 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143130**
□ white **143131**
■ grey **143132**

**T-connector, earth external, right**

16 A max. | polycarbonate (PC)
L: 17.2 cm W: 10.4 cm H: 1.8 cm

■ black Prod. no.: **143080**
□ white **143081**
■ grey **143082**

**Ceiling rose**


6 A max. | polycarbonate (PC)
H: 2.5 cm Diameter: 12.1 cm

■ black Prod. no.: **143380**
□ white **143381**
■ grey **143382**

**X-connector**

16 A max. | polycarbonate (PC)
L: 9.5 cm W: 17.2 cm H: 1.8 cm

■ black Prod. no.: **143160**
□ white **143161**
■ grey **143162**

**Wire rope suspension, 2-piece**

Stainless-steel / brass
L: 500 cm | max. 10 kg

■ nickel Prod. no.: **1002845**

**Flex connector**

16 A max. | polycarbonate (PC)
L: 16.4 cm W: 3.5 cm H: 1.8 cm

■ black Prod. no.: **143110**
□ white **143111**
■ grey **143112**

* with feed-in capacity




143580 483

1001406 143

SINGLE-PHASE

Recessed track with matching accessories



2 m

Nominal voltage (V)	220-240V ~50/60Hz
Max. current (A)	16
Material	aluminium
Colour	☐ white
L x W x H (cm)	200 x 5.5 x 1.8
Recessed W (cm)	4
Prod. no.	143221



Feed-in, earth left

16 A max. | plastic
L: 10.8 cm W: 5.5 cm H: 2 cm
☐ white Prod. no. 143231



End cap

Plastic
L: 2.7 cm W: 5.5 cm H: 1.8 cm
☐ white Prod. no. 143281



Feed-in, earth right

16 A max. | plastic
L: 10.8 cm W: 5.5 cm H: 2 cm
☐ white Prod. no. 143241



Retainer

Steel
L: 7.5 cm W: 1.5 cm H: 4 cm
☐ nickel Prod. no. 143230



Longitudinal connector

16 A max. | plastic/steel
L: 6.5 cm W: 1.8 cm H: 1.7 cm
☐ white Prod. no. 143271



Single-phase adapter with hook

6 A max. | polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 7.4 cm
☐ black Prod. no.: 143170
☐ white 143171
☐ grey 143172



Corner connector, earth inside

16 A max. | plastic
L: 11.2 cm W: 11.2 cm H: 2 cm
☐ white Prod. no. 143261



Single-phase light adapter

6 A max. | polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 4.2 cm
☐ black Prod. no.: 143120
☐ white 143121
☐ grey 143124





Corner connector, earth outside

16 A max. | plastic
L: 11.2 cm W: 11.2 cm H: 2 cm
☐ white Prod. no. 143251


NOBLO SPOT

1Ph., triple track set




PURI TRACK

1Ph., triple track set



220-240V ~50/60Hz | 350mA
Material: aluminium

- 2 x 1m high-voltage track
- 1 x feed-in/longitudinal connector
- 1 x 2 end caps
- 3 x NOBLO light heads



230V ~50Hz
Material: aluminium

- 2 x 1m high-voltage track
- 1 x longitudinal connector
- 1 x 2 end caps
- 3 x PURI light heads
- 3 x LED GU10 lamps
- 3 x decorative rings for GU10



Options	Prod. no.
1860lm 2700K CRI80	
■ black	1002610
1860lm 2700K CRI80	
□ white	1002611
1860lm 2700K CRI80	
■ grey	1002612



GU10

Options	Prod. no.
3xGU10	
■ black	143190
3xGU10	
□ white	143191
3xGU10	
■ grey	143194

1002611 470



143191 470







1004933 471



1004935 471

PANEL TRACK 1Ph., square

NEW



220-240V ~50/60Hz | 450mA
Total wattage: 18W
Material: polycarbonate (PC)/steel




hv	1800lm 3000K	A → G A ↑ E
1004933, 1004934		

Options	Prod. no.
1800lm 3000K CRI90	
■ black	1004933 ■
1800lm 3000K CRI90	
□ white	1004934 ■

PANEL TRACK 1Ph., round

NEW






220-240V ~50/60Hz | 450mA
Total wattage: 18W
Material: polycarbonate (PC)/steel



hv	1800lm 3000K	A → G A ↑ E
1004935, 1004936		

Options	Prod. no.
1800lm 3000K CRI90	
■ black	1004935 ■
1800lm 3000K CRI90	
□ white	1004936 ■

NEW



220-240V ~50/60Hz
Material: aluminium/glass



GU10 <25W





LED GU10 | 3.2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10 ■ black	1006155 ■
1xGU10 □ white	1006156 ■

NEW



220-240V ~50/60Hz
Material: aluminium/glass



GU10 <25W




LED GU10 | 3.2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10 ■ black	1006159 ■
1xGU10 □ white	1006160 ■





1006160 472

ACCESSORIES

Fitu single ceiling rose

16A max.
Steel
H: 3.9 cm
Diameter: 8.5 cm
Incl. strain relief



Options	Prod. no.
■ black	132600
□ white	132601
■ chrome	132605

Fitu triple ceiling rose

16A max.
Steel
H: 5.4 cm
Diameter: 22 cm
Incl. strain relief



Options	Prod. no.
■ black	132610
□ white	132611
■ chrome	132615 ▼

Ceiling rose, 3-piece

16A max.
Steel
L: 60 cm W: 8.5 cm H: 5 cm
Incl. strain relief



Options	Prod. no.
■ black	1001818
□ white	1001819

Single-phase light adapter

6A max.
Polycarbonate (PC)
L: 8.2 cm W: 3.5 cm H: 4.2 cm
Max. mechanical load 2 kg



Options	Prod. no.
■ black	143120
□ white	143121
■ grey	143124




3-phase light adapter

10A max.
Plastic
Max. mechanical load 5 kg



Options	Prod. no.
■ black	145990
□ white	1001542
■ grey	145994

PARA CONE 14 1Ph., QPAR51



220-240V ~50/60Hz
Material: steel



GU10 <25W





LED GU10 | 3.2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ glossy black	1002873
1xGU10	
□ glossy white	1002874
1xGU10	
■ copper	1002875

PARA CONE 14 1Ph., PD, QPAR51



230V ~50Hz
Material: steel

- Textile cable
- Black/gold version with golden reflector
- All other versions with white reflector



GU10 <35W



LED GU10 | 3.2W
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1003101

Options	Prod. no.
1xGU10	
■ glossy black	143990
1xGU10	
□ glossy white	143991
1xGU10	
■ copper	1001968






143594 475

TONGA®
1Ph., PD, E14

SOCKET INSIDE **<60 W**



IP 20

150

220-240V ~50/60Hz
Material: aluminium/glass



1001968 474



E14 <60W
Diameter: 5 cm L: 13 cm





LED E14 | 4.2W | 320°
2700K | 370lm | EEK=F
4kWh/1000h



Prod. no. 1005284

Options	Prod. no.
1xE14	
grey/milky	143594

LIGHT EYE® 90 1Ph., QPAR51



230V ~50/60Hz
Material: steel



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004972



- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151040
- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151041
- Decorative lamp ring, diameter 5.7 cm
Prod. no. 151049

Options	Prod. no.
1xGU10	
■ black/chrome	144010
1xGU10	
□ white/chrome	144011
1xGU10	
■ copper	144019

LIGHT EYE® 150 1Ph., PD, QPAR111



220-240V ~50/60Hz
Material: steel



GU10 <75W





QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276



Options	Prod. no.
1xGU10	
■ black/chrome	1000713
1xGU10	
□ white/chrome	143621
1xGU10	
■ chrome	143620





143932


477

FORCHINI M 40 TRACK

1Ph., E27



SOCKET INSIDE **<40 W**



IP 20 150

220-240V ~50/60Hz
Material: aluminium/steel

- Pendant light adapter colour silver-grey [143930] / black [143932]



E27 <40W
Diameter: 6.8 cm L: 15.2 cm






LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h



Prod. no. 1005303



Options	Prod. no.
1xE27	
black/gold	143930
1xE27	
black/gold	143932

PURI TRACK 1Ph., QPAR51



220-240V ~50/60Hz
Material: aluminium/plastic



PURI TRACK 1Ph., QPAR51



220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)

- Decorative ring for QPAR51 included

PURIA TRACK 1Ph., QPAR51



220-240V ~50/60Hz
Material: aluminium/plastic



GU10 <10W



LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h



Prod. no. 1005077



GU10 <50W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972



GU10 <10W



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ black	1001868
1xGU10	
□ white	1001869
1xGU10	
■ grey	1001870

Options	Prod. no.
1xGU10	
■ black	143390
1xGU10	
□ white	143391
1xGU10	
■ grey	143392

Options	Prod. no.
1xGU10	
■ black	143450
1xGU10	
□ white	143451
1xGU10	
■ grey	143454





143390

478

AVO TRACK 1Ph., QPAR51



SOCKET INSIDE **<50 W**



220-240V ~50/60Hz
Material: steel



GU10 <50W
Diameter: 5 cm



LED GU10 51mm | 6W | 38°
2700K | 450lm | EEK=G
6kWh/1000h





Prod. no. 1005076

Options	Prod. no.
1xGU10	
■ black	144200
1xGU10	
□ white	144201
1xGU10	
■ grey	144204

ENOLA C TRACK


1-phase



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

ENOLA C TRACK




1-phase



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

ENOLA B TRACK

1Ph., QPAR51



220-240V ~50/60Hz
Material: aluminium/steel



hV	Color Temperature	Beam Angle
1000711, 143941	1040lm 3000K	A → G
		A → E



hV	Color Temperature	Beam Angle
1000712, 143951	1040lm 3000K	A → G
		A → E



hV	Color Temperature	Beam Angle
1005079	LED GU10 51mm 6W 38° 3000K 470lm EEK=F 6kWh/1000h	A → G
		A → E

LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h




Prod. no. 1005079

Options	Prod. no.
1040lm 3000K CRI80 35°	
■ black	1000711
1040lm 3000K CRI80 35°	
□ white	143941

Options	Prod. no.
1040lm 3000K CRI80 55°	
■ black	1000712
1040lm 3000K CRI80 55°	
□ white	143951

Options	Prod. no.
1xGU10	
■ black	1002110
1xGU10	
□ white	1002111
1xGU10	
■ grey	1002113



1002110 480




143960 481

ENOLA B
PD, QPAR51



Socket Inside

<50 W



IP 20

150

230V ~50Hz
Material: aluminium/steel



GU10 <50W





LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972

Options	Prod. no.
1xGU10	
■ black	143960
1xGU10	
□ white	143961
1xGU10	
■ grey	143964

BIMA
 1Ph., double, QPAR51


220-240V ~50/60Hz
 Material: aluminium







GU10 <50W
 Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
 2700K | 270lm | EEK=G
 4kWh/1000h

Prod. no. 1004972

Options	Prod. no.
2xGU10	
■ black	143430
2xGU10	
□ white	143431
2xGU10	
■ grey	143432

BIMA
 1Ph., single, QPAR51


220-240V ~50/60Hz
 Material: aluminium




GU10 <50W
 Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 6W | 38°
 3000K | 470lm | EEK=F
 6kWh/1000h

Prod. no. 1005080

Options	Prod. no.
1xGU10	
■ black	143440
1xGU10	
□ white	143441
1xGU10	
■ grey	143442



143430

482




143440




482






1001862 483



143581 483

NOBLO SPOT
Single-phase

220-240V ~50/60Hz | 350mA
Total wattage: 7.5W
Material: aluminium

HELIA 50 TRACK
Single-phase

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium






hv		A → G
1001862, 1001863, 1001864	620lm 2700K	A A G E

Options	Prod. no.
620lm 2700K CRI80	
■ black	1001862
620lm 2700K CRI90	
□ white	1001863
620lm 2700K CRI90	
■ grey	1001864





hv		A → G
143580, 143581	810lm 880lm 3000K	A A G E

Options	Prod. no.
810lm 3000K CRI90	
■ black	143580
880lm 3000K CRI90	
□ white	143581

KALU TRACK
1Ph., PHASE

220-240V ~50/60Hz
Total wattage: 13W
Material: aluminium

KALU TRACK
1Ph., QPAR111

220-240V ~50/60Hz
Material: aluminium/plastic



GU10 <75W



QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276



Options	Prod. no.
860lm 3000K CRI80	
■ black	1002854
860lm 3000K CRI80	
□ white	143731

Options	Prod. no.
860lm 3000K CRI80	
■ black	1002854
860lm 3000K CRI80	
□ white	143731



Options	Prod. no.
1xGU10	
■ black	143540
1xGU10	
□ white	143541
1xGU10	
■ grey	143544

143731 484



1002854 484





220-240V ~50/60Hz
Material: aluminium



GU10 <50W




Prod. no. 1004972

Options	Prod. no.
1xGU10 ■ black	143350
1xGU10 □ white	143351
1xGU10 ■ grey	143354

SNAPPY AND CHIC.

THE DECORATIVE HIGH-VOLTAGE
EASYTEC® II TRACK SYSTEM.

With this decorative track system, you can create your own lighting mood in just a few steps. The aluminium support rails are available in different colours, allowing perfect coordination with any environment.







184440 492



HIGH-VOLTAGE EASYTEC® II TRACK SYSTEM



Matching tracks and accessories can be found on page 491





You can find more lights and variants at www.slv.com
Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808



185590 495

EASYTEC® II

Track with matching accessories




	2 m	2 m
Nominal voltage (V)	220-240V ~50/60Hz	220-240V ~50/60Hz
Max. current (A)	16	16
Material	aluminium	aluminium
Colour	■ black	■ grey
L x W x H (cm)	200 x 1 x 3	200 x 1 x 3
Prod. no.	184020	184022



Flexible feed-in

16A max. | aluminium
L: 7.5 cm W: 7.5 cm H: 6 cm
Cable length 40 cm

■ black Prod. no.: 184004
■ grey 184002



Ceiling suspension, adjustable

Aluminium
Adjustable from 18-26 cm

■ black Prod. no.: 184060
■ grey 184062



Shortbox feed-in

16A max. | aluminium/steel
W: 22 cm H: 10.5 cm

■ black Prod. no.: 184010
■ grey 184012



Flex connector

16 A max. | plastic
L: 21.5 cm W: 3 cm H: 4 cm

■ black Prod. no.: 184300
■ grey 184302



Longitudinal connector electrical

16A max. | aluminium

■ black Prod. no.: 184030
■ grey 184032



End caps

Plastic

■ black Prod. no.: 184140
■ grey 184142



Insulating connector

Aluminium

■ black Prod. no.: 184170
■ grey 184172



Easytec® II Pendant light adapter

3A max. | aluminium/plastic
L: 13 cm
Max. mechanical load 2 kg

■ black Prod. no.: 184290
■ grey 184292



Flexible ceiling suspension, adjustable

Aluminium
Adjustable from 23-31 cm

■ black Prod. no.: 184330
■ grey 184332



Bending tool for radi > 25cm



Steel/plastic

■ grey Prod. no.: 184000

BIMA EASYTEC® II, single, QPAR51



<50 W





220-240V ~50/60Hz
Material: aluminium

BIMA EASYTEC® II, double, QPAR51




<50 W





220-240V ~50/60Hz
Material: aluminium

KANO EASYTEC® II, QPAR51



<50 W



220-240V ~50/60Hz
Material: aluminium/glass



GU10 <50W
Diameter: 5.1 cm L: 5.7 cm



LED GU10 51mm | 5W | 38°
2700-6500K | 380lm | EEK=F
5kWh/1000h

Prod. no. 1005311

Options	Prod. no.
1xGU10	
■ black	184450
1xGU10	
■ grey	184452



GU10 <50W
Diameter: 5.1 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
2xGU10	
■ black	184440



GU10 <50W
Diameter: 5.1 cm L: 5.7 cm



LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h

Prod. no. 1005079

Options	Prod. no.
1xGU10	
■ grey	184071



184450 492



184440 492



ANILA
EASYTEC® II, QPAR51



220-240V ~50/60Hz
Material: aluminium/glass



GU10 <50W
Diameter: 5.1 cm L: 5.7 cm

LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972

Options	Prod. no.
1xGU10	
■ black	184630
1xGU10	
■ grey	184634

TONGA®
EASYTEC® II, PD, E14



220-240V ~50/60Hz
Material: aluminium/glass

E14 <60W
Diameter: 5 cm L: 13 cm

C35 | 4.2W | 320°
2700K | 380lm | EEK=F
5kWh/1000h

Prod. no. 1005284



Options	Prod. no.
1xE14	
■ black	184530
1xE14	
■ grey	184534

184534 494

185590 495



LIGHT EYE® 150
EASYTEC® II, PD, QPAR111



IP 20 150

220-240V ~50/60Hz
Material: steel



GU10 <75W




QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276



Options	Prod. no.
1xGU10	
■ black	184590
1xGU10	
■ black/chrome	185590

LIGHT EYE® 150 TRACK
EASYTEC® II, QPAR111



IP 20 350° 90°

220-240V ~50/60Hz
Material: steel



GU10 <75W



QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276



Options	Prod. no.
1xGU10	
 black/chrome	185580



A PASSION FOR DETAIL.

ACCENT LIGHTING WITH A LOW-VOLTAGE CABLE SYSTEM.

Light helps to give your rooms their own special atmosphere. Wherever you want to create a cosy yet professional look, low-voltage cable systems are the perfect solution, offering scope for individual lighting concepts and creating a sense of comfort.






1002862 504



139112


504



139131

503

LOW-VOLTAGE CABLE SYSTEM



Matching accessories can be found on pages 500-501



You can find more lights and variants at www.slv.com
Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808



TENSEO

Low-voltage cable system with matching accessories



TENSEO 4 mm²	10 m	10 m	10 m
Max. voltage	48V	48V	48V
Max. current load	25A	25A	25A
Material	copper/ plastic	copper/ plastic	copper/ plastic
Colour	■ black	□ white	□ transparent
Diameter (cm)	0,4	0,4	0,4
Length (cm)	1000	1000	1000
Prod. no.	1002602	1002603	1002604

20 m	20 m	20 m
48V	48V	48V
25A	25A	25A
copper/ plastic	copper/ plastic	copper/ plastic
■ black	□ white	□ transparent
0,4	0,4	0,4
2000	2000	2000
139030	139031	139024

TENSEO 4 mm²	100 m	100 m	10 m
Max. voltage	48V	48V	48V
Max. current load	25A	25A	25A
Material	copper/ plastic	copper/ plastic	copper/ plastic
Colour	■ black	□ white	□ transparent
Diameter (cm)	0,4	0,4	0,4
Length (cm)	10000	10000	10000
Prod. no.	139040	139041	139004

TENSEO 6 mm²	20 m	20 m	20 m
Max. voltage	48V	48V	48V
Max. current load	25A	25A	25A
Material	copper/ plastic	copper/ plastic	copper/ plastic
Colour	■ black	□ white	□ transparent
Diameter (cm)	0,6	0,6	0,6
Length (cm)	2000	2000	2000
Prod. no.	139050	139051	139026

100 m	100 m	100 m
48V	48V	48V
25A	25A	25A
copper/ plastic	copper/ plastic	copper/ plastic
■ black	□ white	□ transparent
0,6	0,6	0,6
10000	10000	10000
139060	139061	139006

**TENSEO Transformer | 12V AC**

50VA conventional | steel/brass
H: 11 cm diameter: 11.1 cm

■ black Prod. no. **1002691**
□ white **1002692**
■ chrome **1002693**

**Wall/ceiling bracket, flexible**

Steel/brass
H: 11.5 cm diameter: 5 cm

■ black Prod. no. **186310**
□ white **186311**
■ chrome **186312**

**TENSEO Transformer | 12V AC**

105VA conventional | steel/brass
H: 11 cm diameter: 11.1 cm

□ white Prod. no. **138981**
■ chrome **138982**

**Redirector**

Steel/brass
H: 16 cm diameter: 5 cm

■ black Prod. no. **186640**
□ white **186641**
■ chrome **186642**

**TENSEO Transformer | 12V AC**

210VA conventional | steel/brass
H: 11 cm diameter: 11.1 cm

□ white Prod. no. **138991**
■ chrome **138992**

**Feed-in**

25A max. | brass
H: 1.8 cm diameter: 1 cm

■ black Prod. no. **186350**
□ white **186351**
■ chrome **186352**

**Cord tightener**


25A max. | brass
H: 11 cm diameter: 1 cm

■ black Prod. no. **181530**
□ white **181531**
■ chrome **181532**

**Insulating connector**

25A max. | aluminium/plastic
L: 6.4 cm diameter: 1 cm

■ black Prod. no. **186360**
□ white **186361**
■ chrome **186362**

**Wall bracket**

Steel/brass
L: 3 cm diameter: 5 cm

■ black Prod. no. **186300**
□ white **186301**
■ chrome **186302**

**Spacer TENSEO**

Aluminium
H: 9 cm diameter: 1.25 cm

■ black Prod. no. **1002700**
□ white **1002701**
■ chrome **1002702**

**Ceiling bracket**

Steel/brass
H: 6 cm diameter: 5 cm

■ black Prod. no. **186330**
□ white **186331**
■ chrome **186332**

**Electrical spacer**


25A max. | brass
H: 9 cm diameter: 1.25 cm

■ black Prod. no. **1002703**
□ white **1002704**
■ chrome **1002705**

**Ceiling bracket**

Steel/brass
H: 16 cm diameter: 5 cm

■ black Prod. no. **186340**
□ white **186341**
■ chrome **186342**



**Cable suspension set**

Steel/aluminium
W: 18.6 cm diameter: 1.25 cm L: 2000 cm

■ black Prod. no. **1002697**
□ white **1002698**
■ chrome **1002699**




ASMARA
LV, QR-C51




12V ~50Hz
Material: stainless steel

TELESKOP
LV, QR-C51



12V ~50Hz
Material: steel/brass
• Telescopic fitting adjustable from 21-51cm



GX5.3 <35W



LED GU5.3 | 5.5W | 36°
2700K | 450lm | EEC=G
7kWh/1000h

Prod. no. 1001574



GX5.3 <20W



LED GU5.3 | 5.5W | 36°
3000K | 450lm | EEC=G
7kWh/1000h



Prod. no. 1001575



Options	Prod. no.
1xGX5,3	
■ black	139070
1xGX5,3	
□ white	139071
1xGX5,3	
■ chrome	139072

Options	Prod. no.
1xGX5,3	
■ black	139080
1xGX5,3	
□ white	139081
1xGX5,3	
■ chrome	139082

ORBIT
LV, QR111



12V ~50Hz
Material: steel



G53 <50W






LED G53 | 15W | 40°
2700K | 800lm | EEK=G
17kWh/1000h

Prod. no. 560232

Options	Prod. no.
1xG53	
■ black	139110
1xG53	
□ white	139111
1xG53	
■ chrome	139112

DURNO



12V ~50Hz
Total wattage: 6W
Material: aluminium/stainless steel





		
1002861, 1002862, 1002863	360lm 2700K	

Options	Prod. no.
360lm 2700K CRI80 ■ black	1002861
360lm 2700K CRI80 □ white	1002862
360lm 2700K CRI80 ■ polished chrome/ polished stainless steel	1002863






PLYTTA






120° L70B50

12V ~50Hz
Total wattage: 9.8W
Material: plastic/aluminium






		
1002864, 1002865, 1002866	750lm 2700K	



Options	Prod. no.
750lm 2700K CRI80 ■ black	1002864
750lm 2700K CRI90 □ white	1002865
750lm 2700K CRI90 ■ chrome	1002866

NOBLO SPOT
LV, Rope Track

12V ~50Hz
Total wattage: 8.5W
Material: aluminium/poly (methyl methacrylate) (PMMA)

COMET LED
LV

12V ~50Hz
Total wattage: 6.6W
Material: aluminium/glass

COMET
LV, QR-C51

12V ~50Hz
Material: brass/brass



lv		A → G
1002694, 1002695, 1002696	420lm 450lm 2700K	A G F



lv		A → G
1002688, 1002689, 1002690	410lm 2700K	A G F



GU5.3 <50W



LED GU5.3 | 5.5W | 36°
2700K | 450lm | EEK=G
7kWh/1000h

Prod. no. 1001574



Options	Prod. no.
420lm 2700K CRI80	
■ black	1002694
450lm 2700K CRI80	
□ white	1002695
450lm 2700K CRI80	
■ chrome	1002696

Options	Prod. no.
410lm 2700K CRI80	
■ black/frosted	1002688
410lm 2700K CRI80	
□ white/frosted	1002689
410lm 2700K CRI80	
■ chrome/frosted	1002690


Options	Prod. no.
1xGU5.3	
■ black	139120
1xGU5.3	
□ white	139121
1xGU5.3	
■ chrome	139122



1002695 506



1002690 506




139120 506



SHOW THE WAY.

MOBILE LIGHTS AND FLOOR LIGHTS.

Fumbling around in the dark is now a thing of the past: mobile lights and floor lights are a popular design feature for outdoor areas, showing people the way and keeping them safe. Our outdoor lights owe their unique appearance to their high-quality materials, modern shapes and innovative technologies.





1006184 521



1001823 527



MOBILE LIGHTS AND FLOOR LIGHTS






You can find more lights and variants at www.slv.com

Manufacturer's details for our recommended lamps are given in the 'Lamps' chapter, starting on page 808

ESKINA FRAME 45




Pole, single



220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium

ESKINA FRAME 75





Pole, single



220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium

ESKINA FRAME 75

Pole, double



220-240V ~50/60Hz | 700mA
Total wattage: 27W
Material: aluminium



Spot	1100/1200lm 3000/4000K	A → G D
------	---------------------------	------------



■ Connection box IP68, 3-pole
Prod. no. 228730



Spot	1100/1200lm 3000/4000K	A → G D
------	---------------------------	------------



■ Connection box IP68, 3-pole
Prod. no. 228730



Spot 1/Spot 2	1100/1200lm 3000/4000K	A → G D
---------------	---------------------------	------------



■ Connection box IP68, 3-pole
Prod. no. 228730

Options **Prod. no.**
1100/1200lm | 3000/4000K | CRI80
■ anthracite **1004749**

Options **Prod. no.**
1100/1200lm | 3000/4000K | CRI80
■ anthracite **1004750**



Options **Prod. no.**
Spot 1: 1100/1200lm | 3000/4000K | CRI80
Spot 2: 1100/1200lm | 3000/4000K | CRI80
■ anthracite **1004751**



1004751 512

ESKINA FRAME 125
Pole, double

NEW



220-240V ~50/60Hz | 700mA
Total wattage: 27W
Material: aluminium




Spot 1/Spot 2	1100/1200lm 3000/4000K	A → G A → G
---------------	---------------------------	----------------



Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
Spot 1: 1100/1200lm 3000/4000K CRI80	
Spot 2: 1100/1200lm 3000/4000K CRI80	
anthracite	1005439



1005439 514



1005440 515




ESKINA FRAME 175

Pole, double



NEW



220-240V ~50/60Hz | 700mA

Total wattage: 27W

Material: aluminium



Spot 1/Spot 2	1100/1200lm 3000/4000K	



Connection box IP68, 3-pole
Prod. no. 228730







Options	Prod. no.
Spot 1: 1100/1200lm 3000/4000K CRI80	
Spot 2: 1100/1200lm 3000/4000K CRI80	
anthracite	1005440

ESKINA 30 Pole




ESKINA 80 Pole



220-240V ~50/60Hz | 350mA
Total wattage: 14.5W
Material: aluminium

- IP44 safety plug



220-240V ~50/60Hz | 350mA
Total wattage: 14.5W
Material: aluminium

1002906	1000lm 3000/4000K	A → G E
---------	----------------------	------------


Ground spike
Prod. no. 230060

Options	Prod. no.
1000lm 3000/4000K CRI80 anthracite	1002906

1002907	1000lm 3000/4000K	A → G E
---------	----------------------	------------

Ground spike
Prod. no. 230060

Options	Prod. no.
1000lm 3000/4000K CRI80 anthracite	1002907







232115 517



232125 517

LOGS 40
PoleLOGS 70
Pole

IP 44 L70B50

100-240V ~50/60Hz | 500mA
Total wattage: 10W
Material: aluminium



IP 44 L70B50

100-240V ~50/60Hz | 500mA
Total wattage: 10W
Material: aluminium



		A → G
232115	570lm 3000K	A 1 G D



- Connection box IP68, 3-pole
Prod. no. 228730
- Screw set
Prod. no. 228754
- Ground spike
Prod. no. 231230
- Concrete anchor
Prod. no. 232119

Options	Prod. no.
570lm 3000K CRI80	
■ anthracite	232115



		A → G
232125	570lm 3000K	A 1 G D



- Connection box IP68, 3-pole
Prod. no. 228730
- Screw set
Prod. no. 228754
- Ground spike
Prod. no. 231230
- Concrete anchor
Prod. no. 232119

Options	Prod. no.
570lm 3000K CRI80	
■ anthracite	232125

GRAFIT 30

Pole, round, E27

NEW



GRAFIT 60

Pole, round, E27


NEW



GRAFIT 90


Pole, round, E27

NEW




220-240V ~50/60Hz
Material: aluminium/acrylic

- Open cable end



220-240V ~50/60Hz
Material: aluminium/acrylic

- Open cable end



220-240V ~50/60Hz
Material: aluminium/acrylic

- Open cable end



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 7.5W | 320°
2700K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005304



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h

Prod. no. 1005303



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730



■ Connection box IP68, 3-pole
Prod. no. 228730



■ Connection box IP68, 3-pole
Prod. no. 228730



Options Prod. no.

1xE27
■ anthracite 1006180 ■

Options Prod. no.

1xE27
■ anthracite 1006181 ■

Options Prod. no.

1xE27
■ anthracite 1006182 ■






231225 521



GRAFIT 30

Pole, E27



220-240V ~50/60Hz
Material: aluminium/plastic

- Open cable end



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005290



■ Connection box IP68, 3-pole

Prod. no. 228730

■ Screw set

Prod. no. 228754


■ Ground spike

Prod. no. 231230

Options	Prod. no.
1xE27	
■ anthracite	231215

GRAFIT 60

Pole, E27



220-240V ~50/60Hz
Material: aluminium/plastic

- Open cable end



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



■ Connection box IP68, 3-pole

Prod. no. 228730

■ Screw set

Prod. no. 228754

■ Ground spike

Prod. no. 231230


Options	Prod. no.
1xE27	
■ anthracite	231225

GRAFIT 90

Pole, E27



NEW



220-240V ~50/60Hz
Material: aluminium/acrylic

- Open cable end



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302



■ Connection box IP68, 3-pole

Prod. no. 228730

■ Screw set

Prod. no. 228754

■ Ground spike



Prod. no. 231230

Options	Prod. no.
1xE27	
■ anthracite	1006184

QUADRULO
FL



NEW



100-277V ~50/60Hz | 480mA
Total wattage: 7W
Material: aluminium/acrylic


- IP connection box






		A → G
1005442	340lm 3000K	A G E

Options	Prod. no.
340lm 3000K CRI80 ■ anthracite/white	1005442 ■








RUSTY® SLOT 50
Pole


220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end

RUSTY® SLOT 80
Pole

220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end

RUSTY® SLOT 50
Pole, E27

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

- Open cable end



233447	30lm 3000K	



233457	30lm 3000K	



E27 <11W	Diameter: 4.8 cm L: 13.9 cm	



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231230



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231230



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231230


Options	Prod. no.
30lm 3000K CRI80	
■ rust	233447

Options	Prod. no.
30lm 3000K CRI80	
■ rust	233457

Options	Prod. no.
1xE27	
■ rust	229410



RUSTY® SLOT 80 Pole, E27



IP 44

220-240V ~50/60Hz

Material: FeCSi steel/polycarbonate (PC)

- Open cable end



E27 <11W

Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289



■ Connection box IP68, 3-pole

Prod. no. 228730

■ Ground spike

Prod. no. 231230




Options

Prod. no.

1xE27

■ rust

229411




233447

524



229411

525





230090 526



1001823 527





RUSTY® PATHLIGHT 40 Pole



220-240V ~50/60Hz
Total wattage: 8.9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end


RUSTY® PATHLIGHT 70 Pole



220-240V ~50/60Hz
Total wattage: 8.9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end

RUSTY® PATHLIGHT Pole, TCR-TSE



220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

- Open cable end



1001823	400lm 3000K	A → G F
---------	----------------	------------



1001824	400lm 3000K	A → G F
---------	----------------	------------



GX53 <9W
Diameter: 7.5 cm L: 2.7 cm



LED GX53 | 6W | 120°
4000K | 550lm | EEK=F
6kWh/1000h



Prod. no. 1005269



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229422



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229422





■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229422



Options	Prod. no.
400lm 3000K CRI80	
■ rust	1001823



Options	Prod. no.
400lm 3000K CRI80	
■ rust	1001824

Options	Prod. no.
1xGX53	
■ rust	230090

RUSTY® 40
Pole

220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end

RUSTY® 70
Pole

220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end



		A → G
233427	90lm 3000K	A G E



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229422

Options	Prod. no.
90lm 3000K CRI80	
■ rust	233427




		A → G
233437	90lm 3000K	A G E



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229422

Options	Prod. no.
90lm 3000K CRI80	
■ rust	233437







RUSTY® 40

Pole, E27



RUSTY® 70

Pole, E27



IP 55

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

- Open cable end



IP 55

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

- Open cable end



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005290



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 229422




■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 229422



Options	Prod. no.
1xE27	
■ rust	229420

Options	Prod. no.
1xE27	
■ rust	229421

RUSTY® CONE 24
FL, E14

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)




E14 <40W
Diameter: 4.8 cm L: 13.9 cm



LED E14 | 4.2W | 320°
2700K | 350lm | EEK=G
5kWh/1000h



Prod. no. 1005285

RUSTY® CONE 40
Pole, E27

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730




■ Ground spike
Prod. no. 229423



Options	Prod. no.
1xE14	
■ rust	229430

Options	Prod. no.
1xE27	
■ rust	229431

RUSTY® CONE 70
Pole, E27

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005290



■ Connection box IP68, 3-pole
Prod. no. 228730





■ Ground spike
Prod. no. 229423





Options	Prod. no.	Options	Prod. no.	Options	Prod. no.
1xE14		1xE27		1xE27	
■ rust	229430	■ rust	229431	■ rust	229432



RUSTY® 40
Pole

220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end
- Every light is a unique one-off piece

RUSTY® 70
Pole

220-240V ~50/60Hz
Total wattage: 9W
Material: FeCSi steel/polycarbonate (PC)

- Open cable end
- Every light is a unique one-off piece



		A → G
233407	70lm 3000K	A ↑ G ↓ E



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229022

Options	Prod. no.
70lm 3000K CRI80 ■ rust	233407



		A → G
233417	70lm 3000K	A ↑ G ↓ E



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229022

Options	Prod. no.
70lm 3000K CRI80 ■ rust	233417





229021 533



229020 533



RUSTY® 40

Pole, E27



RUSTY® 70

Pole, E27



IP 55



IP 55

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

220-240V ~50/60Hz
Material: FeCSi steel/polycarbonate (PC)

- Open cable end
- Every light is a unique one-off piece

- Open cable end
- Every light is a unique one-off piece



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



E27 <11W
Diameter: 4.8 cm L: 13.9 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005290



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229022



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 229022




Options	Prod. no.
1xE27	
■ rust	229020

Options	Prod. no.
1xE27	
■ rust	229021

ARROCK GRANITE 40

Pole, square, E27



220-240V ~50/60Hz
Material: granite/304 stainless steel



E27 <15W
Diameter: 5.2 cm L: 11.5 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730




■ Ground spike
Prod. no. 229422



Options	Prod. no.
1xE27	
■ grey	231410

ARROCK GRANITE 70

Pole, square, E27



220-240V ~50/60Hz
Material: granite/304 stainless steel



E27 <15W
Diameter: 5.2 cm L: 11.5 cm



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005290



■ Connection box IP68, 3-pole
Prod. no. 228730



■ Ground spike
Prod. no. 229422



Options	Prod. no.
1xE27	
■ grey	231411






231410 534



231420 535

ARROCK ARC
Pole, QPAR51



IP 44

220-240V ~50/60Hz
Material: granite/304 stainless steel



GU10 <35W
Diameter: 5 cm L: 7.6 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972




■ Ground spike
Prod. no. 231233




Options	Prod. no.
1xGU10	
grey	231420

ARROCK STONE 50 Pole



100-240V ~50/60Hz | 700mA
Total wattage: 9W
Material: basalt/304 stainless steel

ARROCK STONE 75 Pole



100-240V ~50/60Hz | 700mA
Total wattage: 9W
Material: basalt/304 stainless steel



Prod. no.	330lm 3000K	A → G F
231370		



Ground spike
Prod. no. 231235

Options	Prod. no.
330lm 3000K CRI80	
grey	231370




Prod. no.	330lm 3000K	A → G F
231371		



Ground spike
Prod. no. 231235

Options	Prod. no.
330lm 3000K CRI80	
grey	231371






ARROCK SLOT



Socket Inside

40W 60W 75W 100W 150W 200W 250W 300W 350W 400W



IP 44

220-240V ~50/60Hz
Material: granite/304 stainless steel

- Open cable end



GU10 <4W



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004973












■ Connection box IP68, 3-pole

Prod. no. 228730

■ Ground spike
Prod. no. 231235



Options	Prod. no.
1xGU10	
 grey	231440

L-LINE OUT 30
FL, verticalL-LINE OUT 50
Pole, horizontalL-LINE OUT 60
FL, vertical

220-240V ~50/60Hz | 500mA
Total wattage: 11.5W
Material: aluminium/polycarbonate (PC)

220-240V ~50/60Hz | 350mA
Total wattage: 7W
Material: aluminium/polycarbonate (PC)

220-240V ~50/60Hz | 500mA
Total wattage: 11.5W
Material: aluminium/polycarbonate (PC)

- Open cable end
- The light colour must be set prior to installation

- Open cable end
- The light colour must be set prior to installation

- Open cable end
- The light colour must be set prior to installation



1003536	800/810lm 3000/4000K	

1003537	490/530lm 3000/4000K	

1003535	780/800lm 3000/4000K	



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Connection box IP68, 3-pole
Prod. no. 228730

■ Connection box IP68, 3-pole
Prod. no. 228730

Options **Prod. no.**
800/810lm | 3000/4000K | CRI>80
■ anthracite **1003536**



Options **Prod. no.**
490/530lm | 3000/4000K | CRI>80
■ anthracite **1003537**

Options **Prod. no.**
780/800lm | 3000/4000K | CRI80
■ anthracite **1003535**



L-LINE OUT 80

Pole, horizontal



220-240V ~50/60Hz | 350mA

Total wattage: 7W

Material: aluminium/polycarbonate (PC)

- Open cable end
- The light colour must be set prior to installation



		A → G
1003538	490/530lm 3000/4000K	A ↑ G ↓



■ Connection box IP68, 3-pole
Prod. no. 228730



Options	Prod. no.
490/530lm 3000/4000K CRI>80	
■ anthracite	1003538



1003536 538






1003537 538


THEO PATHLIGHT
Pole, single



THEO PATHLIGHT
Pole, double



220-240V ~50/60Hz
Material: aluminium



220-240V ~50/60Hz
Material: aluminium



GU10 <7W



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Connection box IP68, 3-pole
Prod. no. 228730



Options	Prod. no.
1xGU10	
anthracite	1002870



GU10 <7W



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004973



Connection box IP68, 3-pole
Prod. no. 228730




Options	Prod. no.
2xGU10	
anthracite	1002871





1004655 541

THEO BRACKET 50 Pole



IP 65 70°

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <7W
Diameter: 5.1 cm L: 5.7 cm




LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



THEO BRACKET 70 Pole



IP 65 70°

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <7W
Diameter: 5.1 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h




Prod. no. 1004973



Options	Prod. no.
1xGU10	
■ anthracite	1004654




Options	Prod. no.
1xGU10	
■ anthracite	1004655

OVALISK 75 Pole



100-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/glass

OVALISK 100 Pole



100-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/glass



1004680	580/630lm 3000/4000K	



- Concrete anchor
Prod. no. 228712
- Ground spike
Prod. no. 228722
- Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
560/600lm 3000/4000K CRI80	
anthracite	1004680




1004681	580/630lm 3000/4000K	



- Concrete anchor
Prod. no. 228712
- Ground spike
Prod. no. 228722
- Connection box IP68, 3-pole
Prod. no. 228730


Options	Prod. no.
560/600lm 3000/4000K CRI80	
anthracite	1004681



1004680 542





1004681 542





GLOO PURE 27

Pole, E27





220-240V ~50/60Hz
Material: aluminium/glass

- Open cable end

GLOO PURE 44

Pole, E27





220-240V ~50/60Hz
Material: aluminium/glass

- Open cable end

GLOO PURE 70

Pole, E27



220-240V ~50/60Hz
Material: aluminium/glass

- Open cable end



E27 <23W
Diameter: 4.8 cm L: 18 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 231234

Options	Prod. no.
1xE27	
■ anthracite	1001999



E27 <23W
Diameter: 4.8 cm L: 18 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 231234

Options	Prod. no.
1xE27	
■ anthracite	1002000



E27 <23W
Diameter: 4.8 cm L: 18 cm



LED E27 | 8W | 240°
4000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005290



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 231234

Options	Prod. no.
1xE27	
■ anthracite	1002001



227221







546

227219

546

PHOTONIA
PD, E27

PHOTONIA
TL, E27



220-240V ~50/60Hz
Material: aluminium/glass

220-240V ~50/60Hz
Material: aluminium/glass

- IP44 safety plug
- Suspension chain included

- IP44 safety plug



E27 <60W
Diameter: 9 cm L: 15 cm



E27 <60W
Diameter: 9 cm L: 15 cm



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h



Prod. no. 1005268



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h



Prod. no. 1005268



Ceiling rose

Prod. no. 1000398



Options	Prod. no.
1xE27	
 anthracite	232065

Options	Prod. no.
1xE27	
 anthracite	232095 ▼






232075 549



PHOTONIA Pole, E27



SOCKET INSIDE **<60 W**



IP 55

IK03

20

220-240V ~50/60Hz
Material: aluminium/glass

- Open cable end



E27 <60W
Diameter: 9 cm L: 15 cm



LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h



Prod. no. 1005265




■ Connection box IP68, 3-pole
Prod. no. 228730

■ Concrete anchor
Prod. no. 232085



Options	Prod. no.
1xE27	
■ anthracite	232075

OTOS GLAS
Pole, E27



220-240V ~50/60Hz
Material: aluminium/glass

- Concrete anchor included



E27 <15W
Diameter: 6.5 cm L: 14.5 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302



- Connection box IP68, 3-pole
Prod. no. 228730

- Screw set

Prod. no. 228753

Options	Prod. no.
1xE27	
■ anthracite	230465






230435 551



CUBIX
FL, QPAR51



220-240V ~50/60Hz
Material: aluminium/glass

- IP44 safety plug



GU10 <25W





LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972

Options	Prod. no.
1xGU10	
■ anthracite	132835

CONE
FL, E27



220-240V ~50/60Hz
Material: aluminium/glass



E27 <100W
L: 15 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h


Prod. no. 1005302

Options	Prod. no.
1xE27	
■ anthracite	230435

MOLAT
PD, E27



MOLAT
Pole, E27



220-240V ~50/60Hz
Material: aluminium/glass

- IP44 safety plug
- Suspension chain included



E27 60W
Diameter: 6.5 cm L: 14.5 cm



LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005265



■ Ceiling rose
Prod. no. 1000398



Options	Prod. no.
1xE27	
■ anthracite	1000821



220-240V ~50/60Hz
Material: aluminium/glass



E27 60W
Diameter: 6.5 cm L: 14.5 cm



LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h


Prod. no. 1005265



■ Ground spike
Prod. no. 230060



Options	Prod. no.
1xE27	
■ anthracite	1000822



1000821 552



1000822 552

ADEGAN MANILA FL, E27



SOCKET INSIDE                                                   




228965 555

ADEGAN FL, E27



**SOCKET
INSIDE** **<15
W**



IP 44

IK 04

250

220-240V ~50/60Hz
Material: granite/stainless steel

- IP44 safety plug



E27 <15W
Diameter: 4.8 cm L: 18 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h




Prod. no. 1005289

Options	Prod. no.
1xE27	
anthracite/milky	228965



228925

557






228935

557

APONI 90
Pole, PHASE



APONI 120
Pole, PHASE



220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium

- Open cable end





1000682	520lm 3000K	A → G A G E
---------	----------------	-------------------



■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
440lm 3000K CRI80 ■ anthracite	1000682



220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium

- Open cable end



1000683	520lm 3000K	A → G A G E
---------	----------------	-------------------



■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
440lm 3000K CRI80 ■ anthracite	1000683






1000683 558





TRUST 30 Pole

TRUST 60 Pole



220-240V ~50/60Hz
Total wattage: 9W
Material: stainless steel 316

220-240V ~50/60Hz
Total wattage: 9W
Material: stainless steel 316



		A → G
228100	400lm 3000K	A ↑ E

		A → G
228110	400lm 3000K	A ↑ E



■ Ground spike Prod. no. 227922	
■ Ring-shaped grid Prod. no. 228130	
■ Connection box IP68, 3-pole Prod. no. 228730	

■ Ground spike Prod. no. 227922	
■ Ring-shaped grid Prod. no. 228130	
■ Connection box IP68, 3-pole Prod. no. 228730	


Options	Prod. no.
400lm 3000K CRI80 ■ stainless steel	228100

Options	Prod. no.
400lm 3000K CRI80 ■ stainless steel	228110


BIG NAILS 50 POLE, E27



BIG NAILS 80 POLE, E27



220-240V ~50/60Hz
Material: 304 stainless steel/polycarbonate (PC)



220-240V ~50/60Hz
Material: 304 stainless steel/polycarbonate (PC)



E27 <15W
Diameter: 4.5 cm L: 17 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289



Ground spike
Prod. no. 227922



E27 <15W
Diameter: 4.5 cm L: 17 cm



LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h

Prod. no. 1005289




Ground spike
Prod. no. 227922



Options	Prod. no.
1xE27	
■ stainless steel	229162

Options	Prod. no.
1xE27	
■ stainless steel	229172





229172 560



1001490 561





ROX ACRYL 30





220-240V ~50/60Hz
Material: 304 stainless steel

ROX ACRYL 60



220-240V ~50/60Hz
Material: 304 stainless steel

ROX ACRYL 90



220-240V ~50/60Hz
Material: 304 stainless steel



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



■ T-connector box

Prod. no. 228726

■ Ground spike

Prod. no. 231234

■ Concrete anchor

Prod. no. 1001494



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302



■ T-connector box

Prod. no. 228726

■ Ground spike

Prod. no. 231234

■ Concrete anchor

Prod. no. 1001494



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 7.5W | 320°
2700K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005304



■ T-connector box

Prod. no. 228726

■ Ground spike

Prod. no. 231234

■ Concrete anchor

Prod. no. 1001494



Options	Prod. no.
1xE27	
■ stainless steel	1001488

Options	Prod. no.
1xE27	
■ stainless steel	1001489

Options	Prod. no.
1xE27	
■ stainless steel	1001490

VAP 40



SOCKET INSIDE                                                             





230066

565



VAP SLIM 30

Pole, E27




SOCKET INSIDE                                                         

C-POL
POLE, E27



SOCKET
INSIDE



220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)



E27 <24W
Diameter: 5.2 cm L: 17.3 cm



LED E27 | 8W | 240°
3000K | 870lm | EEC=E
8kWh/1000h



Prod. no. 1005289



■ Connection box IP68, 3-pole
Prod. no. 228730



Options	Prod. no.
1xE27	
■ anthracite	231475



231475 566






231595 567

F-POL POLE, E27



**SOCKET
INSIDE** **<20
W**



IP 54 IK05

220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)



E27 <20W
Diameter: 5 cm L: 14.8 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h



Prod. no. 1005289





■ Connection box IP68, 3-pole
Prod. no. 228730



Options	Prod. no.
1xE27	
■ anthracite	231595

SQUARE POLE 30



Pole, E27



220-240V ~50/60Hz
Material: 304 stainless steel

SQUARE POLE 60



Pole, E27



220-240V ~50/60Hz
Material: 304 stainless steel

SQUARE POLE 90

Pole, E27



220-240V ~50/60Hz
Material: 304 stainless steel



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



E27 <20W
Diameter: 6 cm L: 15 cm



LED E27 | 9W | 220°
2700K | 800lm | EEK=F
9kWh/1000h

Prod. no. 1005301



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231234

■ Concrete anchor
Prod. no. 1000343



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231234

■ Concrete anchor
Prod. no. 1000343



■ Connection box IP68, 3-pole
Prod. no. 228730

■ Ground spike
Prod. no. 231234

■ Concrete anchor
Prod. no. 1000343





Options	Prod. no.
1xE27	
■ stainless steel	1000344

Options	Prod. no.
1xE27	
■ stainless steel	1000345

Options	Prod. no.
1xE27	
■ stainless steel	1000346



SLOTS 45 Pole



220-240V ~50/60Hz
Total wattage: 6.3W
Material: aluminium

- Concrete anchor included



231815, 231817	200lm 3000K	A → G E
-------------------	----------------	------------




■ Connection box IP68, 3-pole
Prod. no. 228730



■ Screw set
Prod. no. 228753









Options	Prod. no.
200lm 3000K CRI80 ■ anthracite	231815
200lm 3000K CRI80 ■ rust	231817



231817 570

H-POL 30 Pole

H-POL 60 Pole



100-277V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/plastic

100-277V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/plastic

- This product is intended for in-floor installation
- Recessed fixing kit included
- A larger recessed fixing kit is available for optional installation in the ground. Installation dimensions of the optional recessed fixing kit: L: 14 cm W: 14 cm D: 16 cm

- This product is intended for in-floor installation
- Recessed fixing kit included
- A larger recessed fixing kit is available for optional installation in the ground. Installation dimensions of the optional recessed fixing kit: L: 14 cm W: 14 cm D: 16 cm

Light Type	Beam Angle	Beam Angle
Direct	350lm 3000K	A → G A → G


Light Type	Beam Angle	Beam Angle
Direct	700lm 3000K	A → G A → G

■ Recessed fixing kit, 14x14 cm
Prod. no. 232195

■ Recessed fixing kit, 14x14 cm
Prod. no. 232195

Options	Prod. no.
Direct: 350lm 3000K CRI80	
■ anthracite	232155

Options	Prod. no.
Direct: 700lm 3000K CRI80	
■ anthracite	232165






232175

573

H-POL TWIN 30 Pole



100-277V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/plastic

- This product is intended for in-floor installation
- Recessed fixing kit included
- A larger recessed fixing kit is available for optional installation in the soil. Installation dimensions of the optional recessed fixing kit: L: 14 cm W: 14 cm D: 16 cm




Direct	350lm 3000K	A → G A T G E
--------	----------------	---------------------------



■ Recessed fixing kit, 14x14 cm
Prod. no. 232195

Options	Prod. no.
Direct: 350lm 3000K CRI180	
Direct: 350lm 3000K CRI180	
■ anthracite	232175

H-POL TWIN 60 Pole



220-240V ~50/60Hz | 1000mA
Total wattage: 35W
Material: aluminium/plastic

- This product is intended for in-floor installation
- Recessed fixing kit included
- A larger recessed fixing kit is available for optional installation in the soil. Installation dimensions of the optional recessed fixing kit: L: 14 cm W: 14 cm D: 16 cm



Direct	700lm 3000K	A → G A T G E
--------	----------------	---------------------------




■ Recessed fixing kit, 14x14 cm
Prod. no. 232195

Options	Prod. no.
Direct: 700lm 3000K CRI80	
Direct: 700lm 3000K CRI80	
■ anthracite	232185

SLOTBOX 40

Pole



100-240V ~50/60Hz | 700mA
Total wattage: 8W
Material: aluminium

- Open cable end

		
232135	160lm 3000K	



Connection box IP68, 3-pole


Prod. no. 228730



Options	Prod. no.
160lm 3000K CRI80	
■ anthracite	232135


SLOTBOX 70

Pole



100-240V ~50/60Hz | 700mA
Total wattage: 8.7W
Material: aluminium

- Open cable end

		
232145	160lm 3000K	




Connection box IP68, 3-pole

Prod. no. 228730







Options	Prod. no.
160lm 3000K CRI80	
■ anthracite	232145





1002956 575

FLATT 65 POLE



IP 65 IK03 L70B50

100-240V ~50/60Hz | 350mA
Total wattage: 9.7W
Material: aluminium

- Light colour can be selected using the switch inside the housing prior to installation





Product Code	Light Output	Color Temperature
1002956, 1002957	400lm	3000/4000K



■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
400lm 3000/4000K CRI80	
■ anthracite/anthracite	1002956
400lm 3000/4000K CRI80	
■ anthracite/brown	1002957

FLATT 100 POLE



IP 65 IK03 L70B50

100-240V ~50/60Hz | 350mA
Total wattage: 9.7W
Material: aluminium

- Light colour can be selected using the switch inside the housing prior to installation





Product Code	Light Output	Color Temperature
1002958, 1002959	400lm	3000/4000K





■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
400lm 3000/4000K CRI80	
■ anthracite/anthracite	1002958
400lm 3000/4000K CRI80	
■ anthracite/brown	1002959

ABRIDOR 60
Pole

100-277V ~50/60Hz | 300mA
Total wattage: 14W
Material: aluminium

ABRIDOR 100
Pole

100-277V ~50/60Hz | 300mA
Total wattage: 14W
Material: aluminium



Product	Light Output	Beam Angle
1002991	750lm 3000/4000K	A → G E



■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
750lm 3000/4000K CRI80	
■ anthracite	1002991



Product	Light Output	Beam Angle
1002992	750lm 3000/4000K	A → G E



■ Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
750lm 3000/4000K CRI80	
■ anthracite	1002992







231305 577



232295 577

IPERI 50 Pole



230V ~50Hz
Total wattage: 5W
Material: aluminium/plastic




		A → G
231305	400lm 4000K	A → D



■ Ground spike
Prod. no. 231231

Options	Prod. no.
320lm 4000K CRI90 ■ anthracite	231305

QUADRASYL 75 Pole, TCR-TSE



220-240V ~50/60Hz
Material: aluminium

- Concrete anchor included
- Open cable end



GX53 <11W
Diameter: 7.5 cm L: 2.7 cm




LED GX53 | 6,1W | 120°
4000K | 520lm | EEK=F
6kWh/1000h

Prod. no. 1005269




■ T-connector box
Prod. no. 228726

Options	Prod. no.
1xGX53 ■ anthracite	232295
1xGX53 ■ grey	232294



1003001 578





1005441 579



1000801 579

QUAD POLE



100-277V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/glass

- Open cable end


								
1003001			1550lm 3000K					

 Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
1550lm 3000K CRI90	
 anthracite	1003001



BOOKAT Pole, PHASE




100-277 V ~50/60 Hz | 700 mA
Total wattage: 15W
Material: aluminium

- IP connection box included



Options	Prod. no.
1240/1300lm 3000/4000K CRI 80	
■ anthracite	1005441

RASCALI 45 Pole




220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium



Options	Prod. no.
360lm 3000K CRI90	
■ anthracite	1000799

RASCALI 65 Pole



220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium





Options	Prod. no.
360lm 3000K CRI90	
■ anthracite	1000801

Options	Prod. no.
1240/1300lm 3000/4000K CRI 80	
■ anthracite	1005441

Options	Prod. no.
360lm 3000K CRI90	
■ anthracite	1000799

Options	Prod. no.
360lm 3000K CRI90	
■ anthracite	1000801

ENOLA C
POLE



100-240V ~50/60Hz | 500mA
Total wattage: 12W
Material: aluminium/glass




		A → G
228545	1060lm 3000K	A G E



Connection box IP68, 3-pole
Prod. no. 228730



Options	Prod. no.
800lm 3000K CRI80 ■ anthracite	228545







1002198 581



1002200 581



HELIA Pole, single, PHASE



220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium/glass

- Open cable end

HELIA Pole, double, PHASE



220-240V ~50/60Hz
Total wattage: 16W
Material: aluminium/glass

- Open cable end



1002198	440lm 3000K	



■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 1000736

Options	Prod. no.
450lm 3000K CRI80	
■ anthracite	1002198



1002200	880lm 3000K	





■ Connection box IP68, 3-pole
Prod. no. 228730
■ Ground spike
Prod. no. 1000736

Options	Prod. no.
900lm 3000K CRI80	
■ anthracite	1002200

HELIA

Pole, single, PHASE





220-240V ~50/60Hz
Total wattage: 8W
Material: aluminium

- The height of the light can be increased by a maximum of 2 extension rods
- Open cable end



HELIA

Pole, double, PHASE



220-240V ~50/60Hz
Total wattage: 16W
Material: aluminium

- The height of the light can be increased by a maximum of 2 extension rods
- Open cable end



Light fixture	Light output	Color temperature
233275	440lm	3000K

Options	Prod. no.
Concrete anchor	Prod. no. 228712
Screw set	Prod. no. 228752
Pedestal	Prod. no. 233145
Extension rod, 30 cm	Prod. no. 233165

Options	Prod. no.
450lm 3000K CRI80	
anthracite	233275

Light fixture	Light output	Color temperature
233285	880lm	3000K

Options	Prod. no.
Concrete anchor	Prod. no. 228712
Screw set	Prod. no. 228752
Pedestal	Prod. no. 233145
Extension rod 30, cm	Prod. no. 233165


Options	Prod. no.
900lm 3000K CRI80	
anthracite	233285





MYRA SPOT

Double, GU10



220-240V ~50/60Hz
Material: aluminium

- The height of the light can be increased by a maximum of 2 extension rods
- Open cable end



GU10 <4.5W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Concrete anchor

Prod. no. 228712

Screw set

Prod. no. 228752

Pedestal

Prod. no. 233144

Extension rod

Prod. no. 233164

Options Prod. no.


2xGU10

grey

233184

MYRA SPOT

Double, GU10



220-240V ~50/60Hz
Material: aluminium

- The height of the light can be increased by a maximum of 2 extension rods
- Open cable end



GU10 <4.5W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004973



Concrete anchor

Prod. no. 228712

Screw set

Prod. no. 228752

Pedestal

Prod. no. 233145

Extension rod 30cm

Prod. no. 233165

Options Prod. no.



2xGU10

anthracite

233185

SITRA 360

Pole, TCR-TSE



220-240V ~50/60Hz
Material: aluminium/glass

- The height of the light can be increased by a maximum of 2 extension rods
- Open cable end



GX53 <9W
Diameter: 7.5 cm L: 3.5 cm



LED GX53 | 6W | 120°
4000K | 550lm | EEK=F
6kWh/1000h

Prod. no. 1005269



Ground spike

Prod. no. 230060

Options Prod. no.

2xGX53

anthracite

231505




THE SUN IS RISING.

SPOTLIGHTS CREATE DYNAMIC
LIGHTING EFFECTS.


Do you want to effectively illuminate an outdoor area?
Then check out our wide range of spotlights enabling fully customized
lighting now. Use them to illuminate buildings, seating, paths, other
garden highlights and more.







1004757 592



1006192 589

SPOTLIGHTS

NEW	NEW	NEW							
									
589	589	589	591	591	591	592	593		
									
593	594	595	595	595	597	598	598		
									
599	599	601	601	601	603				





You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the 'Lamps' chapter, starting on page 808



1006193 589

FLOODI S
SP



NEW



220-240V ~50/60Hz
Total wattage: 9.3W
Material: aluminium/glass

FLOODI M
SP



NEW



220-240V ~50/60Hz
Total wattage: 30W
Material: aluminium/glass

FLOODI L
SP

NEW



220-240V ~50/60Hz
Total wattage: 48W
Material: aluminium/glass



		A → G
1006191	1040lm 3000K	A 1 G E

Options Prod. no.

1040lm | 3000K | CRI80
■ anthracite

1006191



		A → G
1006192	2980lm 3000K	A 1 G E

Options Prod. no.

2980lm | 3000K | CRI80
■ anthracite

1006192



		A → G
1006193	5150lm 3000K	A 1 G E




Options Prod. no.

5150lm | 3000K | CRI80
■ anthracite

1006193



1003448 591




GALEN 60
SP

220-240V ~50/60Hz | 450mA
Total wattage: 18W
Material: aluminium/glass



1003447	1570/1570lm 3000/4000K	A → G A+ G E
---------	---------------------------	-----------------

Options **Prod. no.**
1570/1570lm | 3000/4000K | CRI80
■ anthracite **1003447**




GALEN 120
SP

220-240V ~50/60Hz | 900mA
Total wattage: 34W
Material: aluminium/glass



1003448	3000/3100lm 3000/4000K	A → G A+ G E
---------	---------------------------	-----------------

Options **Prod. no.**
3000/3100lm | 3000/4000K | CRI80
■ anthracite **1003448**

FLAC BEAM®
SP

220-240V ~50/60Hz
Total wattage: 27W
Material: aluminium

- IP44 safety plug




The energy efficiency class information for this product was not available at the time of printing. The latest product data can always be found at www.slv.com

Options **Prod. no.**
1800lm | 3000K | CRI90
■ grey **231072**



SAMRINA
SP, single, GU10



IP 65

IK04

280°

150

220-240V ~50/60Hz
Material: plastic/glass

- Contains recycled material
- IP44 safety plug



GU10 7W
Diameter: 6 cm L: 6 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Options	Prod. no.
GU10	
■ black	1004757





NAUTILUS 10
SP, round, QPAR51



SOCKET
INSIDE






231035 597



NAUTILUS 10 SP, square



IP 65

IK04

45°

L70B50

90°


200



100-277 V ~50/60 Hz | 700 mA
Total wattage: 8.5W
Material: aluminium/glass

- IP44 safety plug








		A → G
231035, 1001937	660lm 3000K	A F

Options	Prod. no.
660lm 3000K CRI80	
■ anthracite	231035
660lm 3000K CRI80	
■ rust	1001937




DASAR® PROJECTOR
SP, 12/24V

DASAR® PROJECTOR
SP, 230V



12-24V
Total wattage: 6.5W
Material: 316 stainless steel/glass

- Open cable end



220-240V ~50/60Hz | 400mA
Total wattage: 4.6W
Material: 316 stainless steel/glass

- IP44 safety plug

233570	520lm 3000K	


	Ground spike, 316 stainless steel Prod. no. 233580	
	Mounting plate, 316 stainless steel Prod. no. 233582	
	Plastic ground spike Prod. no. 900011	

Options	Prod. no.
520lm 3000K CRI80	
stainless steel	233570

233571	300lm 3000K	

	Ground spike, 316 stainless steel Prod. no. 233580	
	Mounting plate, 316 stainless steel Prod. no. 233582	
	Plastic ground spike Prod. no. 900011	

Options	Prod. no.
300lm 3000K CRI80	
stainless steel	233571





1000735 599







228555 599

HELIA SPOT S SP, single, PHASE




HELIA SPOT L SP, single, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 6.5W
Material: aluminium

- IP44 safety plug



220-240V ~50/60Hz | 700mA
Total wattage: 15W
Material: aluminium

- IP44 safety plug



		A → G
1000735	440lm 3000K	A t G E



Ground spike
Prod. no. 1000736



		A → G
228555	1340lm 3000K	A t G E



Ground spike
Prod. no. 1000736

Options	Prod. no.
440lm 3000K CRI80	
■ anthracite	1000735

Options	Prod. no.
1340lm 3000K CRI80	
■ anthracite	228555




1004652 601



1002201 601



227504 601



THEO BRACKET
SP


SOCKET INSIDE                                               

**SITRA 360 SPIKE**
SP, single, TCR-TSE

SOCKET
INSIDE



<9
W



IP 44

IK04

90°

150

220-240V ~50/60Hz
Material: aluminium/glass

- IP44 safety plug



GX53 <9W
Diameter: 7.5 cm L: 3.5 cm



LED GX53 | 6.1W | 120°
2700K | 490lm | EEK=G
6kWh/1000h




Prod. no. 1005272

Options	Prod. no.
---------	-----------

1xGX53	
--------	--

■ anthracite	
--------------	--

	231525
--	--------



231525

602




231535

603



SITRA 360 SPIKE

SP, double, TCR-TSE



SOCKET INSIDE <

BRING LIGHT INTO THE DARKNESS.

PRACTICAL WALL AND CEILING LIGHTS.

As lighting solutions that shine through even the worst of weather conditions, our wall and ceiling lights are robust, energy efficient and powerful. In addition to various features, you can also choose from wide range of designs. Looking for something a bit more modern? Traditional? Round? Or maybe square? You're sure to find it here!







234525 620



1002403 629

WALL AND CEILING LIGHTS

							
611	611	611	612	612	612	615	615
							
615	616	616	616	618	619	619	619
							
620	621	621	622	622	622	624	624
							
624	626	626	627	627	629	629	629
							
630	630	631	631	632	633	633	634
							
634	635	636	636	637	637	638	639
							
639	639	640	640	641	641	642	642
							
643	643	643	644	644	644	645	645



You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808

WALL LIGHTS








234515

619

234525

620



ENOLA ROUND S
WL, single

100-240V ~50/60Hz | 500mA
Total wattage: 6W
Material: aluminium/glass





1003422	450/500lm 3000/4000K	



■ Spacers	
Prod. no. 1002853	
■ Reflector, 60°	
Prod. no. 1005262	

Options	Prod. no.
450/500lm 3000/4000K CRI90	
■ anthracite	1003422

ENOLA ROUND M
WL, single

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass






1003423	860/980lm 3000/4000K	



■ Spacers	
Prod. no. 1002853	
■ Lens, 19°	
Prod. no. 1005205	
■ Asymmetrical lens	
Prod. no. 1005206	
■ Reflector, 60°	
Prod. no. 1005207	

Options	Prod. no.
860/980lm 3000/4000K CRI90	
■ anthracite	1003423

ENOLA ROUND L
WL, single

220-240V ~50/60Hz | 900mA
Total wattage: 36W
Material: aluminium/glass





1003440	3300/3700lm 3000/4000K	






■ Spacers	
Prod. no. 1002853	
■ Reflector, 60°	
Prod. no. 1005263	




Options	Prod. no.
3300/3700lm 3000/4000K CRI90	
■ anthracite	1003440

ENOLA ROUND S
UP/DOWN
WL

220-240V ~50/60Hz | 350mA
Total wattage: 7.8W
Material: aluminium/glass

ENOLA ROUND M
UP/DOWN
WL

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium/glass

ENOLA ROUND L
UP/DOWN
WL

220-240V ~50/60Hz | 700mA
Total wattage: 55W
Material: aluminium/glass



Up/Down	310/350lm 3000/4000K	A → G E
---------	-------------------------	------------



■ Spacers
Prod. no. 1002853
■ Reflector, 60°
Prod. no. 1005262



Up/Down	830/950lm 3000/4000K	A → G E
---------	-------------------------	------------



■ Spacers
Prod. no. 1002853
■ Lens, 19°
Prod. no. 1005205
■ Asymmetrical lens
Prod. no. 1005206
■ Reflector, 60°
Prod. no. 1005207



Up/Down	2700/3000lm 3000/4000K	A → G E
---------	---------------------------	------------



■ Spacers
Prod. no. 1002853
■ Reflector, 60°
Prod. no. 1005263

Options Prod. no.

Up: 310/350lm | 3000/4000K | CRI90
Down: 310/350lm | 3000/4000K | CRI90
■ anthracite **1003424**


Options Prod. no.



Up: 830/950lm | 3000/4000K | CRI90
Down: 830/950lm | 3000/4000K | CRI90
■ anthracite **1003425**

Options Prod. no.




Up: 2700/3000lm | 3000/4000K | CRI90
Down: 2700/3000lm | 3000/4000K | CRI90
■ anthracite **1003441**








ENOLA SQUARE S
WL, single

100-240V ~50/60Hz | 500mA
Total wattage: 6W
Material: aluminium/glass

ENOLA SQUARE M
WL, single

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

ENOLA SQUARE L
WL, single

220-240V ~50/60Hz | 900mA
Total wattage: 36W
Material: aluminium/glass



		A → G
1003416	450/500lm 3000/4000K	A ↑ G ↓ E



■ Spacers	
Prod. no. 1002853	
■ Reflector, 60°	
Prod. no. 1005262	



		A → G
1003417	860/980lm 3000/4000K	A ↑ G ↓ E



■ Spacers	
Prod. no. 1002853	
■ Lens, 19°	
Prod. no. 1005205	
■ Asymmetrical lens	
Prod. no. 1005206	
■ Reflector, 60°	
Prod. no. 1005207	



		A → G
1003437	3300/3700lm 3000/4000K	A ↑ G ↓ E





■ Spacers	
Prod. no. 1002853	
■ Reflector, 60°	
Prod. no. 1005263	





Options	Prod. no.
450/500lm 3000/4000K CRI90	
■ anthracite	1003416

Options	Prod. no.
860/980lm 3000/4000K CRI90	
■ anthracite	1003417




Options	Prod. no.
3300/3700lm 3000/4000K CRI90	
■ anthracite	1003437

ENOLA SQUARE S
UP/DOWN
WL

220-240V ~50/60Hz | 350mA
Total wattage: 7.8W
Material: aluminium/glass

ENOLA SQUARE M
UP/DOWN
WL

220-240V ~50/60Hz | 500mA
Total wattage: 20W
Material: aluminium/glass

ENOLA SQUARE L
UP/DOWN
WL

220-240V ~50/60Hz | 700mA
Total wattage: 55W
Material: aluminium/glass



Up/Down	310/350lm 3000/4000K	A → G E
---------	-------------------------	------------



■ Spacers
Prod. no. 1002853
■ Reflector, 60°
Prod. no. 1005262



Up/Down	830/950lm 3000/4000K	A → G E
---------	-------------------------	------------



■ Spacers
Prod. no. 1002853
■ Lens, 19°
Prod. no. 1005205
■ Asymmetrical lens
Prod. no. 1005206
■ Reflector, 60°
Prod. no. 1005207



Up/Down	2700/3000lm 3000/4000K	A → G E
---------	---------------------------	------------



■ Spacers
Prod. no. 1002853
■ Reflector, 60°
Prod. no. 1005263

Options **Prod. no.**
Up: 310/350lm | 3000/4000K | CRI90
Down: 310/350lm | CRI90
■ anthracite **1003418**

Options **Prod. no.**
Up: 830/950lm | 3000/4000K | CRI90
Down: 830/950lm | 3000/4000K | CRI90
■ anthracite **1003419**

Options **Prod. no.**
Up: 2700/3000lm | 3000/4000K | CRI90
Down: 2700/3000lm | CRI90
■ anthracite **1003438**



1003419 + 1005205 + 1005206 616 + 617

ENOLA S, M, L
Reflector, 56°

NEW



H: 1.85 cm Diameter: 4.5 cm | S
H: 4 cm Diameter: 7.5 cm | M
H: 6.96 cm Diameter: 11 cm | L
Material: polycarbonate (PC)



Options	Prod. no.
chrome S	1005262
chrome M	1005207
chrome L	1005263

ENOLA M
Lens, 19°

NEW



H: 3.8 cm
Diameter: 7.5 cm
Material: steel/polycarbonate (PC)



Options	Prod. no.
black/chrome	1005205

ENOLA M
Asymmetrical lens

NEW



H: 3 cm
Diameter: 7.5 cm
Material: steel/polycarbonate (PC)



Options	Prod. no.
black/chrome	1005206






234515 619

THEO UP/DOWN
WL, QPAR51



SOCKET INSIDE                 



BIG THEO BEAM UP/
FLOOD DOWN
WL

220-240V ~50/60Hz | 500mA
Total wattage: 29W
Material: aluminium/glass



		A → G
Down	2000lm 3000K	A → E
Beam	130lm 3000K	A → F

Options	Prod. no.
Down: 2000lm 3000K CRI80 Beam: 130lm 3000K CRI80	
■ anthracite	234515

BIG THEO UP/DOWN
WL, QPAR111

220-240V ~50/60Hz
Material: aluminium/glass






GU10 <75W



QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276

Options	Prod. no.
2xGU10	
■ anthracite	229575
2xGU10	
■ grey	229574

BIG THEO FLOOD
UP/DOWN
WL

220-240V ~50/60Hz | 1000mA
Total wattage: 42W
Material: aluminium/glass




		A → G
Up/Down	2000lm 3000K	A → E

Options	Prod. no.
Up: 2000lm 3000K CRI80 Down: 2000lm 3000K CRI80	
■ anthracite	234505

THEO
WL, QPAR51

SOCKET
INSIDE

<35
W



IP 44

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <35W



LED GU10 51mm | 4W | 36°
3000K | 280lm | EEK=F
4kWh/1000h

Prod. no. 1004973

Options	Prod. no.
1xGU10	
■ anthracite	229525
1xGU10	
■ grey	229524

229525 620





234525 621





229564 621

BIG THEO
WL, QPAR111

IP 44

220-240V ~50/60Hz
Material: aluminium/glass




GU10 <75W



QPAR111 | 12.5W | 60°
2700K | 1040lm | EEK=F
13kWh/1000h

Prod. no. 1005277

Options	Prod. no.
1xGU10	
■ anthracite	229565
1xGU10	
■ grey	229564

BIG THEO
WL



IP 44 IK02 24° L70B50

100-277V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/glass






		A → G
234525	2000lm 3000K	A E

Options	Prod. no.
2000lm 3000K CRI80	
■ anthracite	234525

BIG QUAD
WL

100-277V ~50/60Hz | 350mA
Total wattage: 4.5W
Material: aluminium/glass

SITRA CUBE
WL




100-277V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Light colour can be selected using the switch inside the housing



Up/Down	550/635lm 3000/4000K	A → G D
---------	-------------------------	------------

Options	Prod. no.
Up: 550/635lm 3000/4000K CRI80 Down: 550/635lm 3000/4000K CRI80	
■ anthracite	1002032
Up: 550/635lm 3000/4000K CRI80 Down: 550/635lm 3000/4000K CRI80	
□ white	1002033
Up: 550/635lm 3000/4000K CRI80 Down: 550/635lm 3000/4000K CRI80	
■ rust	1002034

SITRA CUBE
WL, TCR-TSE

220-240V ~50/60Hz
Material: aluminium/glass



GX53 <9W
Diameter: 7.5 cm L: 2.7 cm




LED GX53 | 6W | 120°
4000K | 550lm | EEK=F
6kWh/1000h

Prod. no. 1005269





Options	Prod. no.
290lm 3000K CRI80 □ white	232431



SITRA S
WL, single, square



NEW



220-240V ~50/60Hz | 500mA
Total wattage: 6.2W
Material: aluminium/glass

SITRA M
WL, up/down, square



NEW



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium/glass

SITRA L
WL, up/down, square

NEW



220-240 V ~50/60 Hz | 600 mA
Total wattage: 24W
Material: aluminium/glass



Options	Prod. no.
1005148, 1005149, 1005150	580/620lm 3000/4000K
	A → G

Options	Prod. no.
580/620 lm 3000/4000 K CRI80	
■ anthracite	1005148
580/620 lm 3000/4000 K CRI80	
□ white	1005149
580/620 lm 3000/4000 K CRI80	
■ rust	1005150



Options	Prod. no.
Up/Down	800/850lm 3000/4000K
	A → G

Options	Prod. no.
Up: 800/850lm 3000/4000K CRI80	
Down: 800/850lm 3000/4000K CRI80	
■ anthracite	1005151
Up: 800/850lm 3000/4000K CRI80	
Down: 800/850lm 3000/4000K CRI80	
□ white	1005153
Up: 800/850lm 3000/4000K CRI80	
Down: 800/850lm 3000/4000K CRI80	
■ rust	1005154




Options	Prod. no.
Up/Down	1350/1400lm 3000/4000K
	A → G

Options	Prod. no.
Up: 1350/1400lm 3000/4000K CRI80	
Down: 1350/1400lm 3000/4000K CRI80	
■ anthracite	1005155
Up: 1350/1400lm 3000/4000K CRI80	
Down: 1350/1400lm 3000/4000K CRI80	
□ white	1005156
Up: 1350/1400lm 3000/4000K CRI80	
Down: 1350/1400lm 3000/4000K CRI80	
■ rust	1005157




5



E27 <11W
Diameter: 6 cm L: 11.5 cm



5




E27 <11W
Diameter: 6 cm L: 11.5 cm



Options	Prod. no.
1xE27	
■ anthracite	1006179 


Options	Prod. no.
1xE27	
 anthracite	1006178 



1006183 627

GRAFIT SENSOR WL, square, E27

NEW



IP 44

220-240V ~50/60Hz
Material: aluminium/acrylic



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 13.2W | 220°
2700K | 1300lm | EEK=F
13kWh/1000h

Prod. no. 1005302

Options Prod. no.


1xE27

■ anthracite

1006183



GRAFIT WL, square, E27



IP 44

220-240V ~50/60Hz
Material: aluminium/plastic



E27 <11W
Diameter: 6 cm L: 11.5 cm



LED E27 | 9W | 220°
2700K | 770lm | EEK=F
9kWh/1000h

Prod. no. 1005301

Options Prod. no.



1xE27

■ anthracite

231205






QUADRULO
WL**NEW**

100-277V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium/acrylic



		A → G
1005201	270lm 3000K	A → G

Options	Prod. no.
270 lm 3000 K CRI80	
■ anthracite	1005201 ■


QUADRULO SENSOR
WL, E27

220-240V ~50/60Hz
Material: aluminium/glass



E27 <15W Diameter: 8 cm L: 18 cm	
LED E27 7.5W 320° 2500K 700lm EEK=F 8kWh/1000h	C.L.
Prod. no. 1005265	

Options	Prod. no.
1xE27	
■ anthracite	1002402


QUADRULO
WL, E27

220-240V ~50/60Hz
Material: aluminium/glass



E27 <15W Diameter: 8 cm L: 18 cm	
LED E27 7.5W 320° 2500K 700lm EEK=F 8kWh/1000h	C.L.
Prod. no. 1005265	

Options	Prod. no.
1xE27	
■ anthracite	1002403

MERIDIAN BOX SENSOR
WL, E27<25
W

IP 54


220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)

- The ambient brightness and operating time can be adjusted

E27 <25W
Diameter: 7 cm L: 17.5 cmLED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289

Options	Prod. no.
1xE27 ■ anthracite	230085
1xE27 ■ grey	230084

MERIDIAN BOX
WL, E27<25
W

IP 54

220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)E27 <25W
Diameter: 7 cm L: 17.5 cmLED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h


Prod. no. 1005265

Options	Prod. no.
1xE27 ■ anthracite	230655
1xE27 ■ rust	230657

230044 630



230655 630













1004748 631



1004748 631

ESKINA FRAME
WLESKINA FRAME
WL, double

220-240V ~50/60Hz | 350mA
Total wattage: 15W
Material: aluminium



220-240V ~50/60Hz | 700mA
Total wattage: 27W
Material: aluminium



		A → G
1004747	1100/1200lm 3000/4000K	A ↑ G ↓ D

Options

Prod. no.

1100/1200lm | 3000/4000K | CRI80
■ anthracite **1004747**



		A → G
Spot1/Spot2	1100/1200lm 3000/4000K	A ↑ G ↓ D




Options

Prod. no.

Spot 1: 1100/1200lm | 3000/4000K | CRI80
Spot 2: 1100/1200lm | 3000/4000K | CRI80
■ anthracite **1004748**

BOOKAT
WL

NEW



100-277V ~50/60Hz | 700mA

Total wattage: 15W

Material: aluminium






1005443	920/990lm 3000/4000K	

Options Prod. no.





920/990lm | 3000/4000K | CRI80

■ anthracite **1005443** ■

1005443 632

BIG QUAD
WL

100-277V ~50/60Hz | 350mA
Total wattage: 4.5W
Material: aluminium/glass

QUAD
WL

200-240V ~50/60Hz | 700mA
Total wattage: 4.6W
Material: aluminium/glass





		A → G
232435	260lm 3000K	A1 F

Options **Prod. no.**
260lm | 3000K | CRI96
■ anthracite **232435**







		A → G
232465, 232461	80lm 100lm 3000K	A1 G

Options **Prod. no.**
80lm | 3000K | CRI80
■ anthracite **232465**
100lm | 3000K | CRI80
□ white **232461**

QUAD UP/DOWN 12
WL

100-277V ~50/60Hz | 700mA
Total wattage: 6.4W
Material: aluminium/glass

QUAD UP/DOWN 15
WL

100-277V ~50/60Hz | 350mA
Total wattage: 8W
Material: aluminium/glass




Options	Prod. no.
Up/Down	125lm 3000K CRI80
	125lm 3000K CRI80
■ anthracite	232475
□ white	232471



Options	Prod. no.
Up/Down	260lm 3000K CRI80
	260lm 3000K CRI80
■ anthracite	232445
□ white	232441

232471

634



232445


634




1005126 635

BIG QUAD UP/DOWN
WL

640lm

LED
INSIDE

3000K

CRI
80

IP 54



30°



30°

35 000
Hours


L70B50

200-240V ~50/60Hz | 350mA

Total wattage: 8.2W

Material: aluminium/glass



		
Up/Down	320lm 3000K	

Options

Prod. no.

Up: 320lm | 3000K | CRI80

Down: 320lm | 3000K | CRI80

■ anthracite




1005126

Up: 320lm | 3000K | CRI80



Down: 320lm | 3000K | CRI80

□ white

1005125

RUSTY® UP/DOWN
WL, square

220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: FeCSi stainless steel/aluminium

RUSTY® UP/DOWN
WL, round

220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: FeCSi stainless steel/aluminium



		A → G
Up	259/260lm 3000/4000K	A G E
Down	285/288lm 3000/4000K	A G E

Options

Prod. no.

Up: 259/260lm | 3000/4000K | CRI80
Down: 285/288lm | 3000/4000K | CRI80
■ rust **1004650**




		A → G
Up	249/254lm 3000/4000K	A G E
Down	267/271lm 3000/4000K	A G E


Options

Prod. no.

Up: 249/254lm | 3000/4000K | CRI80
Down: 267/271lm | 3000/4000K | CRI80
■ rust **1004651**





1004650 636



1004651 636



1004679 637

OVALISK SENSOR
WL

IP 65 IK02 L70B50



220-240V ~50/60Hz | 500mA
Total wattage: 9.6W
Material: aluminium/glass



		A → G
1004679	580/630lm 3000/4000K	A1 G D

Options Prod. no.

580/630lm | 3000/4000K | CRI80
■ anthracite 1004679

OVALISK
WL

IP 65 IK02 L70B50




220-240V ~50/60Hz | 500mA
Total wattage: 9.2W
Material: aluminium/glass



		A → G
1004678	580/630lm 3000/4000K	A1 G D

Options Prod. no.

580/630lm | 3000/4000K | CRI80
■ anthracite 1004678

PEMA®
WL



220-240V ~50/60Hz
Total wattage: 3.8W
Material: aluminium/glass





- IP44 protection rating only when mounted with light emission downwards.



		A → G
231015, 231010, 231012	170lm 3000K	A F

Options	Prod. no.
170lm 3000K CRI80	
■ anthracite	231015
170lm 3000K CRI80	
□ white	231010
170lm 3000K CRI80	
■ grey	231012



PEMA®
WL



220-240V ~50/60Hz
Total wattage: 7.7W
Material: aluminium/glass

- Protection rating IP54 only when mounted with light emission downwards.



		A → G
1002069, 1002070	640lm 3000K	A → G E

Options	Prod. no.
640lm 3000K CRI80 ■ anthracite	1002069
640lm 3000K CRI80 □ white	1002070




PEMA®
WL

100-277V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium/glass



		A → G
1003453, 1003454	1340/1420lm 3000/4000K	A → G D

Options	Prod. no.
1340/1420lm 3000/4000K CRI80 ■ black	1003453
1340/1420lm 3000/4000K CRI80 ■ grey	1003454

PEMA®
WL, E27

220-240V ~50/60Hz
Material: aluminium/glass



E27 <15W
Diameter: 4.5 cm L: 21 cm






LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h







Prod. no. 1005289

Options	Prod. no.
1xE27	
■ black	230030
1xE27	
■ grey	230034

FLATT SENSOR
WL

100-277V ~50/60Hz | 500mA
Total wattage: 16W
Material: aluminium

FLATT
WL


100-277V ~50/60Hz | 300mA
Total wattage: 14W
Material: aluminium




Options	Prod. no.
600lm 3000/4000K CRI80	
■ anthracite	1002954
600lm 3000/4000K CRI80	
■ anthracite/brown	1002955








Options	Prod. no.
460lm 3000/4000K CRI80	
■ anthracite	1002952
500lm 3000/4000K CRI80	
■ anthracite/brown	1002953








Options	Prod. no.
2xGU10	
stainless steel	233302

ANGOLUX SENSOR
WL

100-240V ~50/60Hz | 240mA
Total wattage: 9.8W
Material: aluminium/plastic

- Angle of coverage 120°. Max. coverage distance 9m. Adjustable response sensitivity and operating time
- IP44 protection rating only when mounted with light emission downwards

ANGOLUX
WL

220-240V ~50/60Hz | 80mA
Total wattage: 6.8W
Material: aluminium/plastic




- IP44 protection rating only when mounted with light emission downwards





Options	Prod. no.
750lm 3000K CRI80	
■ anthracite	1001969
750lm 3000K CRI80	
□ white	1001970





Options	Prod. no.
550lm 3000K CRI80	
■ anthracite	231355
550lm 3000K CRI80	
□ white	231351







VILUA S
WL

100-277V ~50/60Hz | 700mA
Total wattage: 9W
Material: aluminium/glass

VILUA L
WL

100-277V ~50/60Hz | 350mA
Total wattage: 17W
Material: aluminium/glass

VILUA
UP/DOWN, WL

100-277V ~50/60Hz | 700mA
Total wattage: 16W
Material: aluminium/glass



		A → G
1002503	405lm 3000K	A ↑ G ↓ F

Options **Prod. no.**
405lm | 3000K | CRI80
■ anthracite **1002503**





		A → G
1002504	940lm 3000K	A ↑ G ↓ E

Options **Prod. no.**
940lm | 3000K | CRI80
■ anthracite **1002504**



		A → G
Up/Down	400lm 3000K	A ↑ G ↓ F

Options **Prod. no.**
Up: 400lm | 3000K | CRI80
Down: 400lm | 3000K | CRI80
■ anthracite **1002505**

MYRA UP/DOWN
WL, QPAR51

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <35W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h






Prod. no. 1004972



■ Surface mounting frames
Prod. no. 233215



Options	Prod. no.
2xGU10	
■ anthracite	233115
2xGU10	
■ grey	233114


SITRA UP/DOWN
WL

220-240V ~50/60Hz
Total wattage: 18W
Material: aluminium/glass



Up/Down	488lm 3000K	A → G A → E

Options	Prod. no.
Up: 488lm 3000K CRI80	
Down: 488lm 3000K CRI80	
■ anthracite	1002018

SITRA UP/DOWN
WL, TCR-TSE

220-240V ~50/60Hz
Material: aluminium/glass



GX53 <9W
Diameter: 7.5 cm L: 3.5 cm



LED GX53 | 6W | 120°
4000K | 550lm | EEK=F
6kWh/1000h



Prod. no. 1005269

Options	Prod. no.
2xGX53	
■ anthracite	230365




230365 644




1000334 645

ROX
WL, QPAR111ROX UP/DOWN
WL, QPAR111

SOCKET INSIDE <50 W



SOCKET INSIDE <50 W



IP 44

220-240V ~50/60Hz
Material: aluminium/glass



IP 44

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <50W



QPAR111 | 12.5W | 10°
2700K | 920lm | EEK=F
13kWh/1000h

Prod. no. 1005275



GU10 <50W



QPAR111 | 12.5W | 30°
2700K | 950lm | EEK=F
13kWh/1000h

Prod. no. 1005276



Options

Prod. no.

1xGU10

aluminium

1000333


Options



Prod. no.

2xGU10

aluminium

1000334





DELWA
WL

220-240V ~50/60Hz | 700mA
Total wattage: 10W
Material: aluminium/glass



Options	Prod. no.
1000342, 1000340	840lm 3000K
	A → G
	A t G E

Options	Prod. no.
840lm 3000K CRI80	
■ anthracite	1000342
840lm 3000K CRI80	
□ white	1000340




SLOTS
WL

220-240V ~50/60Hz
Total wattage: 4.5W
Material: aluminium/glass



Options	Prod. no.
231805, 231807	140lm 3000K
	A → G
	A t G E

Options	Prod. no.
140lm 3000K CRI80	
■ anthracite	231805
140lm 3000K CRI80	
■ rust	231807

WALLYX
WL, QPAR51

220-240V ~50/60Hz
Material: aluminium/glass



GU10 <50W L: 7.6 cm






LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972

Options	Prod. no.
1xGU10	
■ anthracite	227195
1xGU10	
■ grey	227194






DOWNUNDER OUT WL, round



100-240V ~50/60Hz | 500mA
Total wattage: 4.3W
Material: aluminium

DOWNUNDER OUT WL, square



100-240V ~50/60Hz | 500mA
Total wattage: 4.3W
Material: aluminium




1002868	150/160lm 3000/4000K	A → G A ↑ G E
---------	-------------------------	------------------

Options **Prod. no.**
150/160lm | 3000/4000K | CRI80
■ anthracite **1002868**



1002869	150/160lm 3000/4000K	A → G A ↑ G E
---------	-------------------------	------------------




Options **Prod. no.**
150/160lm | 3000/4000K | CRI80
■ anthracite **1002869**






1002869 648



1002868 648


ABRIDOR SENSOR
WL

100-277V ~50/60Hz | 500mA
Total wattage: 14W
Material: aluminium

ABRIDOR
WL

100-277V ~50/60Hz | 500mA
Total wattage: 14W
Material: aluminium

1002990 650



1002990, 1002989	750lm 3000/4000K	

Options **Prod. no.**
750lm | 3000/4000K | CRI80
■ anthracite **1002990**





1002990, 1002989	750lm 3000/4000K	

Options **Prod. no.**
750lm | 3000/4000K | CRI90
■ anthracite **1002989**



232915 651

ORDI SENSOR
WL

IP 44 IK02 120° L70B50

220-240V ~50/60Hz | 110mA
Total wattage: 9W
Material: aluminium





		A → G
232915, 232905	740lm 3000K	A 1 G D

Options

Prod. no.

740lm | 3000K | CRI80
■ anthracite

232915

ORDI
WL

IP 44 IK02 120° L70B50

220-240V ~50/60Hz | 110mA
Total wattage: 9W
Material: aluminium





		A → G
232915, 232905	740lm 3000K	A 1 G D

Options

Prod. no.

740lm | 3000K | CRI80
■ anthracite

232905

BOX-L
WL, E27

220-240V ~50/60Hz
Material: aluminium/acrylic




E27 <18W
Diameter: 6 cm L: 17.5 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289

BOX UP/DOWN
WL, QT-DE12

220-240V ~50/60Hz
Material: aluminium/glass







R7s 78mm <80W



LED R7s | 9W | 330°
3000K | 980lm | EEK=E
9kWh/1000h

Prod. no. 1005287

LOGS
WL

220-240V ~50/60Hz | 500mA
Total wattage: 9.5W
Material: aluminium



232105, 232101, 232104	520lm 800lm 570lm 3000K	A → G A → G
------------------------------	-----------------------------------	----------------

Options	Prod. no.
1xE27	
■ anthracite	232495
1xE27	
□ white	232491
1xE27	
■ rust	232497

Options	Prod. no.
1xR7s 78mm	
■ anthracite	232485

Options	Prod. no.
520lm 3000K CRI80	
■ anthracite	232105
800lm 3000K CRI80	
□ white	232101
570lm 3000K CRI80	
■ silver	232104









1002902 655



229664 655



1002605 655



OUT-BEAM UP/
FLOOD DOWN
WL

220-240V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/glass



		A → G
Down	690lm 3000K CRI80	A t G F
Beam	50lm 3000K	A t G F

Options	Prod. no.
Down: 690lm 3000K CRI80 Beam: 50lm 3000K CRI80	
■ anthracite	229665
Down: 690lm 3000K CRI80 Beam: 50lm 3000K CRI80	
■ grey	229664





MANA OUT
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/aluminium



		A → G
Up/Down	325lm 3000K CRI80	A t G E

Options	Prod. no.
Up: 325lm 3000K CRI80 Down: 325lm 3000K CRI80	
■ anthracite	1002900
Up: 325lm 3000K CRI80 Down: 325lm 3000K CRI80	
■ rust	1002902



SAIL
WL

200-240V ~50Hz
Total wattage: 18W
Material: aluminium



		A → G
1002605, 1002606	400lm 590lm 3000K	A t G F

Options	Prod. no.
400lm 3000K CRI80	
■ anthracite	1002605
590lm 3000K CRI80	
□ white	1002606


L-LINE OUT
WL

220-240V ~50/60Hz | 350mA
Total wattage: 7W
Material: aluminium/polycarbonate (PC)



1003539	500/570lm 3000/4000K	

Options	Prod. no.
500/570lm 3000/4000K CRI80	
■ anthracite	1003539






1000820 657

PHOTONIA WL, E27



SOCKET INSIDE **<60 W**



IP 55

IK03

220-240V ~50/60Hz
 Material: aluminium/glass



E27 <60W
 Diameter: 9 cm L: 15 cm



LED E27 | 7.5W | 320°
 2500K | 700lm | EEK=F
 8kWh/1000h


Prod. no. 1005265




■ Spacers
 Prod. no. 1002853

Options	Prod. no.
1xE27	
■ anthracite	232045

MOLAT WL, E27



SOCKET INSIDE **60 W**



IP 44

IK02

220-240V ~50/60Hz
 Material: aluminium/glass



E27 60W
 Diameter: 6.5 cm L: 14.5 cm





LED E27 | 7.5W | 320°
 2700K | 800lm | EEK=F
 8kWh/1000h

Prod. no. 1005268



■ Spacers
 Prod. no. 1002853

Options	Prod. no.
1xE27	
■ anthracite	1000820

GLOO PURE
WL, E27

220-240V ~50/60Hz
Material: aluminium/glass






E27 <23W
Diameter: 4.8 cm L: 18 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289

APONI
WL, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 6.3W
Material: aluminium



		A → G
1000681	520lm 3000K	A f G E




■ Spacers
Prod. no. 1002853



Options	Prod. no.
1xE27	
■ anthracite	1002002

Options	Prod. no.
520lm 3000K CRI80	
■ anthracite	1000681



1002002 658



1000681 658




231465 659



1000682 558

C-POL
WL, E27



IP 54

220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)



E27 <24W
Diameter: 5.2 cm L: 17.3 cm




LED E27 | 13.5W | 240°
3000K | 1520lm | EEK=E
14kWh/1000h

Prod. no. 1005307



Options	Prod. no.
1xE27	
■ anthracite	231465

F-POL
WL, E27



IP 54

220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)



E27 <20W
Diameter: 5 cm L: 14 cm




LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289



Options	Prod. no.
1xE27	
■ anthracite	231585

BIG NAILS
WL, E27

IP 44

220-240V ~50/60Hz
Material: 304 stainless steel/polycarbonate (PC)



E27 <15W
Diameter: 4.5 cm L: 17 cm





LED E27 | 8W | 240°
3000K | 880lm | EEK=E
8kWh/1000h



Prod. no. 1005289

Options	Prod. no.
1xE27	
■ stainless steel	229182

SQUARE
WL, E27

IP 44 IK02

220-240V ~50/60Hz
Material: 304 stainless steel



E27 <20W
Diameter: 7 cm L: 13 cm






LED E27 | 9W | 220°
2700K | 770lm | EEK=F
9kWh/1000h








Prod. no. 1005301

Options	Prod. no.
1xE27	
■ stainless steel	1000336



KERAS ELT
WL, E27SITRA
WL, TCR-TSERASCALI
WL

SOCKET INSIDE                                               

IPERI
WLQUADRASYL
WL, TCR-TSESQUARE TURN
WL, G9

220-240V ~50/60Hz
Total wattage: 4,5W
Material: aluminium/plastic

- IP44 protection rating only when mounted with light emission downwards.



220-240V ~50/60Hz
Material: aluminium/glass



220-240V ~50/60Hz
Material: aluminium/glass



		A → G
231315	400lm 4000K	A → G D



GX53 <11W
Diameter: 7.5 cm L: 2.7 cm



LED GX53 | 6W | 120°
4000K | 550lm | EEK=F
6kWh/1000h

Prod. no. 1005269



G9 <42W
Diameter: 3.5 cm L: 8 cm



LED G9 | 3.7W | 300°
3000K | 430lm | EEK=E
4kWh/1000h

Prod. no. 1005286







Options	Prod. no.
400lm 4000K CRI80 ■ anthracite	231315

Options	Prod. no.
1xGX53 ■ anthracite	232285

Options	Prod. no.
1xG9 ■ grey	1000335








TODAY PRO
Display

220-240V ~50/60Hz | 640mA
Total wattage: 29W
Material: aluminium

Options	Prod. no.
2800lm 4000K CRI70	
■ black	1000880
2800lm 4000K CRI70	
□ white	1000881




Options	Prod. no.
2800lm 4000K CRI70	
■ black	1000880
2800lm 4000K CRI70	
□ white	1000881

ESKINA D
Display, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 14.5W
Material: aluminium

Options	Prod. no.
1000lm 3000/4000K CRI80	
■ anthracite	1002905

Options	Prod. no.
1000lm 3000/4000K CRI80	
■ anthracite	1002905

MYRA DISPLAY
WL, curved, QPAR51



220-240V ~50/60Hz
Material: aluminium

Options	Prod. no.
GU10 <50W Diameter: 5 cm L: 5.7 cm	


Options	Prod. no.
LED GU10 51mm 4W 36° 2700K 270lm EEK=G 4kWh/1000h	
Prod. no. 1004972	

Options	Prod. no.
Surface mounting frames	
Prod. no. 233215	




Options	Prod. no.
1xGU10	
■ anthracite	233135
1xGU10	
■ grey	233134

LED SPOT
SP

100-240V ~50/60Hz | 240mA
Total wattage: 6W
Material: aluminium/glass

NAUTILUS
WL QPAR51

220-240V ~50/60Hz
Material: aluminium

MYRA
CW, single, QPAR51

220-240V ~50/60Hz
Material: aluminium/glass

- Adapter frame for surface mounting available



1004649, 1004957	400lm 3000K	A → G F
---------------------	----------------	------------



GU10 <11W
Diameter: 5 cm L: 8.3 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



GU10 <50W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004973



■ NAUTILUS | mounting plate
Prod. no. 1002884



■ NAUTILUS | mounting plate
Prod. no. 1002884





■ Surface mounting frames
Prod. no. 233215



Options	Prod. no.
400lm 3000K CRI80	
■ anthracite	1004649
400lm 3000K CRI80	
■ rust	1004957

Options	Prod. no.
1xGU10	
■ black	1002867

Options	Prod. no.
1xGU10	
■ anthracite	233105
1xGU10	
■ grey	233104







CEILING LIGHTS





1003421 672



ENOLA ROUND S
CL

220-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/glass





		A → G
1003426	540/610lm 3000/4000K	A ↑ G ↓ E



■ Spacer	
Prod. no. 1003479	
■ Reflector, 60°	
Prod. no. 1005262	

Options	Prod. no.
540/610lm 3000/4000K CRI90	
■ anthracite	1003426

ENOLA ROUND M
CL

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass





		A → G
1003427	840/960lm 3000/4000K	A ↑ G ↓ E



■ Spacer	
Prod. no. 1003479	
■ Lens, 19°	
Prod. no. 1005205	
■ Asymmetrical lens	
Prod. no. 1005206	
■ Reflector, 60°	
Prod. no. 1005207	

Options	Prod. no.
840/960lm 3000/4000K CRI90	
■ anthracite	1003427

ENOLA ROUND L
CL

220-240V ~50/60Hz | 900mA
Total wattage: 36W
Material: aluminium/glass





		A → G
1003442	3200/3500lm 3000/4000K	A ↑ G ↓ E





■ Spacer	
Prod. no. 1003479	
■ Reflector, 60°	
Prod. no. 1005263	



Options	Prod. no.
3200/3500lm 3000/4000K CRI90	
■ anthracite	1003442

ENOLA SQUARE S
CL

220-240V ~50/60Hz | 500mA
Total wattage: 9W
Material: aluminium/glass

ENOLA SQUARE M
CL

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

ENOLA SQUARE L
CL

220-240V ~50/60Hz | 900mA
Total wattage: 36W
Material: aluminium/glass



1003420	540/610lm 3000/4000K	



1003421	840/960lm 3000/4000K	



1003439	3200/3500lm 3000/4000K	



■ Spacer	
Prod. no. 1003479	
■ Reflector, 60°	
Prod. no. 1005262	



■ Spacer	
Prod. no. 1003479	
■ Lens, 19°	
Prod. no. 1005205	
■ Asymmetrical lens	
Prod. no. 1005206	
■ Reflector, 60°	
Prod. no. 1005207	



■ Spacer	
Prod. no. 1003479	
■ Reflector, 60°	
Prod. no. 1005263	

Options	Prod. no.
540/610lm 3000/4000K CRI90	
■ anthracite	1003420



Options	Prod. no.
840/960lm 3000/4000K CRI90	
■ anthracite	1003421

Options	Prod. no.
3200/3500lm 3000/4000K CRI90	
■ anthracite	1003439



1003421 + 1005207 672 + 617



BIG THEO
CLBIG THEO
CL, QPAR111

100-277V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/glass



220-240V ~50/60Hz
Material: aluminium/glass



		A → G
234535	2000lm 3000K	A ↑ G ↓ E



GU10 <75W



LED QPAR111 | 8W | 38°
2700K | 680lm | EEK=F
8kWh/1000h



Prod. no. 1005274

Options	Prod. no.
2000lm 3000K CRI80	
■ anthracite	234535

Options	Prod. no.
1xGU10	
■ anthracite	229555
1xGU10	
□ white	229551
1xGU10	
■ grey	229554








1005202 675

QUADRULO
CL

NEW



100-277V ~50/60Hz | 480mA
Total wattage: 7.5W
Material: aluminium/acrylic



		A → G
1005202	230lm 3000K	A ↑ G



Options

Prod. no.

230 lm | 3000 K | CRI80
■ anthracite

1005202



OVALISK
CL

220-240V ~50/60Hz | 350mA
Total wattage: 7.9W
Material: aluminium/glass



		A → G
1004677	540/570lm 3000/4000K	A → G D



Options **Prod. no.**
540/570lm | 3000/4000K | CRI80
■ anthracite **1004677**





PHOTONIA CL, E27

MOLAT CL, E27



IP 44 IK03

220-240V ~50/60Hz
Material: aluminium/glass



IP 44 IK02

220-240V ~50/60Hz
Material: aluminium/glass



E27 <60W
Diameter: 9 cm L: 15 cm



LED E27 | 7.5W | 320°
2500K | 700lm | EEK=F
8kWh/1000h

Prod. no. 1005265



Spacers
Prod. no. 1002853



E27 <60W
Diameter: 6.5 cm L: 14.5 cm



LED E27 | 7.5W | 320°
2700K | 800lm | EEK=F
8kWh/1000h

Prod. no. 1005268



Options

Prod. no.

1xE27

■ anthracite

232055

Options

Prod. no.

1xE27

■ anthracite

1000823





WALL AND CEILING LIGHTS





1005089 690





ESKINA SPOT SENSOR
CW, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 14.5W
Material: aluminium



1002904	1000lm 3000/4000K	



Options	Prod. no.
1000lm 3000/4000K CRI80 ■ anthracite	1002904



1002904 682



ESKINA SPOT CW, PHASE



220-240V ~50/60Hz | 350mA
Total wattage: 14,5W
Material: aluminium



		A → G
1002903	1000lm 3000/4000K	A → G





Options	Prod. no.
1000lm 3000/4000K CRI80	
■ anthracite	1002903



SITRA 360
CW, TCR-TSE



THEO BRACKET
CW



220-240V ~50/60Hz
Material: aluminium/glass

220-240V ~50/60Hz
Material: aluminium/glass



GX53 <9W
Diameter: 7.5 cm L: 3.5 cm



GU10 <7W
Diameter: 5.1 cm L: 5.7 cm



LED GX53 | 6.1W | 120°
4000K | 490lm | EEK=G
6kWh/1000h



Prod. no. 1005271



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h



Prod. no. 1004972

Options	Prod. no.
1xGX53	
■ anthracite	231515

Options	Prod. no.
1xGU10	
■ anthracite	1004653





233245 685






HELIA

CW, single, PHASE





HELIA

CW, double, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 6.5W
Material: aluminium/glass



220-240V ~50/60Hz | 500mA
Total wattage: 13W
Material: aluminium/glass



1004653 684



233245	440lm 3000K	A → G E
--------	----------------	------------



Spacers
Prod. no. 1002853

Options	Prod. no.
440lm 3000K CRI80 ■ anthracite	233245






233255	880lm 3000K	A → G E
--------	----------------	------------





Spacers
Prod. no. 1002853




Options	Prod. no.
880lm 3000K CRI80 ■ anthracite	233255

MYRA
WL, double, QPAR51

220-240V ~50/60Hz
Material: aluminium/glass

OUT-BEAM FRAME
SP

100-277V ~50/60Hz | 700mA
Total wattage: 3.5W
Material: aluminium/acrylic

BOX-L
WL

100-277V ~50/60Hz | 500mA
Total wattage: 19 W
Material: aluminium/acrylic



GU10 <50W
Diameter: 5 cm L: 5.7 cm



LED GU10 51mm | 6W | 38°
3000K | 470lm | EEK=F
6kWh/1000h



Prod. no. 1005079



Spacers
Prod. no. 1002853



Options	Prod. no.
2xGU10	
■ anthracite	233095
2xGU10	
■ grey	233094



Options	Prod. no.
60lm 3000K CRI80	
■ anthracite	1003518
60lm 3000K CRI80	
□ white	1003519

Options	Prod. no.
600lm 3000K CRI90	
■ anthracite	1002035



Options	Prod. no.
600lm 3000K CRI90	
■ anthracite	1002035

Options	Prod. no.
600lm 3000K CRI90	
■ anthracite	1002035



1002035 686







1003518 687





AINOS
CW

AINOS
CW SENSOR



220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/polycarbonate (PC)



220-240V ~50/60Hz | 500mA
Total wattage: 22W
Material: aluminium/polycarbonate (PC)




Options	Prod. no.
1430lm 3000K CRI80	
■ anthracite	229965
1430lm 3000K CRI80	
□ white	229961





Options	Prod. no.
1430lm 3000K CRI80	
■ anthracite	229975
1430lm 3000K CRI80	
□ white	229971






AINOS CW, square



AINOS CW SENSOR, square



IP 65 L70B50

220-240V ~50/60Hz | 500mA
Total wattage: 17W
Material: aluminium/polycarbonate (PC)



IP 65 L70B50

220-240V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/polycarbonate (PC)







1003450, 1003449	1300lm 3000/4000K	

Options	Prod. no.
1300lm 3000/4000K CRI80	
anthracite	1003450
1300lm 3000/4000K CRI80	
white	1003449




1003452, 1003451	1300lm 3000/4000K	

Options	Prod. no.
1300lm 3000/4000K CRI80	
anthracite	1003452
1300lm 3000/4000K CRI80	
white	1003451

LIPA
CW, PHASERUBA 27/42
CW

220-240V ~50/60Hz | 500mA
Total wattage: 21W
Material: aluminium/polycarbonate (PC)



220-240V ~50/60Hz | 300mA
Total wattage: 12W
Material: polycarbonate (PC)





Options	Prod. no.
1500lm 3000/4000K CRI80	
■ anthracite	1001856
1600lm 3000/4000K CRI80	
□ white	1001855



The energy efficiency class information for this product is not available at the time of printing. The latest product data can always be found at www.slv.com

Options	Prod. no.
960/1100lm 3000/4000K CRI90 Diameter: 27 cm	
□ white	1005089
2000/2300lm 3000/4000K CRI90 Diameter: 42 cm	
□ white	1005090





220-240V ~50/60Hz
Material: aluminium/polycarbonate (PC)



E27 <25W
Diameter: 5.2 cm L: 17.3 cm





LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h






Prod. no. 1005289




Options	Prod. no.
2xE27	
☒ anthracite	229085
2xE27	
☐ white	229081

TERANG 200
CW

220-240V ~50/60Hz
Total wattage: 11W
Material: aluminium/polycarbonate (PC)

IMPERVA 120
CW

220-240V ~50/60Hz | 700mA
Total wattage: 40W
Material: polycarbonate (PC)

IMPERVA 150
CW

220-240V ~50/60Hz | 1050mA
Total wattage: 55W
Material: polycarbonate (PC)



Options	Prod. no.
830lm 3000K CRI80	
■ anthracite	229935
830lm 3000K CRI80	
□ white	229931



Options	Prod. no.
4600lm 3000K CRI80	
■ grey	1001314
5095lm 4000K CRI80	
■ grey	1001315



Options	Prod. no.
7600lm 4000K CRI80	
■ grey	1001317



229935 692



1001317 692

TOUGH ENOUGH FOR ANYTHING.

RECESSED LIGHTS OFFER LIGHT
AND SECURITY.

Here you will find the right product to suit every application thanks to high-quality design, carefully selected materials and various IP protection ratings and technologies.





1006106 717



1002898 719




RECESSED LIGHTS



You can find more lights and variants at www.slv.com
 Manufacturer's details for our recommended lamps are given in the chapter 'Lamps', from page 808


RECESSED WALL LIGHTS





233605 701

ADI
EL



IP 55

IK02

L70B50

100-277V ~50/60Hz | 500mA
Total wattage: 18W
Material: aluminium/polycarbonate (PC)

- Only mount the light with the light beam pointing downwards



		A → G
233635	940lm 3000K	A → G E

Recessed fixing kit

Prod. no. 233639



Options	Prod. no.
940lm 3000K CRI80	
anthracite	233635



DOWNUNDER OUT S
EL



220-240V ~50/60Hz | 300mA
Total wattage: 1.7W
Material: aluminium/plastic

- Only mount the light with the light beam pointing downwards

DOWNUNDER OUT M
EL

220-240V ~50/60Hz | 300mA
Total wattage: 4W
Material: aluminium/plastic

- Only mount the light with the light beam pointing downwards

DOWNUNDER OUT L
EL

220-240V ~50/60Hz | 300mA
Total wattage: 4W
Material: aluminium/plastic

- Only mount the light with the light beam pointing downwards



Options	Prod. no.
233605, 233601	25lm 65lm 3000K
	A → G
	A → G

Options	Prod. no.
125 lm 3000 K CRI80	
anthracite/black	233605
65lm 3000K CRI80	
white/black	233601



Options	Prod. no.
233625, 233621	85lm 155lm 3000K
	A → G
	A → G




Options	Prod. no.
85lm 3000K CRI80	
anthracite/black	233625
155lm 3000K CRI80	
white/black	233621



Options	Prod. no.
233615, 233611	85lm 155lm 3000K
	A → G
	A → G

Options	Prod. no.
85lm 3000K CRI80	
anthracite/black	233615
155lm 3000K CRI80	
white/black	233611


BRICK MESH EL, E14



100-240V ~50/60Hz | 24V
Total wattage: 3.3W
Material: 316 stainless steel/glass

- Recessed fixing kit included



BRICK EL, symmetrical



220-240V ~50/60Hz | 700mA
Total wattage: 11W
Material: aluminium/316 stainless steel

- Recessed fixing kit included

BRICK EL, asymmetrical



220-240V ~50/60Hz | 700mA
Total wattage: 11W
Material: aluminium/316 stainless steel

- Recessed fixing kit included



Options	Prod. no.
52lm 3000K CRI80	229110
■ stainless steel	



Options	Prod. no.
950lm 3000K CRI80	233650
■ stainless steel	





Options	Prod. no.
850lm 3000K CRI80	233660
■ stainless steel	

Options	Prod. no.
52lm 3000K CRI80	229110
■ stainless steel	



Options	Prod. no.
950lm 3000K CRI80	233650
■ stainless steel	

Options	Prod. no.
850lm 3000K CRI80	233660
■ stainless steel	

BRICK DOWNUNDER
EL, E14

220-240V ~50/60Hz
Material: aluminium/glass

- No recessed fixing kit required

BRICK DOWNUNDER
EL

220-240V ~50/60Hz
Total wattage: 4W
Material: aluminium/glass

- Recessed fixing kit included



E14 <40W
Diameter: 4.3 cm L: 12 cm



LED E14 | 4.2W | 320°
2700K | 370lm | EEK=F
5kWh/1000h



Prod. no. 1005284

Options	Prod. no.
1xE14	
grey	229062



		
229702	30lm 3000K	



Options	Prod. no.
30lm 3000K CRI80	
■ grey	229702



RECESSED CEILING LIGHTS







PATTA-I
EL, round, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 7.3W
Material: aluminium/glass

- Products are delivered with spring clips.
Leaf springs are included with the product
and can be replaced
- Material thickness: max. 20mm

PATTA-I
DL, square, PHASE

220-240V ~50/60Hz | 350mA
Total wattage: 7.3W
Material: aluminium/glass

- Products are delivered with spring clips.
Leaf springs are included with the product
and can be replaced
- Material thickness: max. 20mm




Options	Prod. no.
440lm 1800-3000K CRI95	
■ black	1002098
440lm 1800-3000K CRI95	
□ white	1002099
440lm 1800-3000K CRI95	
■ brushed aluminium	1002100



Options	Prod. no.
440lm 1800-3000K CRI90	
■ black	1002101
440lm 1800-3000K CRI95	
□ white	1002102
440lm 1800-3000K CRI95	
■ brushed aluminium	1002103

Options	Prod. no.
440lm 1800-3000K CRI95	
■ black	1002098
440lm 1800-3000K CRI95	
□ white	1002099
440lm 1800-3000K CRI95	
■ brushed aluminium	1002100



Options	Prod. no.
440lm 1800-3000K CRI90	
■ black	1002101
440lm 1800-3000K CRI95	
□ white	1002102
440lm 1800-3000K CRI95	
■ brushed aluminium	1002103





1002100 706



PATTA-I EL, round, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Material thickness: max. 20mm

PATTA-I EL, square, PHASE



220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Material thickness: max. 20mm






Options	Prod. no.
114420, 114421, 114426	910lm 3000K
	A → G
	A ↑ G E

Options	Prod. no.
910lm 3000K CRI90	
■ black	114420
910lm 3000K CRI80	
□ white	114421
910lm 3000K CRI80	
■ brushed aluminium	114426






Options	Prod. no.
114430, 114431, 114436	910lm 3000K
	A → G
	A ↑ G E

Options	Prod. no.
910lm 3000K CRI80	
■ black	114430
910lm 3000K CRI80	
□ white	114431
910lm 3000K CRI80	
■ brushed aluminium	114436

**PATTA-F**
EL, round, PHASE




220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Material thickness: max. 20mm

PATTA-F
EL, square, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Products are delivered with spring clips.
Leaf springs are included with the product
and can be replaced
- Material thickness: max. 20mm

OUT 65
EL, round, PHASE

220-240V ~50/60Hz | 500mA
Total wattage: 11W
Material: aluminium/glass

- Products are delivered with spring clips.
Leaf springs are included with the product
and can be replaced
- Material thickness: max. 20mm



Options	Prod. no.
745lm 3000K CRI95	
■ black	114440
860lm 3000K CRI80	
□ white	114441





Options	Prod. no.
745lm 3000K CRI80	
■ black	114450
860lm 3000K CRI80	
□ white	114451



Options	Prod. no.
510lm 3000K CRI80	
■ black/matte	114460
640lm 3000K CRI80	
□ white/matte	114461

KINI
EL, PHASE



220-240V ~50/60Hz | 260mA
Total wattage: 12W
Material: aluminium/polycarbonate (PC)

- Material thickness of mounting surface:
5-20mm




		A → G
1000833	850lm 3000K	A T G E


Options	Prod. no.
850lm 3000K CRI80 □ white	1000833



114441 708



114460 708





1000833 709



KAMUELA ECO
EL, round, PHASE





KAMUELA ECO
EL, round, PHASE



220-240V ~50Hz
Total wattage: 6W
Material: aluminium/plastic

- Material thickness of mounting surface:
max. 40mm



220-240V ~50Hz
Total wattage: 6W
Material: aluminium/plastic

- Material thickness of mounting surface:
max. 40mm



Options	Prod. no.
500lm 3000K CRI84	
■ black	1001015
500lm 3000K CRI84	
□ white	1001016




Options	Prod. no.
530lm 4000K CRI84	
■ black	1001017
530lm 4000K CRI84	
□ white	1001018


Options	Prod. no.
500lm 3000K CRI84	
■ black	1001015
500lm 3000K CRI84	
□ white	1001016

Options	Prod. no.
530lm 4000K CRI84	
■ black	1001017
530lm 4000K CRI84	
□ white	1001018






VARU
EL, QPAR51



Socket Inside

Icons representing different light bulb types: incandescent, CFL, LED, and others.

<5 W



IP 20,
IP 65

IK02

220-240V ~50/60Hz

Material: aluminium/glass

- Material thickness: max. 20mm



GU10 <5W

Diameter: 5 cm



LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h





Prod. no. 1004972

Options	Prod. no.
1xGU10	
■ black	1001930
1xGU10	
□ white	1001931



1001165 713



DOLIX OUT
EL, round, QPAR51

IP 65 IK02

220-240V ~50/60Hz
Material: aluminium/glass

- Material thickness: max. 20mm



GU10 <50W





LED GU10 51mm | 4W | 36°
2700K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004972



Options	Prod. no.
1xGU10  white	1001165
1xGU10  chrome	1001166
1xGU10  grey	1001167
1xGU10  silver	1001168

DOLIX OUT
EL, square, QPAR51



IP 65 IK02

220-240V ~50/60Hz
Material: aluminium/glass

- Material thickness: max. 20mm



GU10 <50W



LED GU10 51mm | 4W | 36°
3000K | 270lm | EEK=G
4kWh/1000h

Prod. no. 1004973



Options	Prod. no.
1xGU10  white	1001169
1xGU10  chrome	1001170
1xGU10  grey	1001171
1xGU10  silver	1001172





RECESSED FLOOR LIGHTS





DASAR® FLAT 80
EL



220-240V ~50/60Hz
Total wattage: 3.5W
Material: 304 stainless steel/glass

- Recessed fixing kit included
- Suitable for installation in wood
- Open cable end

228412, 1002188	140lm 130lm 3000K 4000K	

Connection box IP68, 3-pole
Prod. no. 228730

Options	Prod. no.
140lm 3000K CRI80 ■ stainless steel	228412
130lm 4000K CRI80 ■ stainless steel	1002188



228412 716





1006106 717



1006106 717

DASAR® FLAT 120 EL

NEW



220-240V ~50/60Hz | 350mA

Total wattage: 7W

Material: 304 stainless steel



- Open cable end



		A → G
1006106, 1006107	520lm 3000K 4000K	A F G D

Options	Prod. no.
520lm 3000K CRI80	
■ stainless steel	1006106
520lm 4000K CRI80	
■ stainless steel	1006107

DASAR® 255 EL





220-240V ~50/60Hz | 750mA
Total wattage: 31W
Material: 316 stainless steel/glass

- Recessed fixing kit included



Options	Prod. no.
1660lm 3000K CRI90 ■ stainless steel	229383
1720lm 4000K CRI90 ■ stainless steel	229381

DASAR® 920 EL



12-24 V
Total wattage: 6.5W
Material: 316 stainless steel/glass

- Recessed fixing kit included
- Open cable end



Options	Prod. no.
520lm 3000K CRI80 ■ stainless steel	233500



233500 718



Options	Prod. no.
1660lm 3000K CRI90 ■ stainless steel	229383
1720lm 4000K CRI90 ■ stainless steel	229381




Options	Prod. no.
520lm 3000K CRI80 ■ stainless steel	233500




1002893 719

DASAR® 270 EL, asymmetrical

DASAR® 270 EL, symmetrical



220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/316 stainless steel



220-240V ~50/60Hz | 700mA
Total wattage: 30W
Material: aluminium/316 stainless steel



Options	Prod. no.
2000lm 3000K CRI80 ■ stainless steel	1002893
2100lm 4000K CRI80 ■ stainless steel	1002895




Options	Prod. no.
2500lm 3000K CRI80 ■ stainless steel	1002897
2600lm 4000K CRI80 ■ stainless steel	1002898





■ DASAR® 270 |
Honeycomb cover
Prod. no. 1002899

Options	Prod. no.
2000lm 3000K CRI80 ■ stainless steel	1002893
2100lm 4000K CRI80 ■ stainless steel	1002895

Options	Prod. no.
2500lm 3000K CRI80 ■ stainless steel	1002897
2600lm 4000K CRI80 ■ stainless steel	1002898





DASAR® 215
EL, round/square, QPAR111



220-240V - 50/60Hz
Material: 316 stainless steel/glass

- Recessed fixing kit included



DASAR® 215
EL, round, E27



220-240V - 50/60Hz
Material: 316 stainless steel/glass

- Surface temperature:
Energysaver = 48°C/
PAR 30 = 119°C/
PAR 38 = 108°C
- Recessed fixing kit included

DASAR® 218
EL, QR111



220-240V - 50/60Hz / 12V
Material: 316 stainless steel/glass

- Recessed fixing kit included



GU10 <75W



LED QPAR111 | 12.5W | 30°
4000K | 290lm | EEK=F
13kWh/1000h

Prod. no. 1005282



Options	Prod. no.
1xGU10	
 stainless steel	229230
1xGU10	
 stainless steel	229234



E27 <11W
Diameter: 4.5 cm L: 13.4 cm



LED E27 | 8W | 240°
3000K | 870lm | EEK=E
8kWh/1000h

Prod. no. 1005289



Options	Prod. no.
1xE27	
 stainless steel	229200



G53 <50W



LED G53 | 15W | 24°
2700K | 760lm | EEK=G
17kWh/1000h


Prod. no. 560231



Options	Prod. no.
1xG53	
 stainless steel	228370




228370 722



229234 723

DASAR® 370

EL, round



12-24 V
Power consumption: 2W
Material: 316 stainless steel/glass

- Suitable for installation in wood
- Open cable end



		
233540	120lm 3000K	





233540 723

Options

Prod. no.




120lm | 3000K | CRI80
■ stainless steel

233540

TRAIL-LITE® 60
EL

12V ~50/60Hz
Power consumption: 0.3W
Material: 316 stainless steel/glass

- Only operate with a conventional transformer
- Recessed fixing kit included
- Suitable for installation in wood



POWER TRAIL-LITE®
EL, round/square

350mA
Total wattage: 1W
Material: 316 stainless steel/glass

- Only operate with 350mA driver. Only wire together multiple PowerLEDs in series!
- Installation sleeve included
- Suitable for installation in wood
- Open cable end

Options	Prod. no.
228332, 228342	45lm 3000K
LED driver 320mA 3W incl. strain relief	Prod. no. 464108

Options	Prod. no.
45lm 3000K CRI90	228332
45lm 3000K CRI90	228342

GIMBLE OUT
EL

220-240 V ~50/60 Hz | 600 mA
Total wattage: 13W
Material: 316 stainless steel/glass


- Open cable end

Options	Prod. no.
1000384	1000lm 3000K
Connection box IP68, 3-pole	Prod. no. 228730
Installation pipe DN160	Prod. no. 233792
Floor-recessed fixing kit	Prod. no. 1000655

Options	Prod. no.
1000lm 3000K CRI80	1000384

Options	Prod. no.
Transformer, 12V AC 105VA IP44	Prod. no. 227140

Options	Prod. no.
10lm 3000K CRI80	227462





1006171 + 1006173 727




SMALL PLOT Cover, 2-pack

NEW





Material 1006173: 316 stainless steel
Material 1006174: aluminium



Options	Prod. no.
stainless steel	1006173
anthracite	1006174



SMALL PLOT Modules

NEW



SMALL PLOT Modules

NEW




SMALL PLOT Cover, 4-pack

NEW



Material 1006175: 316 stainless steel
Material 1006176: aluminium



Options	Prod. no.
stainless steel	1006175
anthracite	1006176



24V DC
Power consumption: 3W
Material: aluminium/polymethylmethacrylate (PMMA)

- Open cable end



24V DC
Power consumption: 3W
Material: polymethylmethacrylate (PMMA)

- Open cable end







		A → G
1006172	240lm 3000K	A ↑ G F

Options	Prod. no.
240lm 3000K CRI80	
aluminium	1006172



		A → G
1006171	240lm 3000K	A ↑ G F

Options	Prod. no.
240lm 3000K CRI80	
stainless steel	1006171

**BIG PLOT**
Modules**BIG PLOT**
Modules

220-240V ~50/60Hz | 16mA
Total wattage: 5.5W
Material: aluminium/polymethylmethacrylate (PMMA)

- Open cable end
- This product is delivered without a cover.
You can find suitable covers on page 728



220-240V ~50/60Hz | 16mA
Total wattage: 5.5W
Material: polymethylmethacrylate (PMMA)

- Open cable end
- This product is delivered without a cover.
You can find suitable covers on page 728



The energy efficiency class information for this product was not available at the time of printing. The latest product data can always be found at www.slv.com



The energy efficiency class information for this product was not available at the time of printing. The latest product data can always be found at www.slv.com



■ Connection box IP68, 3-pole
Prod. no. 228730



■ Connection box IP68, 3-pole
Prod. no. 228730




Options	Prod. no.
460lm 3000K CRI80	
■ aluminium	1001256

Options	Prod. no.
460lm 3000K CRI80	
■ stainless steel	1001359

BIG PLOT
Cover, 2-pack

Material: 1001254/316 stainless steel
Material 1001252/1001262: aluminium

1001254 loadable up to 0.8t
1001252 loadable up to 0.5t
1001262 loadable up to 0.5t




Options	Prod. no.
■ stainless steel	1001254
■ grey	1001252
■ anthracite	1001262


BIG PLOT
Cover, 4-pack

Material: 1001255: 316 stainless steel
Material: 1001253/1001263: aluminium



1001255 loadable up to 0.8t
1001253 loadable up to 0.5t
1001263 loadable up to 0.5t



Options	Prod. no.
■ stainless steel	1001255
■ grey	1001253
■ anthracite	1001263





1001359 + 1001255 728

ROCCI
EL, round

100-277 V ~50/60 Hz | 700 mA
Total wattage: 8.6W
Material: 316 stainless steel/glass

- Recessed fixing kit included




ROCCI
EL, square

100-277 V ~50/60 Hz | 700 mA
Total wattage: 8.6W
Material: 316 stainless steel/glass

- Recessed fixing kit included

ROCCI 200
EL, round/square

NEW



100-277V ~50/60Hz | 350mA
Total wattage: 16W
Material: steel

- Recessed fixing kit included



Options	Prod. no.
580lm 3000K CRI80	
■ stainless steel	227600



Options	Prod. no.
580lm 3000K CRI80	
■ stainless steel	227604






Options	Prod. no.
1530lm 3000K CRI80	
○ stainless steel	1006104
1530lm 3000K CRI80	
□ stainless steel	1006105


Options	Prod. no.
580lm 3000K CRI80	
■ stainless steel	227600

Options	Prod. no.
580lm 3000K CRI80	
■ stainless steel	227604

Options	Prod. no.
1530lm 3000K CRI80	
○ stainless steel	1006104
1530lm 3000K CRI80	
□ stainless steel	1006105



Technical drawing of a rectangular box. The front view shows a box with a top flange. The top flange has an outer diameter of $\varnothing 12$ and a height of 0,4. The main body has a height of 15,2. The base has a diameter of $\varnothing 10,5$. The side view shows a box with a top flange of size 12×12 and a height of 0,4. The main body has a height of 15,2. The base has a diameter of $\varnothing 10,5$. The bottom view shows three square patterns: a circle, a square, and a square with an upward arrow. The side view is labeled with a height of 15,2 cm.



- Recessed fixing kit included






























Options	Prod. no.
1xGU10	
  stainless steel	227680
1xGU10	
  stainless steel	227684

LED PROFILE

OVERVIEW




LED profile			Installation type			Cross-section	Beam angle	Page
			Surface-mounted	Recessed	Pendant			
GRAZIA 10	Standard		✓	–	–			735
	Flat		✓	–	–			735
	Recessed		–	✓	–			735
GRAZIA 10 EDGE	Surface-mounted		✓	–	–			738
GRAZIA 20	Standard		✓	–	✓			741
	Flat		✓	–	✓			741
	Recessed		–	✓	–			742
GRAZIA 60	Surface-mounted		✓	–	–			747
	Recessed		–	✓	–			747




You can find suitable strips and components from page 750 and suitable accessories (mains adapters, drivers, etc.) from page 795

GRAZIA 10

SURFACE-MOUNTED AND RECESSED PROFILE



SURFACE-MOUNTED PROFILE, FLAT





Surface-mounted, flat, aluminium, white, black

Length	Colour	Material	Prod. no.	
200 cm	aluminium	aluminium	1000460	
	white		1000461	
	black		1000462	

Width/height: 1.75/1.1 cm, max. width LED strip: 1.0 cm, cover not included

SURFACE-MOUNTED PROFILE, STANDARD





Surface-mounted, standard, aluminium, white, black

Length	Colour	Material	Prod. no.	
200 cm	aluminium	aluminium	1000463	
	white		1000464	
	black		1000465	

Width/height: 1.75/1.62 cm, max. width LED strip: 1.0 cm, cover not included

RECESSED PROFILE



Recessed profile, anodised aluminium, white, black

Length	Colour	Material	Prod. no.	
200 cm	aluminium	aluminium	1000457	
	white		1000458	
	black		1000459	

Width/height: 3.0/1.62 cm, max. width LED strip: 1.0 cm, cover not included

GRAZIA 10

ACCESSORIES


COVERS




flat, frosted




flat, opaque



flat, transparent



high, opaque (only suitable for surface-mounted profile)



high, frosted (only suitable for surface-mounted profile)

Length	Colour	Material	Prod. no.	
200 cm	☐ flat, frosted	Plastic PC	1000466	
	☐ flat, opaque	Plastic PMMA	1000468	
	☐ flat, transparent	Plastic PC	1000467	
	☐ flat, frosted	Plastic PMMA	1000469	
	☐ high, opaque*	Plastic PC	1000470	
	☐ high, frosted*	Plastic PMMA	1000471	

Plastic PMMA/PC:

Profile covers made of PMMA are especially uniform.

Profile covers made of PC are break-proof and especially suitable for use in contexts requiring high resilience.

* The high covers are only suitable for GRAZIA 10 surface-mounted profiles, not for recessed profiles.

MOUNTING CLIPS



Mounting clip, not visible




Mounting clip, 45°


Description	Dimensions	Prod. no.	
Mounting clip, not visible	W/H/D: 1.53/0.3/1 cm	1000487	
Mounting clip, 45°	W/H/D: 1.62/1.62/1 cm	1000489	

Material: stainless steel, Packaging contents: 2 pieces


END CAPS FOR SURFACE-MOUNTED PROFILE




for standard profile, flat cover




for standard profile, high cover




available colour variants



for flat profile, flat cover



for flat profile, high cover




Profile with mounted end caps


Description	Colour	visible depth	Prod. no.	
End caps for flat profile, flat cover	■ aluminium	0.2 cm	1000475	
	□ white		1000476	
	■ black		1000477	
End cap for flat profile, high cover	■ aluminium	0.2 cm	1000481	
	□ white		1000482	
	■ black		1000483	
End caps for standard profile, flat cover	■ aluminium	0.2 cm	1000478	
	□ white		1000479	
	■ black		1000480	
End caps for standard profile, high cover	■ aluminium	0.2 cm	1000484	
	□ white		1000485	
	■ black		1000486	

Material: aluminium, Packaging contents: 2 pieces


END CAPS FOR RECESSED PROFILE



for recessed profile



available colour variants



Profile with mounted end caps

Description	Colour	visible depth	Prod. no.	
End cap for recessed profile	■ aluminium	0.7 cm	1000472	
	□ white		1000473	
	■ black		1000474	

Material: aluminium, Packaging contents: 2 pieces



Please note that when using end caps, the visible depth must be subtracted from the profile length to obtain the desired overall length.


visible depth of end caps + profile length = total length

GRAZIA 10 EDGE


SURFACE-MOUNTED PROFILES



SURFACE-MOUNTED PROFILES



Surface-mounted, aluminium, white




Length	Colour	Material	Prod. no.	
200 cm	☐ aluminium ☐ white	aluminium	1004889 1004890	

Aluminium, Width/height: 1.95/1.95 cm, max. width LED strip: 1.0 cm


GRAZIA 10 EDGE

ACCESSORIES

COVERS



frosted, plastic PC



transparent, plastic PC



opaque, plastic PC



Length	Colour	Material	Prod. no.	
200 cm	☐ frosted	Plastic PC	1000466	
	☐ transparent	Plastic PC	1000467	
	☐ opaque	Plastic PMMA	1000468	
	☐ frosted	Plastic PMMA	1000469	

Plastic PMMA/PC:

Profile covers made of PMMA are especially uniform.

Profile covers made of PC are break-proof and especially suitable for use in contexts requiring high resilience.

END CAPS



Description	Colour	visible depth	Prod. no.	
End caps	☐ aluminium	2 mm	1004893	
	☐ white	2 mm	1004894	


Material: aluminium, Packaging contents: 2 pieces



Please note that when using end caps, the visible depth must be subtracted from the profile length to obtain the desired overall length.

visible depth of end caps + profile length = total length

MOUNTING CLIPS




Description	Colour	Dimensions	Prod. no.	
Mounting clips	☒ stainless steel	L/B/H: 2.25/15/3.25 cm	1004895	

Material: steel, Packaging contents: 4 pieces

GRAZIA 20

SURFACE-MOUNTED PROFILES



can also be used as a pendant light (pendant suspension p. 745)



high-quality powder-coated aluminium surface




available colour variants: aluminium, white, black


GRAZIA 20

SURFACE-MOUNTED PROFILES


STANDARD



smooth



grooved



Description	Length	Colour	Material:	Prod. no.	
Standard smooth	150 cm	aluminium	aluminium	1004918	
		white		1004919	
		black		1004920	
	300 cm	aluminium		1000523	
		white		1000524	
		black		1000525	
Standard grooved	300 cm	aluminium		1000514	
		white		1000515	
		black		1000516	

Width/height: 3.5/3.2 cm, max. width LED strip: 2.0 cm, cover not included


FLAT



smooth



grooved




Description	Length	Colour	Material:	Prod. no.	
Flat smooth	150 cm	aluminium	aluminium	1004921	
		white		1004922	
		black		1004923	
	300 cm	aluminium		1000532	
		white		1000533	
		black		1000534	
Flat grooved	300 cm	aluminium		1000505	
		white		1000506	
		black		1000507	


Width/height: 3.5/2.2 cm, max. width LED strip: 2.0 cm, cover not included

GRAZIA 20


RECESSED PROFILE



RECESSED PROFILE



Recessed, aluminium, white, black




Length	Colour	Material	Prod. no.	
150 cm	☐ aluminium	aluminium	1004924	
	☐ white		1004925	
	☐ black		1004926	
300 cm	☐ aluminium		1000496	
	☐ white		1000497	
	☐ black		1000498	

Width/height: 5.2/3.2 cm, max. width LED strip: 2.0 cm, cover not included


GRAZIA 20

ACCESSORIES


COVERS




flat, transparent




flat, transparent



flat, opaque



high, transparent



high, opaque

Length	Colour	Material	Prod. no.	
150 cm	☐ flat, frosted	Plastic PC	1004927	
	☐ flat, frosted	Plastic PMMA	1004928	
	☐ flat, opaque	Plastic PMMA	1004929	
	☐ high, frosted*	Plastic PC	1004930	
	☐ high, frosted*	Plastic PMMA	1004931	
	☐ high, frosted*	Plastic PMMA	1004931	
300 cm	☐ flat, frosted	Plastic PC	1000540	
	☐ flat, frosted	Plastic PMMA	1000546	
	☐ flat, opaque	Plastic PMMA	1000549	
	☐ high, frosted*	Plastic PMMA	1000555	
	☐ high, frosted*	Plastic PC	1000552	
	☐ high, frosted*	Plastic PC	1000552	


Plastic PMMA/PC:

Profile covers made of PMMA are especially uniform.

Profile covers made of PC are break-proof and especially suitable for use in contexts requiring high resilience.

* The high covers are only suitable for GRAZIA 20 surface-mounted profiles, not for recessed profiles.

LONGITUDINAL CONNECTOR




Description	Colour	Dimensions	Prod. no.	
Longitudinal connector	aluminium	L/W/H: 3.8/1.4/0.4 cm	1000571	

Material: aluminium, Packaging contents: 2 pieces


GRAZIA 20

ACCESSORIES


END CAPS FOR SURFACE-MOUNTED PROFILE




for standard profile, flat cover




for standard profile, high cover




available colour variants



for flat profile, flat cover



for flat profile, high cover



Profile with mounted end caps

Description	Colour	visible depth	Prod. no.
End caps for standard profile, flat cover	aluminium	0.25 cm	1000565
	white		1000566
	black		1000567
End caps for standard profile, high cover	aluminium	0.25 cm	1000568
	white		1000569
	black		1000570
End caps for flat profile, flat cover	aluminium	0.25 cm	1000559
	white		1000560
	black		1000561
End cap for flat profile, high cover	aluminium	0.25 cm	1000562
	white		1000563
	black		1000564

Material: aluminium, Packaging contents: 2 pieces



Please note that when using end caps, the visible depth must be subtracted from the profile length to obtain the desired overall length.

visible depth of end caps + profile length = total length


END CAPS FOR RECESSED PROFILE



for recessed profile



available colour variants



Profile with mounted end caps

Description	Colour	visible depth	Prod. no.
End cap for recessed profile	aluminium	0.085 cm	1000556
	white	0.085 cm	1000557
	black	0.085 cm	1000558

Material: aluminium, Packaging contents: 2 pieces



Please note that when using end caps, the visible depth must be subtracted from the profile length to obtain the desired overall length.

visible depth of end caps + profile length = total length



PENDANT SUSPENSION



Pendant suspension (only for surface-mounted profile)


Description	Dimensions	Prod. no.	
Pendant suspension*	Pendant L: 200 cm	1000535	

Material: stainless steel, Packaging contents: 2 pieces


* The pendant suspension is only suitable for the surface-mounted profile.

MOUNTING CLIPS

NEW VARIANT



Mounting clip, not visible



Mounting clip, visible (only for grooved surface-mounted profile)



Mounting clip for drywall ceiling

Description	Dimensions	Prod. no.	
Mounting clip, not visible	L/W/H: 2.82/1.2/1.4 cm	1000536	
Mounting clip, visible*	L/W/H: 3.65/6.2/1.5 cm	1000537	
Mounting clip	L/W/H: 5.5/1.1/2.3 cm	1004932	


Material: stainless steel, Packaging contents: 2 pieces

The visible mounting clip is only suitable for the **GRAZIA 20 Standard, grooved profile and the **GRAZIA 20 Flat, grooved** profile.




GRAZIA 60


SURFACE-MOUNTED AND RECESSED PROFILE



SURFACE-MOUNTED PROFILE




Surface-mounted profile, black, white




Length	Colour	Material	Prod. no.	
150 cm	■ black	aluminium	1004896	
	□ white		1004897	
300 cm	■ black		1004898	
	□ white		1004899	

Width/height: 7/9.5 cm, max. width LED strip: 2.0 cm, cover not included

RECESSED PROFILE



Recessed profile, black, white



Length	Colour	Material	Prod. no.	
150 cm	■ black	aluminium	1004905	
	□ white		1004906	
300 cm	■ black		1004907	
	□ white		1004908	

Width/height: 8.5/3.3 cm, max. width LED strip: 2.0 cm, cover not included

GRAZIA 60

ACCESSORIES

COVERS



black, aluminium, 150 cm



white, aluminium, 150 cm



frosted, plastic PC, 150 cm



frosted, plastic PMMA, 150 cm



frosted, plastic PC, 300 cm



frosted, plastic PC, 300 cm

Length	Colour	Material	Prod. no.
150 cm	☒ black	aluminium	1004912
	☐ white	aluminium	1004913
	☐ frosted	Plastic PC	1004914
	☐ frosted	Plastic PMMA	1004916
300 cm	☐ frosted	Plastic PC	1004915
	☐ frosted	Plastic PMMA	1004917

Plastic PMMA/PC:


Profile covers made of PMMA are especially uniform.

Profile covers made of PC are break-proof and especially suitable for use in contexts requiring high resilience.

END CAPS



for surface-mounted profile



for recessed profile

Description	Colour	visible depth	Prod. no.
End cap for surface-mounted profile	☒ black	0.085 cm	1004900
	☐ white	0.085 cm	1004901
End cap for recessed profile	☒ black	0.085 cm	1004909
	☐ white	0.085 cm	1004910

Material: aluminium, Packaging contents: 2 pieces




Please note that when using end caps, the visible depth must be subtracted from the profile length to obtain the desired overall length.

visible depth of end caps + profile length = total length

GRAZIA 60

ACCESSORIES

CEILING MOUNTING PROFILE FOR SURFACE MOUNTED PROFILE



Description	Colour	Dimensions	Prod. no.	
Mounting accessories	■ black	L/W/H: 150/7/9.5 cm	1004902	

Material: aluminium, Packaging contents: 1 piece


LONGITUDINAL CONNECTOR



Description	Colour	Dimensions	Prod. no.	
Longitudinal connector	□ aluminium	L/W/H: 8/4.2/1 cm	1004903	

Material: aluminium, Packaging contents: 2 pieces

FEED-IN



Description	Colour	Dimensions	Prod. no.	
Feed-in	□ aluminium	L/W/H: 8/4.2/2.4 cm	1004904	

Material: aluminium, Packaging contents: 1 piece

MOUNTING CLIP FOR RECESSED PROFILE



Description	Colour	Dimensions	Prod. no.	
Mounting clip	■ chrome	L/W/H: 13/17/4 cm	1004911	

Material: steel, Packaging contents: 2 pieces

LINING UP TO IMPRESS

LED STRIPS FOR A SPECIAL ATMOSPHERE.

Would you like to add a touch of variation? LED strips are modern and unusual design features that give rooms a special atmosphere. The long lights in various colour variants also really look the part when used as guidance lighting.






1004709 754

WHICH LED STRIP DO I NEED?

LED strips and profiles for your project.
Everything at a glance.



									LED strips	Profile
20	✓	2700-4000K	–	–	3500-3750lm	5 m	1 cm		GRAZIA FLEXSTRIP LED, 24V P. 754	GRAZIA 10 P. 735 GRAZIA 10 EDGE From P. 738
20	✓	2700-4000K	–	–	6500-7000lm	5 m	1 cm		GRAZIA PRO FLEXSTRIP, 24V P. 755	GRAZIA 10 P. 735 GRAZIA 10 EDGE From P. 738
20	✓	2700-6500K	–	–	8500-9100K	5 m	1 cm		GRAZIA PRO FLEXSTRIP, 24V P. 756	GRAZIA 10 P. 735 GRAZIA 10 EDGE From P. 738
20	✓	3000-4000K	–	–	12500-13000lm	5 m	2 cm		GRAZIA PRO MAX FLEXSTRIP, 24V P. 757	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Recessed P. 742
20	✓	3000-4000K	–	–	20000-21400lm	5 m	2 cm		GRAZIA PRO MAX FLEXSTRIP, 24V P. 758	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Re- cessed P. 742
20	✓	2700-6500K	✓	–	3400-3700lm	5 m	1 cm		GRAZIA PRO FLEXSTRIP, Tunable white, 24V P. 759	GRAZIA 10 P. 735 GRAZIA 10 EDGE From P. 738
20	✓	3000 K	–	✓	2050-2500lm	5 m	2 cm		GRAZIA PRO FLEXSTRIP, RGBW, 24V P. 760	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Recessed P. 742
54	✓	2700-4000K	–	–	3350-3600lm	5 m	2 cm		GRAZIA IP FLEXSTRIP, 24V P. 761	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Recessed P. 742
54	✓	2700-6500K	–	–	3210-3500lm	5 m	2 cm		GRAZIA IP FLEXSTRIP, Tunable white, 24V P. 762	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Recessed P. 742
54	✓	3000 K	–	✓	1940-2350lm	5 m	2 cm		GRAZIA IP FLEXSTRIP, RGBW, 24V P. 763	GRAZIA 20 surface-mounted P. 741 GRAZIA 20 Recessed P. 742

GRAZIA FLEXSTRIP LED

24V



GRAZIA FLEXSTRIP LED, 24V



LEDs per metre: 70
Width: 1 cm
Height: 0.12 cm
LED gap: 1.4 cm
Can be separated every: 10 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
2700	3500	44W	90	3	500	1004708	
3000	3500					1004709	
4000	3750					1004710	

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
☐ LED power supply	60W	Polycarbonate (PC)	18	4,5	2,7	1005383	

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.



GRAZIA PRO FLEXSTRIP

24V



GRAZIA PRO FLEXSTRIP, 24V



LEDs per metre: 126
Width: 1 cm
Height: 0.12 cm
LED gap: 0.8 cm
Can be separated every 5.6 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
2700	6500	73W	90	3	500	1004712	
3000	6500					1004713	
4000	7000					1004714	

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
■ LED power supply	100W	Polycarbonate (PC)	18,2	8,8	3,5	470500	
■ LED power supply PHASE	100W	Polycarbonate (PC)	21	6,7	3,4	1003105	
□ LED power supply DALI	100W	Polycarbonate (PC)	34,7	4	2,2	1004776	

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.

GRAZIA PRO FLEXSTRIP

24V



GRAZIA PRO FLEXSTRIP, 24V



LEDs per metre: 168
Width: 1 cm
Height: 0.12 cm
LED gap: 0.6 cm
Can be separated every 4.2 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
2700	8500	91W	90	3	500	1004716	
3000	8500					1004717	
4000	9100					1004718	
6500	9100					1004719	

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
■ LED power supply	100W	Polycarbonate (PC)	18,2	8,8	3,5	470500	
■ LED power supply PHASE	100W	Polycarbonate (PC)	21	6,7	3,4	1003105	
□ LED power supply DALI	100W	Polycarbonate (PC)	34,7	4	2,2	1004776	

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.

GRAZIA PRO MAX FLEXSTRIP

24V



GRAZIA PRO MAX FLEXSTRIP, 24V



LEDs per metre: 196
 Width: 2 cm
 Height: 0.15 cm
 LED gap: 0.5 cm
 Can be separated every 3.6 cm
 IP code: IP 20
 Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
3000	12500	126W	90	3	500	1004720	
4000	13000					1004721	

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
 From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
☒ LED power supply	150W	Polycarbonate (PC)	20,7	11	4,5	470549	
☐ DALI Controller	120W	Polycarbonate (PC)	11,6	4,2	1,8	1003106	
☐ LED power supply DALI	200W	Polycarbonate (PC)	42,5	4,8	2,5	1004777	



To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
 Reverse of the LED strip with adhesive tape.

GRAZIA PRO MAX FLEXSTRIP

24V



GRAZIA PRO MAX FLEXSTRIP, 24V



LEDs per metre: 196
Width: 2 cm
Height: 0.15 cm
LED gap: 1 cm
Can be separated every 7.1 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.
3000	20000	193W	90	3	500	1004722
4000	21400					1004723

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.
■ LED power supply	150W	Polycarbonate (PC)	20,7	11	4,5	470549
□ DALI Controller	120W	Polycarbonate (PC)	11,6	4,2	1,8	1003106
□ LED power supply DALI	200W	Polycarbonate (PC)	42,5	4,8	2,5	1004777

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.




GRAZIA PRO FLEXSTRIP

TUNABLE WHITE, 24V



GRAZIA PRO FLEXSTRIP, TUNABLE WHITE, 24V



LEDs per metre: 224
Width: 1 cm
Height: 0.12 cm
LED gap: 0.9 cm
Can be separated every 6.3 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
2700-6500	3400-3700	80W	90	6	500	1004725	

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
☐ LED power supply DALI, 24V, 2-channel	60W	Polycarbonate (PC)	20,2	5,8	3	1006133	
☐ LED power supply DALI, 24V, 2-channel	100W	Polycarbonate (PC)	34,7	4	2,2	1006134	

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.

GRAZIA PRO FLEXSTRIP

RGBW, 24V



GRAZIA PRO FLEXSTRIP, RGBW, 24V



LEDs per metre: 70
Width: 1.2 cm
Height: 0.22 cm
LED gap: 1.4 cm
Can be separated every: 10 cm
IP code: IP 20
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.
RGB	2500	60				
W 3000	2050	27	>90	6SDCM	500	1004727

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.




Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.
LED power supply	150W	Polycarbonate (PC)	20.7	11	4.5	470549

i To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.

GRAZIA IP FLEXSTRIP

24V



GRAZIA IP FLEXSTRIP, 24V



LEDs per metre: 70
 Width: 1.2 cm
 Height: 0.4 cm
 LED gap: 1.4 cm
 Can be separated every: 10 cm
 IP code: IP 54
 Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
2700	3350	44W	90	4	502	1004734	
3000	3350					1004735	
4000	3600					1004736	

Incl. 2 end caps and fittings

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
 From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
■ LED power supply	150W	Polycarbonate (PC)	23.4	11.4	4.9	470548	
□ LED power supply	200W	Polycarbonate (PC)	34.7	4	2.2	1004776	



To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
 Reverse of the LED strip with adhesive tape.

GRAZIA IP FLEXSTRIP

TUNABLE WHITE, 24V



GRAZIA IP FLEXSTRIP, TUNABLE WHITE, 24V



LEDs per metre: 224
Width: 1.2 cm
Height: 0.4 cm
LED gap: 0.9 cm
Can be separated every 6.3 cm
IP code: IP 54
Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.
2700-6500	3210-3500	80W	90	4	502	1004726

Incl. 2 end caps and fittings

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.
☒ LED power supply	150W	Polycarbonate (PC)	23,4	11,4	4,9	470548
☐ LED power supply DALI, 24V, 2-channel	60W	Polycarbonate (PC)	20,2	5,8	3	1006133
☐ LED power supply DALI, 24V, 2-channel	100W	Polycarbonate (PC)	34,7	4	2,2	1006134



To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
Reverse of the LED strip with adhesive tape.

GRAZIA IP FLEXSTRIP

RGBW, 24V



GRAZIA IP FLEXSTRIP, RGBW, 24V



LEDs per metre: 70
 Width: 1.4 cm
 Height: 0.46 cm
 LED gap: 1.4 cm
 Can be separated every: 10 cm
 IP code: IP 54
 Feed cable on both sides

Colour temperature (K)	Luminous flux (lm)	Wattage	Colour rendering index (CRI)	Colour consistency (SDMC)	Length (cm)	Prod. no.	
RGB	2350	60					
W 3000K	1940	27	>90	6SDCM	500	1004737	

Incl. 2 end caps and fittings

In order to obtain a consistent light output from a length of 3 m, we recommend feeding the strips on both sides.
 From a length of 5 m, a new feed-in must be provided.



Options	Max. current load	Material	Length (cm)	Width (cm)	Height (cm)	Prod. no.	
■ LED power supply	150W	Polycarbonate (PC)	23.4	11.4	4.9	470548	



To ensure heat dissipation, the LED strips must be glued into an aluminium profile.
 Reverse of the LED strip with adhesive tape.





DISCOVER DALI, AND NETWORK YOUR LIGHTING

Familiarise yourself with the protocol that makes it possible to easily install, manage and communicate with individual lights and lighting installations.

Already familiar with the terms smart home or smart building? Do you want to install flexible lighting scenarios and sequences? Unveiling DALI and suitable SLV products: the Digital Addressable Lighting Interface (DALI) simplifies digital communication between electronic ballasts, transformers and corresponding actuators: flexible light management for modern buildings combined with typical SLV light diversity.

- Flexible and intelligent light management.
- Centrally controlled with other building systems.
- Easy to install, universal use.


The basis for intelligent lighting.

DALI - an excellent basis for flexible and intelligent light management in modern buildings. With DALI 2.0, it is now also possible to integrate sensors into the network. These can independently access the bus, communicate with a master controller, lighting controllers or other sensor controls and control the lights.






SAFELY COMBINABLE: SLV, DALI AND SCHNEIDER ELECTRIC PRODUCTS.

Working in close collaboration with Schneider Electric, we offer a tailored and easily installable solution. You benefit from SLV DALI lights, which largely already support DALI 2.0. Extensive testing guarantees compatibility between the KNX DALI Gateway of Schneider Electric and SLV DALI products.

This means you can easily and seamlessly integrate all SLV DALI lights into a streamlined building management system via the Schneider Electric Gateway. The newly introduced NUMINOS® lighting system along with our MEDO family offer an excellent choice of combinations and applications. Discover more about SLV lighting that can be networked with DALI on the following pages.





Lights	Page	DALI Version	Compatible with Schneider Electric KNX/Dali Gateway
NUMINOS®, 3-circuit	62-71		
NUMINOS® CW	72-79		
NUMINOS® CL	80-87		
NUMINOS® PD	88-95		
ONE 60/80/TRIPLE PD	119,120		
ONE 60/80/DOUBLE PD UP/DOWN	122,123		
ONE 40 WL	294		
ONE 40 TRACK 3-circuit	443		
WORKLIGHT PD DALI	146		
MEDO 30/40/60 AMBIENT CW	260-261		
MEDO 60 CL, square	261		
MEDO RING 60 PD	129		
MEDO 90 AMBIENT CL	261		
FERA 25 CL	284		
I-PENDANT PRO PD	140		
LIPSY® 40/50 CW Drum	330		
PANEL 60 CL round	263		
PANEL CL 1200x300mm	263		
PANEL 60 PD round	141		
PARA FLAC PD/CL	179		
Q-LINE® PD single	145		
SIGHT TRACK 3-circuit	440		
SIGHT MOVE 3-circuit	441		

DALI. TECHNICALLY LIT.

All lighting components must feature a DALI interface. This allows up to 64 addresses, 16 groups and 16 scenes to be centrally managed. The status of a light or lighting control device is displayed and set using bi-directional data exchange via a DALI control device.

- The voltage ranges from 9.5 to 22.5V
- The system voltage is a maximum of 250 mA
- The data transmission rate is 1,200 baud
- DALI is optionally expandable

Heating appliances, air-conditioning units, blind systems and much more - if the 64 available addresses are not enough and additional building system components need to be centrally managed along with the lighting, that's no problem: DALI-based applications can be networked via a Gateway throughout different rooms and higher-level controls. A KNX system such as the new Schneider Electric KNX/DALI Gateway is typically used.



All DALI-compatible products are marked in the BIG WHITE® '22 with a symbol.





NUMINOS®
ZOOM M,
3-circuit
Product no.
1006117
Page 71

Our NUMINOS® Down and Spotlight System can be found on pages 14 to 95, with compatible DALI LED drivers on pages 58 to 60.

Or simply configure your system online at:
www.numinos.slv.com

A LIGHTING SYSTEM. FOR EVERY SCENARIO.

And optimally connected with DALI 2.0. This means that the lights in the SLV NUMINOS® Down and Spotlight System can be perfectly integrated anywhere that is in need of adjustable lighting. Whether as accent lighting or to illuminate sales areas, in gastronomy, or in offices.







NUMINOS®
GIMBLE M, DL
Product no.
1005953
Page 53







NUMINOS® XL
3-circuit
Product no.
1005796
Page 69

ONE 60 PD, DALI






220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel

ONE 80 PD, DALI



220-240V ~50/60Hz | 800mA
Total wattage: 32W
Material: aluminium/steel

ONE TRIPLE PD, DALI



220-240 V ~50/60 Hz | 1700 mA
Total wattage: 64W
Material: aluminium/steel



Options	Prod. no.
1480/1550lm 3000/4000K CRI90	
black	1002909
1480/1550lm 3000/4000K CRI90	
white	1002910



Options	Prod. no.
1930/2140lm 3000/4000K CRI90	
black	1002911
1930/2140lm 3000/4000K CRI90	
white	1002912



Options	Prod. no.
4040/4200lm 3000/4000K CRI90	
black	1002913
4040/4200lm 3000/4000K CRI90	
white	1002914





1002913 770






1002915 771

ONE 40 CW, DALI



220-240V ~50/60Hz | 350mA
Total wattage: 14W
Material: aluminium/steel

ONE 60 WL, DALI





220-240V ~50/60Hz | 600mA
Total wattage: 24W
Material: aluminium/steel





Options	Prod. no.
700/730lm 3000/4000K CRI90 Diameter: 40 cm	
black	1002915
700/730lm 3000/4000K CRI90 Diameter: 40 cm	
white	1002917



Options	Prod. no.
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
black	1002918
1350/1430lm 3000/4000K CRI90 Diameter: 60 cm	
white	1002919

ONE 40 TRACK
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15.2W
Material: aluminium

ONE 40 TRACK
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 15.2W
Material: aluminium



Options	Prod. no.
650lm 3000K CRI90 ■ black	1004769
650lm 3000K CRI90 □ white	1004770



Options	Prod. no.
670lm 4000K CRI90 ■ black	1004771
670lm 4000K CRI90 □ white	1004772



1004770

772



1004771




772






1004691 773



1004690 773

SIGHT MOVE
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)

SIGHT MOVE
3Ph., DALI

220-240V ~50/60Hz | 350mA
Total wattage: 26W
Material: aluminium/poly (methyl methacrylate)
(PMMA)



h _v	Light spectrum	A → G
1004690, 1004691	2700lm 3000K	A f G E

Options	Prod. no.
2700lm 3000K CRI90	
■ black	1004690
2700lm 3000K CRI90	
□ white	1004691






h _v	Light spectrum	A → G
1004692, 1004693	3100lm 4000K	A f G E

Options	Prod. no.
3100lm 4000K CRI90	
■ black	1004692
3100lm 4000K CRI90	
□ white	1004693



WORKLIGHT
PD, DALI

NEW



200-240V ~50/60Hz | 1500mA
Total wattage: 57W
Material: aluminium



		A → G
Up	2000lm 4000K	A ↑ G D
Down	3000lm 4000K	A ↑ G D

Options	Prod. no.
Up: 2000lm 4000K CRI80 Down: 3000lm 4000K CRI80	
■ black	1005395 ■
Up: 2000lm 4000K CRI80 Down: 3000lm 4000K CRI80	
□ white	1005396 ■





1005395 774



1001309 775

Q-LINE® PD, DALI, single



220-240V ~50/60Hz | 700mA
Total wattage: 47W
Material: aluminium/acrylic



1001309, 1001310	3700lm 3000K	A → G E
---------------------	-----------------	------------


Options	Prod. no.
3700lm 3000K CRI80	
black	1001309
3700lm 3000K CRI80	
white	1001310



MEDO LUMINAIRE FAMILY.

CEILING OR PENDANT LIGHTS.

	MEDO 30 AMBIENT CW, DALI	MEDO 40 AMBIENT CW, DALI	MEDO 60 AMBIENT CW, DALI	MEDO 90 AMBIENT CL, DALI	MEDO 60 CL, square, DALI
Example					
Lamp					
Size	Ø: 30 cm	Ø: 40 cm	Ø: 60 cm	Ø: 90 cm	W L: 60cm
Light strength	Down: 1230/1280lm Up: 20lm	Down: 2750/2900lm Up: 50lm	Down: 4350/4750lm Up: 120lm	Down: 9500/10100lm Up: 125lm	3300 lm
UGR	25	25	25	25	22
Dimmable					
Suspension kit	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m	1.5 m 5 m





DALI INTERFACE 1-10V + on/off



IP 20

220-240V ~50/60Hz
L: 5.85 cm W: 3.25 cm H: 1.5 cm
Material: plastic

- Suitable for controlling electronic ballasts with 1-10V control input
- Galvanic isolation of DALI input and 1-10V output

Wattage up to 1000W

Options	Prod. no.
■ grey	1002218

Manufacturer:
LUNATONE Industrielle Elektronik GmbH

DALI UNIVERSAL DIMMER 3-25W



IP 20

220-240V ~50/60Hz
L: 5.85 cm W: 3.25 cm H: 1.5 cm
Material: plastic

- Suitable for R, L, and C thanks to automatic load detection. DALI power consumption: 6mA

Wattage of 3W
Wattage up to 25W

Options	Prod. no.
■ grey	1002220

Manufacturer:
LUNATONE Industrielle Elektronik GmbH

DALI UNIVERSAL DIMMER 10-300W



IP 20

220-240V ~50/60Hz
L: 12.02 cm W: 3.02 cm H: 2.16 cm
Material: plastic

- Suitable for R, L, and C thanks to automatic load detection. DALI power consumption: 6mA

Wattage of 10W
Wattage up to 300W

Options	Prod. no.
■ grey	1002221

Manufacturer:
LUNATONE Industrielle Elektronik GmbH





SIMPLE. COMPATIBLE. SMART.

ZigBee® 3.0: the smart wireless system.

Dimmers, changing colours, lighting moods at the push of a button: it's not only lighting systems that are based on the standard ZigBee® 3.0. The wireless standard is versatile, with minimum energy consumption and is easy to install, making it suitable for anyone who wants to easily network lights without having to deal with complicated technology. A theoretical range of up to 100 metres is possible for all types of living areas, houses and commercial buildings.

The SLV VALETO® SMART LIGHT SYSTEM

The intelligent lighting solution for homes, hotels, restaurants and shops. Thanks to the ZigBee® 3.0 standard, you can enjoy compatibility with various common smart home systems:

Schneider Electric | Philips Hue | Amazon Alexa | and much more

It is easily managed via remote control, app or Amazon Alexa. The SLV VALETO® SMART LIGHT SYSTEM is of course easy to integrate into existing electrical installations.

Highly compatible.

Tested with Schneider Electric products.

With the VALETO® SMART LIGHT SYSTEM, SLV offers a variety of system-compatible lighting management based on the ZigBee® 3.0 standard.

Schneider Electric PlusLink products, which support switch actuators, dimmers, blinds, motion sensors and 1-10V DALI interfaces, are easily integrated into the system.

This enables seamless integration of the switch design with various switch programmes. You can also look forward to many other application solutions as part of our future collaboration with Schneider Electric.



**SLV
VALETO®**



Scalable:

Installations with up to 200 lights can be realised with the SLV VALETO® Gateway.



Integrable:

SLV VALETO® is, thanks to the ZigBee® 3.0 standard, compatible with other manufacturers' products and systems.



Controllable:

Easy to control via app, remote control or voice assistance systems.



Coverage:

By integrating an own mesh network, SLV VALETO® products can also be controlled from large distances.*



Secure:

The Gateway only stores your data locally, never in the cloud.

*Excluding battery-operated devices.

SIMPLE.

The ideal starting point for smart lighting management: simply couple our SLV VALETO® remote controls (e.g.: 1002994) with the SLV VALETO® lights (e.g.: 1001917) and see how easy smart can be.



ADVANCE.

Would you like something more?

The choice is yours when it comes to the SLV VALETO® SMART LIGHT SYSTEM: manage your home lighting using our SLV VALETO® remote control (1002994), or an app on your smartphone via our SLV VALETO® Gateway (1002411).

There are no limits when it comes to managing your smart lighting thanks to the latest ZigBee standard (ZigBee® 3.0).





PROFESSIONAL.

Major plans?

Easily integrate more than 150 smart products into a smart lighting management with our SLV VALETO® SMART LIGHT SYSTEM. Simply manage your lighting at any time, using any device, and perfectly showcase your projects.

MORE COMFORT AND SECURITY

The perfect solution for wireless control and monitoring of individual lights, specific rooms or the entire home.





COMMUNICATION.

The SLV VALETO® Gateway is at the heart of the smart lighting system

SLV VALETO® Gateway



IP 20

220-240V ~50/60Hz
Operating voltage: 5V DC
Wattage: <1W
L: 10.6 cm W: 10.6 cm H: 2.6 cm
Material: aluminium/plastic

ZigBee® 3.0 certified product. A router connection via a LAN cable is required to manage the Gateway.

Scope of delivery

SLV VALETO® Gateway
Steckernetzteil 5V, 1A
Network cable, CAT6, 2m, black



INTEGRABLE



GERMAN
ENGINEERING



BANDWIDTH



SECURE

Options	Prod. no.
aluminium/black	1002411



All ZIGBEE-compatible products are marked in the BIG WHITE® '22 with a symbol.





CONTROL.

SLV VALETO®
Remote control, CCT/TGBW




Voltage: 3V battery operation
L: 6.5 cm W: 6.5 cm H: 1.95 cm
Material: plastic PC

The SLV VALETO® CCT/RGBW remote control can manage up to 20 ZigBee® devices in three groups. CCT and RGBW settings available.

Options	Prod. no.
☐ white	1002994

CONTROL UNIT.

SLV VALETO®
Recessed wall dimmer




220-240V ~50/60Hz
Wattage: max. 200W
L: 4.5 cm W: 4.5 cm H: 2.2 cm
Material: plastic PC

Controllable with SLV VALETO® CCT/RGBW remote control [1002994] or Gateway [1002411]
Can be used as an independent dimmer without ZigBee®. Dimmer process: phase control.
Dimmer for resistive (high-voltage halogen lamps) and capacitive loads (LED drivers). Suitable for all 60mm UP switch boxes with a depth of 42mm. 200W LED load.




Rated voltage	220-240V ~50/60Hz
Output voltage	220-240V ~50/60Hz
LED rated power	200W
Environmental temp. max.	50°C

Options	Prod. no.
☒ black	1002995





CONNECTED LED PANEL
595x595mm, UGR<19



100-240V ~50/60Hz | 1050mA
Total wattage: 43W
Material: aluminium/acrylic




- Remote control and dimming with Remote Control CCT/DIM [1002994] or Gateway [1002411]



1001250	3200-3600lm 2700-6500K	

Options	Prod. no.
3200-3600lm 2700-6500K CRI90 ☐ white	1001250

CONNECTED LED PANEL
620x620mm, UGR<19



100-240V ~50/60Hz | 1050mA
Total wattage: 43W
Material: aluminium/acrylic

- Remote control and dimming with Remote Control CCT/DIM [1002994] or Gateway [1002411]



1001251	3200-3600lm 2700-6500K	



Options	Prod. no.
3200-3600lm 2700-6500K CRI80 ☐ white	1001251





1002858 785

MALANG CW



100-240V ~50/60Hz | 24V
Total wattage: 39W
Material: aluminium / polyethylene (PE)

- Can be controlled and dimmed with SLV VALETO remote control 1002994 or Gateway 1002411
- Ring light and panel can be controlled separately (Zigbee 3.0)



The energy efficiency class information for this product is not available at the time of printing. The latest product data can always be found at www.slv.com



■ Suspension kit 1.5m
Prod. no. 135250

□ Suspension kit 1.5m
Prod. no. 135251

■ Suspension kit 1.5m
Prod. no. 135254

□ Suspension kit 5m
Prod. no. 1001950





■ Suspension kit 5m
Prod. no. 1001951

■ Suspension kit 5m
Prod. no. 1001952

□ SLV VALETO® |
remote control, CCT/RGBW
Prod. no. 1002994

Options	Prod. no.
Ring: 350lm RGB+W (3000K) CRI>80	
Panel: 2100-2400lm 2700-6500K CRI>80	
□ white	1002858

NEW FLAT WL, RGB-W



220-240V ~50/60Hz | 24V
Total wattage: 11.3W
Material: aluminium/acrylic

- Can be controlled with Gateway [prod. no. 1002411] or remote control [prod. no. 1002994]




		A → G
Up	300lm 3000K	A G
Down	280lm 3000K	A G

Options	Prod. no.
Up: RGB-W (300lm 3000K CRI>80)	
Down: RGB-W (280lm 3000K CRI>80)	
□ white	1003022
Up: RGB-W (300lm 3000K CRI>80)	
Down: RGB-W (280lm 3000K CRI>80)	
□ aluminium	1003023



LIGHTING.

LED A60 E27, tunable 2700-6500K, smart

NEW



220-240V ~50/60Hz
Wattage: 9W
Material: polyamide 66 (PA 66)
Ø: 6 cm H: 11 cm

Luminous flux	800lm
Lamp current	0.067A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white 2700-6500K	1005317 ■

LED QPAR51 GU10, tunable 2700-6500K, smart

NEW



220-240V ~50/60Hz
Wattage: 5W
Material: polyamide 66 (PA 66)/
polycarbonate (PC)
Ø: 5 cm H: 5.4 cm

Luminous flux	380lm
Lamp current	0.04A
Max. luminosity	530cd
Colour rendering index	90
Wattage	5W
Energy consumption/1000h	5kWh



Options	Prod. no.
☐ white 2700-6500K	1005311 ■

LED A60 E27, RGBW, smart

NEW


220-240V ~50/60Hz
Wattage: 9W
Material: polyamide 66 (PA 66)/
polycarbonate (PC)
Ø: 6 cm H: 11 cm

Luminous flux	800lm
Lamp current	0.073A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white / opaque	1005318 ■

LED QPAR51 GU10, RGBW, smart

NEW


220-240V ~50/60Hz
Wattage: 5.2W
Material: polyamide 66 (PA 66)/
polycarbonate (PC)
Ø: 5 cm H: 6.1 cm

Luminous flux	370lm
Lamp current	0.042A
Max. luminosity	680cd
Colour rendering index	90
Wattage	5.2W
Energy consumption/1000h	6kWh



Options	Prod. no.
☐ white	1005312 ■

1002858 474





LIGHTING.

QPAR111

GU10, tunable 2700-6500K, smart

NEW



IP 20



25°



25 000

220-240V ~50/60Hz
Wattage: 10W
Material: aluminium/polycarbonate (PC)
Ø: 11.1 cm H: 7 cm

Luminous flux	760lm
Lamp current	0.051A
Max. luminosity	4300cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh



Options	Prod. no.
☐ white 2700-6500K	1005313 ■
☐ white 2700-6500K	1005314 ■

LED QPAR111

GU10, RGBW, smart

NEW



IP 20



25°



25 000

220-240V ~50/60Hz
Wattage: 10W
Material: aluminium
Ø: 11.1 cm H: 7 cm

Luminous flux	750lm
Lamp current	0.056A
Max. luminosity	3500cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh



Options	Prod. no.
☐ white	1005315 ■

LED QPAR111

GU10, RGBW, smart

NEW



IP 20



40°



25 000

220-240V ~50/60Hz
Wattage: 10W
Material: aluminium
Ø: 11.1 cm H: 7 cm

Luminous flux	790lm
Lamp current	0.056A
Max. luminosity	3500cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh



Options	Prod. no.
☐ white	1005316 ■



1003029 + 1000764 99 + 107

IN BRILLIANT COMPANY

ACCESSORIES FOR INDIVIDUAL LIGHTING AESTHETICS

Light has many facets. And the possibilities are just as diverse when it comes to illuminating rooms and outdoor spaces. With our accessories, these possibilities can be further expanded, allowing you to literally shed new light on different spaces, with various light installations.





152960 457

FIND A DIMMER. COMBINED TO PERFECTION.

ATMOSPHERIC ROOM LIGHTING, THANKS TO THE PERFECT COMBINATION OF LIGHT AND DIMMER. **AT FIND-A-DIMMER.SLV.COM**

When dimming, you must ensure compatibility between the light or lamp and the dimmer. And in particular with LED lights, you must first check which dimmer is required. Given the wide range of different products, it is not always easy finding the right combination. Our "Find a Dimmer" overview should help you here. Alongside a wide range of combinations of lights/lamps and dimmers, at **find-a-dimmer.slv.com** you can also

find additional information regarding the minimum number of lights or lamps required for flawless operation. **The overview is regularly updated and expanded.**

In case of special queries, contact our tech. Support at **service@slv.de**



1 Suitable

- Ideal dimming behaviour
- The minimum number of lights/lamps required for flawless operation is stated as a number.



Only suitable under certain conditions

- No optimal dimming behaviour
- May flicker



Not compatible



find-a-dimmer.slv.com



ACCESSORIES

IP44 Transformers
12V AC



792

Transformers
12V AC



792

Transformers
TENSEO
12V AC



793

1-10V Dimmer



792

DALI interface
1-10V



794

DALI Universal Dimmer



794

DALI Controller



794

Compensation module



794

LED mains adapter
12V/24V DC



795

LED mains adapter
24V DC



795

LED mains adapter
24V DC
dimnable



796

LED driver
DALI dimmable



797, 800

LED driver
dimmable



797-799

LED driver
not dimmable



800-802

Ceiling hook




803

Cable clamp



803

GLENOS®
Ceiling roses



803

Textile cable
10 m



803

Cable
10 m clear



803

Wire rope suspension



803

Stopper
for wire rope



804

Cable extensions
1 m
2 m



804

Connector strip
3 outlets



804

Double-sided tape



804

Socket
GU10



804

Socket
GU10



804

Connection boxes



805

T-connector boxes



805

Reducer rings




806-807



You can find additional accessories at www.slv.com

TRANSFORMER

12V AC | 10VA IP44



IP 44

220-240V 50/60Hz

L: 7.5 cm W: 5 cm H: 4.5 cm

Material: plastic

Output voltage	12V AC
Wattage up to	10W
Control gear power factor	0,98
Thermal protection	133°C
Number of secondary outputs	1

Options	Prod. no.
■ black	227140 ▼

Manufacturer:
Elektromaschinenbau Wittlich GmbH

TRANSFORMER

12V AC | 60VA IP44



IP 44

220-240V 50/60Hz

L: 7.5 cm W: 5 cm H: 4.5 cm

Material: plastic

Output voltage	12V AC
Wattage up to	60W
Control gear power factor	0,98
Thermal protection	133°C
Number of secondary outputs	1

Options	Prod. no.
■ black	227160 ▼

Manufacturer:
Elektromaschinenbau Wittlich GmbH

TRANSFORMER

12V AC | 150VA



IP 20

220-240V 50/60Hz

L: 16.6cm W: 3.9 cm H: 3.3 cm

Material: plastic

Output voltage	12V AC
Wattage of	50W
Wattage up to	150W
Control gear power factor	0,98
Thermal protection	110°C
Number of secondary outputs	3

Options	Prod. no.
■ black	461157

Manufacturer:
WeiSen Electronic Co., Ltd

TRANSFORMER

12V AC | 60VA IP44



IP 20

220-240V 50/60Hz

L: 10.5 cm W: 3.3 cm H: 2.2 cm

Material: polycarbonate (PC)

Output voltage	12V AC
Wattage of	10W
Wattage up to	60W
Control gear power factor	0,98
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
□ white	461060

Manufacturer: HEP GmbH

1-10V DIMMER

10W



IP 20


L: 2.3 cm W: 3.9 cm H: 2 cm

Material: polycarbonate (PC)

Options	Prod. no.
□ white	470505

Manufacturer: HEP GmbH

TRANSFORMER TENSEO
12V AC | 50VA



220-240V 50/60Hz
Steel/brass
H: 11 cm
Ø: 11.1 cm

Output voltage	12V AC
Number of secondary outputs	1
Nominal wattage VA	50
Wattage up to	50W
Thermal protection	130°C
Primary protection	1.6A

Options	Prod. no.
☒ black	1002691
☐ white	1002692
☐ chrome	1002693

TRANSFORMER TENSEO
12V AC | 105VA



220-240V 50/60Hz
Steel/brass
H: 11 cm
Ø: 11.1 cm

Output voltage	12V AC
Number of secondary outputs	1
Nominal wattage VA	105
Wattage up to	105W
Thermal protection	130°C
Primary protection	1.6A

Options	Prod. no.
☐ white	138981
☒ chrome	138982

TRANSFORMER TENSEO
12V AC | 210VA



220-240V 50/60Hz
Steel/brass
H: 11 cm
Ø: 13.5 cm

Output voltage	12V AC
Number of secondary outputs	1
Nominal wattage VA	210
Wattage up to	210W
Thermal protection	130°C
Primary protection	3.15A

Options	Prod. no.
☐ white	138991
☒ chrome	138992



DALI INTERFACE 1-10V + on/off



IP 20

220-240V ~50/60Hz

L: 5.85 cm W: 3.25 cm H: 1.5 cm

Material: plastic

- Suitable for controlling electronic ballasts with 1-10V control input
- Galvanic isolation of DALI input and 1-10V output

Wattage up to 1000W

Options	Prod. no.
■ grey	1002218

Manufacturer: LUNATONE Industrielle Elektronik GmbH

DALI UNIVERSAL DIMMER 3-25W



IP 20

220-240V ~50/60Hz

L: 5.85 cm W: 3.25 cm H: 1.5 cm

Material: plastic

- Suitable for R, L, and C thanks to automatic load detection. DALI power consumption: 6mA

Wattage of 3W
Wattage up to 25W

Options	Prod. no.
■ grey	1002220

Manufacturer: LUNATONE Industrielle Elektronik GmbH

DALI UNIVERSAL DIMMER 10-300W



IP 20

220-240V ~50/60Hz

L: 12.02 cm W: 3.02 cm H: 2.16 cm

Material: plastic

- Suitable for R, L, and C thanks to automatic load detection. DALI power consumption: 6mA

Wattage of 10W
Wattage up to 300W

Options	Prod. no.
■ grey	1002221

Manufacturer: LUNATONE Industrielle Elektronik GmbH

DALI CONTROLLER 24V DC



IP 20

10-24V DC

L: 11.6 cm W: 4.2 cm H: 1.8 cm

Material: polycarbonate (PC)

Output voltage 10-24V DC
Number of secondary outputs 1

Options	Prod. no.
□ white	1003106

COMPENSATION MODULE



IP 20

220-240V ~50/60Hz

L: 9.5 cm

Ø: 1.5 cm

Material: polycarbonate (PC)


- Reduces or corrects problems when dimming, such as flickering, flashing, or when the LED light does not go 100% out when switched off. The compensator is always connected after the dimmer or switch and parallel to the downlight spot or LED driver.

Options	Prod. no.
■ glossy black	1002785▼



LED POWER SUPPLY
12V | 15W

NEW



200-240V ~50/60Hz
H: 22 cm Ø: 55 cm
Material: polycarbonate (PC)

Output voltage	12V DC
Wattage of	0W
Wattage up to	15W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1


Options Prod. no.

☐ white 1005444 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY
24V | 15W

NEW



200-240V ~50/60Hz
H: 22 cm Ø: 55 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	0W
Wattage up to	15W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1


Options Prod. no.

☐ white 1005445 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY
12V | 12W with strain relief

NEW



100-240V ~50/60Hz
L: 10.6 cm W: 3.3 cm H: 2.2 cm
Material: polycarbonate (PC)

Output voltage	12
Wattage of	0W
Wattage up to	12W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options Prod. no.

☐ white 1005241 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY
24V | 12W with strain relief

NEW



100-240V ~50/60Hz
L: 10.6 cm W: 3.3 cm H: 2.2 cm
Material: polycarbonate (PC)

Output voltage	24
Wattage of	0W
Wattage up to	12W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options Prod. no.

☐ white 1005380 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY
24V | 20W

NEW



220-240V ~50/60Hz
L: 11.5 cm W: 4.1 cm H: 2.5 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	0W
Wattage up to	20W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options Prod. no.

☐ white 1005381 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY
24V | 40W

NEW



220-240V ~50/60Hz
L: 18 cm W: 4.5 cm H: 2.7 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	0W
Wattage up to	40W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options Prod. no.

☐ white 1005382 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V DC | 150W incl. strain relief



220-240V ~50/60Hz
L: 20.7 cm W: 11 cm H: 4.5 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	0W
Wattage up to	150W
Control gear power factor	0,98
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
■ black	470549 ▼

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V | 60W



220-240V ~50/60Hz
L: 18 cm W: 4.5 cm H: 2.7 cm
Material: polycarbonate (PC)


Output voltage	24V DC
Wattage of	0W
Wattage up to	60W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
□ white	1005383 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V DC | 100W incl. strain relief



220-240V ~50/60Hz
L: 18.2 cm W: 8.8 cm H: 3.5 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	0W
Wattage up to	100W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	2

Options	Prod. no.
■ black	470500

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V DC | 150W



220-240V ~50/60Hz
L: 23.4 cm W: 11.4 cm H: 4.9 cm
Material: polycarbonate (PC)


Output voltage	24V DC
Wattage of	0W
Wattage up to	150W
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
■ black	470548

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V DC | 50W incl. strain relief



220-240V ~50/60Hz
L: 18.4 cm W: 6.1 cm H: 3.2 cm
Material: polycarbonate (PC)


Output voltage	24V DC
Wattage of	12W
Wattage up to	50W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
■ white/blue	1003104

Manufacturer: HEP GmbH

LED POWER SUPPLY

24V DC | 100W incl. strain relief




220-240V ~50/60Hz
L: 21 cm W: 6.7 cm H: 3.4 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	34W
Wattage up to	100W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
■ white/blue	1003105

Manufacturer: HEP GmbH

LED POWER SUPPLY 12V DC | 100W incl. strain relief




220-240V ~50/60Hz
L: 34.7 cm W: 4 cm H: 2.2 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	5W
Wattage up to	100W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1004776

Manufacturer: HEP GmbH

LED POWER SUPPLY 60W | DALI, 24V, 2 channel




220-240V ~50/60Hz
L: 20.2 cm W: 5.8 cm H: 3 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	5W
Wattage up to	60W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	2

Options	Prod. no.
☐ white	1006133 ■

Manufacturer: HEP GmbH

LED POWER SUPPLY 100W | DALI, 24V, 2 channel




220-240V ~50/60Hz
L: 34.7 cm W: 4 cm H: 2.2 cm
Material: polycarbonate (PC)

Wattage of	5W
Wattage up to	100W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	2

Options	Prod. no.
☐ white	1006134 ■

Manufacturer: HEP GmbH

LED DRIVER DALI




220-240V ~50/60Hz
L: 42.5 cm W: 4.8 cm H: 2.5 cm
Material: polycarbonate (PC)

Output voltage	24V DC
Wattage of	5W
Wattage up to	200W
Control gear power factor	0,95
Thermal protection	90°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1004777 ■

Manufacturer: HEP GmbH

LED DRIVER 200mA | 6-8.4W incl. strain relief




220-240V ~50/60Hz
L: 8.5 cm B: 4.1 cm H: 2.2 cm
Material: polycarbonate (PC)

Output voltage	30-42V DC
Wattage of	6W
Wattage up to	8.4W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1003254

Manufacturer: HEP GmbH

LED DRIVER 350mA | 3W



220-240V ~50/60Hz
L: 6.3 cm W: 4 cm H: 2.3 cm
Material: polycarbonate (PC)

Output voltage	10-17V DC
Wattage of	3.5W
Wattage up to	5.9W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002791

Manufacturer: HEP GmbH

LED DRIVER
350mA | 10W

IP 20

220-240V ~50/60Hz

L: 8.5 cm B: 4.1 cm H: 2.2 cm

Material: polycarbonate (PC)

Output voltage	13-26V DC
Wattage of	4.55W
Wattage up to	9.1W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464140

Manufacturer: HEP GmbH

LED DRIVER
350mA | 15W

IP 20

220-240V ~50/60Hz

L: 8.5 cm B: 4.1 cm H: 2.2 cm

Material: polycarbonate (PC)

Output voltage	26-43
Wattage of	9W
Wattage up to	15W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002803

Manufacturer: HEP GmbH

LED DRIVER
350mA | 20W

IP 20

220-240V ~50/60Hz

L: 11.5 cm W: 4.1 cm H: 2.5 cm

Material: polycarbonate (PC)

Output voltage	32-54V DC
Wattage of	11.2W
Wattage up to	18.9W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1005449

Manufacturer: HEP GmbH

LED DRIVER
500mA | 15W

IP 20

220-240V ~50/60Hz

L: 8.5 cm B: 4.1 cm H: 2.2 cm

Material: polycarbonate (PC)

Output voltage	18-30V DC
Wattage of	9W
Wattage up to	15W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464144

Manufacturer: HEP GmbH

LED DRIVER
700mA | 10W

IP 20

220-240V ~50/60Hz


L: 8.5 cm B: 4.1 cm H: 2.2 cm

Material: polycarbonate (PC)

Output voltage	13-26V DC
Wattage of	4.55W
Wattage up to	9.1W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464142

Manufacturer: HEP GmbH

LED DRIVER
700mA | 6W

IP 20

220-240V ~50/60Hz

L: 6.3 cm W: 4 cm H: 2.3 cm

Material: polycarbonate (PC)

Output voltage	4.8-8.6V DC
Wattage of	3.4W
Wattage up to	6W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002792

Manufacturer: HEP GmbH

LED DRIVER

700mA | 20W | dimmable | incl. strain relief



220-240V ~50/60Hz
L: 11.5 cm W: 4.1 cm H: 2.5 cm
Material: polycarbonate (PC)


Output voltage	18-26V DC
Wattage of	12.6W
Wattage up to	182W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1006202

Manufacturer: HEP GmbH

LED DRIVER

700mA | 39W incl. strain relief



220-240V ~50/60Hz
L: 16.6 cm W: 5.2 cm H: 2.4 cm
Material: polycarbonate (PC)

Output voltage	28-56V DC
Wattage of	20W
Wattage up to	39W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☒ grey/blue	1001267

LED DRIVER

700mA | 40W

FOLLOWER

220-240V ~50/60Hz
L: 14.5 cm B: 4 cm H: 3 cm
Material: polycarbonate (PC)


Output voltage	32-54V DC
Wattage of	22.4W
Wattage up to	37.8W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1005446 ☒

Manufacturer: HEP GmbH

LED DRIVER

1000mA | 39W incl. strain relief



220-240V ~50/60Hz
L: 16.6 cm W: 5.2 cm H: 2.4 cm
Material: polycarbonate (PC)

Output voltage	28-56V DC
Wattage of	20W
Wattage up to	39W
Control gear power factor	0,95
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464804

LED DRIVER

1000mA | 40W

FOLLOWER

200-240V ~50/60Hz
L: 14.5 cm B: 4 cm H: 3 cm
Material: polycarbonate (PC)

Output voltage	25-40V DC
Wattage of	26.3W
Wattage up to	42W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1005387 ☒

Manufacturer: HEP GmbH

LED DRIVER

250-700mA | 20W incl. strain relief



220-240V ~50/60Hz

L: 15 cm W: 5.2 cm H: 2.8 cm

Material: polycarbonate (PC)

Output voltage	6-60V DC
Wattage of	1.5W
Wattage up to	20W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002423

Manufacturer: HEP GmbH

LED DRIVER

250-700mA | 40W incl. strain relief



220-240V ~50/60Hz

L: 12.3 cm W: 7.9 cm H: 2.4 cm

Material: polycarbonate (PC)


Output voltage	9-58V DC
Wattage of	4.5W
Wattage up to	40W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002424

Manufacturer: HEP GmbH

LED DRIVER

700-1500mA | 50W incl. strain relief



220-240V ~50/60Hz

L: 12.3 cm W: 7.9 cm H: 2.4 cm

Material: polycarbonate (PC)

Output voltage	6-58V DC
Wattage of	4.2W
Wattage up to	50W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1002425

Manufacturer: HEP GmbH

LED DRIVER

250mA | 10 W



220-240V ~50/60Hz

L: 6.5 cm W: 3.9 cm H: 2 cm

Material: polycarbonate (PC)

Output voltage	26-40V DC
Wattage of	6.5W
Wattage up to	10W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1004780

Manufacturer: HEP GmbH

LED DRIVER

320mA | 3W incl. strain relief



220-240V ~50/60Hz

L: 5.5 cm W: 3.9 cm H: 2 cm

Material: polycarbonate (PC)

Output voltage	3-9V DC
Wattage of	1W
Wattage up to	3W
Control gear power factor	0,4
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464108

Manufacturer: HEP GmbH

LED DRIVER

350mA | 3W incl. strain relief



220-240V ~50/60Hz
L: 5.6 cm W: 3.9 cm H: 2 cm
Material: polycarbonate (PC)

- 350mA AMP plug included


Output voltage	3-9V DC
Wattage of	1W
Wattage up to	3.6W
Control gear power factor	0,4
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464107

Manufacturer: HEP GmbH

LED DRIVER

350mA | 15W incl. strain relief



220-240V ~50/60Hz
L: 15.8 cm W: 2.2 cm H: 1.9 cm
Material: polycarbonate (PC)


Output voltage	2-40V DC
Wattage of	0W
Wattage up to	15W
Control gear power factor	0,6
Thermal protection	100°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464031

Manufacturer: TCI Telecomunicazioni Italia Srl

LED DRIVER

350mA | 20W incl. strain relief



220-240V ~50/60Hz
L: 11.6 cm W: 4.4 cm H: 3 cm
Material: plastic

Wattage of	12.6W
Wattage up to	19.5W
Control gear power factor	0,9
Thermal protection	110°C

Options	Prod. no.
☐ white	1002420

Manufacturer: HEP GmbH

LED DRIVER

500mA | 10W incl. strain relief

FOLLOWER



220-240V ~50/60Hz
L: 6.5 cm W: 3.9 cm H: 2 cm
Material: polycarbonate (PC)


Output voltage	13-20V DC
Wattage of	6.5W
Wattage up to	10W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1005384

Manufacturer: HEP GmbH

LED DRIVER

700mA | 3W incl. strain relief



220-240V ~50/60Hz
L: 5.5 cm W: 3.9 cm H: 2 cm
Material: polycarbonate (PC)

Output voltage	4-5Vdc
Wattage of	3W
Wattage up to	3W
Control gear power factor	0,4
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	464200

Manufacturer: HEP GmbH

LED DRIVER

500/600/700mA | 30W incl. strain relief



220-240V ~50/60Hz
L: 14.7 cm B: 4.3 cm H: 3 cm
Material: polycarbonate (PC)

Output voltage	30-42V DC
Wattage of	21W
Wattage up to	29.5W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1004781

Manufacturer: HEP GmbH

LED DRIVER
800/900/1050mA | 40W incl. strain relief



220-240V ~50/60Hz
L: 14.7 cm B: 4.3 cm H: 3 cm
Material: polycarbonate (PC)

Output voltage	30-42V DC
Wattage of	31.5W
Wattage up to	44W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☐ white	1004782

Manufacturer: HEP GmbH

LED DRIVER
700/90/100mA | 40W incl. strain relief

FOLLOWER



120-277V ~50/60Hz
L: 12.3 cm W: 7.9 cm H: 3 cm
Material: polycarbonate (PC)

Output voltage	28-52V DC
Wattage of	19.6W
Wattage up to	40W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	3

Options	Prod. no.
☐ white	1006120

Manufacturer: HEP GmbH

LED DRIVER
1000mA | 60W incl. strain relief




220-240V ~50/60Hz

Output voltage	28-57V DC
Wattage of	28W
Wattage up to	57W
Control gear power factor	0,9
Thermal protection	110°C
Number of secondary outputs	1

Options	Prod. no.
☒ black	1002422

Manufacturer: HEP GmbH



CEILING HOOK



IP 20


L: 4.6 cm Ø: 1.8 cm
Material: aluminium

CABLE CLAMP



IP 20

L: 3.1 cm Ø: 1.4 cm
Material: aluminium

GLENOS®
Ceiling rose

IP 20

230V ~50Hz
L: 8.5 cm W: 8.5 cm H: 2.7 cm
Material: aluminium

Nominal voltage	230V ~50Hz
Max. current load	8.5A

Options	Prod. no.
■ black	132670
□ white	132671

Options	Prod. no.
■ black	132680
□ white	132681

Options	Prod. no.
■ black	210060
□ white	210061
■ grey	210064

TEXTILE CABLE
10m

IP 20

L: 1000 cm Ø: 0.6 cm
Material: Polyvinyl chloride (PVC)

CABLE
3-pole, 3 x 0.75 mm², 10 m

L: 1000 cm

WIRE ROPE SUSPENSION



IP 20



40 kg

L: 500 cm Ø: 0.15 cm
Material: steel/plastic

• 3 cable clips included

Max. voltage 300V

Max. voltage 300V


Options	Prod. no.
■ black	961270
□ white	961271
■ red	961276

Options	Prod. no.
■ silver	961250

Options	Prod. no.
■ silver	961037

Manufacturer: Reutlinger GmbH

STOPPER FOR WIRE ROPE



IP 20

Ø: 0.8 cm
Material: steel

CABLE EXTENSION



IP 20

L: 100 cm
Material: plastic

- With amp plug and socket

Max. current load 350mA

CONNECTOR STRIP

3 outlets



IP 20

L: 5.2 cm W: 1.4 cm H: 1.3 cm
Material: plastic

Max. current load 350mA

Options Prod. no.

■ grey

961034

Options Prod. no.

■ black/red

111861

Options Prod. no.

■ black

111850

DOUBLE-SIDED TAPE



L: 300 cm B: 0.9 cm

GU10 SOCKET



IP 20

230V ~50Hz
H: 1.6 cm
Ø: 2.8 cm
Material: ceramic

Nominal voltage 220-240V
~50/60Hz

Options Prod. no.

□ transparent

220000

Options Prod. no.

□ white

955135

GU10 SOCKET

with connection box and quick clamp



IP 20

L: 27 cm

Options Prod. no.

■ white/black

1000909

CONNECTION BOX
5-pole




220-240V ~50/60Hz
L: 13 cm Ø: 3.2 cm
Material: Polyamide (PA)

Max. voltage	450V
Max. current load	32A

Options	Prod. no.
■ black	228725

CONNECTION BOX
IP68, 3-pin



220-240V ~50/60Hz
L: 11.5 cm Ø: 2.7 cm
Material: Polyamide (PA)

Max. voltage	450V
Max. current load	17.5A

Options	Prod. no.
■ black	228730

T-CONNECTOR BOX
3-pole



220-240V ~50/60Hz
L: 11 cm W: 6.4 cm H: 3 cm
Material: Polyamide (PA)

Max. voltage	500V
Max. current load	17.5A

Options	Prod. no.
■ black	228726



1001823 527

NEW

TIME FOR A CHANGE. TIME FOR AN UPDATE.

An old recessed ceiling light, often still fitted with conventional bulbs, should give way to an energy-efficient and cost-effective alternative. When removing the old fitting, a larger ceiling cut-out will often be required than before.

Here SLV offers the appropriate solution – our new reducer rings.

The reducer rings completely cover the larger ceiling cut-out, while at the same time providing perfect support for your new, compact, recessed ceiling light.

Neat, time-saving, uncomplicated.

And also perfectly tailored to the NUMINOS® Downlight and Spotlight system.



1. Old recessed ceiling light with larger ceiling cut-out.



2. Removal of the old recessed ceiling light.



3. Installation of the reducer ring.



4. Reducer ring installed.
Larger ceiling cut-out fully covered.



5. Electrical connection and installation of the new recessed ceiling light.



6. New recessed ceiling light placed into the reducer ring.





Reducer ring, round



Material	steel	steel	steel	steel	steel
External Ø	16 cm	16 cm	24 cm	24 cm	24 cm
Height	5.3 cm	5.3 cm	5.3 cm	5.3 cm	5.3 cm
Internal Ø	7 cm	9 cm	12 cm	15 cm	18 cm
Ceiling cut-out	8.5 - 13 cm	12 - 15 cm	14 - 18 cm	17 - 20 cm	20 - 22 cm
Material thickness	3 cm	3 cm	3 cm	3 cm	3 cm
Prod. no. black	1006135	1006139	1006143	1006147	1006151
Prod. no. white	1006136	1006140	1006144	1006148	1006152

Reducer ring, square



Material	steel	steel	steel	steel	steel
Length	16 cm	16 cm	24 cm	24 cm	24 cm
Width	16 cm	16 cm	24 cm	24 cm	24 cm
Height	5.3 cm	5.3 cm	5.3 cm	5.3 cm	5.3 cm
Internal Ø	7 cm	9 cm	12 cm	15 cm	18 cm
Ceiling cut-out	8.5 - 13 cm	12 - 15 cm	14 - 18 cm	17 - 20 cm	20 - 22 cm
Material thickness	3 cm	3 cm	3 cm	3 cm	3 cm
Prod. no. black	1006137	1006141	1006145	1006149	1006153
Prod. no. white	1006138	1006142	1006146	1006150	1006154

THE SOURCE OF ALL LIGHTS

THE RIGHT LAMP FOR EVERY LIGHTING SOLUTION.

The right lighting effect is the result of the perfect coming together of light and lamp. Alongside design, energy-efficiency is an important criterion. In recent years, a wide range of alternatives to the classic incandescent lamp have been introduced to the market. As such, you are sure to find the right lamp for every application and for every type of light fitting.

LAMP

GENERAL INFORMATION

- Operation with open lights, without protective glass, is only permitted with low-pressure lamps. Lamps with this symbol (Standard IEC 357) are suitable for use in lights without protective glass.
- Halogen lamps and metal halide (high intensity) can result in the respective light housing heating up. They should therefore only be touched once the housing has cooled down. Adjustable lights and light heads that do not feature insulated positioning levers, or which exceed the maximum permissible housing temperature at the positioning point when operated at maximum wattage, should also be mounted out of reach. Appropriate solutions can be found in this chapter.
- In many cases, low voltage lights can also be used with suitable LED retrofit lamps. However, in some cases, due to the coming together of specific transformer and LED technologies, not all lights can be combined with all lamps - even those that may appear compatible. Should you have questions regarding compatibility, you can find information at slv.com, or you can contact our sales department.
- The dimensions of the lamps always refer to the complete external dimensions. This is inclusive of the threaded fitting.
- **All bulbs must be sorted before disposal and do not belong in the household waste.**



LED QT14
G9

NEW



220-240V ~50/60Hz
Wattage: 3.6W
Material: ceramic
Ø: 1.8 cm H: 5.4 cm


Luminous flux	400lm
Lamp current	0.03A
Colour rendering index	90
Wattage	3.6W
Energy consumption/1000h	4kWh



Options	Prod. no.
□ white 3000K	1005286 ■

LED QT-DE12
R7S, 78 mm

NEW



220-240V ~50/60Hz
Wattage: 9W
Material: polycarbonate (PC)
Ø: 2.9 cm L: 7.8 cm

Luminous flux	1050lm
Lamp current	0.043A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
■ grey 3000K	1005287 ■

LED QT-DE12
R7S, 118 mm

NEW



220-240V ~50/60Hz
Wattage: 15W
Material: polycarbonate (PC)
Ø: 2.9 cm L: 11.8 cm


Luminous flux	2000lm
Lamp current	0.068A
Colour rendering index	90
Wattage	15W
Energy consumption/1000h	15kWh



Options	Prod. no.
■ grey 3000K	1005288 ■

LED C35
E14

NEW



220-240V ~50/60Hz
Wattage: 4.2W
Material: glass
Ø: 3.5 cm H: 9.8 cm


Luminous flux	380lm
Lamp current	0.025A
Colour rendering index	90
Wattage	4.2W
Energy consumption/1000h	5kWh



Options	Prod. no.
□ transparent 2700K	1005284 ■

LED C35
E14

NEW



220-240V ~50/60Hz
Wattage: 4.2W
Material: glass
Ø: 3.5 cm H: 9.8 cm


Luminous flux	350lm
Lamp current	0.025A
Colour rendering index	90
Wattage	4.2W
Energy consumption/1000h	5kWh



Options	Prod. no.
□ white 2700K	1005285 ■

LED TCR-TSE
GX53

NEW



220-240V ~50/60Hz
Wattage: 6.1W
Material: polycarbonate (PC) / polycarbonate (PC)
Ø: 7.5 cm H: 2.4 cm

Luminous flux	490lm
Lamp current	0.034A
Colour rendering index	90
Wattage	6.1W
Energy consumption/1000h	6kWh

1005272
1005271

1005269

Options	Prod. no.
□ white/opaque 2700K	1005272 ■
□ white/opaque 3000K	1005271 ■
□ white/opaque 4000K	1005269 ■



LED QR51 GU5,3



12V AC
Wattage: 5.5W
Material: glass
Ø: 5 cm L: 4.5 cm

Luminous flux	450lm
Lamp current	0.63A
Max. luminosity	1000cd
Colour rendering index	80
Wattage	5.5W
Energy consumption/1000h	7kWh

A t G **G** 1001574 **A t G** **F** 1001575

Options	Prod. no.
transparent 2700K	1001574 ■
transparent 3000K	1001575

Manufacturer: Signify B.V.

LED G53



12V AC
Wattage: 15W
Material: plastic/aluminium
Ø: 11.1 cm L: 6.2 cm


Luminous flux	760lm
Lamp current	1.8A
Max. luminosity	3900cd
Colour rendering index	90
Wattage	15W
Energy consumption/1000h	17kWh

A t G **G**

Options	Prod. no.
silver 2700K	560231
silver 3000K	560233

Manufacturer: Signify B.V.

LED G53



12V AC
Wattage: 15W
Material: plastic/aluminium
Ø: 11.1 cm L: 6.2 cm


Luminous flux	800lm
Lamp current	1.8A
Max. luminosity	1400cd
Colour rendering index	90
Wattage	15W
Energy consumption/1000h	17kWh

A t G **G**

Options	Prod. no.
silver 2700K	560232
silver 3000K	560234

Manufacturer: Signify B.V.

LED T32 FILAMENT GU10



220-240V ~50/60Hz
Wattage: 3.2W
Material: glass
Ø: 3.2 cm L: 10 cm


Luminous flux	270lm
Lamp current	0.0175A
Colour rendering index	90
Wattage	3.2W
Energy consumption/1000h	4kWh

A t G **G**

Options	Prod. no.
transparent 2700K	1003101

Manufacturer: Segula GmbH

1006160 166





LED QPAR51 GU10, tunable 2700-6500K, smart

NEW



IP 20



38°

25 000
Hours

220-240V ~50/60Hz
Wattage: 5W
Material: polyamide 66 (PA 66) /
polycarbonate (PC)
Ø: 5 cm H: 5.4 cm

Luminous flux	380lm
Lamp current	0.04A
Max. luminosity	530cd
Colour rendering index	90
Wattage	5W
Energy consumption/1000h	5kWh



Options	Prod. no.
---------	-----------

☐ white 2700-6500K	1005311
---	----------------

LED QPAR51 GU10, RGBW, smart

NEW



IP 20



38°

25 000
Hours

220-240V ~50/60Hz
Wattage: 5.2W
Material: polyamide 66 (PA 66) /
polycarbonate (PC)
Ø: 5 cm H: 6.1 cm

Luminous flux	370lm
Lamp current	0.042A
Max. luminosity	680cd
Colour rendering index	90
Wattage	5.2W
Energy consumption/1000h	6kWh



Options	Prod. no.
---------	-----------

☐ white	1005312
--------------------------------	----------------

LED QPAR51 GU10



IP 20



36°

20 000
Hours

220-240V ~50/60Hz
Wattage: 4W
Material: plastic
Ø: 5 cm L: 5.5 cm

• Contains recycled material

Luminous flux	270lm
Lamp current	0.035 A
Max. luminosity	400cd
Colour rendering index	80
Wattage	4W
Energy consumption/1000h	4kWh



1004972

1004973
1004974

Options	Prod. no.
---------	-----------

☐ white 2700K	1004972 ▼
☐ white 3000K	1004973 ▼
☐ white 4000K	1004974 ▼

LED QPAR51 GU10

NEW



IP 20



36°

40 000
Hours

220-240V ~50/60Hz
Wattage: 6W
Material: glass
Ø: 5 cm L: 5.4 cm

Luminous flux	360lm
Lamp current	0.033A
Max. luminosity	680cd
Colour rendering index	90
Wattage	6W
Energy consumption/1000h	6kWh




Options	Prod. no.
---------	-----------

☐ silver 2200-2700K	1005273
--	----------------





LED QPAR51 GU10




220-240V ~50/60Hz
Wattage: 6W
Material: polycarbonate (PC)
Ø: 5 cm L: 5.4 cm

Luminous flux	450lm
Lamp current	0.037A
Max. luminosity	880cd
Colour rendering index	90
Wattage	6W
Energy consumption/1000h	6kWh



Options	Prod. no.
■ black 2700K	1005077
■ black 3000K	1005080
■ black 4000K	1005083

LED QPAR51 GU10




220-240V ~50/60Hz
Wattage: 6W
Material: polycarbonate (PC)
Ø: 5 cm L: 5.4 cm

Luminous flux	450lm
Lamp current	0.037A
Max. luminosity	880cd
Colour rendering index	90
Wattage	6W
Energy consumption/1000h	6kWh



Options	Prod. no.
□ white 2700K	1005076
□ white 3000K	1005079
□ white 4000K	1005082

LED QPAR51 GU10



220-240V ~50/60Hz
Wattage: 6W
Material: polycarbonate (PC)
Ø: 5 cm L: 5.4 cm

Luminous flux	450lm
Lamp current	0.037A
Max. luminosity	880cd
Colour rendering index	90
Wattage	6W
Energy consumption/1000h	6kWh




Options	Prod. no.
■ grey 2700K	1005075
■ grey 3000K	1005078
■ grey 4000K	1005081

QPAR111 GU10, tunable 2700-6500K, smart



NEW



220-240V ~50/60Hz
Wattage: 10W
Material: aluminium / polycarbonate (PC)
Ø: 11.1 cm H: 7 cm

Luminous flux	760lm
Lamp current	0.051A
Max. luminosity	4300cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh



Options	Prod. no.
□ white 2700-6500K	1005313 ■
□ white 2700-6500K	1005314 ■

LED QPAR111 GU10, RGBW, smart



NEW



220-240V ~50/60Hz
Wattage: 10W
Material: aluminium
Ø: 11.1 cm H: 7 cm

Luminous flux	750lm
Lamp current	0.056A
Max. luminosity	3500cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh




Options	Prod. no.
□ white	1005315 ■

LED QPAR111 GU10, RGBW, smart



NEW



220-240V ~50/60Hz
Wattage: 10W
Material: aluminium
Ø: 11.1 cm H: 7 cm


Luminous flux	790lm
Lamp current	0.056A
Max. luminosity	3500cd
Colour rendering index	90
Wattage	10W
Energy consumption/1000h	10kWh



Options	Prod. no.
□ white	1005316 ■

LED QPAR 111
GU10

NEW



220-240V ~50/60Hz
Wattage: 12.5W
Material: aluminium
Ø: 11.1 cm H: 7 cm

Luminous flux	900lm
Lamp current	0.058A
Max. luminosity	11000cd
Colour rendering index	90
Wattage	12.5W
Energy consumption/1000h	13kWh



Options	Prod. no.
silver 2700K	1005275
silver 3000K	1005278
silver 4000K	1005281

LED QPAR 111
GU10

NEW



220-240V ~50/60Hz
Wattage: 12.5W
Material: aluminium
Ø: 11.1 cm H: 7 cm


Luminous flux	950lm
Lamp current	0.058A
Max. luminosity	3000cd
Colour rendering index	90
Wattage	12.5W
Energy consumption/1000h	13kWh



Options	Prod. no.
silver 2700K	1005276
silver 3000K	1005279
silver 4000K	1005282

LED QPAR 111
GU10

NEW



220-240V ~50/60Hz
Wattage: 12.5W
Material: aluminium
Ø: 11.1 cm H: 7 cm

Luminous flux	1000lm
Lamp current	0.058A
Max. luminosity	1000cd
Colour rendering index	90
Wattage	12.5W
Energy consumption/1000h	13kWh


1005277
1005280

1005283

Options	Prod. no.
silver 2700K	1005277
silver 3000K	1005280
silver 4000K	1005283

LED QPAR111
GU10

NEW



220-240V ~50/60Hz
Wattage: 8W
Material: glass
Ø: 11.1 cm H: 6.1 cm


Luminous flux	680lm
Lamp current	0.046A
Max. luminosity	1300cd
Colour rendering index	90
Wattage	8W
Energy consumption/1000h	8kWh



Options	Prod. no.
transparent 2700K	1005274

LED QPAR111
GU10

NEW



220-240V ~50/60Hz
Wattage: 7.3W
Material: plastic/aluminium
Ø: 11.1 cm H: 7.1 cm

Luminous flux	530lm
Lamp current	0.051A
Max. luminosity	1470cd
Colour rendering index	90
Wattage	7.3W
Energy consumption/1000h	7kWh



Options	Prod. no.
silver 2700K	1005291
silver 3000K	1005292
silver 4000K	1005293

LED QPAR111
GU10

NEW



220-240V ~50/60Hz
Wattage: 7.3W
Material: plastic/aluminium
Ø: 11.1 cm H: 7.1 cm

Luminous flux	500lm
Lamp current	0.051A
Max. luminosity	1040cd
Colour rendering index	90
Wattage	7.3W
Energy consumption/1000h	7kWh



Options	Prod. no.
silver 2700K	1005294
silver 3000K	1005295
silver 4000K	1005296



LED A60 E27, tunable 2700-6500K, smart

NEW

IP 20



230°

25 000
Hours

220-240V ~50/60Hz
Wattage: 9W
Material: polyamide 66 (PA 66)
Ø: 6 cm H: 11 cm

Luminous flux	800lm
Lamp current	0.067A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white 2700-6500K	1005317 ■

LED A60 E27, RGBW, smart

NEW

IP 20



230°

25 000
Hours

220-240V ~50/60Hz
Wattage: 9W
Material: polyamide 66 (PA 66) / polycarbonate (PC)
Ø: 6 cm H: 11 cm

Luminous flux	800lm
Lamp current	0.073A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white / opaque	1005318 ■

LED A60 E27

NEW

C.L.



320°

15 000
Hours

220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 6 cm H: 10.5 cm

Luminous flux	700lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ frosted 2700K	1005304 ■

LED A60 E27

NEW

C.L.



IP 20



220°

25 000
Hours

220-240V ~50/60Hz
Wattage: 9W
Material: plastic
Ø: 6 cm H: 11 cm

Luminous flux	800lm
Lamp current	0.048A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white 2700K	1005301 ■

LED A60 E27

NEW

C.L.



IP 20



220°

25 000
Hours

220-240V ~50/60Hz
Wattage: 9W
Material: plastic
Ø: 6 cm H: 11 cm

Luminous flux	1300lm
Lamp current	0.062A
Colour rendering index	90
Wattage	9W
Energy consumption/1000h	9kWh



Options	Prod. no.
☐ white 2700K	1005302 ■

LED A60 E27

NEW

C.L.



320°

15 000
Hours

220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 6 cm H: 10.5 cm


Luminous flux	800lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ transparent 2700K	1005303 ■

LED T38
E27

NEW



220-240V ~50/60Hz
Wattage: 8W
Material: plastic
Ø: 3.8 cm H: 11.6 cm


Luminous flux	880lm
Lamp current	0.035 A
Colour rendering index	90
Wattage	8W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ white 3000K	1005289 ■
☐ white 4000K	1005290 ■

LED T45
E27

NEW



220-240V ~50/60Hz
Wattage: 13.5W
Material: plastic
Ø: 4.5 cm H: 14 cm


Luminous flux	1520lm
Lamp current	0.06A
Colour rendering index	90
Wattage	13.5W
Energy consumption/1000h	14kWh



Options	Prod. no.
☐ white 3000K	1005307 ■
☐ white 4000K	1005308 ■

LED ST64
E27

NEW



220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 6.4 cm H: 14.5 cm

Luminous flux	700lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ gold 2500K	1005265 ■

LED G95
E27

NEW



220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 9.5 cm H: 13.8 cm

Luminous flux	800lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ transparent 2700K	1005309 ■

LED A60
E27, mirrorhead, chrome

NEW



220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 6 cm H: 10.5 cm


Luminous flux	720lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ chrome 2700K	1005305 ■

LED ST58
E27

NEW



220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 5.8 cm H: 14.2 cm

Luminous flux	800lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
☐ transparent 2700K	1005268 ■



LED G125

E27, mirrorhead, chrome

NEW

220-240V ~50/60Hz
Wattage: 7.5W
Material: glass
Ø: 12.5 cm H: 17.8 cm

Luminous flux	720lm
Lamp current	0.038A
Colour rendering index	90
Wattage	7.5W
Energy consumption/1000h	8kWh



Options	Prod. no.
chrome 2700K	1005306 

1002146 109



EASY TO INSTALL.

When we say “Easy to install”, we are referring to well thought out features for increased efficiency. For you this means: time-saving installation for fast project completion, impeccable work and satisfied customers.

MOUNTABLE LAMP HEADS.

With our ENOLA® family, the lamp head can be separated from the mounting plate that is fixed to the wall. This way, after mounting using the integrated nib and establishing the electrical connection using the plug connection, both hands remain free to securely screw on the lights.




Practical nib



Secure assembly




Finally, fix it in place



EFFICIENCY PAYS OFF.


Because efficiency always pays off, SLV lights are easy, quick and safe to install. On account of the fixed mounting plates, detachable lamp heads, spring clamps, through wiring, cable entries and various other features, they offer crucial benefits: in that they save you time, effort, and expense.



1005155 624

PRACTICAL SPRING CLAMPS.

The cube-shaped SITRA CUBE wall lights offer wonderful modern simplicity. This means they are also fast and simple to install: Simply directly connect the connection cable (no tools required) and connect the mounting plate coupling to the light connector – done!



Connection
of the power line



Simply plug together



NEW

1005202 675

FEED-THROUGH WIRING


Our QUADRULO wall and ceiling lights show how simply through-wiring functions in practice. Two cable entries in a figure of 8 configuration are provided in the light's baseplate. The spring clamp also has two connection options. This means that multiple lights can be quickly and simply installed simultaneously.



Secure cable entry



Feed-through wiring




A FAMILY MATTER.

OUR SLV LUMINAIRE FAMILIES.



Particularly when visual continuity is desired, our luminaire families are perfectly suited for designing rooms and settings in a uniform way while still remaining versatile.

ABRIDOR




ACCANTO






ALTRA DICE




ANELA




APONI



ASTINA




AVO




BIG NAILS



BIMA




BOOKAT







ENOLA

Pendant	Wall	Wall	Wall	Wall	Wall	Wall
						
161	611	611	611	612	612	612
Wall	Wall	Wall	Wall	Wall	Wall	
						
615	615	615	616	616	616	
Wall	Wall	Wall	Wall	Wall	Wall	
						
671	671	671	672	672	672	

ENOLA B

Pendant	Wall	Wall	Ceiling	Wall/ceiling
				
161	217	217	281	307
Wall/ceiling	Wall/ceiling	Single-circuit track	Single-circuit track	
				
307	307	480	481	

ENOLA C

Ceiling	Ceiling	3-circuit track	Single-circuit track	Paths/floor
				
281	281	459	480	580

**ESKINA**

Paths/floor



516

Wall



665

Wall



683

Wall



682

**ESKINA
FRAME**

Paths/floor



512

Paths/floor



512

Paths/floor



514

Paths/floor

NEW

515

Wall

NEW

631

Wall



631

**FENDA
MIX & MATCH**

Table



104

Floor



104

Table




105

Floor



105

Floor



106

Pendant



154

Wall




218

Wall



219

Wall



219

Ceiling



276

Shades



107, 155

Shades



107, 155, 277

Shades



107, 154

Shades



154

Shades



218

Shades



218


**FITU
MIX & MATCH**

Floor



109

Floor




109

Pendant



150

Pendant



150

Wall




215

Wall



214

Wall/ceiling



214

Wall/ceiling




318




FORCHINI



GLENOS



GLOO PURE



GRAPHITE






HELIA


Pendant  158	Pendant  159	Pendant  158	Pendant  159	Pendant  157	Pendant  157
Wall/ceiling  299	Wall/ceiling  299	Recessed  400	3-circuit track  457	Single-circuit track  483	
Paths/floor  581	Paths/floor  581	Paths/floor  828	Paths/floor  582		
Spotlight  599	Spotlight  599	Wall  685	Wall  685		

KALU



Wall/ceiling  302	Wall/ceiling  302	Wall/ceiling  302	Wall/ceiling  302		
Wall/ceiling  304	Wall/ceiling  304	Wall/ceiling  304	Wall/ceiling  304		
3-circuit track  454	3-circuit track  454	3-circuit track  454	Single-circuit track  484	Single-circuit track  484	Single-circuit track  484



KARPO

Table  108	Floor  108	Wall  224	Wall  224	Wall  225	Wall  225
Wall/ceiling  296	Wall/ceiling  296	Recessed  400			


LIGHT EYE

Pendant  172	Pendant  172	3-circuit track  446	3-circuit track  446	Single-circuit track  476	Single-circuit track  476
Easytec® II  495	Easytec® II  495				

LISENNE

Pendant  164	Wall  213	Paths/floor  553	Paths/floor  553
---	--	---	---

L-LINE

Wall  242	Wall  242	Paths/floor  538	Paths/floor  538	Paths/floor  538, 539	Wall  656
--	--	---	---	---	--

LOGS

Wall  196	Wall  196	Wall  197	Wall  197	Paths/floor  517	Paths/floor  517	Wall  652
--	--	--	--	--	---	--

**MAGANDA**

Table



113

Wall



232

MANA

Wall



185

Wall



185

Wall



185

Wall



185

Wall



186

Shade



186

Shade



186

Wall



187

Wall




187

Shade



187

Shade



187

Wall



655

MECANICA

Table



111

Floor



111

MEDO LED

Pendant/ceiling



133, 257

Pendant/ceiling



132, 257

Pendant/ceiling



130, 254

Pendant/ceiling



131, 255

Pendant/ceiling



131, 255

Pendant/ceiling



131, 255

Pendant/ceiling



134, 258

Pendant/ceiling



134, 258

Pendant/ceiling



134, 258

Pendant/ceiling



135, 259

Pendant/ceiling



136, 260

Pendant/ceiling



136, 260

Pendant/ceiling



136, 260

Pendant/ceiling



137, 261

Pendant/ceiling



132, 256

Pendant/ceiling



138, 261

Pendant



128

Pendant



128

Pendant



129

Recessed



414, 415

Recessed




416, 417



MOLAT





MYRA



NAUTILUS







NOBLO





NUMINOS®

Recessed  	Recessed  	Recessed  	Recessed  	Recessed  
029	031	033	035	037
Recessed  	Recessed  	Recessed  	Recessed  	Recessed  
039	041	043	045	047
Recessed  	Recessed  	Recessed  	Recessed  	Recessed  
049	051	053	055	057
3-circuit track  	3-circuit track  	3-circuit track  	3-circuit track  	3-circuit track  
063	065	067	069	071
Wall/ceiling  	Ceiling  	Ceiling  	Ceiling  	
073	075	077	079	
Ceiling  	Ceiling  	Ceiling  	Ceiling  	
081	083	085	087	
Pendant  	Pendant  	Pendant  	Pendant  	
089	091	093	095	

**OCCULDAS**Design:
David Morgan**OCULUS****ONE****OVALISK****PARA CONE**



PLASTRA

Pendant 	Wall 	Wall 	Wall 	Wall 	Wall 	Wall 
						
175	190	190	191	191	193	193

Wall 	Wall 	Wall 	Wall 	Wall 	Ceiling 	Ceiling 
						
193	194	194	194	223	282	282

Ceiling 	Ceiling 	Recessed 	Recessed 
			
282	283	402	403

P-LIGHT

Wall/ceiling 	Wall/ceiling 	Wall/ceiling 	Recessed 
340	340	341	420

PURI

Wall/ceiling 	Wall/ceiling 	Wall/ceiling 	Wall/ceiling 	3-circuit track 	3-circuit track 
					
312	312	312	312	453	453

Single-circuit track 	Single-circuit track 	Single-circuit track 
		
470	478	478

Q-LINE

Pendant 	Pendant 	Pendant 	Wall 	Ceiling 	Ceiling 
					
144, 145	144, 145	145, 775	243	264	265



QUADRASS

Pendant



165

Wall



212

Wall



212

QUADRASYL

Paths/floor



577

Wall



662

QUADRULO

Paths/floor



522

Wall

NEW



629

Wall

NEW



629


Ceiling



675

RASCALI

Paths/floor



579

Wall



661

ROTOBALL

Pendant



174

Pendant



174

Pendant



174

Ceiling



289

Ceiling



289

Floor



546

Floor



546

Floor



546

ROX

Paths/floor



561

Paths/floor



561

Paths/floor



561

Wall



645

Wall



645

Ceiling



679

Ceiling



679

RUSTY

Paths/floor



524

Paths/floor



524, 525

Paths/floor



527

Paths/floor



527

Paths/floor



528

Paths/floor



529

Paths/floor



530

Paths/floor



530

Paths/floor



532

Paths/floor



533

Wall



636

Wall




636



SENSOR

Wall/ceiling	Wall/ceiling	Wall/ceiling	Wall/ceiling	Wall/ceiling	Wall/ceiling
					
319	319	319	320	320	320
Recessed	Recessed	Recessed	Recessed	Recessed	Recessed
					
389	389	389	390	390	390

SIGHT LED

Wall/ceiling	Wall/ceiling	3-circuit track	3-circuit track	3-circuit track	3-circuit track
					
					
337	337	440	441, 773	448	450

SITRA

Paths/floor	Spike	Spike	Wall	Wall	Wall	Wall
						
						
583	602	603	622	622	624	624
Wall	Wall	Wall	Wall	Ceiling	Wall/ceiling	
						
						
624	644	644	661	679	684	

SLOTS

Paths/floor	Paths/floor	Wall
		
		
570	571	647

SQUARE

Paths/floor	Paths/floor	Paths/floor	Wall	Wall
				
				
568	568	568	660	662



SUPROS

Pendant  148	Pendant  148, 149	Wall  189	Ceiling  270	Ceiling  271
Recessed  382	Recessed  383	Recessed  384, 385	Recessed  386, 387	

THEO

Wall  216	Paths/floor  540	Paths/floor  540	Paths/floor  541	Spike  601		
Wall  618	Wall  619	Wall  619	Wall  619	Wall  620	Wall  621	Wall  621
Ceiling  674	Ceiling  674	Ceiling  684				

TONGA

Pendant  165	Single-circuit track  475	Easytec® II  494
---	--	---

WORKLIGHT

Table  100	Floor  101	Pendant  146, 774
---	---	--



1005394 100

1005392 100



NUMINOS®

DOWNLIGHTS AND SPOTLIGHTS

can be found on the following pages:

Recessed lights	28 - 57
3-phase track systems	62 - 71
Wall and ceiling lights	72 - 73
Ceiling lights	72 - 86
Pendant lights	88 - 95

Or simply configure your system online at: www.numinos.slv.com





Please note: The 7-digit product numbers can be found from page 843 onwards.

111000	113540..... 355	114386..... 360
111262..... 409	113541..... 355	114390..... 361
111292..... 408	113550..... 355	114391..... 361
111360..... 352	113830..... 355	114396..... 361
111361..... 353	113840..... 355	114400..... 356
111362..... 354	113841..... 355	114401..... 356
111380..... 355	113870..... 362	114406..... 356
111381..... 355	113871..... 362	114420..... 421, 707
111382..... 355	113876..... 362	114421..... 421, 707
111710..... 352	113880..... 362	114426..... 421, 707
111711..... 352	113881..... 362	114430..... 421, 707
111716..... 352	113886..... 362	114431..... 421, 707
111720..... 352	113890..... 364	114436..... 421, 707
111721..... 352	113891..... 364	114440..... 422, 708
111726..... 352	113896..... 364	114441..... 422, 708
111850..... 804	113900..... 362	114450..... 422, 708
111861..... 804	113901..... 362	114451..... 422, 708
	113906..... 362	114460..... 423, 708
112000	113910..... 363	114461..... 423, 708
112161..... 394	113911..... 363	114480..... 399
112162..... 394	113916..... 363	114481..... 399
112165..... 394	113920..... 365	114490..... 399
112221..... 394	113921..... 365	114491..... 399
112222..... 394	113926..... 365	
112225..... 394	113930..... 269	115000
112242..... 404	113931..... 269	115510..... 376
112682..... 393	113940..... 269	115511..... 376
112692..... 393	113941..... 269	115520..... 376
112702..... 393	113951..... 357	115521..... 376
112720..... 408	113956..... 357	115530..... 376
112721..... 408	113961..... 357	115531..... 376
112780..... 408, 409, 410	113966..... 357	115540..... 378
112781..... 408, 409, 410	113970..... 356	115541..... 378
112910..... 372	113971..... 356	115550..... 378
112911..... 372	113976..... 356	115551..... 378
		115700..... 379
113000	114000	115701..... 379
113140..... 370	114102..... 148, 149, 270,	115710..... 379
113141..... 370	 384, 385, 386, 387	115711..... 379
113150..... 371	114104..... 148, 149, 270,	115720..... 379
113151..... 371	 384, 385, 386, 387	115721..... 379
113160..... 372	114220..... 366	115730..... 380
113161..... 372	114221..... 366	115731..... 380
113170..... 374	114230..... 366	115740..... 380
113171..... 374	114231..... 366	115741..... 380
113262..... 409	114240..... 366	
113292..... 408	114241..... 366	116000
113440..... 351	114250..... 367	116302..... 148, 189, 271, 382, 383
113441..... 351	114251..... 367	116304..... 148, 189, 271, 382, 383
113446..... 351	114260..... 368	116310..... 382
113450..... 351	114261..... 368	116311..... 382
113451..... 351	114270..... 368	116320..... 383
113456..... 351	114271..... 368	116321..... 383
113490..... 352	114280..... 369	116330..... 271
113491..... 353	114281..... 369	116331..... 271
113492..... 354	114290..... 369	116340..... 189
113510..... 352	114291..... 369	116341..... 189
113511..... 353	114380..... 360	
113512..... 354	114381..... 360	

117000	135124..... 131, 255	143042..... 467
117100..... 275	135170..... 131, 255	143050..... 467
117101..... 275	135171..... 131, 255	143051..... 467
117110..... 275	135174..... 131, 255	143052..... 467
117111..... 275	135250..... 135, 255, 295, 785	143060..... 467
117311..... 397	135251..... 135, 255, 295, 785	143061..... 467
117321..... 273	135254..... 135, 255, 295, 785	143062..... 467
117331..... 397		143070..... 467
117351..... 273	138000	143071..... 467
	138981..... 501, 793	143072..... 467
132000	138982..... 501, 793	143080..... 467
132020..... 308	138991..... 501, 793	143081..... 467
132021..... 308	138992..... 501, 793	143082..... 467
132024..... 308		143090..... 467
132600..... 151, 473	139000	143091..... 467
132601..... 151, 473	139004..... 500	143092..... 467
132605..... 151, 473	139006..... 500	143100..... 467
132610..... 151, 473	139024..... 500	143101..... 467
132611..... 151, 473	139026..... 500	143102..... 467
132615..... 151, 473	139030..... 500	143110..... 467
132620..... 151	139031..... 500	143111..... 467
132621..... 151	139040..... 500	143112..... 467
132625..... 151	139041..... 500	143120..... 151, 467, 469, 473
132660..... 154	139050..... 500	143121..... 151, 467, 469, 473
132661..... 154	139051..... 500	143124..... 151, 467, 469, 473
132662..... 154	139060..... 500	143130..... 467
132670..... 803	139061..... 500	143131..... 467
132671..... 803	139070..... 502	143132..... 467
132680..... 803	139071..... 502	143151..... 467
132681..... 803	139072..... 502	143152..... 467
132690..... 150	139080..... 502	143160..... 467
132691..... 150	139081..... 502	143161..... 467
132835..... 551	139082..... 502	143162..... 467
	139090..... 503	143169..... 467
133000	139091..... 503	143170..... 467, 469
133019..... 167	139092..... 503	143171..... 467, 469
133060..... 167	139100..... 503	143172..... 467, 469
133120..... 148	139101..... 503	143190..... 470
133121..... 148	139102..... 503	143191..... 470
133310..... 169	139110..... 504	143194..... 470
133320..... 169	139111..... 504	143221..... 469
133444..... 165	139112..... 504	143230..... 469
133481..... 172	139120..... 506	143231..... 469
133482..... 172	139121..... 506	143241..... 469
133489..... 172	139122..... 506	143251..... 469
133490..... 172	139130..... 503	143261..... 469
133491..... 172	139131..... 503	143281..... 469
133840..... 128	139132..... 503	143350..... 485
133841..... 128		143351..... 485
133850..... 128	143000	143354..... 485
133851..... 128	143010..... 465	143380..... 467
	143011..... 465	143381..... 467
135000	143012..... 465	143382..... 467
135020..... 133, 257	143020..... 465	143390..... 478
135021..... 133, 257	143021..... 465	143391..... 478
135024..... 133, 257	143022..... 465	143392..... 478
135070..... 133, 257	143030..... 467	143430..... 482
135071..... 133, 257	143031..... 467	143431..... 482
135074..... 133, 257	143032..... 467	143432..... 482
135120..... 131, 255	143040..... 467	143440..... 482
135121..... 131, 255	143041..... 467	143441..... 482

143442.....	482	145670.....	437	148018.....	190
143450.....	478	145674.....	437	148019.....	223
143451.....	478	145680.....	437	148060.....	193
143454.....	478	145684.....	437	148070.....	402
143540.....	484	145690.....	437	148071.....	403
143541.....	484	145694.....	437	148091.....	193
143544.....	484	145700.....	437	148540.....	230
143580.....	483	145710.....	437		
143581.....	483	145714.....	437	149000	
143594.....	475	145720.....	437	149381.....	161
143620.....	476	145724.....	437	149387.....	161
143621.....	476	145730.....	437	149388.....	161
143731.....	484	145734.....	437	149452.....	222
143811.....	485	145830.....	437	149471.....	205
143930.....	477	145834.....	437	149511.....	205
143932.....	477	145990.....	151, 437, 473	149762.....	234
143941.....	480	145994.....	151, 437, 473	149772.....	234
143951.....	480				
143960.....	481	146000		151000	
143961.....	481	146000.....	110	151040.....	172, 228, 476
143964.....	481	146010.....	110	151041.....	172, 245, 476
143990.....	474	146332.....	245	151049.....	172, 245, 476
143991.....	474	146472.....	245	151271.....	201
		146682.....	229	151275.....	201
144000		146692.....	228	151282.....	237
144010.....	476			151311.....	200
144011.....	476	147000		151315.....	200
144019.....	476	147301.....	304	151320.....	196
144200.....	479	147306.....	304	151321.....	196
144201.....	479	147311.....	304	151325.....	196
144204.....	479	147316.....	304	151410.....	202
		147321.....	304	151411.....	202
145000		147326.....	304	151416.....	202
145100.....	435	147360.....	312	151450.....	202
145102.....	435	147361.....	312	151451.....	202
145200.....	435	147370.....	312	151456.....	202
145202.....	435	147371.....	312	151511.....	274
145300.....	435	147380.....	312	151514.....	274
145302.....	435	147381.....	312	151531.....	274, 308
145510.....	437	147411.....	311	151534.....	274, 308
145514.....	437	147412.....	311	151591.....	211
145520.....	437	147414.....	311	151710.....	203
145524.....	437	147441.....	316	151711.....	203
145530.....	437	147442.....	316	151740.....	203
145534.....	437	147443.....	316	151741.....	203
145551.....	439	147444.....	316	151781.....	207
145560.....	437	147529.....	211	151786.....	207
145564.....	437	147550.....	308	151791.....	207
145580.....	437	147551.....	308	151796.....	207
145584.....	437	147559.....	308	151800.....	217
145590.....	437			151801.....	217
145594.....	437	148000		151803.....	217
145600.....	437	148001.....	282	151804.....	217
145604.....	437	148002.....	283	151810.....	281
145630.....	437	148004.....	282	151811.....	281
145634.....	437	148005.....	282	151813.....	281
145640.....	437	148010.....	191	151830.....	307
145644.....	437	148012.....	194	151831.....	307
145660.....	437	148013.....	194	151840.....	217, 281, 307
145664.....	437	148016.....	194	151850.....	161

151851.....	161	153850.....	452	165390.....	174
151853.....	161	153851.....	452	165400.....	174
151950.....	412			165410.....	174
151952.....	412	155000			
151960.....	412	155156.....	288	175000	
151962.....	412	155180.....	332	175060.....	433
		155236.....	332	175080.....	433
152000		155373.....	278	175160.....	433
152010.....	307	155490.....	105	175180.....	433
152011.....	307	155492.....	105	175190.....	433
152013.....	307	155530.....	170	175210.....	433
152020.....	307	155540.....	105		
152021.....	307	155550.....	276	181000	
152023.....	307	155551.....	276	181530.....	501
152101.....	281	155552.....	276	181531.....	501
152230.....	456	155582.....	107, 155, 277	181532.....	501
152231.....	456	155583.....	107, 155, 277		
152232.....	456	155592.....	107, 155, 277	184000	
152240.....	456	155714.....	164	184000.....	491
152241.....	456	155752.....	213	184002.....	491
152242.....	456	155780.....	104	184004.....	491
152320.....	453	155785.....	104	184010.....	491
152321.....	453	155790.....	104	184012.....	491
152330.....	296	155795.....	104	184020.....	491
152331.....	296	155870.....	156	184022.....	491
152340.....	225	155871.....	156	184030.....	491
152341.....	225	155910.....	171	184032.....	491
152360.....	158	155930.....	171	184060.....	491
152361.....	158			184062.....	491
152370.....	159	156000		184071.....	492
152371.....	159	156050.....	278	184140.....	491
152380.....	400	156051.....	278	184142.....	491
152381.....	400	156100.....	155, 277	184170.....	491
152430.....	459	156111.....	107, 155, 277	184172.....	491
152431.....	459	156113.....	107, 155, 277	184290.....	491
152600.....	454	156122.....	107, 155, 277	184292.....	491
152601.....	454	156141.....	107, 155	184300.....	491
152610.....	454	156143.....	107, 155	184302.....	491
152611.....	454	156152.....	107, 155	184330.....	491
152640.....	459	156500.....	299	184332.....	491
152641.....	459	156501.....	299	184440.....	492
152750.....	451	156510.....	299	184450.....	492
152751.....	451	156511.....	299	184452.....	492
152780.....	451	156530.....	400	184530.....	494
152781.....	451	156531.....	400	184534.....	494
152960.....	457			184590.....	495
152961.....	457	158000		184630.....	494
		158400.....	158	184634.....	494
153000		158401.....	158		
153112.....	446	158410.....	159	185000	
153130.....	447	158411.....	159	185580.....	495
153140.....	445			185590.....	495
153141.....	445	161000			
153420.....	452	161271.....	398	186000	
153421.....	452	161291.....	398	186300.....	501
153560.....	453	161461.....	285	186301.....	501
153561.....	453			186302.....	501
153564.....	453	165000		186310.....	501
153580.....	454	165358.....	179	186311.....	501
153581.....	454	165359.....	179	186312.....	501

186330.....	501	228730.....	805	229702.....	703
186331.....	501	228752.....	582, 583	229740.....	594
186332.....	501	228753.....	550, 570, 571	229741.....	595
186340.....	501	228754.....	517, 521	229931.....	692
186341.....	501	228771.....	641	229935.....	692
186342.....	501	228775.....	641	229961.....	688
186350.....	501	228776.....	641	229965.....	688
186351.....	501	228925.....	557	229971.....	688
186352.....	501	228935.....	557	229975.....	688
186360.....	501	228945.....	557		
186361.....	501	228965.....	555	230000	
186362.....	501			230030.....	639
186640.....	501	229000		230034.....	639
186641.....	501	229020.....	533	230060.....	516, 552, 565, 583
186642.....	501	229021.....	533	230061.....	565
		229022.....	532, 533	230063.....	565
210000		229050.....	562	230066.....	565
210060.....	803	229054.....	562	230069.....	565
210061.....	803	229057.....	562	230084.....	630
210064.....	803	229059.....	562	230085.....	630
		229062.....	703	230090.....	527
220000		229071.....	691	230355.....	661
220000.....	804	229072.....	691	230365.....	644
		229075.....	691	230435.....	551
227000		229081.....	691	230465.....	550
227140.....	792	229085.....	691	230655.....	630
227160.....	792	229090.....	595	230657.....	630
227176.....	661	229110.....	702		
227194.....	647	229162.....	560	231000	
227195.....	647	229172.....	560	231010.....	638
227219.....	546	229182.....	660	231012.....	638
227220.....	546	229200.....	722	231015.....	638
227221.....	546	229230.....	722	231035.....	597
227410.....	593	229234.....	722	231072.....	591
227418.....	593	229320.....	721	231205.....	627
227462.....	724	229324.....	721	231215.....	521
227504.....	601	229374.....	721	231225.....	521
227505.....	601	229381.....	718	231230.....	517, 521, 524, 525
227507.....	601	229383.....	718	231231.....	577
227600.....	730	229410.....	524	231233.....	535
227604.....	730	229411.....	525	231234.....	545, 561, 568
227680.....	731	229420.....	529	231235.....	536, 537
227684.....	731	229421.....	529	231305.....	577
227922.....	559, 560	229422.....	527, 528, 529, 534, 553, 530	231315.....	662
		229430.....	530	231351.....	642
228000		229431.....	530	231355.....	642
228100.....	559	229432.....	530	231370.....	536
228110.....	559	229524.....	620	231371.....	536
228130.....	559	229525.....	620	231410.....	534
228332.....	724	229531.....	618	231411.....	534
228342.....	724	229532.....	618	231420.....	535
228370.....	722	229535.....	618	231440.....	537
228412.....	716	229551.....	674	231455.....	571
228430.....	721	229554.....	674	231457.....	571
228434.....	721	229555.....	674	231465.....	659
228545.....	580	229564.....	621	231475.....	566
228555.....	599	229565.....	621	231505.....	583
228712.....	542, 557, 582, 583	229574.....	619	231515.....	684
228722.....	542, 557	229575.....	619	231525.....	602
228725.....	805	229664.....	655	231535.....	603
228726.....	561, 577, 805	229665.....	655	231541.....	679

231545.....	679	233165.....	582, 583	464140.....	412, 798
231585.....	659	233184.....	583	464141.....	157, 375
231595.....	567	233185.....	583	464142.....	798
231805.....	647	233215.....	644, 665, 666	464144.....	798
231807.....	647	233245.....	685	464147.....	349
231815.....	570	233255.....	685	464200.....	801
231817.....	570	233275.....	582	464804.....	799
		233285.....	582		
232000		233302.....	641	470000	
232045.....	657	233407.....	532	470500.....	796
232055.....	677	233417.....	532	470505.....	792
232065.....	548	233427.....	528	470548.....	796
232075.....	549	233437.....	528	470549.....	796
232085.....	549	233447.....	524		
232095.....	548	233457.....	524	560000	
232101.....	652	233500.....	718	560231.....	811
232104.....	652	233540.....	723	560232.....	811
232105.....	652	233570.....	598	560233.....	811
232115.....	517	233571.....	598	560234.....	811
232119.....	517	233580.....	598		
232125.....	517	233582.....	598	631000	
232135.....	574	233601.....	701	631337.....	339
232145.....	574	233605.....	701	631339.....	339
232155.....	572	233611.....	701	631347.....	339
232165.....	572	233615.....	701	631349.....	339
232175.....	573	233621.....	701	900011.....	595, 598
232185.....	573	233625.....	701		
232195.....	572, 573	233635.....	700	955000	
232285.....	662	233639.....	700	955135.....	804
232294.....	577	233650.....	702		
232295.....	577	233660.....	702	961000	
232431.....	622	233792.....	724	961034.....	804
232435.....	633			961037.....	803
232441.....	634	234000		961250.....	803
232445.....	634	234505.....	619	961270.....	803
232461.....	633	234515.....	619	961271.....	803
232465.....	633	234525.....	621	961276.....	803
232471.....	634	234535.....	674		
232475.....	634			1000100	
232485.....	652	240000		1000127.....	303
232491.....	652	240000.....	340	1000128.....	303
232495.....	652	240002.....	340	1000129.....	303
232497.....	652	240004.....	341	1000130.....	303
232531.....	622	240006.....	420	1000131.....	303
232535.....	622	240007.....	340, 341	1000132.....	303
232537.....	622	240008.....	340, 341	1000135.....	303
232905.....	651	240009.....	341	1000136.....	303
232915.....	651	240010.....	341		
		240020.....	340	1000300	
233000		240021.....	340	1000327.....	216
233094.....	686	240022.....	341	1000329.....	216
233095.....	686	240024.....	420	1000330.....	216
233104.....	666			1000331.....	618
233105.....	666	461000		1000332.....	679
233114.....	644	461060.....	792	1000333.....	645
233115.....	644	461157.....	792	1000334.....	645
233134.....	665			1000335.....	662
233135.....	665	464000		1000336.....	660
233144.....	583	464031.....	801	1000339.....	679
233145.....	582, 583	464107.....	801	1000340.....	647
233164.....	583	464108.....	800	1000342.....	647

1000343.....	568	1000533.....	741	1000683.....	558
1000344.....	568	1000534.....	741	1000685.....	264
1000345.....	568	1000535.....	745	1000686.....	264
1000346.....	568	1000536.....	745	1000688.....	264
1000384.....	724	1000537.....	745	1000689.....	264
1000398.....	548, 552	1000540.....	743	1000691.....	265
		1000546.....	743	1000692.....	265
1000400		1000549.....	743	1000694.....	265
1000422.....	199	1000552.....	743	1000695.....	265
1000423.....	199	1000555.....	743		
1000426.....	298	1000556.....	744	1000700	
1000427.....	298	1000557.....	744	1000702.....	304
1000443.....	288	1000558.....	744	1000703.....	304
1000445.....	288	1000559.....	744	1000704.....	304
1000457.....	735	1000560.....	744	1000707.....	446
1000458.....	735	1000561.....	744	1000708.....	446
1000459.....	735	1000562.....	744	1000709.....	446
1000460.....	735	1000563.....	744	1000711.....	480
1000461.....	735	1000564.....	744	1000712.....	480
1000462.....	735	1000565.....	744	1000713.....	476
1000463.....	735	1000566.....	744	1000714.....	395
1000464.....	735	1000567.....	744	1000715.....	395
1000465.....	735	1000568.....	744	1000716.....	395
1000466.....	736, 739	1000569.....	744	1000717.....	395
1000467.....	736, 739	1000570.....	744	1000718.....	395
1000468.....	736, 739	1000571.....	743	1000719.....	395
1000469.....	736, 739	1000574.....	408	1000720.....	395
1000470.....	736	1000575.....	408	1000721.....	395
1000471.....	736	1000576.....	409	1000725.....	132, 256
1000472.....	737	1000577.....	409	1000726.....	132, 256
1000473.....	737	1000579.....	107, 155, 277	1000727.....	132, 256
1000474.....	737	1000580.....	107, 155, 277	1000729.....	217
1000475.....	737			1000730.....	217
1000476.....	737	1000600		1000731.....	217
1000477.....	737	1000613.....	186	1000735.....	599
1000478.....	737	1000614.....	187	1000736.....	581, 599
1000479.....	737	1000615.....	187	1000746.....	333
1000480.....	737	1000616.....	186	1000748.....	333
1000481.....	737	1000618.....	186	1000763.....	106
1000482.....	737	1000619.....	186	1000764.....	107, 154
1000483.....	737	1000621.....	187	1000773.....	154
1000484.....	737	1000623.....	187	1000777.....	238
1000485.....	737	1000624.....	187	1000780.....	239
1000486.....	737	1000631.....	281	1000783.....	262
1000487.....	736	1000634.....	201	1000784.....	262
1000489.....	736	1000635.....	201	1000785.....	262
1000496.....	742	1000636.....	201	1000786.....	262
1000497.....	742	1000637.....	201	1000797.....	661
1000498.....	742	1000638.....	196	1000799.....	579
		1000639.....	196		
1000500		1000640.....	196	1000800	
1000505.....	741	1000655.....	724	1000801.....	579
1000506.....	741	1000656.....	457	1000807.....	287
1000507.....	741	1000657.....	457	1000808.....	287
1000514.....	741	1000665.....	553	1000809.....	164, 287
1000515.....	741	1000666.....	553	1000810.....	164, 287
1000516.....	741	1000668.....	243	1000811.....	164, 287
1000523.....	741	1000669.....	243	1000812.....	164, 287
1000524.....	741	1000670.....	243	1000813.....	164
1000525.....	741	1000681.....	658	1000820.....	657
1000532.....	741	1000682.....	558	1000821.....	552

1000822.....	552	1001200		1001468.....	231
1000823.....	677	1001250.....	418, 784	1001472.....	231
1000824.....	186	1001251.....	418, 784	1001488.....	561
1000825.....	187	1001252.....	728	1001489.....	561
1000827.....	179	1001253.....	728	1001490.....	561
1000833.....	407, 709	1001254.....	728	1001494.....	561
1000855.....	130, 254	1001255.....	728	1001495.....	296
1000856.....	130, 254	1001256.....	728	1001496.....	296
1000857.....	130, 254	1001262.....	728		
1000864.....	131, 255	1001263.....	728	1001500	
1000865.....	131, 255	1001264.....	407	1001505.....	262
1000866.....	131, 255	1001267.....	799	1001506.....	262
1000880.....	665	1001272.....	218	1001508.....	262
1000881.....	665	1001273.....	218	1001509.....	262
1000886.....	315	1001274.....	218	1001510.....	435
1000887.....	315	1001275.....	218	1001511.....	435
1000889.....	315	1001276.....	218	1001512.....	435
1000890.....	315	1001283.....	337	1001513.....	437
1000892.....	315	1001284.....	337	1001514.....	437
1000893.....	315	1001285.....	337	1001515.....	437
1000895.....	315	1001286.....	337	1001516.....	437
1000896.....	315	1001287.....	337	1001517.....	437
		1001288.....	337	1001518.....	437
1000900		1001299.....	242	1001519.....	437
1000909.....	804			1001520.....	437
1000910.....	216	1001300		1001521.....	437
1000911.....	216	1001300.....	242	1001522.....	437
1000914.....	370	1001301.....	242	1001523.....	437
1000915.....	370	1001303.....	242	1001524.....	437
1000917.....	370	1001304.....	242	1001525.....	437
1000918.....	179	1001305.....	242	1001526.....	437
1000926.....	144	1001309.....	145, 775	1001527.....	437
1000927.....	144	1001310.....	145, 775	1001528.....	437
1000929.....	144	1001314.....	692	1001529.....	437
1000930.....	144	1001315.....	692	1001530.....	437
1000932.....	145	1001317.....	692	1001531.....	439
1000933.....	145	1001359.....	728	1001532.....	439
1000935.....	145	1001380.....	433	1001533.....	439
1000936.....	145	1001382.....	433	1001534.....	439
1000957.....	155, 277	1001390.....	433	1001536.....	439
		1001392.....	433	1001537.....	439
1001000		1001395.....	433	1001538.....	439
1001015.....	406, 710			1001539.....	439
1001016.....	406, 710	1001400		1001542.....	151, 437, 439, 473
1001017.....	406, 710	1001400.....	143	1001574.....	811
1001018.....	406, 710	1001403.....	143	1001575.....	811
1001019.....	336	1001406.....	143		
1001020.....	336	1001409.....	143	1001600	
		1001419.....	459	1001676.....	109
1001100		1001420.....	459	1001691.....	179
1001155.....	401	1001449.....	219	1001692.....	179
1001156.....	401	1001450.....	219		
1001165.....	405, 713	1001451.....	218	1001700	
1001166.....	405, 713	1001452.....	218	1001701.....	170
1001167.....	405, 713	1001453.....	218		
1001168.....	405, 713	1001454.....	218	1001800	
1001169.....	405, 713	1001460.....	108	1001818.....	151, 473
1001170.....	405, 713	1001461.....	108	1001819.....	151, 473
1001171.....	405, 713	1001462.....	108	1001820.....	151
1001172.....	405, 713	1001463.....	108	1001821.....	151

1001823.....	527	1001968.....	474	1002102.....	420, 706
1001824.....	527	1001969.....	642	1002103.....	420, 706
1001855.....	690	1001970.....	642	1002110.....	480
1001856.....	690	1001978.....	361	1002111.....	480
1001861.....	485	1001980.....	350	1002113.....	480
1001862.....	483	1001981.....	350	1002116.....	229
1001863.....	483	1001982.....	350	1002117.....	228
1001864.....	483	1001989.....	361	1002118.....	228
1001865.....	458	1001990.....	361	1002119.....	228
1001866.....	458	1001991.....	361	1002140.....	225
1001868.....	478	1001992.....	361	1002146.....	109
1001869.....	478	1001993.....	361	1002147.....	214
1001870.....	478	1001994.....	350	1002148.....	214
1001871.....	453	1001995.....	350	1002149.....	214
1001872.....	453	1001996.....	350	1002151.....	465
1001877.....	134, 258	1001999.....	545	1002152.....	465
1001878.....	135, 259			1002153.....	465
1001879.....	135, 259	1002000		1002163.....	151
1001880.....	135, 259	1002000.....	545	1002164.....	151
1001881.....	134, 258	1002001.....	545	1002165.....	151
1001882.....	134, 258	1002002.....	658	1002168.....	150
1001883.....	134, 258	1002003.....	269	1002169.....	159
1001884.....	134, 258	1002004.....	266	1002170.....	158
1001885.....	134, 258	1002005.....	266	1002171.....	159
1001886.....	134, 258	1002006.....	266	1002172.....	158
1001887.....	134, 258	1002008.....	269	1002188.....	716
1001888.....	134, 258	1002010.....	266	1002190.....	235
1001889.....	136, 260	1002011.....	266	1002191.....	235
1001890.....	137, 261	1002012.....	266	1002192.....	235
1001891.....	137, 261	1002013.....	266	1002198.....	581
1001892.....	137, 261	1002015.....	266		
1001893.....	136, 260	1002018.....	644	1002200	
1001894.....	136, 260	1002020.....	326	1002200.....	581
1001895.....	136, 260	1002021.....	326	1002201.....	601
1001896.....	136, 260	1002022.....	326	1002203.....	601
1001897.....	136, 260	1002023.....	304	1002215.....	274, 308
1001898.....	136, 260	1002024.....	304	1002216.....	274
1001899.....	136, 260	1002025.....	304	1002217.....	154
		1002029.....	312	1002218.....	777, 794
1001900		1002030.....	312	1002220.....	777, 794
1001900.....	136, 260	1002032.....	622	1002221.....	777, 794
1001901.....	414	1002033.....	622	1002228.....	237
1001902.....	415	1002034.....	622	1002229.....	237
1001903.....	415	1002035.....	686	1002238.....	191
1001904.....	415	1002045.....	173	1002239.....	208
1001905.....	416	1002046.....	173	1002240.....	208
1001906.....	416	1002047.....	175	1002264.....	151
1001907.....	416	1002051.....	289	1002265.....	151
1001908.....	417	1002052.....	289		
1001930.....	404, 711	1002069.....	639	1002400	
1001931.....	404, 711	1002070.....	639	1002402.....	629
1001937.....	597	1002075.....	329	1002403.....	629
1001939.....	285	1002076.....	329	1002404.....	111
1001950.....	135, 255, 295, 785	1002077.....	329	1002405.....	111
1001951.....	135, 255, 295, 785	1002098.....	420, 706	1002411.....	782
1001952.....	135, 255, 295, 785	1002099.....	420, 706	1002420.....	801
1001962.....	595			1002422.....	802
1001963.....	595	1002100		1002423.....	800
1001964.....	593	1002100.....	420, 706	1002424.....	800
1001965.....	593	1002101.....	420, 706	1002425.....	800

1002430.....	228	1002659.....	433	1002891.....	129
1002431.....	228	1002660.....	433	1002893.....	719
1002432.....	228	1002686.....	445	1002895.....	719
1002494.....	554	1002688.....	506	1002897.....	719
		1002689.....	506	1002898.....	719
1002500		1002690.....	506	1002899.....	719
1002503.....	643	1002691.....	793		
1002504.....	643	1002692.....	793	1002900	
1002505.....	643	1002693.....	793	1002900.....	655
1002558.....	150	1002694.....	506	1002902.....	655
1002562.....	150	1002695.....	506	1002903.....	683
1002563.....	150	1002696.....	506	1002904.....	682
1002564.....	150	1002697.....	501	1002905.....	665
1002583.....	112	1002698.....	501	1002906.....	516
1002584.....	318	1002699.....	501	1002907.....	516
1002585.....	318			1002909.....	120, 770
1002591.....	375	1002700		1002910.....	120, 770
1002592.....	375	1002700.....	501	1002911.....	120, 770
1002594.....	375	1002701.....	501	1002912.....	120, 770
1002596.....	375	1002702.....	501	1002913.....	119, 770
		1002703.....	501	1002914.....	119, 770
1002600		1002704.....	501	1002915.....	294, 771
1002602.....	500	1002705.....	501	1002917.....	294, 771
1002603.....	500	1002785.....	794	1002918.....	294, 771
1002604.....	500	1002791.....	797	1002919.....	294, 771
1002605.....	655	1002792.....	798	1002922.....	413
1002606.....	655			1002925.....	210
1002607.....	228	1002800		1002926.....	210
1002608.....	228	1002803.....	389, 390, 798	1002927.....	210
1002610.....	470	1002842.....	197	1002928.....	197
1002611.....	470	1002843.....	197	1002929.....	197
1002612.....	470	1002844.....	197	1002930.....	197
1002631.....	431	1002845.....	433, 437, 467	1002931.....	217
1002632.....	431	1002853.....	611, 615, 657, 685	1002932.....	217
1002633.....	431	1002854.....	484	1002933.....	217
1002634.....	431	1002855.....	220	1002934.....	287
1002635.....	431	1002856.....	220	1002935.....	287
1002636.....	431	1002858.....	139, 295, 785	1002936.....	287
1002637.....	433	1002859.....	222	1002937.....	160
1002638.....	433	1002860.....	245	1002938.....	160
1002639.....	433	1002861.....	504	1002939.....	160
1002640.....	433	1002862.....	504	1002940.....	330
1002641.....	433	1002863.....	504	1002941.....	330
1002642.....	433	1002864.....	505	1002942.....	221
1002643.....	433	1002865.....	505	1002943.....	221
1002644.....	433	1002866.....	505	1002944.....	279
1002645.....	433	1002867.....	666	1002945.....	279
1002646.....	433	1002868.....	648	1002946.....	156
1002647.....	433	1002869.....	648	1002947.....	156
1002648.....	433	1002870.....	540	1002949.....	169
1002649.....	433	1002871.....	540	1002950.....	169
1002650.....	433	1002873.....	474	1002952.....	640
1002651.....	433	1002874.....	474	1002953.....	640
1002652.....	433	1002875.....	474	1002954.....	640
1002653.....	433	1002876.....	445	1002955.....	640
1002654.....	433	1002877.....	445	1002956.....	575
1002655.....	433	1002878.....	445	1002957.....	575
1002656.....	433	1002882.....	138, 261	1002958.....	575
1002657.....	433	1002884.....	666	1002959.....	575
1002658.....	433	1002890.....	129	1002960.....	244

1002961.....	244	1003035.....	219	1003289.....	270
1002962.....	207	1003040.....	263	1003290.....	270
1002964.....	207	1003041.....	263	1003299.....	384
1002965.....	287	1003042.....	263		
1002967.....	284	1003043.....	263	1003300	
1002968.....	284	1003044.....	141	1003300.....	384
1002969.....	300	1003045.....	141	1003301.....	384
1002970.....	300	1003046.....	141	1003302.....	384
1002971.....	300	1003047.....	141	1003303.....	384
1002973.....	300	1003048.....	140	1003304.....	384
1002974.....	300	1003049.....	140	1003305.....	385
1002975.....	300	1003050.....	140	1003306.....	385
1002976.....	300	1003051.....	140	1003307.....	386
1002977.....	300	1003052.....	263	1003308.....	386
1002978.....	300	1003053.....	263	1003309.....	387
1002979.....	410	1003054.....	263	1003310.....	387
1002980.....	410	1003055.....	263	1003311.....	386
1002981.....	410	1003057.....	357	1003312.....	386
1002982.....	413	1003058.....	358	1003313.....	387
1002983.....	413	1003059.....	358	1003314.....	387
1002984.....	413	1003060.....	358	1003316.....	204
1002985.....	245	1003061.....	357	1003317.....	204
1002986.....	245	1003062.....	359		
1002987.....	245	1003063.....	359	1003400	
1002989.....	650	1003064.....	359	1003416.....	615
1002990.....	650	1003065.....	358	1003417.....	615
1002991.....	576	1003066.....	358	1003418.....	616
1002992.....	576	1003067.....	358	1003419.....	616
1002993.....	211	1003068.....	359	1003420.....	672
1002994.....	139, 295, 783, 785	1003069.....	359	1003421.....	672
1002995.....	783	1003070.....	359	1003422.....	611
		1003073.....	419	1003423.....	611
1003000		1003074.....	419	1003424.....	612
1003001.....	578	1003083.....	419	1003425.....	612
1003004.....	162	1003084.....	419	1003426.....	671
1003005.....	162			1003427.....	671
1003006.....	162	1003100		1003428.....	212
1003007.....	162	1003101.....	811	1003429.....	212
1003008.....	389	1003104.....	796	1003430.....	212
1003009.....	389	1003105.....	796	1003431.....	212
1003010.....	389	1003106.....	794	1003432.....	165
1003011.....	390	1003107.....	179	1003435.....	157
1003012.....	390			1003436.....	157
1003013.....	390	1003200		1003437.....	615
1003014.....	320	1003254.....	797	1003438.....	616
1003015.....	320	1003275.....	148	1003439.....	672
1003016.....	320	1003276.....	148	1003440.....	611
1003017.....	319	1003277.....	148	1003441.....	612
1003018.....	319	1003278.....	148	1003442.....	671
1003019.....	319	1003279.....	149	1003443.....	163
1003022.....	209, 785	1003280.....	149	1003444.....	163
1003023.....	209, 785	1003281.....	149	1003447.....	591
1003028.....	106	1003282.....	149	1003448.....	591
1003029.....	106	1003283.....	270	1003449.....	689
1003030.....	104	1003284.....	270	1003450.....	689
1003031.....	104	1003285.....	270	1003451.....	689
1003032.....	105	1003286.....	270	1003452.....	689
1003033.....	105	1003287.....	270	1003453.....	639
1003034.....	219	1003288.....	270	1003454.....	639

1003455.....	226	1004685.....	433	1004746.....	151
1003456.....	226	1004686.....	448	1004747.....	631
1003457.....	226	1004687.....	448	1004748.....	631
1003458.....	226	1004688.....	448	1004749.....	512
1003459.....	227	1004689.....	448	1004750.....	512
1003460.....	227	1004690.....	441, 773	1004751.....	512
1003466.....	410	1004691.....	441, 773	1004757.....	592
1003467.....	198	1004692.....	441, 773	1004759.....	121
1003468.....	198	1004693.....	441, 773	1004760.....	121
1003479.....	671, 672	1004694.....	389	1004761.....	121
		1004695.....	389	1004762.....	121
1003500		1004696.....	389	1004763.....	122
1003506.....	241	1004697.....	390	1004764.....	122
1003507.....	241	1004698.....	390	1004765.....	123
1003508.....	241	1004699.....	390	1004766.....	123
1003518.....	686			1004767.....	123
1003519.....	686	1004700		1004768.....	123
1003530.....	142	1004700.....	320	1004769.....	443, 772
1003532.....	142	1004701.....	320	1004770.....	443, 772
1003535.....	538	1004702.....	320	1004771.....	443, 772
1003536.....	538	1004703.....	319	1004772.....	443, 772
1003537.....	538	1004704.....	319	1004773.....	107, 155
1003538.....	539	1004705.....	319	1004774.....	107, 155, 277
1003539.....	656	1004706.....	224	1004775.....	107, 155, 277
		1004707.....	224	1004776.....	797
1004600		1004708.....	754	1004777.....	797
1004649.....	666	1004709.....	754	1004780.....	800
1004650.....	636	1004710.....	754	1004781.....	801
1004651.....	636	1004712.....	755	1004782.....	802
1004652.....	601	1004713.....	755	1004783.....	467
1004653.....	684	1004714.....	755	1004784.....	467
1004654.....	541	1004716.....	756	1004785.....	467
1004655.....	541	1004717.....	756		
1004657.....	185	1004718.....	756	1004800	
1004660.....	185	1004719.....	756	1004889.....	738
1004661.....	185	1004720.....	757	1004890.....	738
1004662.....	185	1004721.....	757	1004893.....	739
1004663.....	185	1004722.....	758	1004894.....	739
1004664.....	296	1004723.....	758	1004895.....	739
1004665.....	296	1004725.....	759	1004896.....	747
1004666.....	280	1004726.....	762	1004897.....	747
1004667.....	280	1004727.....	760	1004898.....	747
1004668.....	396	1004729.....	233	1004899.....	747
1004669.....	396	1004730.....	233		
1004670.....	188	1004731.....	233	1004900	
1004671.....	188	1004732.....	193	1004900.....	748
1004672.....	147	1004733.....	190	1004901.....	748
1004673.....	147	1004734.....	761	1004902.....	749
1004674.....	151	1004735.....	761	1004903.....	749
1004675.....	151	1004736.....	761	1004904.....	749
1004676.....	151	1004737.....	763	1004905.....	747
1004677.....	676	1004738.....	215	1004906.....	747
1004678.....	637	1004739.....	215	1004907.....	747
1004679.....	637	1004740.....	206	1004908.....	747
1004680.....	542	1004741.....	206	1004909.....	748
1004681.....	542	1004742.....	206	1004910.....	748
1004682.....	214	1004743.....	206	1004911.....	749
1004683.....	214	1004744.....	151	1004912.....	748
1004684.....	433	1004745.....	151	1004913.....	748

1004914.....	748	1005100		1005294.....	814
1004915.....	748	1005125.....	635	1005295.....	814
1004916.....	748	1005126.....	635	1005296.....	814
1004917.....	748	1005148.....	624		
1004918.....	741	1005149.....	624	1005300	
1004919.....	741	1005150.....	624	1005301.....	815
1004920.....	741	1005151.....	624	1005302.....	815
1004921.....	741	1005153.....	624	1005303.....	815
1004922.....	741	1005154.....	624	1005304.....	815
1004923.....	741	1005155.....	624	1005305.....	816
1004924.....	742	1005156.....	624	1005306.....	817
1004925.....	742	1005157.....	624	1005307.....	816
1004926.....	742	1005177.....	121	1005308.....	816
1004927.....	743	1005178.....	123	1005309.....	816
1004928.....	743			1005310.....	816
1004929.....	743	1005200		1005311.....	812
1004930.....	743	1005201.....	629	1005312.....	812
1004931.....	743	1005202.....	675	1005313.....	813
1004932.....	745	1005205.....	611, 615, 672	1005314.....	813
1004933.....	471	1005206.....	611, 615, 672	1005315.....	813
1004934.....	471	1005207.....	611, 615, 672	1005316.....	813
1004935.....	471	1005214.....	176	1005317.....	815
1004936.....	471	1005215.....	176	1005318.....	815
1004937.....	431	1005216.....	176	1005380.....	795
1004938.....	431	1005217.....	176	1005381.....	795
1004939.....	433	1005218.....	176	1005382.....	795
1004940.....	433	1005241.....	795	1005383.....	796
1004941.....	433	1005262.....	611, 615, 672	1005384.....	801
1004942.....	433	1005263.....	611, 615, 672	1005387.....	799
1004943.....	433	1005265.....	816	1005390.....	101
1004944.....	433	1005268.....	816	1005391.....	101
1004957.....	666	1005269.....	810	1005392.....	100
1004969.....	185	1005271.....	810	1005394.....	100
1004970.....	113	1005272.....	810	1005395.....	146, 774
1004971.....	232	1005273.....	812	1005396.....	146, 774
1004972.....	812	1005274.....	814	1005397.....	440
1004973.....	812	1005275.....	814	1005399.....	440
1004974.....	812	1005276.....	814		
		1005277.....	814	1005400	
1005000		1005278.....	814	1005400.....	450
1005075.....	813	1005279.....	814	1005401.....	450
1005076.....	813	1005280.....	814	1005402.....	450
1005077.....	813	1005281.....	814	1005407.....	349
1005078.....	813	1005282.....	814	1005408.....	349
1005079.....	813	1005283.....	814	1005409.....	349
1005080.....	813	1005284.....	810	1005410.....	349
1005081.....	813	1005285.....	810	1005415.....	349
1005082.....	813	1005286.....	810	1005416.....	349
1005083.....	813	1005287.....	810	1005417.....	349
1005085.....	322	1005288.....	810	1005418.....	349
1005086.....	322	1005289.....	816	1005423.....	349
1005087.....	323	1005290.....	816	1005424.....	349
1005088.....	323	1005291.....	814	1005425.....	349
1005089.....	690	1005292.....	814	1005426.....	349
1005090.....	690	1005293.....	814	1005435.....	373

1005436.....	373	1006161.....	224
1005439.....	514	1006162.....	224
1005440.....	515	1006171.....	727
1005441.....	579	1006172.....	727
1005442.....	522	1006173.....	727
1005443.....	632	1006174.....	727
1005444.....	795	1006175.....	727
1005445.....	795	1006176.....	727
1005446.....	799	1006178.....	626
1005449.....	798	1006179.....	626
1005496.....	800	1006180.....	518
1005497.....	799	1006181.....	518
		1006182.....	518
1006100		1006183.....	627
1006104.....	730	1006184.....	521
1006105.....	730	1006185.....	118
1006106.....	717	1006186.....	118
1006107.....	717	1006187.....	118
1006120.....	802	1006188.....	118
1006121.....	371	1006189.....	118
1006122.....	371	1006190.....	118
1006123.....	334	1006191.....	589
1006124.....	334	1006192.....	589
1006125.....	334	1006193.....	589
1006126.....	334		
1006127.....	334	1006200	
1006128.....	334	1006202.....	799
1006133.....	797		
1006134.....	797		
1006135.....	807		
1006136.....	807		
1006137.....	807		
1006138.....	807		
1006139.....	807		
1006140.....	807		
1006141.....	807		
1006142.....	807		
1006143.....	807		
1006144.....	807		
1006145.....	807		
1006146.....	807		
1006147.....	807		
1006148.....	807		
1006149.....	807		
1006150.....	807		
1006151.....	807		
1006152.....	807		
1006153.....	807		
1006154.....	807		
1006155.....	472		
1006156.....	472		
1006157.....	444		
1006158.....	444		
1006159.....	166, 444, 472		
1006160.....	166, 444, 472		







1005739 69

SINGLE-CIRCUIT

SINGLE-CIRCUIT MOUNTING TRACKS ...	528
SINGLE-CIRCUIT MOUNTING TRACKS	
accessories.....	467
SINGLE-CIRCUIT RECESSED TRACK.....	469
SINGLE-CIRCUIT RECESSED TRACK	
accessories.....	469

3-CIRCUIT

EUTRAC®

EUTRAC® 3-CIRCUIT MOUNTING	
TRACK.....	435
EUTRAC® 3-CIRCUIT MOUNTING	
TRACK accessories	437
EUTRAC® 3-CIRCUIT RECESSED	
TRACK.....	439
EUTRAC® 3-CIRCUIT RECESSED	
TRACK accessories	439

S-TRACK

S-TRACK 3-CIRCUIT MOUNTING	
TRACK DALI.....	431
S-TRACK 3-CIRCUIT MOUNTING	
TRACK DALI accessories	433

A

ABRIDOR 60 Pole.....	576
ABRIDOR 100 Pole.....	576
ABRIDOR SENSOR WL.....	650
ABRIDOR WL.....	650
ACCANTO CL, E27.....	279
ACCANTO PD, E27.....	156
ACCANTO WL, E27.....	221

ACCESSORIES

1-10V dimmer 10W.....	792
Cable clamp	803
Cable extension	804
Compensation module	794
Ceiling hook.....	803
Connection box 5-pole.....	805
Connection box IP68, 3-pole.....	805
Connector strip 3 outlets.....	804
DALI CONTROLLER 24V DC.....	794
DALI INTERFACE 1-10V + on/off.....	777, 794
DALI UNIVERSAL DIMMER 10-300W.....	777, 794
DALI UNIVERSAL DIMMER 3-25W	777, 794
Double-sided tape	804
GLENOS® Ceiling rosette	803
GU10 fitting	804
GU10 fitting with connection box	
and quick clamp	804
LED power supply 60W DALI, 24V,	
2-channel	797
LED driver 1000mA 39W	
incl. strain relief	799
LED driver 100mA 40W	799
LED driver 100mA 60W	
incl. strain relief	802
LED driver 1050mA 30W	
incl. strain relief	799
LED driver 200mA 10W	
incl. strain relief	800
LED driver 200mA 6-8,4W	
incl. strain relief	797
LED driver 250-700mA 20W	
incl. strain relief	800
LED driver 250-700mA 40W	
incl. strain relief	800
LED driver 250mA 10 W.....	800
LED driver 320mA 3W	
incl. strain relief	800
LED driver 350mA 10W.....	798
LED driver 350mA 15W.....	798
LED driver 350mA 15W	
incl. strain relief	801

LED driver 350mA 20W.....	798
LED driver 350mA 20W	
incl. strain relief	801
LED driver 350mA 3W.....	797
LED driver 350mA 3W	
incl. strain relief	801
LED driver 500/600/700mA 30W	
incl. strain relief	801
LED driver 500mA 10W	
incl. strain relief	801
LED driver 500mA 15W.....	798
LED driver 700-1500mA 50W	
incl. strain relief	800
LED driver 700/90/100mA 40W	
incl. strain relief	802
LED driver 700mA 10W.....	798
LED driver 700mA 20W dimmable	
incl. strain relief	799
LED driver 700mA 39W	
incl. strain relief	799
LED driver 700mA 3W	
incl. strain relief	801
LED driver 700mA 40W.....	799
LED driver 700mA 6W.....	798
LED driver 800/900/1050mA 40W	
incl. strain relief	802
LED driver DALI.....	797
LED power supply.....	797
LED power supply 100W DALI, 24V,	
2-channel	797
LED power supply 12V 100W	
incl. strain relief	797
LED power supply 12V 12W	
with strain relief	795
LED power supply 12V 15W.....	795
LED power supply 24V 12W	
with strain relief	795
LED power supply 24V 15W.....	795
LED power supply 24V 20W.....	795
LED power supply 24V 40W.....	795
LED power supply 24V 50W	
incl. strain relief	796
LED power supply 24V 60W.....	796
LED power supply 24V DC 100W	
with strain relief	796
LED power supply 24V DC 150W	796
LED power supply 24V DC 150W	
incl. strain relief	796
SLV VALETO® remote control,	
CCT/RGBW	783
SLV VALETO® Gateway	782
SLV VALETO® Wall-recessing dimmer.....	783
Stopper for wire rope	804
T-connector box 3-pole.....	805
TENSEO Transformer 12V AC 50VA	793
TENSEO Transformer 12V AC 105VA.....	793
TENSEO Transformer 12V AC 210VA	793
Textile cable 10m	803
Transformer 12V AC 10VA IP44	792
Transformer 12V AC 60VA	792
Transformer 12V AC 60VA IP44	792
Transformer 12V AC 150VA	792
Wire rope suspension.....	803

ADEGAN FL, E27.....	555
ADEGAN MANILA FL, E27	554
ADI EL	700
AINOS CW.....	688
AINOS CW SENSOR.....	688
AINOS CW SENSOR, square	689
AINOS CW, square	689
AKALO D83 EL, PHASE	407
ALPA CONE 100 Pole, E27	557
ALPA MUSHROOM 45 Pole, E27	557
ALPA MUSHROOM 75 Pole, E27	557
ALTRA DICE CL, QPAR51	274
ALTRA DICE CW, double, QPAR51... ..	274, 308
ALTRA DICE TRACK 1Ph., QPAR51	485
ALTRA DICE TRACK 3Ph., QPAR51	453
ANDREAS WL, QT-DE12.....	210

ANELA CL, PHASE	287
ANELA PD, PHASE	164
ANGOLUX SENSOR WL	642
ANGOLUX WL	642
ANILA EASYTEC® II, QPAR51.....	494
APONI 90 Pole, PHASE.....	558
APONI 120 Pole, PHASE.....	558
APONI WL, PHASE	658
ARLINA 60 WL.....	208
ARLINA 130 WL.....	208
ARROCK ARC Pole, QPAR51.....	535
ARROCK GRANITE 40 Pole,	
square, E27	534
ARROCK GRANITE 70 Pole,	
square, E27	534
ARROCK SLOT	537
ARROCK STONE 50 Pole.....	536
ARROCK STONE 75 Pole.....	536
ASMARA LV, QR-C51	502
ASSO 70 WL	200
ASSO 300 WL, PHASE	201
ASSO WL, PHASE	201
ASTINA CL, QPAR51	287
ASTINA PD, QPAR51	160
ASTINA STEEL WL, QPAR51.....	641
ASTINA UP/DOWN WL, QPAR51	217
ASTINA WL, QPAR51.....	641
ASTO CW, double, QPAR51	316
ASTO CW, quad, QPAR51.....	316
ASTO CW, single, QPAR51.....	316
ASTO CW, triple, QPAR51	316
ASTO TUBE CW, double, QPAR51	311
ASTO TUBE CW, single, QPAR51.....	311
ASTO TUBE CW, triple, QPAR51	311
AVO CW, double, QPAR51	315
AVO CW, quad, QPAR51.....	315
AVO CW, single, QPAR51.....	315
AVO CW, triple, QPAR51.....	315
AVO TRACK 1Ph., QPAR51.....	479
AVO TRACK 3Ph., QPAR51.....	459

B

BASKET WL, E27	211
BATO 35 CW, E27	333
BATO 45 CW, E27	288
BATTEN 120 CW	334
BATTEN 60 CW	334
BENA 120 CW.....	339
BENA 150 CW.....	339
BIG NAILS 50 POLE, E27	560
BIG NAILS 80 POLE, E27	560
BIG NAILS WL, E27	660
BIG NAUTILUS SP, round, QPAR51	593
BIG PLOT cover, 2er	728
BIG PLOT cover, 4er	728
BIG PLOT Module	728
BIG QUAD Up/Down WL.....	635
BIG QUAD WL	622, 633
BIG THEO CL	674
BIG THEO CL, QPAR111	674
BIG THEO UP/DOWN WL, QPAR111	619
BIG THEO WL.....	621
BIG THEO WL, QPAR111.....	621
BIMA 1Ph., double, QPAR51.....	482
BIMA 1Ph., single, QPAR51	482
BIMA 3Ph., double, QPAR51	456
BIMA 3Ph., single, QPAR51	456
BIMA EASYTEC® II, double, QPAR51	492
BIMA EASYTEC® II, single, QPAR51	492
BOOKAT Pole, PHASE	579
BOOKAT WL.....	632
BOX UP/DOWN WL, QT-DE12	652
BOX-L WL	686
BOX-L WL, E27	652
BRICK DOWNUNDER EL	703
BRICK DOWNUNDER EL, E14	703
BRICK EL, asymmetrical	702
BRICK EL, symmetrical	702
BRICK MESH EL, E14.....	702

BULAN CW, E14	691
BULAN GRID CW, E27	691

C

C-POL POLE, E27	566
C-POL WL, E27	659
CARISO WL, PHASE	203
CHROMBO WL, PHASE	204
COMET LED LV	506
COMET LV, QR-C51	506
CONE FL, E27	551
CONNECTED LED PANEL 595x595mm, UGR<19	418
CONNECTED LED PANEL 620x620mm, UGR<19	418
CONTONE® DL, round, rigid, PHASE	398
CONTONE® DL, round, adjustable, PHASE	398
COSMIC LV, QR-C51	503
COUPA FLEX WL	222
COUPA WL, QT14	222
CUBIX FL, QPAR51	551

D

DASAR®

DASAR® 70 EL, square, QPAR51	721
DASAR® 80 EL, round/square, QPAR51 ...	721
DASAR® 215 EL, round, E27	722
DASAR® 215 EL, round/square, QPAR111 ...	722
DASAR® 218 EL, QR111	722
DASAR® 255 EL	718
DASAR® 270 EL, asymmetrical	719
DASAR® 270 EL, symmetrical	719
DASAR® 370 EL, round	723
DASAR® 920 EL	718
DASAR® EXACT 116 EL, round/square, QPAR51	721
DASAR® FLAT 80 EL	716
DASAR® FLAT 120 EL	717
DASAR® PROJECTOR SP, 12/24V	598
DASAR® PROJECTOR SP, 230V	598

DEKLED EL	404
DELWA WL	647
DENA 30 WL, E14	211
DIO FLEX PLATE WL	228, 229
DIO FLEX PLATE WL QPAR51	228
DIRETO 60 WL, PHASE	206
DIRETO 90 WL, PHASE	206
DISPLAY ADL 50 QPAR51	245
DL 126 EL	394
DOLIX OUT EL, square, QPAR51	405, 713
DOLIX OUT EL, round, QPAR51	405, 713
DORISA 30	238
DORISA 50	239
DOWNUNDER OUT L EL	701
DOWNUNDER OUT M EL	701
DOWNUNDER OUT S EL	701
DOWNUNDER OUT WL, square	648
DOWNUNDER OUT WL, round	648
DOWNUNDER PUR 80 EL	412
DOWNUNDER PUR 150 EL	412
DURNO	504

E

EASYTEC® II

EASYTEC® II track	491
EASYTEC® II track, accessories	491

ENOLA

ENOLA B CL, QPAR51	281
ENOLA B CW, double, QPAR51	307
ENOLA B CW, single, QPAR51	307
ENOLA B PD, QPAR51	161, 481
ENOLA B TRACK 1Ph., QPAR51	480
ENOLA B WL, QPAR51	217
ENOLA C CL	281
ENOLA C CL, PHASE	281

ENOLA C POLE	580
ENOLA C TRACK 1Ph	480
ENOLA C TRACK 3Ph	459
ENOLA PD, E27	161
ENOLA ROUND S CL	671
ENOLA ROUND S WL, single	611
ENOLA ROUND L CL	671
ENOLA ROUND L WL, single	611
ENOLA ROUND M CL	671
ENOLA ROUND M WL, single	611
ENOLA SQUARE S CL	672
ENOLA SQUARE S WL, single	615
ENOLA SQUARE M CL	672
ENOLA SQUARE M WL, single	615
ENOLA SQUARE L CL	672
ENOLA SQUARE L WL, single	615
ENOLA accessories	617

ESKINA 30 Pole	516
ESKINA 80 Pole	516
ESKINA D display, PHASE	665
ESKINA FRAME 45 Pole, single	512
ESKINA FRAME 75 Pole, double	512
ESKINA FRAME 75 Pole, single	512
ESKINA FRAME 125 Pole, double	514
ESKINA FRAME 175 Pole, double	515
ESKINA FRAME WL	631
ESKINA FRAME WL, double	631
ESKINA SPOT CW, PHASE	683
ESKINA SPOT SENSOR CW, PHASE	682
EURO CUBE 3Ph	451
EURO SPOT TRACK 1Ph., QPAR51	485
EURO SPOT TRACK 3Ph., QPAR111	452
EURO SPOT TRACK 3Ph., QPAR51	452

F

F-POL POLE, E27	567
F-POL WL, E27	659

FENDA

FENDA 15 cm, round	107, 155
FENDA 30 cm, round	107, 155, 277
FENDA 45 cm, round	107, 155, 277
FENDA BOW BASIS FL, E27	106
FENDA ceiling rosette, E27	276
FENDA FL, E27	104, 105
FENDA glass screen	154
FENDA half shade	218
FENDA Ø 20 cm, round	218
FENDA Ø 40 cm, round	107, 154
FENDA Ø 70 cm, round	107, 155, 277
FENDA PD, E27	154
FENDA TL, E27	104, 105
FENDA WL, Basis, E27	218, 219
FENDA WL, E27	219

FERA 25 CL	285
FERA 25 CL, DALI	284
FITU CUBE WL, E27	215
FITU CW, E27	318
FITU FL, E27	109
FITU MIX & MATCH accessories	151
FITU PD, E27	150
FITU TL, E27	109
FITU wall bracket	214
FITU WL, E27	214
FLAC BEAM® SP	591
FLATT 100 POLE	575
FLATT 65 POLE	575
FLATT SENSOR WL	640
FLATT WL	640
FLOODI L SP	589
FLOODI M SP	589
FLOODI S SP	589
FORCHINI 50 PD, E27	170
FORCHINI 70 PD, E27	170
FORCHINI M 40 PD, E27	171
FORCHINI M 40 TRACK 1Ph., E27	477
FORCHINI M 40 TRACK 3Ph., PD, E27	447
FORCHINI M 50 PD, E27	171

FRAME BASIC RL	409
FRAME BASIC RL, HV	409
FRAME BASIC SET RL	408
FRAME CURVE EL	408
FRAME CURVE EL, HV	408

G

GALEN 120 SP	591
GALEN 60 SP	591
GIMBLE OUT EL	724
GLASSA CW, square, E27	332
GLENOS PD, 1m, 1-10V	143
GLENOS PD, 2m, 1-10V	143
GLENOS® 60 WL	241
GLOO PURE 27 Pole, E27	545
GLOO PURE 44 Pole, E27	545
GLOO PURE 70 Pole, E27	545
GLOO PURE WL, E27	658
GRAFIT 30 Pole, E27	521
GRAFIT 30 Pole, round, E27	518
GRAFIT 60 Pole, E27	521
GRAFIT 60 Pole, round, E27	518
GRAFIT 90 Pole, E27	521
GRAFIT 90 Pole, round, E27	518
GRAFIT SENSOR WL, square, E27	627
GRAFIT SENSOR WL, round, E27	626
GRAFIT WL, square, E27	627
GRAFIT WL, round, E27	626

GRAZIA LED strips

GRAZIA IP FLEXSTRIP, 24V	761
GRAZIA IP FLEXSTRIP, RGBW, 24V	763
GRAZIA IP FLEXSTRIP, Tunable white, 24V	762
GRAZIA PRO FLEXSTRIP, 24V	756
GRAZIA PRO FLEXSTRIP, RGBW, 24V	760
GRAZIA PRO FLEXSTRIP, Tunable white, 24V	759
GRAZIA PRO MAX FLEXSTRIP, 24V	757, 758

GRAZIA profiles

GRAZIA 10 Mounting profile, flat	735
GRAZIA 10 Mounting profile, standard	735
GRAZIA 10 Installation profile	735
GRAZIA 10 Accessories	736, 737
GRAZIA 10 EDGE Mounting profile	738
GRAZIA 10 EDGE Accessories	739
GRAZIA 20 Mounting profile, Flat	741
GRAZIA 20 Mounting profile, standard	741
GRAZIA 20 Installation profile	742
GRAZIA 20 Accessories	743, 744, 745
GRAZIA 60 Mounting profile	747
GRAZIA 60 Installation profile	747
GRAZIA 60 Accessories	748, 749

H

H-LIGHT DL, oval, PHASE	399
H-LIGHT DL, round, PHASE	399
H-POL 30 Pole	572
H-POL 60 Pole	572
H-POL TWIN 30 Pole	573
H-POL TWIN 60 Pole	573
HELIA 30 PD	158
HELIA 30 PD, PHASE	158
HELIA 40 PD	159
HELIA 40 PD, PHASE	159
HELIA 50 TRACK 1Ph	483
HELIA 50 TRACK 3Ph	457
HELIA AMBIENT 35 PD	157
HELIA AMBIENT 35 PD, PHASE	157
HELIA CW, double, PHASE	299, 685
HELIA CW, single, PHASE	299, 685
HELIA EL	400
HELIA Pole, double, PHASE	581, 582
HELIA Pole, single, PHASE	581, 582
HELIA SPOT S SP, single, PHASE	599
HELIA SPOT L SP, single, PHASE	599
HORN DL, double, QPAR51	371
HORN DL, GU10, blower door tested	373

HORN DL, single, asymmetrical, QPAR51	371
HORN DL, single, QPAR51	370, 372
HORN EL, single, QPAR51	372
HORN MAGNA	375
HORN MINI EL	370
HORN-T EL, QPAR111	374

I

I-PENDANT PRO PD, 1195x295mm, DALI ..	140
IMPERVA 120 CW	692
IMPERVA 150 CW	692
INDA CW, QPAR51	308
IPERI 50 Pole	577
IPERI WL	662

K

KADUX EL, double, 1-10V	380
KADUX EL, double, PHASE	379
KADUX EL, double, QPAR111	378
KADUX EL, double, QPAR51	376
KADUX EL, single, 1-10V	380
KADUX EL, single, PHASE	379
KADUX EL, single, QPAR111	378
KADUX EL, single, QPAR51	376
KADUX EL, triple, PHASE	379
KADUX EL, triple, QPAR51	376
KALU CW, double, PHASE	303
KALU CW, double, QPAR111	304
KALU CW, quad, PHASE	303
KALU CW, quad, QPAR111	304
KALU CW, single, PHASE	303
KALU CW, single, QPAR111	304
KALU CW, triple, PHASE	303
KALU CW, triple, QPAR111	304
KALU TRACK 1Ph., PHASE	484
KALU TRACK 1Ph., QPAR111	484
KALU TRACK 3Ph., PHASE	454
KALU TRACK 3Ph., QPAR111	454
KALU TRACK 3Ph., QR111	454
KAMUELA ECO EL, round, PHASE ..	406, 710
KANO EASYTEC® II, QPAR51	492
KARDAMOD CL, double, square, QPAR111	275
KARDAMOD CL, single, square, QPAR111	275
KARPO 30 CW, single 296	
KARPO 30 CW, single, PHASE	296
KARPO 30 EL	400
KARPO 30 WL, single	225
KARPO FL	108
KARPO GOOSE WL	224
KARPO MAGN CW, single, PHASE	224
KARPO TL	108
KARPO WL	225
KENKUA SPOT WL, E27	220
KENKUA WL, E27	220
KERAS ELT WL, E27	661
KINI EL, PHASE	407, 709

L

L-LINE 120 WL	242
L-LINE 60 WL	242
L-LINE OUT 30 FL, vertical	538
L-LINE OUT 50 Pole, horizontal	538
L-LINE OUT 60 FL, vertical	538
L-LINE OUT 80 Pole, horizontal	539
L-LINE OUT WL	656
LED PANEL 600x600mm	419
LED PANEL 620x620mm	419
LIGHT EYE® 150 3Ph., PD, QPAR111	446, 476
LIGHT EYE® 150 EASYTEC® II, PD, QPAR111	495
LIGHT EYE® 150 PD, QPAR111	172
LIGHT EYE® 150 TRACK 3Ph., QPAR111 ..	446
LIGHT EYE® 150 TRACK EASYTEC® II, QPAR111	495

LIGHT EYE® 90 1Ph., QPAR51	476
LIGHT EYE® 90 PD, GU10	172

LIGHTBULB

LED A60 E27	815
LED A60 E27, Mirrorhead, chrome	816
LED A60 E27, RGBW, smart	815
LED A60 E27, tunable 2700-6500K, smart	815
LED C35 E14	810
LED G125 E27, Mirrorhead, chrome	817
LED G53	811
LED G95 E27	816
LED QPAR 111 GU10	814
LED QPAR111 GU10, RGBW, smart	813
LED QPAR111 GU10, RGBW, smart	813
LED QPAR111 GU10, tunable 2700-6500K, smart	813
LED QPAR51 GU10	812, 813
LED QPAR51 GU10, RGBW, smart	812
LED QPAR51 GU10, tunable 2700-6500K, smart	812
LED QR51 GU5,3	811
LED QT-DE12 R7S, 118 mm	810
LED QT-DE12 R7S, 78 mm	810
LED QT14 G9	810
LED SPIKE SP	601
LED SPOT SP	666
LED ST58 E27	816
LED ST64 E27	816
LED T32 Filament GU10	811
LED T38 E27	816
LED T45 E27	816
LED TCR-TSE GX53	810

LIGHTPOINT EL	401
LIPA CW, PHASE	690
LIPSY® 30 CW, Dome	326
LIPSY® 30 CW, Drum	329
LIPSY® 40 CW, Dome	326
LIPSY® 40 CW, Drum	329
LIPSY® 40 CW, Drum, DALI	330
LIPSY® 50 CW, Dome	326
LIPSY® 50 CW, Drum	329
LIPSY® 50 CW, Drum, DALI	330
LISENNE 40 Pole, E27	553
LISENNE 70 Pole, E27	553
LISENNE PD, E27	164
LISENNE WL, E27	213
LOGS 40 Pole	517
LOGS 70 Pole	517
LOGS IN L WL, PHASE	197
LOGS IN WL	196
LOGS IN WL, PHASE	196
LOGS WL	652
LONG GRILL CW	336

M

MAGANDA TL	113
MAGANDA WL	232
MALANG CW	139, 295
MANA 40 Shade, round	185
MANA 60 Shade, round	185
MANA BASE round	185
MANA BASE WL, round, PHASE	185
MANA OUT WL, PHASE	655
MANA Shade	186, 187
MANA WL, Basis	187
MANA WL, Basis, PHASE	186, 187
MARONA WL, PHASE	288
MARYLIN 40/60/90 WL	235
MECANICA PLUS FL	111
MECANICA PLUS TL	111

MEDO

MEDO 30 AMBIENT CW, DALI	136, 260
MEDO 30 AMBIENT CW, PHASE	134, 258
MEDO 30 CL, 1-10V	130, 254
MEDO 30 CL, PHASE	133, 257

MEDO 30 EL, Mounting frame	416
MEDO 30 EL, Frameless	414
MEDO 40 AMBIENT CW, DALI	136, 260
MEDO 40 AMBIENT CW, PHASE	134, 258
MEDO 40 CL, 1-10V	131, 255
MEDO 40 CL, PHASE	133, 257
MEDO 40 EL, Mounting frame	416
MEDO 40 EL, Frameless	415
MEDO 60 AMBIENT CW, DALI	136, 260
MEDO 60 AMBIENT CW, PHASE	134, 258
MEDO 60 CL, 1-10V	131, 255
MEDO 60 CL, square, 1-10V	132, 256
MEDO 60 CL, square, DALI	138, 261
MEDO 60 EL, Mounting frame	416
MEDO 60 EL, Frameless	415
MEDO 90 AMBIENT CL, DALI	137, 261
MEDO 90 AMBIENT CL, PHASE	135, 259
MEDO 90 CL, 1-10V	131, 255
MEDO 90 EL, Mounting frame	417
MEDO 90 EL, Frameless	415
MEDO RING 60 PD, 1-10V	128
MEDO RING 60 PD, DALI	129
MEDO RING 90 PD, 1-10V	128

MELAN CW, E27	332
MERADO FLOOD WL, PHASE	231
MERIDIAN BOX SENSOR WL, E27	630
MERIDIAN BOX WL, E27	630
MIBO UP/DOWN WL, QT14	237
MILANDOS 4 DL	349
MILANDOS 6 DL	349
MILANDOS 8 DL	349
MOBALA EL	413
MOLAT CL, E27	677
MOLAT PD, E27	552
MOLAT Pole, E27	552
MOLAT WL, E27	657
MYRA CW, single, QPAR51	666
MYRA DISPLAY WL, curved, QPAR51	665
MYRA SPOT Double, GU10	583
MYRA UP/DOWN WL, QPAR51	644
MYRA WL, double, QPAR51	686

N

NAGY 75 CL, QPAR51	287
NAUTILUS 10 SP, square	597
NAUTILUS 10 SP, round, QPAR51	593, 594
NAUTILUS 10 SPOT LED SP	595
NAUTILUS 10 SPOT SP, QPAR51	595
NAUTILUS SP, QR-C51	595
NAUTILUS WL QPAR51	666
NEPRO DISPLAY QT-DE12	245
NEW FLAT WL, RGB-W	209

NEW TRIA

NEW TRIA 45 DL, round	356
NEW TRIA 45 Single, square, CS	356
NEW TRIA 68 DL, square	357, 359
NEW TRIA 68 DL, square, PHASE	359, 361
NEW TRIA 68 DL, square, QPAR51	350
NEW TRIA 68 DL, round	357, 358
NEW TRIA 68 DL, round, PHASE	360, 361
NEW TRIA 68 DL, round, QPAR51	350
NEW TRIA 77 DL, square	362, 363
NEW TRIA 77 DL, round	362
NEW TRIA 78 DL, square, QPAR51 ..	352, 353
NEW TRIA 78 DL, round, QPAR51	352
NEW TRIA 78 XL DL, square, QPAR51 ..	351
NEW TRIA 78 XL DL, round, QPAR51 ..	351
NEW TRIA 110 DL, square, PHASE ..	366, 367
NEW TRIA 110 DL, round, PHASE	366
NEW TRIA 150 DL, square, 1-10V	369
NEW TRIA 150 DL, square, QPAR111 ..	355
NEW TRIA 150 DL, round, 1-10V	368
NEW TRIA 150 DL, round, QPAR111 ..	355
NEW TRIA 155 DL, double	364, 365
NEW TRIA 155 DL, double, QPAR51 ..	354
NEW TRIA 300 DL, double, QPAR111 ..	355

NOBLO CW, double, PHASE	300
NOBLO CW, PHASE	300
NOBLO CW, single, PHASE	300
NOBLO CW, triple, PHASE	300
NOBLO SPOT 1Ph.	483
NOBLO SPOT 1Ph., Triple Track Set	470
NOBLO SPOT 3-circuit	458
NOBLO SPOT LV, Rope Track	506
NOTAPO L RL	410
NOTAPO S RL	410
NOYA PD, PHASE	142

NUMINOS®

NUMINOS® accessories	58-61
NUMINOS® 3Ph.	62-71
NUMINOS® CL	74-87
NUMINOS® CW	72-73
NUMINOS® DL	28-61
NUMINOS® PD	88-95

O

OCCULDAS 13 DL, indirect, PHASE	273
OCCULDAS 14 EL, indirect, PHASE	397
OCCULDAS 23 DL, indirect, PHASE	273
OCCULDAS 23 EL, indirect, PHASE	397
OCULUS CL, Move, PHASE	396
OCULUS CL, PHASE	280
OCULUS CW, PHASE	296
OCULUS PD, single, PHASE	147
OCULUS UP/DOWN WL, PHASE	188
ONE 40 CW, DALI	294
ONE 40 TRACK 3Ph., DALI	443
ONE 60 PD, DALI	120
ONE 60 PD, DALI, up/down	121
ONE 60 PD, PHASE, up/down	121
ONE 60 WL, DALI	294
ONE 80 PD, DALI	120
ONE 80 PD, DALI, up/down	122
ONE DOUBLE PD, DALI, up/down	123
ONE DOUBLE PD, PHASE, up/down	123
ONE LINEAR 100 PD, PHASE, up/down	118
ONE LINEAR 140 PD, PHASE, up/down	118
ONE TRIPLE PD, DALI	119
ORBIT LV, QR111	504
ORDI SENSOR WL	651
ORDI WL	651
OSSA 180 WL, QT-DE12	202
OSSA 300 WL, QT-DE12	202
OTOS GLAS Pole, E27	550
OUT 65 EL, round, PHASE	423, 708
OUT-BEAM FRAME SP	686
OVALISK 75 Pole	542
OVALISK 100 Pole	542
OVALISK CL	676
OVALISK SENSOR WL	637
OVALISK WL	637

P

P-LIGHT CW	340, 341
P-LIGHT EL	420
PANEL 60 CL, round, DALI	263
PANEL 60 CL, round, PHASE	262
PANEL 60 PD, round, DALI	141
PANEL CL, 1200x300mm, DALI	263
PANEL CL, 1200x300mm, PHASE	262
PANEL TRACK 1Ph., square	471
PANEL TRACK 1Ph., round	471
PANTILO 20 PD, E27	162
PANTILO 28 PD, E27	162
PANTILO CONVEX 29	163
PANTILO CONVEX 40 PD, E27	163
PARA 380 PD, E27	179
PARA CONE 14 1Ph., PD, QPAR51	474
PARA CONE 14 1Ph., QPAR51	474
PARA CONE 14 3Ph., PD, QPAR51	445
PARA CONE 14 3Ph., QPAR111	445
PARA CONE 30 PD, E27	167

PARA CONE GL 1Ph., GU10	472
PARA CONE GL 3Ph., GU10	444
PARA CONE GL PD, GU10	166, 444, 472
PARA DOME PD, E27	176
PARA DOME	Shade 176
PARA FLAC PD/CL	179
PARA FLAC PD/CL, DALI	179
PATTA-F EL, square, PHASE	422, 708
PATTA-F EL, round, PHASE	422, 708
PATTA-I DL, square, PHASE	420, 706
PATTA-I EL, square, PHASE	421, 707
PATTA-I EL, round, PHASE	420, 421, 706, 707
PEMA® WL	638, 639
PEMA® WL, E27	639
PHELIA 25 PD, E27	169
PHELIA 30 PD, E27	169
PHELIA FL, E27	110
PHELIA TL, QPAR51	110
PHELIA WL, QPAR51	230
PHOTONIA CL, E27	677
PHOTONIA PD, E27	548
PHOTONIA Pole, E27	549
PHOTONIA TL, E27	548
PHOTONIA WL, E27	657
PIKA DL, round, QPAR51, pivoting	395
PIKA DL, round, QPAR51, rigid	395

PLASTRA

PLASTRA 101 WL, E14	194
PLASTRA 104 CL, E27	283
PLASTRA 104 WL, QT14	194
PLASTRA 105 CL, E27	282
PLASTRA 25 PD, round, TCR-TSE	175
PLASTRA CL, PHASE	282
PLASTRA CL, QPAR51	282
PLASTRA CW, round	193
PLASTRA RL, square, QPAR51	403
PLASTRA RL, round, QPAR51	402
PLASTRA WL, Cube, QT14	190
PLASTRA WL, Cubes	190
PLASTRA WL, Curve, QT-DE12	194
PLASTRA WL, E14	191
PLASTRA WL, square	223
PLASTRA WL, semi-circle	193
PLASTRA WL, QPAR51	193
PLASTRA WL, square, QT-DE12	191

PLYTTA	505
POWER TRAIL-LITE® EL, round/square	724
PURI CW, double, QPAR51	312
PURI CW, quad, QPAR51	312
PURI CW, single, QPAR51	312
PURI CW, triple, QPAR51	312
PURI TRACK 1Ph., QPAR51	478
PURI TRACK 1Ph., Triple Track Set	470
PURI TRACK 3Ph., QPAR51	453
PURIA TRACK 1Ph., QPAR51	478
PURISA WL, E27	211

Q

Q-LINE® CL, 1m, BAP, PHASE	264
Q-LINE® CL, 2m, BAP, PHASE	265
Q-LINE® PD, 1m, BAP, PHASE	144, 145
Q-LINE® PD, 2m, BAP, PHASE	144, 145
Q-LINE® PD, DALI, single	145
Q-LINE® WL	243
QUAD FRAME 14 WL	198
QUAD FRAME 19 WL	198
QUAD FRAME 9 WL	410
QUAD POLE	578
QUAD UP/DOWN 12 WL	634
QUAD UP/DOWN 15 WL	634
QUAD WL	633
QUADRASS PD, E27	165
QUADRASS SPOT WL, E27	212
QUADRASS WL, E27	212
QUADRASYL 75 Pole, TCR-TSE	577
QUADRASYL WL, TCR-TSE	662

QUADRULO CL	675
QUADRULO FL	522
QUADRULO SENSOR WL, E27	629
QUADRULO WL	629
QUADRULO WL, E27	629

R

RASCALI 45 Pole	579
RASCALI 65 Pole	579
RASCALI WL	661
RETRATO WL, PHASE	244
ROCCI 200 EL, round/square	730
ROCCI EL, square	730
ROCCI EL, round	730
ROTOBALL 25 CL, E27	289
ROTOBALL 25 FL, E27	546
ROTOBALL 25 PD, E27	174
ROTOBALL 40 CL, E27	289
ROTOBALL 40 FL, E27	546
ROTOBALL 40 PD, E27	174
ROTOBALL 50 FL, E27	546
ROTOBALL 50 PD, E27	174
ROX ACRYL 30	561
ROX ACRYL 60	561
ROX ACRYL 90	561
ROX CL, GX53	679
ROX CL, QPAR111	679
ROX UP/DOWN WL, QPAR111	645
ROX WL, QPAR111	645
RUBA 27/42 CW	690
RUSTY® UP/DOWN WL, square	636
RUSTY® UP/DOWN WL, round	636
RUSTY® 40 Pole	528, 532
RUSTY® 40 Pole, E27	529, 533
RUSTY® 70 Pole	528, 532
RUSTY® 70 Pole, E27	529, 533
RUSTY® CONE 24 FL, E14	530
RUSTY® CONE 40 Pole, E27	530
RUSTY® CONE 70 Pole, E27	530
RUSTY® PATHLIGHT 40 Pole	527
RUSTY® PATHLIGHT 70 Pole	527
RUSTY® PATHLIGHT Pole, TCR-TSE	527
RUSTY® SLOT 50 Pole	524
RUSTY® SLOT 50 Pole, E27	524
RUSTY® SLOT 80 Pole	524
RUSTY® SLOT 80 Pole, E27	525

S

SAIL WL	655
SALUNA LV, QR-C51	503
SAMRINA SP, single, GU10	592
SEDO 7 WL	207
SEDO 14 WL	207
SEDO 21 WL	207
SENDER 12 CW, square, PHASE	319
SENDER 12 CW, round, PHASE	320
SENDER 12 EL, round	389, 390
SENDER 18 CW, square, PHASE	319
SENDER 18 CW, round, PHASE	320
SENDER 18 EL, round	389, 390
SENDER 24 CW, square, PHASE	319
SENDER 24 CW, round, PHASE	320
SENDER 24 EL, round	389, 390
SHELL 15 WL, PHASE	199
SHELL 30 WL, PHASE	199
SIGHT 60 CW	337
SIGHT 115 CW	337
SIGHT MOVE 3Ph., DALI	441
SIGHT MOVE 3Ph.	448
SIGHT TRACK 3Ph.	450
SIGHT TRACK 3Ph., DALI	440
SIMA CW, square, PHASE	323
SIMA CW, square, Sensor	323
SIMA CW, round, PHASE	322
SIMA CW, round, Sensor	322
SITRA 360 CW, TCR-TSE	684
SITRA 360 Pole, TCR-TSE	583
SITRA 360 SPIKE SP, double, TCR-TSE ...	603
SITRA 360 SPIKE SP, single, TCR-TSE	602

SITRA CL, TCR-TSE.....	679
SITRA CUBE WL.....	622
SITRA CUBE WL, TCR-TSE.....	622
SITRA S WL, single, square.....	624
SITRA M WL, up/down, square.....	624
SITRA L WL, up/down, square.....	624
SITRA UP/DOWN WL.....	644
SITRA UP/DOWN WL, TCR-TSE.....	644
SITRA WL, TCR-TSE.....	661
SLOTBOX 40 Pole.....	574
SLOTBOX 70 Pole.....	574
SLOTS 45 Pole.....	570
SLOTS 65 Pole.....	571
SLOTS WL.....	647
SMALL PLOT cover, double.....	727
SMALL PLOT cover, quadruple.....	727
SMALL PLOT module.....	727
SOLASTO EL, round.....	731
SOLID CUBE WL, QT14.....	216
SOMNILA FLEX WL, left.....	227
SOMNILA FLEX WL, right.....	227
SOMNILA SPOT WL, left.....	226
SOMNILA SPOT WL, right.....	226
SOPRANA CL, E27.....	278
SPOT 79 CW, QPAR51.....	308
SPOT DISPLAY E27.....	245
SQUARE POLE 30 Pole, E27.....	568
SQUARE POLE 60 Pole, E27.....	568
SQUARE POLE 90 Pole, E27.....	568
SQUARE TURN WL, G9.....	662
SQUARE WL, E27.....	660
STRUCTEC ZOOM 3 Ph.....	457
SUN / BIG SUN PD, E27.....	173
SUPROS 78 CL, PHASE.....	271
SUPROS 78 EL, Move, PHASE.....	383
SUPROS 78 EL, PHASE.....	382
SUPROS 78 PD.....	148
SUPROS 78 UP/DOWN WL, PHASE.....	189
SUPROS CL, Move.....	270
SUPROS DL.....	384, 385
SUPROS DL, Move.....	386, 387
SUPROS PD.....	148, 149
SYNA SP.....	601
SYROS LV, QR-C51.....	503

T

TEC KALU TRACK 3Ph., double, PHASE.....	459
TELESKOP LV, QR-C51.....	502
TENORA CL, E27.....	278

TENSEO Low-voltage cable

TENSEO Low-voltage cable.....	500
TENSEO Low-voltage cable accessories.....	501

TERANG 200 CW.....	692
THEO BRACKET 50 Pole.....	541
THEO BRACKET 70 Pole.....	541
THEO BRACKET CW.....	684
THEO BRACKET SP.....	601
THEO PATHLIGHT Pole, double.....	540
THEO PATHLIGHT Pole, single.....	540
THEO UP/DOWN WL, QPAR51.....	216, 618
THEO WL, QPAR51.....	620
TODAY PRO Display.....	665
TONGA® 1Ph., PD, E14.....	475
TONGA® EASYTEC® II, PD, E14.....	494
TONGA® PD, E14.....	165
TONILA TL.....	112
TOTHEE CW, PHASE.....	298
TRAIL-LITE® 60 EL.....	724
TRIADDEM PD, E27.....	156
TRILEDO CL, double, square.....	269
TRILEDO CL, double, square, QPAR51.....	266
TRILEDO CL, single, square.....	269
TRILEDO CL, single, square, QPAR51.....	266
TRILEDO CL, single, round.....	269
TRILEDO CL, single, round, QPAR51.....	266
TRUKKO 60 WL.....	234

TRUKKO 90 WL.....	234
TRUKKO WL, rectangular.....	233
TRUKKO WL, round.....	233
TRUST 30 Pole.....	559
TRUST 60 Pole.....	559

V


VAP 40.....	562
VAP 70.....	562
VAP 100.....	562
VAP SLIM 30 Pole, E27.....	565
VAP SLIM 60 Pole, E27.....	565
VAP SLIM 90 Pole, E27.....	565
VARU EL, QPAR51.....	404, 711
VERLUX EL, square, PHASE.....	393
VILUA S WL.....	643
VILUA L WL.....	643
VILUA UP/DOWN, WL.....	643

W

WALLYX WL, QPAR51.....	647
WL 106 E14.....	237
WL 149 WL, PHASE.....	205
WL 149 WL, QT-DE12.....	205
WORKLIGHT FL.....	101
WORKLIGHT PD, DALI.....	146
WORKLIGHT TL.....	100
WORO EL.....	413

REFERENCE PROJECTS WITH **SLV LIGHTING** **SOLUTIONS**

Get to know many other possible applications of SLV products within real projects. GOOD LIGHT References provides you with an overview of diverse lighting concepts by and for our customers.





From single-family homes with gardens to DALI-controllable shop lighting and right through to large projects such as hotel and office complexes: with SLV you have a strong partner for all areas of application at your side.

See for yourself and be inspired by our completed projects.

SCAN THE QR CODE NOW >>>

You can find more inspiration and references at
www.slv.com








„Raum und Licht und Ordnung.

Das sind die Dinge, die man genauso braucht
wie Brot oder einen Platz zum Schlafen.“

Le Corbusier





„Design is the appropriate combination of materials in order to solve a problem.“

Charles Eames, Designer










„Inspiration exists,
but you have
to find it working.“

Pablo Picasso

„Licht schafft Atmosphäre und
das Gefühl des Raums
sowie den Ausdruck einer Struktur.“

Le Corbusier






„The details are
not the details.
They make the design.“
Charles Eames, Designer



Have you completed your own successful projects using SLV lights? We would love to hear about it! Feel free to send us some photos and detailed background information at: references@slv.de



SLV WORLDWIDE.



**MORE THAN 100 COUNTRIES –
ONE SHARED LANGUAGE:
EXPERIENCE LIGHT.**

Our SLV lights illuminate **the dark, all over the world.**

Our lights are already in use in more than 100 countries.

And the journey continues: together with you, we want to inspire people **all over the world** to experience light in the best way possible.

SYMBOLS KEY

PRODUCT CHARACTERISTICS

	Energy efficiency class "This light is suitable for bulbs with an energy class rating of..."
	Lights with integrated LEDs "This light contains integrated LED light bulbs. The bulbs in the light cannot be replaced." (cf. EU Regulation 874/2012) "This light contains integrated LED light bulbs. The bulbs in the light cannot be replaced." (cf. EU Regulation 874/2012) <i>Note for the end user:</i> The light source in this light may only be replaced by the manufacturer, or by a service technician assigned by the manufacturer.
	Dimmable with... · C = leading-edge phase dimmer · L = trailing-edge phase dimmer · Uni = universal dimmer · 1-10 V · Dali = Dali busbar system · Switch = switch/button or touch control on the light
	Dim to warm With dimmers, the light colour can be altered from cold white to warm white.
	Rotating and pivoting capacity in degrees: · Rotation range · Pivot range · Gimballed
	Beam angle Describes the beam angle in degrees. The smaller the angle, the more concentrated the light will be.
	Pendant cable length in cm
	Power cable length in cm Feed-in length in cm (with open cable ends)
	Average lifespan of a lightbulb or light source in hours
	Lumen maintenance Describes the amount by which the luminous flux of an LED decreases during a specified period.
	Indicates products that can be operated via remote control
	UGR = Unified Glare Rating The lower the UGR value, the lower the psychological glare.

SAFETY DETAILS

	Protection categories · Protection category I/protective conductor · Protection class II/protection through double or strengthened insulation · Protection category III/protection through low voltage
	The IK degree of shock resistance is a measure of the resistance of the housing of electrical equipment to mechanical stress, especially impact stress..

SPECIFIC DETAILS - RECESSED LIGHTS

	Shape of the installation opening
	Installation depth specification
	Product suitability for being driven over stated
	Weight-bearing capacity of the product up to specified value in tonnes. Measurements based on concrete installation.

APPLICATION AREA · ASSEMBLY

	IP protection class Indicates the suitability of electrical equipment for different environmental conditions.
	Allows the installation of electrical control equipment on materials whose flammability is not known.
	Through-wiring possible.
	Independent converter (control equipment also for use outside of lights)
	Short circuit protected safety control equipment
	· For indoor use only · Not suitable for use indoors

SPECIAL SYMBOLS

	Indicates products that have been added to the catalogue for the first time
	Indicates new versions of existing products · New product variant · Successor
	Items with this symbol are discontinued models
	Indicates products · with integrated LEDs · with lamp socket
	Connected lighting Indicates smart products that use the following protocols: · Zigbee® · DALI · Bluetooth
	Indicates lights with a movement sensor (microwave technology (MR)/infrared/radio)
	Using the integrated CCT switch , the light colour can be switched between 3000K and 4000K during installation.
	Indicates lights with RGB+W and RGB (Red-Green-Blue + White and Red-Green-Blue)
	· USB charging function · Inductive (wireless) charging function for Smartphones
	Indicates products that can be combined
	Indicates lights that, after priming can be individually covered with wall paint or wallpaper.
	Indicates lights from a single lighting family
	Award-winning lights · Red Dot Design Award · German Design Award

CUSTOMER INFORMATION

Information regarding light housing heat generation

Halogen lamps operate at high temperatures and can lead to the heating of the housing of the light fixture. They should therefore only be touched once the housing has cooled down. Adjustable lights and light heads that do not feature insulated positioning levers, or which exceed the maximum permissible housing temperature at the positioning point when operated at maximum wattage, should also be mounted out of reach. LED retrofit lamps offer a low-temperature alternative to most of our halogen lights.

Luminous flux

The total amount of light produced by a light source is given in lumens (lm).

Luminosity

The luminosity is the luminous flux indicated per solid angle and is expressed in candelas (cd).

Colour rendering index

The colour rendering property of a light source is indicated by the Colour Rendering Index (CRI). A CRI of 80 or higher is required for light sources used indoors. Light sources used outdoors must have a CRI of at least 65.

Colour temperature

The colour temperature of a light source is indicated in K (Kelvin).

Standard LED

This is the classic version of the LED (3 mm or 5 mm LED). These were originally developed for indication purposes, e.g. in instrument panels.

Standard SMD LED

SMD means "Surface Mounted Device". This is a compact LED that is soldered directly onto the circuit board without wire connections. SMDs are available in different sizes and are suitable for lighting purposes.

PowerLED

PowerLED is a high-performance LED with a power of 1W or more. It places increased demands on current constancy and should therefore always be operated with constant current sources. If you wish to connect several LEDs, they must therefore be connected in series. A parallel connection is not permitted. Please ensure that you observe the installation sequence so that the LEDs are not exposed to high current for a short time, which could damage them. Ultimately, the following rule applies: first you should completely connect the secondary circuit (LEDs to driver), then you should close the primary circuit (driver to power source).

Chip On Board LED (COB LED); Large surface LED

This is an LED with an exceptionally flat shape. The advantage of COB LEDs is good heat dissipation when technically implemented with cooling surfaces, which enables high light output and a long lifespan.

Stainless Steel 304

(1.4301) Good resistance to corrosion is shown in natural environmental media (water, urban and rural atmosphere) in the absence of significant chlorine and salt concentrations. 1.4301 is, however, not suitable for use in areas where there is contact with seawater, salt water or a salty atmosphere, or for use in swimming pools or similar contexts.

Stainless Steel 316

(1.4404) In natural environmental media (water, urban and rural atmosphere) as well as in industrial areas with moderate chlorine and salt concentration, in the food and pharmaceutical industry and in the agricultural food sector, 1.4404 shows excellent resistance to corrosion. 1.4404 is not resistant to seawater.

Please note:

A large part of the products shown in this catalogue are protected by trademarks, registered designs, utility models or patents. Any violation of these property rights or the use of text and layout design or copyrighted images without our authorisation will be prosecuted. The illustrations and information contained in this catalogue are for illustrative purposes only and are not legally binding in terms of colour, shape, design or technical details. All product descriptions and specifications are subject to alteration and errors.

All of the products in our range are subject to our strict quality assurance procedures and comply with generally applicable standards. This catalogue contains a general range and is not country specific. Any deviations from country-specific guidelines must be clarified before ordering. SLV cannot be held responsible for any deviations in terms of technical standards.

All weights and dimensions are given in kg and cm respectively unless stated otherwise. We reserve the right to make technical alterations.

The presentation of our lights with realistic photos showing examples of use is possible thanks to the kind cooperation and agreement of the owners or designers of the environments depicted in the images. We would like to take this opportunity to thank all those who contributed to the creation and use of our photos by giving their consent.

With the appearance of this catalogue, the prices stated in previous lists and catalogues are rendered invalid. SLV has the right to adapt the relevant price list in line with changes in market conditions, in the event of substantial changes in procurement costs or similar circumstances.

All prices are recommended retail prices (GBP) and indicated in Euro without VAT.

Publisher

SLV GmbH, Germany
Daimlerstrasse 21-23
52531 Uebach-Palenberg
T +49 2451 4833-355
slv.com

Copyright

© SLV GmbH, 2021

Image credits

SLV GmbH
External photographers: Andreas Fein, Anja Lynen, Gerd Arnolds,
Günther Preissler, Marc Derkum, Dirk Hoffmann



EXPERIENCE LIGHT

SLV LIGHTING UK LTD

Unit E Chiltern Park,
Boscombe Road
Dunstable
LU5 4LT

T + 44 (0)203 968 11 00

F + 44 (0)203 968 11 09

sales@uk.slv.com

slv.com



Innovative use of combined heat and power technology when printing this product reduced CO₂ emissions by up to 52% in comparison to conventional methods in Germany.