Hand Hygiene Specialist Range

HAND DRYER MAN/M



NOZZLE DRYER FAST DRY MAN/K2300



MAN/500



- No touch infrared detection
- An economical ABS cover
- 2500 4200rpm induction motor
- 225 x 275 x 160mm $(H \times W \times D)$

- IP22 Rated
- Cable entry bottom right
- Weight: 3.3kg
- CE approved

- 23 second drying time
- Infrared touch free activation
- Blue LED dry zone indicator
- Rotating nozzle for hand or face drying
- Steel construction with chrome Sound: 54 dB(A) or
 69 dB(A) at 1m

 Power: 1.25kW or 2kW at 240V

 Supply voltage: 220-240V/1/50Hz

 237 x 270 x 208mm (H x W x D)
 2.3kW Output

 P23 Rating plated nozzles for added durability
 Anti-tamper fixing screws

 •

 - Sound: 70 dB(A) @1m
 - Weight: 4.8kg
 - CE approved

- 10 second drying time
- No touch Infra-Red detection
- Unique blue dry zone indicator
- 220-240V/1/50Hz
- 260 x 180 x 152mm (H x W x D)
- Sound: 72 dB(A) @1m
- Weight: 3.0kg
- CE approved

Cat. No.	Cover	Power
MAN/M-88A	ABS - White	1.25kW
MAN/M-89A	ABS - White	2.0kW

Cat. No.	Cover	Power
MAN/ K2300W	Stainless Steel with glossy white coating	2.3kW
MAN/ K2300PS	Stainless Steel Polished	2.3kW

Cat. No.	Cover	Power
MAN/ 500W	White enameled steel	1.3kW
MAN/ 500WSS	Stainless Steel Satin	1.3kW
MAN/ 500PS	Stainless Steel Polished	1.3kW

Applications - Hand Dryers

The model MAN/M-88A & MAN/M-89A are suitable for use within office and commercial organisations, such as clinics and catering establishments. They are not recommended for use in public areas prone to vandalism, for example public lavatories and unsupervised areas.

All other models are suitable for use in public areas such as lavatories, factories, schools, railway and motorway service stations and are designed for heavy usage and unsupervised areas.



