# **Heating Range**





# **Plinth Heaters**

### **Features & Benefits**

- Ideal for where wall space is at a premium
- Finishes: Stainless steel, Brown or White
- Optional thermostatic control 5-30°C
- Can be used with remote switch VARSU 436494
- Two heat settings 1kW & 2kW
- Fan only mode

Vent-Axia Plinth Heaters are designed for use in kitchens and bedrooms. They fit neatly into most types of fitted furniture, fascias, display units and false walls.


When installed in a corner with an adjacent cupboard to the right, a distance of at least 150mm must be maintained between the right hand end of the heater and the front of the adjacent cupboard door.

Vent-Axia Plinth Heaters are supplied with 1.5m of  $1\,\text{mm}^2$  3 core cable, terminating on the right hand side of the unit.

# **Models**

Model	Stock Ref
VAPL2TC-S	459115
VAPL2TC-W	459116
VAPL2TC-B	459117

### Dimensions (mm)



Weight: 3kg Cut Out (WxH): 470x85mm



# Warm Air Curtains

## Features & Benefits

- Integral Switching for faster installation
- Three heat settings and fan only mode
- Models to suit single and double doorways
- Suitable for use as a high level fan heater

Vent-Axia Warmair Curtains provide a heated downflow of warm air in doorways of commercial premises such as shops, offices and schools.

The robust outer case is made from painted steel with an off white epoxy finish. Accommodating varying door widths is easily achieved by installing Warmair units 'side by side'.

Vent-Axia Warmair Curtains are supplied with 0.75m of 3 core cable, and mounting brackets.

Three Warmair models are available offering heat outputs & fan only :

Warmair 3 - 3 kW, 2 kW, 1 kW Warmair 4.5 - 4.5 kW, 3 kW, 1.5 kW Warmair 6 - 6kW,4 kW, 2 kW

# **Models**

X

£Trade

119.08

119.08

119.08

Warm Air Curtains				
Model	Stock Ref	£Trade		
Warmair 3	456343	228.18		
Warmair 4.5	456344	260.83		
Warmair 6	456345	414.95		

### Remote Switch

Remote Switch unit to control Warmair units. Switch allows for fan only & three heat settings.

Model	SIOCK KEI	£IIuue
VARSU	436494	56.31

## Specification

	Rating	Dimensions mm			Weight
Model	kW	W	н	D	kg
Warmair 3	3.0	650	103	210	6.1
Warmair 4.5	4.5	650	103	210	6.5
Warmair 6	6.0	900	103	210	8.7
-					

220-240V-50Hz. BEAB Approved.



## **Downflow Heater**

# **Features & Benefits**

- Stylish compact design
- Two heat settings, 1kW and 2kW
- Pullcord operation
- Overheat protection
- Fan only option
- IP23 rated

The IP23 rated Downflow Heater operates via a pullcord and is suitable for use within Zone 2 of the bathroom. The Downflow Heater has two heat settings; 1kW/2kW plus a fan only option and is designed to be permanently wall mounted for use with an AC electrical supply.

Function	Indication
Off	0
Fan Only	B
Fan + Heat Setting 1	1
Fan + Heat Setting 2	2

For maximum safety the heater includes a thermal cut-out feature to prevent overheating.

Models Downflow He	ater	X
Model	Stock Ref	£Trade
VADH2	455834	63.78

### Specification

X

	Rating	Dimensions mm			Weight
Model	kW	W	н	D	kg
VADH 2	2	240	255	135	2
000 0 10	1.5011				

220-240V-50Hz.