# Vent-Axia. Residential Fans

# Solo®

# Centrifugal Bathroom/ Toilet Fans

#### Features & Benefits

- 100mm high performance centrifugal extract fan for internal bathrooms, toilets and other small rooms
- High performance 24l/s
- Single speed and overrun timer models
- Suitable for wall, ceiling, panel and window mounting
- PIR version also available
- · Suitable for use with flat ducting
- Double insulated
- IPX4 rated

# **High Performance Ventilation**

The Solo range of high performance centrifugal extract fans from Vent-Axia have been specifically designed for effective ducted ventilation of internal bathrooms, toilets and other small rooms. Finished in White. The Solo range can be used with 100mm diameter smooth bore duct in straight runs equal to 50m, yet still meets the 151/s required by the current Building Regulations Document F for ventilation of bathrooms. IP44 Rated.

Models are available for surface or recessed mounting directly into standard 100mm diameter ducting. Suitable for panel, wall and ceiling installations and windows up to 25mm thick. For high rise or coastal applications, install through the wall with a Vent Cowl (Stock Ref 561403).

## Models

Solo P

#### (Pullcord)

Single speed 24l/s. Control by pullcord or from light/remote switch or sensor.

Stock Ref

11101010

# Solo T (Timer)

Single speed 241/s. Control by light/remote switch. Overrun timer variable from 5 to 30 minutes.

Stock Ref 11101030

# Solo TM2

# (Timer/PIR)

Control by integral PIR detector. Fan is switched ON when PIR is triggered. Built-in overrun timer, variable from 5 to 30 minutes, switches fan Off.

Stock Ref

11101060

#### Solo HTP

# (Humidity and Timer)

Humidity controlled single speed fan with pullcord override. 17 min overrun timer.

Stock Ref 11101080

#### Accessories

Wall Kit

Stock Ref

254102 (White)

254100 (Brown)

Window Kit

Stock Ref

11461685

## **Performance**

	Extract Pe	rformance	Max	dB(A)	Amps
Model	m³/h	l/s	Watts	@ 3m	@ 240V
Solo P/T/TM2/HTP	85	24	35	42	0.15


# Dimensions (mm)

Α	В	С	DØ	Ε	F	G	Н
155	140	36	98	85	55	60	195


Weight 1.35kg

## Wall


Front view







## Window



Window fixing hole Ø113mm

T: 0844 856 0590