

LED Highbay



Features

- CCT 4000K or 6500K options
- 90° Beam Angle
- Integral, flicker free driver
- Hanging loop included
- Fitted with 0.5 meters of flex
- IP65 rating for total protection against dust and low pressure jets of water from any direction
- 5-year guarantee

Technical Specification

Voltage	220V-240V	
Frequency	50-60Hz	
Power Factor	≥0.9	
Protection Class	Class I	
Colour Temperature	BR3503/BR3505/BR3507	4000K
	BR3504/BR3506/BR3508	6500K
CRI	≥80	
Beam Angle	90°	
Dimmable	No	
Construction	Aluminium Body & polycarbonate diffuser	
IP Rating	IP65	
IK rating	IK08	
Operating Temperature	-20°C to +40°C	
Mounting Height	8-10m	
Lifespan	25,000hrs	
Light Source	Non-replaceable LED	
Luminous Flux	100W	14,000lm
	150W	21,000Lm
	200W	28,000Lm
Light Source	100W	15,450Lm
Luminous Flux	150W	21,870Lm
	200W	30,030Lm
Light Source	100W	153Lm/W
Luminous Efficacy	150W	148Lm/W
	200W	152Lm/W
Energy Efficiency Class	E	
Standards	EN IEC 61000-3-2:2019 EN IEC 60598-1	

Description

The Highbay range is available in 4000K or 6500K colour temperatures, provides a unique high bay solution for warehouses, factories and other large spaces.

Range

BR3503	100W LED Highbay non-dimmable 4000K
BR3504	100W LED Highbay non-dimmable 6500K
BR3505	150W LED Highbay non-dimmable 4000K
BR3506	150W LED Highbay non-dimmable 6500K
BR3507	200W LED Highbay non-dimmable 4000K
BR3508	200W LED Highbay non-dimmable 6500K

Dimensions

	Diameter	Depth
100W	Ø205.8mm	125.7mm
150W	Ø250.0mm	131.6mm
200W	Ø294.0mm	143.0mm

No Serviceable parts

Contact your local authority for information concerning the correct disposal of your product