

CCT3 Power Selectable LED PRO Batten



Description

High performance LED batten providing an energy saving, retrofittable replacement solution for T8 fluorescent fittings used in commercial applications.

- CCT3 selectable 3000K/4000K/6000K via internal 3-way switch
Power selectable via internal 3-way switch
4ft Single = 10-20W Twin = 21-36W
5ft Single = 21-33W Twin = 29-53W
6ft Single = 20-38W Twin = 32-62W
- Steel body construction with polycarbonate diffuser, suitable for ceiling or suspension mounting
- Hinged diffuser locks when open for ease of maintenance/installation
- 3 hour emergency function with LiFePO4 battery supplied
- IP20 rating, suitable for indoor use
- 5-year Guarantee

Range

BR5214	4ft 10-20W CCT3 IP20 Batten
BR5214E	4ft 10-20W CCT3 IP20 Batten + EM
BR5214T	4ft 21-36W CCT3 IP20 Batten
BR5214TE	4ft 21-36W CCT3 IP20 Batten + EM
BR5215	5ft 21-33W CCT3 IP20 Batten
BR5215E	5ft 21-33W CCT3 IP20 Batten + EM
BR5215T	5ft 29-53W CCT3 IP20 Batten
BR5215TE	5ft 29-53W CCT3 IP20 Batten + EM
BR5216	6ft 20-38W CCT3 IP20 Batten
BR5216E	6ft 20-38W CCT3 IP20 Batten + EM
BR5216T	6ft 32-62W CCT3 IP20 Batten
BR5216TE	6ft 32-62W CCT3 IP20 Batten + EM

Technical Specification

Voltage	220-240V~
Frequency	50-60Hz
Power Factor	≤0.9
Colour Temperature	3000K / 4000K / 6000K
Beam Angle	120°
Construction	Steel body & Polycarbonate diffuser
IP Rating	IP20
IK Rating	IK08
Dimmable	No
Light Source	Non-replaceable LED
Lifespan	50,000hrs
Luminous Flux	4ft 2600-4800 lm
	5ft 4000-6500 lm
	6ft
Luminous Efficacy	120 lm/W
Light source Luminous Efficacy	150lm/W
Energy Efficiency Rating	D
Standards	BS EN 60598-1

Weight & Dimensions

	Length	Width	Height
4ft	1170mm	60mm	75mm
5ft	1500mm	60mm	75mm
6ft	1800mm	60mm	75mm