



## Dimmer Switches

### Description

The elegantly styled Vimark Pro Décor range is available in Chrome, Stainless Steel and Matt Black finishes.

Our LED versions are designed specifically with LED lighting in mind and are optimised to control our dimmable LED Fire Rated Downlights, as well as other leading brands of LED lamps, with minimal programming.

Each product is supplied in its own polybag, protecting it up to the point of installation

### Features

- Suitable for use with dimmable LED lamps, Halogen, and Incandescent Lamps
- Push on / push off control
- Dimmer automatically changes mode, to either Leading Edge (LE) or Trailing Edge (TE), to suit LED load
- Programmable to set desired brightness levels
- LED back light to indicate the dimming mode i.e. Leading or Trailing edge
- Ideal for controlling DETA range of Fire Rated Dimmable LED Downlights
- 2-year guarantee

### Range

#### Universal Dimmers

1 gang 2-way 150W LED	VPD1414
2 gang 2-way 150W LED	VPD1415

#### Suffix finish with:-

Chrome	CH
Stainless Steel	SS
Matt Black	MB

### Technical Specification

Voltage rating	250Vac
Frequency	50Hz
LED dimmers	<ul style="list-style-type: none"> <li>• LED – 150W (100W LE Mode)</li> <li>• Tungsten halogen – 250W</li> <li>• Incandescent and ECO halogen – 250W</li> <li>• LV Transformers – 250W</li> </ul>

No user serviceable parts

### Standards

- BS EN 60669-2-1

### Back Boxes

Minimum recommended depth

	Flush 35mm	Dry Lining 35mm
VC1414	DB164	DB2540
VC1415	DB164	DB2540

### Terminal Capacity

	1mm <sup>2</sup>	1.5mm <sup>2</sup>
L	2	2