

Rex Slim LED Floodlight 110V



Features

- Highly efficient LED chips, providing an ideal replacement for both metal halide or sodium fittings
- Driverless technology ensures a sleek yet durable design
- Less weight means easier to install and smaller fixings
- 50W-300W options available
- Angled bracket for easy installation
- IP65 rating for total protection from dust and low-pressure jets of water from any direction
- 3-year Guarantee

Range

N6279	50W Rex Slim 110V LED Floodlight
N6280	70W Rex Slim 110V LED Floodlight
N6281	100W Rex Slim 110V LED Floodlight
N6282	150W Rex Slim 110V LED Floodlight
N6283	300W Rex Slim 110V LED Floodlight

Description

The LED 110V floodlight range offers a sleek and durable lighting solution for commercial, industrial and site applications, where 110v site power is required.

Technical Specification

Voltage	110V-140V	
Frequency	50-60Hz	
Power Factor	≤0.9	
Colour Temperature	4000K Cool White	
Beam Angle	120°	
Construction	Aluminium Body & Toughened Glass	
IP Rating	IP65	
IK Rating	IK08	
Cable length	50W - 0.5m 70-300W - 1.5m	
Dimmable	No	
Light Source	Non-replaceable LED	
Lifespan	30,000hrs	
Luminous Flux	50W	5500 lm
	70W	7700 lm
	100W	11000 lm
	150W	16500 lm
	300W	33000 lm
Luminous Efficacy	110 lm/W	
Energy Efficiency Rating	F	
Standards	BS EN 60598-1	
No user serviceable parts		

Weight & Dimensions

	Height	Width	Depth	Weight
N6279	200mm	237mm	36mm	2.13Kg
N6280	282mm	320mm	38mm	2.23Kg
N6281	282mm	320mm	38mm	2.24Kg
N6282	420mm	333mm	51mm	3.5Kg
N6283	429mm	471mm	70mm	4.9Kg

All dimensions are for the body and do not include the bracket