Garage & Shower Consumer Units



Description

Range of consumer units suitable for domestic new build installations and the replacement of consumer unit in existing properties during renovation/upgrade

All consumer units are supplied with a 100A Main Switch & RCBO's

Features

- All metal enclosures are compliant to BS 7671:2018:A3:2024 wiring regulations
- Lockable cover to prevent circuits being switched on accidentally – lock available separately
- Conduit entry on top, bottom walls and side walls
- Large rectangular knockout on rear of enclosure, supplied with grommet
- Raised DIN rail to allow cables to pass underneath
- TX1910 supplied with 1x 32A & 1x 6A RCBO
- TX1911 supplied with 1x 50A RCBO & 1 blank module
- 10-year guarantee

Range

Item Code	Description
TX1910	IP2X 4 Module, Garage Unit 100A Main Switch, 1x 32A & 1 x 6A Bidirectional RCBOs
TX1911	IP2X 4 Module, Shower Unit 100A Main Switch, 1 x Unidirectional 50A RCBO + 1 Blank

Compatible with the Timeguard TX series of consumer unit devices only

Knockouts

Enclosure Size	Top	Bottom	Back Wall
4 Module	2 x Ø20mm 1 x Ø32mm	2 x Ø20mm 1 x Ø32mm	1 x 90mm x 50mm
All Enclosures have a 32mm knockout on each side			

Dimensions

Back Box

Enclosure Size	Height	Width	Depth
4 Module	259mm	160mm	87mm

Cover

Enclosure Size	Height	Width	Depth
4 Module	136mm	152mm	22mm

Technical Specification

Voltage	240V ac
Current Rating	63A max.
Cable Terminal Capacity (E & N bars)	16mm^2 max.
N°. of Neutral Bars	1
Standard	BS EN 61439-3

Deta Electrical Company Ltd.
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk