



Description

Timeguard Standalone PIRs with parallel wireable and IP65. They also offer detachable back cases and push connection terminals for easy fitting. Black and White options are available.

Range

SLB2301	2000W, IP65 PIR SENSOR Black
SLW2301	2000W, IP65 PIR SENSOR White

Features

- The range of the Standalone PIR Sensors are fully rewirable (compatible with existing or new fittings) and features easily accessible push-fit terminals
- Slave terminal for linking extra sensors to a single sensor
- Detachable back case and fixings accessories included for ease of installation
- Durable powder coated finish
- 2 x IP65 Compression glands included for loop in-out wiring

Dimensions

	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
SLB2301	80	78	80	0.1364
SLW2301	80	78	80	0.1364

Technical Specification

PIR sensor	
Load	2000W
Input Voltage	220 - 240V AC
Frequency	50 - 60Hz
Operating Power	0.5W
Power Factor	0.9
Incandescent / Halogen	2000W
Compact Fluorescent	200W
Fluorescent	400W
LED	400W
IP Rating	IP65
IK Rating	IK07
Detection Angle	180°
Construction	PC / RAL9016
Insulation Class	Class II
Operating Temperature	-25°C to 50°C
Detection Range	0 - 12M
Lux Setting min-max	20 - 1000 lux
Standby Settings	2s 15s 30s 1min 5min 15min
Sensor Head Adjustment	Pan - 45° Tilt - 30°
Manual Override	Yes