MCB's



Description

A wide range MCB's for use with Timeguard consumer units suitable for domestic new build installations and the replacement of consumer units in existing properties during renovation/upgrade.
Provides overcurrent and earth leakage protection to individual circuits.

Features

- Supplied with contact position indicator
- 35mm DIN rail mounting
- Terminal cages include no miss blanking plate, preventing incorrect fitting of cable or busbar
- Max torque settings conveniently printed on side and front of device
- MCBs can be removed without removing the busbar
- Protection against both overload and short circuits
- 6000A short circuit breaking capacity
- 5-year guarantee

Range

B Curve MCB single pole

Item	Description
TX2306	6A 6KA Type B Curve MCB
TX2310	10A 6KA Type B Curve MCB
TX2316	16A 6KA Type B Curve MCB
TX2320	20A 6KA Type B Curve MCB
TX2332	32A 6KA Type B Curve MCB
TX2340	40A 6KA Type B Curve MCB
TX2345	45A 6KA Type B Curve MCB
TX2350	50A 6KA Type B Curve MCB

C Curve MCB single pole

Item	Description
TX2306C	6A 6KA Type C Curve MCB
TX2310C	10A 6KA Type C Curve MCB
TX2316C	16A 6KA Type C Curve MCB
TX2320C	20A 6KA Type C Curve MCB
TX2332C	32A 6KA Type C Curve MCB
TX2340C	40A 6KA Type C Curve MCB
TX2345C	45A 6KA Type C Curve MCB
TX2350C	50A 6KA Type C Curve MCB

Compatible with the Timeguard TX series of consumer units only

Technical Specification

Voltage (U_n)	240V ac
Current Rating (I_n)	See Range
Terminal Capacity	25mm^2 max.
Electrical Endurance	4,000 Cycles
Mechanical Endurance	10,000 Cycles
Dielectric Strength	2500V
Short Circuit Breaking Capacity	6kA Energy Limiting Class 3
Terminal Tightening Torque	2.5Nm
Standards	IEC/BS EN 60898-1 IEC/BS EN 60947-2
Housing Material	PA6

Dimensions

Height	81mm
Width	18mm
Depth	73mm

Deta Electrical Company Ltd.
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk