



S1230



S1231

Features

- Twin USB C and single USB-A ports deliver up to 20W USB charging
- Use Power Delivery and Quick Charge protocols to deliver optimised high speed charging across connected devices
- Captive and backed out top facing cage terminals with large cable lead ins and clear embossed and white printed markings

Technical Specification

- **Voltage Rating** - 250VAC
- **Current Rating** - 13A
- **No. of Poles** - Single Pole
- **Contact Gap** - 3mm Minimum
- **Minimum Back Box Depth** - 25mm
- **Frontplate Material** - Urea Formaldehyde (UL94)
- **Terminal Capacity** - 3 x 2.5mm², 2 x 4mm², 1 x 6mm²

USB Charging Specification

Single USB C	Power Delivery 3.0 20W 15W (5V/3A), 20W (9V/2.2A), 20W (12V/1.7A)
Single USB A	Quick Charge 3.0 18W 15W (5V/3A), 18W (9V/2A), 18W (12V/1.5A)
Multiple	15W (5V/3A) Shared

For the fastest charging, connect a single device only.
Charging multiple devices may result in slower charging speeds.

USB Sockets

Slimline USB Sockets feature a built-in 20W USB charger with three charging ports, allowing up to three devices to be charged simultaneously while keeping both sockets free for appliances. Twin USB-C and single USB-A ports provide a flexible charging solution, while Power Delivery and Quick Charge protocols maximise charging speeds with compatible devices.

Slimline accessories are manufactured from durable white urea and feature a contemporary low-profile design with curved top and bottom edges and matching fixing screw caps, providing a sleek finish suitable for domestic and commercial applications.

Premium features including top access terminals, captive and backed-out terminal screws, clear terminal markings and a recessed earth bar aid installation, while the compact design fits within a 25mm back box.

Product Code

S1230	2G 13A SP Switched Socket with 20W USB C+C+A
S1231	2G 13A SP OB Switched Socket with 20W USB C+C+A

Compliance

- BS 1363: Part 2
- IEC 62368-1

Guarantee

- 2 Years