Main Switch Consumer Units



Features

- All metal enclosures are compliant to BS 7671:2018:A4:2026 wiring regulations
- Pre-fitted 100A DP Main Switch
- Lockable visor to prevent circuits being switched on accidentally during house build – visor locking kit available separately
- Conduit entry on top, bottom and side walls
- Large rectangular knockouts on rear of enclosure, supplied with grommets
- Raised and removable DIN rail to allow cables to pass underneath
- Supplied with live busbar, blank modules, rear grommets and circuit identification labels

Dimensions

Back Box

Enclosure Size	Height	Width	Depth
8/10 Module	259mm	232mm	87mm
14 Module	259mm	304mm	87mm
18 Module	259mm	376mm	87mm
22 Module	259mm	450mm	87mm
28 Module	512mm	304mm	87mm
32 Module	512mm	376mm	87mm

Cover

Enclosure Size	Height	Width	Depth
8/10 Module	136mm	223mm	22mm
14 Module	136mm	296mm	22mm
18 Module	136mm	362mm	22mm
22 Module	136mm	440mm	22mm
28 Module	136mm	296mm	22mm
32 Module	136mm	362mm	22mm

Description

Range of main switch consumer units suitable for domestic new build installations and the replacement of consumer unit in existing properties during renovation/upgrade.

All consumer units are supplied with a 100A DP main switch.

Range

Item Code	Description
TX1308	8M, 6FW, Main Switch (No SPD)
TX1310	10M, 8FW, Main Switch (No SPD)
TX1314	14M, 12FW, Main Switch (No SPD)
TX1318	18M, 16F Main Switch (No SPD)
TX1322	22M, 20FW, Main Switch (No SPD)
TX1328	28M (2 x 14,) 25FW, Main Switch (No SPD)
TX1332	32M (2 x 16), 29FW, Main Switch (No SPD)

Compatible with the Timeguard TX series of consumer unit devices only

Knockouts

Enclosure Size	Top	Bottom	Back Wall
8 Module	4 x Ø20mm 1 x Ø32mm	4 x Ø20mm 1 x Ø32mm	1 x 90mm x 50mm
10 Module	5 x Ø20mm 1 x Ø32mm	5 x Ø20mm 1 x Ø32mm	
14 Module	7 x Ø20mm 1 x Ø32mm	6 x Ø20mm 2 x Ø32mm	2 x 90mm x 50mm
18 Module	9 x Ø20mm 1 x Ø32mm	8 x Ø20mm 2 x Ø32mm	2 x 90mm x 50mm
22 Module	12 x Ø20mm 1 x Ø32mm	11 x Ø20mm 2 x Ø32mm	3 x 90mm x 50mm
28 Module	7 x Ø20mm 1 x Ø32mm	6 x Ø20mm 2 x Ø32mm	4 x 90mm x 50mm
32 Module	9 x Ø20mm 1 x Ø32mm	8 x Ø20mm 2 x Ø32mm	4 x 90mm x 50mm
All Enclosures have a 32mm knockout on side walls			

Technical Specification

Voltage	240V ac
Current Rating	100A max.
Cable Terminal Capacity (E & N bars)	25mm² max.
N°. of Neutral Bars	1
Standard	BS EN 61439-3

Deta Electrical Company Ltd.
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk