

Plasterers Lights

Description

Suitable for lighting solutions when working in confined spaces



Features

- Suitable lighting solution for working in confined spaces
- Supplied with foldaway stand for ease of storage and transportation
- Ideal replacement for fluorescent plasterers lights
- Wide voltage range 100V-277V
- Polycarbonate base with opal diffuser and steel stand, complete with LED tray
- IP65 fitting rating for total protection against dust and low pressure jets of water
- Supplied with two 16A outlet connections for linkable applications
- Complete with 5m power lead and 16A 110V yellow plug
- Operating temperature of -15° to + 50°C
- Emergency fitting supplied 3 hour maintained with Ni-Cad battery
- 1-year guarantee

Range

P1000	2ft 20W A-Frame Plasterer Light
P1010	2ft 20W Tripod Plasterer Light
P1020	5ft 30W Tripod Plasterer Light
P1025	5ft 30W Tripod Emergency Plasterer Light

Technical Specification

Voltage	100V-277V	
Frequency	50-60Hz	
Operating Wattage	2ft	20W
	5ft	30W
Power Factor	≤0.9	
Colour Temperature	6400K Daylight White	
Luminous Flux	570-600lm	
Beam Angle	120°	
IP Rating	IP65	
IK Rating	IK08	
Light Source	Non-replaceable LED	
Lifespan	30,000 Hours	

No user serviceable parts