


Connections Units



Description

This stylish range is easy to install, with coloured terminals, clear white terminal markings and the frontplates are supplied in protective bags.

Features

- Complete with surface mounting box
- Selected products available with and without knockouts in mounting box
- Lockable fuse carrier for safety isolation
- Captive fuse carrier
- Neon versions available
- Neon leads enclosed
- Clear terminal markings
- Colour coded terminals
- Terminals have large lead ins
- 2 earth terminals
- Captive and backed out terminal screws
- 25-year guarantee

Technical Specification

Voltage rating	250Vac
Current Rating	13A
Contact gap	3mm
Size 1g	78mm x 78mm
Depth	46mm

No user serviceable parts

Standards

- BS 1363: Part 4

Range

Back boxes with knockouts

Unswitched spur	M1210
Unswitched spur with neon	M1217
Unswitched spur with flex outlet	M1210FL
Switched spur	M1211
Switched spur with flex outlet	M1211FL
Switched spur with neon	M1212
Switched spur with flex outlet and neon	M1212FL

Back boxes without knockouts

Unswitched spur	M1310
Unswitched spur with neon	M1317
Switched spur	M1311

Back Boxes

All knockouts are 20mm diameter

	Back boxes with knockouts		Back boxes without knockouts	
	Sides	Back	Sides	Back
1g	5	1	0	1

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	4	3	2	1