



CCT3 Commercial Downlight

Description

The CCT3 LED Commercial downlight is backlit, ensuring a uniform light distribution and an improved contrast.

Features

- Suitable for a number of commercial applications
- Flicker free LED driver
- CCT3 selectable via dip switch (3000K/4000K/6000K)
- Raised retaining springs allow for installation in ceiling tiles up to 40mm deep
- Plug in emergency pack option available (BR1191 sold separately)
- UGR<22 in compliance with BS EN 12464-1
- IP44 rating for protection from solid objects larger than 1mm and splashes of water from any direction
- 5-year guarantee

Dimensions

	Cut out Size	Diameter	Height
BR2001	150mm	170mm	69mm
BR2002	200-210mm	230mm	79mm

Contact your local authority for information concerning the correct disposal of your product.

Range

BR2001	15W CCT3 Commercial Downlight
BR2002	18W CCT3 Commercial Downlight

Technical Specification

Voltage	220-240VAC	
Frequency	50-60Hz	
Power Factor	≥0.9	
Electrical Class	Class II	
Colour Temperature (Switch Selectable)	3000K Warm white 4000K Cool white 6000K Daylight white	
Beam Angle	90°	
CRI	≥80	
Construction	Steel Body, PC Diffuser	
IP Rating	IP44	
Dimmable	No	
Light Source	Non-replaceable LED	
Lifespan	50,000hrs	
Operating Temperature	-20°C to +40°C	
Lumens	15W	1500 Lm
	18W	1800 Lm
Light Source Lumens	15W	1900 Lm
	18W	2300 Lm
Light Source Luminous Efficiency	127 Lm/W	
Standards	BS EN 60598-1	

No user serviceable parts