



## Wireless Alarm Controller

### Description

Wireless alarm controller for remote interlinking with DETA's combined optical smoke and heat alarms.

Aesthetically pleasing front profile blends seamlessly with modern day domestic and commercial surroundings.

### Features

- Interlinks wirelessly with combined smoke and heat alarm 1171
- Remote testing of wireless alarms
- Alarm location feature identifies the alarm that was activated by silencing other wireless alarms in the system
- Can be wall mounted using the bracket supplied. Easy to remove the controller from the bracket to carry out walk around testing
- Battery powered (AA batteries supplied)
- Visual indication when a fire alarm is activated
- Over 10 years product life
- 5-year guarantee

### Range

Wireless Alarm Controller 1190

### Technical Specification

No of Interlinked Alarms	50 max
RF Frequency	868MHz
Transmission distance	35m (over 100m in open area)
Battery Type	2 x 1.5V AA (included)
Product Life	Over 10 Years
Housing Material	ABS
Operating Conditions	4°C to +38°C @ 10-95%RH
IP Rating	IP20
Dimensions	90 x 90 x 24mm

### Standards

RF	EN 301 489-1 EN 301 489-3 EN 300-220-2
EMC	EN 55032 EN 55035
Safety	EN IEC 62368-1