

EnOcean Easyclickpro valve actuator

Product Data Sheet



Mounting method	Radiator valve
Degree of protection (IP)	IP20
Radio frequent bidirectional	Yes

EnOcean Easyclickpro valve actuator

The battery-powered bidirectional Easyclickpro actuator facilitates the convenient regulation of radiator heating in individual rooms. These operations require a switching module (e.g. D 454 FU-SPV 4REG) and the antenna (D 450 ANT) from the Easyclickpro modular system. The switching module features a room temperature regulating function; analyses the telegrams from the room temperature sensor, window contacts/handles and hotel card switches, and transmits the required information back to the actuator on request. The actuator is programmed to the switching module via a button/L16.6.2021 Includes 3 batteries (AA)

Technical data:

Radio technology: EnOcean (IEC 14543-3-10)
 Frequency: 868 MHz
 Data transfer: bidirectional
 EnOcean profile: EEP A5-20-01
 Power supply: battery-operated, 3 alkaline Mignon batteries (type AA)
 Temperature measuring range: 0 .. +40 °C
 Temperature accuracy: +/- 0.5 °C (typ. at 25 °C)
 Measuring interval: Every 2 .. 20 min., adjustable
 Transmit interval: Every 2 .. 20 min., adjustable
 Display: Status LED, multi-coloured
 Box: RAL 9010 pure white
 Protection class: IP40 according to DIN EN 60529
 Ambient condition: 0 .. +50 °C
 Weight: 157 g without, 225 g with batteries
 Installation: Installation position +/- 90°
 Actuation noise: < 28 dB(A)
 Actuation travel: to 3 mm
 Actuation time: up to 10 s/mm
 Actuation force: 100 N nominal
 Status display: Travel scale Connection for valves: M30 x 1.5
 Dimensions: 91.5 x 85 x 47 mm

Material No.	Article No.	EAN-code
00324867	D 451 FU-E MSA2	4010105324860

PEHA Elektro GmbH & Co.KG

a Honeywell Company
 Daimlerstraße 4
 58553 HALVER
 DEUTSCHLAND

Tel.: 02353 9118 001
 Fax: 02353 9118 311
 mail: peha@honeywell.com
www.peha.de

Änderungen vorbehalten. © Honeywell PEHA