# Product datasheet

Specifications



Discontinued

## C60HC 2P 10A C BSEN

C60HC210

Discontinued on: 31 Mar 2017

## Main

| | |
|---|---|
| **Device application** | Distribution |
| **Range** | Multi9 |
| **Product name** | C60 |
| **Product or component type** | Miniature circuit-breaker |
| **Device short name** | C60H |
| **Poles description** | 2P |
| **Number of protected poles** | 2 |
| **Trip unit technology** | Thermal-magnetic |
| **Curve code** | C |

## Complementary

| | |
|---|---|
| **[In] rated current** | 10 A |
| **Breaking capacity** | 10 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>15 kA Icu at 400...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10000 A Icn at 230/400 V AC 50/60 Hz conforming to EN 60898<br>25 kA Icu at 125 V DC 2P conforming to EN/IEC 60947-2<br>30 kA Icu at 230...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>40 kA Icu at 125 V DC 3P conforming to EN/IEC 60947-2<br>50 kA Icu at <= 250 V DC 4P conforming to EN/IEC 60947-2 |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Longer

#### Lifetime extension

| | |
|---|---|
| Repair | No |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |