Product datasheet

Specifications

Discontinued

C60HD1P6ADBSEN

C60HD106

Discontinued on: 17 Nov 2017

Main

Device application	Distribution
Range	Multi9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60H
Poles description	1P
Number of protected poles	1
Trip unit technology	Thermal-magnetic
Curve code	D

Complementary

[In] rated current	6 A
Breaking capacity	30 kA Icu at 130 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA Icu at 230...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA Icu at 60 V DC 1P conforming to EN/IEC 60947-2 4 kA Icu at 400...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 10000 A Icn at 230/400 V AC 50/60 Hz conforming to EN 60898

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins