

# Product datasheet

Specifications



Empty enclosure, zinc alloy, grey  
RAL 7032, 1 cut-out, Ø22 mm,  
80x80x51.5 mm

XAPG19201

EAN Code: 3389118381926

## Main

|                               |                                                              |
|-------------------------------|--------------------------------------------------------------|
| Range of product              | Harmony XAP                                                  |
| Product or component type     | Die-cast empty control station                               |
| Device short name             | XAPG                                                         |
| Product destination           | For Ø 22 mm control and signalling units                     |
| Number of cut-out             | 1 cut-out                                                    |
| Colour of base of enclosure   | Grey (RAL 7032)                                              |
| Colour of cover               | Grey (RAL 7032)                                              |
| Control station type          | Metal                                                        |
| Material                      | Die cast zinc                                                |
| Sale per indivisible quantity | 1                                                            |
| IP degree of protection       | IP65 conforming to IEC 60529<br>IP65 conforming to IEC 60529 |
| Resistance to chemical agents | Special treatment can be obtained on request                 |

## Complementary

|                           |                                |
|---------------------------|--------------------------------|
| Number of vertical rows   | 1                              |
| Number of horizontal rows | 1                              |
| Cut-out dimensions        | Ø 22 mm                        |
| Cable entry               | cable gland<br>1 x cable gland |
| Thread type               | 3/4 NPT                        |
| CAD overall width         | 80 mm                          |
| CAD overall height        | 80 mm                          |
| CAD overall depth         | 51.5 mm                        |
| Net weight                | 0.524 kg                       |
| Compatibility code        | XAPG                           |

## Environment

|                                       |                                                                      |
|---------------------------------------|----------------------------------------------------------------------|
| Protective treatment                  | TH                                                                   |
| Ambient air temperature for storage   | -40...70 °C                                                          |
| Ambient air temperature for operation | -25...70 °C                                                          |
| Electrical shock protection class     | Class I conforming to IEC 60536<br>Class I conforming to NF C 20-030 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                         |                              |
|-------------------------|------------------------------|
| IK degree of protection | IK07 conforming to IEC 62262 |
|-------------------------|------------------------------|

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 8.600 cm  |
| Package 1 Width              | 9.000 cm  |
| Package 1 Length             | 9.000 cm  |
| Package 1 Weight             | 530.000 g |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 6.800 kg  |

## Logistical informations

|                   |    |
|-------------------|----|
| Country of origin | MA |
|-------------------|----|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 4 kg CO2 eq.                                  |
| Carbon footprint of the manufacturing phase [A1 to A3] | 4 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                         |
| Packaging without single use plastic   | Yes                                                                         |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

## Use Again



### Repack and remanufacture

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Recyclability potential, in %   | 17                                       |
| End of life manual availability | No need of specific recycling operations |
| Take-back                       | No                                       |

Image of product / Alternate images

Alternative

---





