Data Sheet | Item Number: 2092-1630

Unlocking tool; orange

https://www.wago.com/2092-1630



Color: orange

Material data	
Color	orange
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.015 MJ
Weight	0.5 g

Commercial data	
Product Group	26 (picoMAX Connectors)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821479260
Customs tariff number	82055980000

Product Classification	
UNSPSC	27112109
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Continued on next page

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 1977	E45171

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2092-1630

CAD/CAE-Data

CAD data


2D/3D Models 2092-1630

CAE data


ZUKEN Portal 2092-1630

Installation Notes


Locking system



Disconnecting female connector via unlocking tool. Plug unlocking tool into the male header's locking latch.



Disconnecting a female connector via unlocking tool. Plug unlocking tool into the male header's locking latch.



Pull on both unlocking tool and conductors to remove female connector from male header.