
Data Sheet | Item Number: 216-141

Ferrule; Sleeve for 0.5 mm² / 20 AWG; uninsulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92

https://www.wago.com/216-141



Similar to illustration



Dimensions in mm

Connection Data	
Metric cross-section of the ferrule	0.5 mm²
Strip length	10 mm / 0.39 inches
Cross-section (AWG) of ferrule	20 AWG

Physical data	
Total length (L)	10 mm
Wall thickness of crimp sleeve (W2)	0.15 mm
Diameter crimp sleeve inside (D2)	1 mm

Mechanical data	
Plastic collar	No

Material data	
Weight	0 g

Commercial data	
Product Group	2 (Terminal Block Accessories)
PU (SPU)	5000 (1000) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918016353
Customs tariff number	85369010000

Product Classification

UNSPSC	39121405
eCl@ss 10.0	27-40-02-01
eCl@ss 9.0	27-40-02-01
ETIM 9.0	EC000005
ETIM 10.0	EC000005
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 216-141

Documentation

Bid Text

216-141	19.02.2019	xml 2.87 KB	
216-141	13.06.2017	doc 23.00 KB	

Installation Notes



A perfect gas-tight crimp – both electrically and mechanically reliable