Data Sheet | Item Number: 216-288


Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow

https://www.wago.com/216-288



Color: yellow

Similar to illustration



Dimensions in mm

Connection Data

Metric cross-section of the ferrule	6 mm²
Strip length	20 … 21 mm / 0.79 … 0.83 inches
Cross-section (AWG) of ferrule	10 AWG

Physical data

Total length (L)	26 mm
Wall thickness of crimp sleeve (W2)	0.2 mm
Wall thickness (plastic collar W1)	0.3 mm
Crimp length (length of sleeve L1)	18 mm
Inner diameter of plastic collar (D1)	6.3 mm
Diameter crimp sleeve inside (D2)	3.5 mm

Mechanical data

Plastic collar	Standard collar
Suitable	2010 to 2016 Series

Material data

Color	yellow
Fire load	0.016 MJ
Weight	0.5 g

Commercial data

Product Group	2 (Terminal Block Accessories)
PU (SPU)	100 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143654760
Customs tariff number	85369010000

Product Classification

UNSPSC	39121405
eCl@ss 10.0	27-40-02-01
eCl@ss 9.0	27-40-02-01
ETIM 9.0	EC000005
ETIM 10.0	EC000005
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 216-288

Documentation

Bid Text

216-288	11.09.2017	doc 24.50 KB	
216-288	19.02.2019	xml 2.80 KB	


CAD/CAE-Data

CAD data

2D/3D Models 216-288

Continued on next page

Installation Notes



A perfect gas-tight crimp – both electrically and mechanically reliable