Data Sheet | Item Number: 249-137

Test plug module; without locking device; modular; for 2-conductor terminal blocks; gray

https://www.wago.com/249-137



Color: gray

Notes

Safety Information	Middle pressure, 2.2 N per pole

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	500 V

Ratings per IEC/EN – Notes

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)

Ratings per IEC/EN 2

Ratings (note)	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)

General information

Test voltage	500 V
Test current	0.5 A

Physical data

Width	7 mm / 0.276 inches
Height	12 mm / 0.472 inches
Depth	25.1 mm / 0.988 inches
Module width	7 mm / 0.276 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.019 MJ
Weight	1.1 g

Commercial data

Product Group	2 (Terminal Block Accessories)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821868927
Customs tariff number	85366990990

Product Classification

UNSPSC	39121402
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 9.0	EC002555
ETIM 10.0	EC002555
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	b33b9467-f8a9-4db1-8165-6cd5fb8cd0db
SCIP notification number (Belgium)	05110c70-61f2-4a46-a617-6ad896e58ea6
SCIP notification number (Bulgaria)	7b2ad740-6ca4-4a69-b244-29722f7d0c36
SCIP notification number (Czech Republic)	56de8b48-47b8-483a-9a8a-df9f7f5ac2cc
SCIP notification number (Denmark)	5d07a681-1d3a-472c-b8ad-0c2e8d9305ac
SCIP notification number (Finland)	d437dea4-6dee-483d-9d9a-f7e14313af28
SCIP notification number (France)	186967e1-a093-417a-8fa5-6daa86e69ff0
SCIP notification number (Germany)	d7e004af-aed2-4025-ab4d-8e778d2f5475
SCIP notification number (Hungary)	34f3bcbf-7a65-48e9-91e6-0460b9b55e2a
SCIP notification number (Italy)	b52ed689-b804-4dd6-b0c2-2bcfbb641335
SCIP notification number (Netherlands)	6c2ccd93-80d1-4d52-813e-8cfe40149b93
SCIP notification number (Poland)	e47b79b1-79d0-4745-adad-465a33a1bea4
SCIP notification number (Romania)	85c103c2-76c2-4099-a44a-23e2eb569291
SCIP notification number (Sweden)	46e07948-bab3-4bc9-9223-a30d0c2d8f84

Continued on next page

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-137

Documentation

Bid Text

249-137	19.02.2019	xml 3.14 KB
249-137	17.08.2017	doc 24.00 KB

CAD/CAE-Data

CAD data

2D/3D Models 249-137

CAE data

WSCAD Universe 249-137

1 Compatible Products

1.1 Optional Accessories

1.1.1 Test and measurement


1.1.1.1 Testing accessories



Item No.: 210-136
Test plug; 2 mm Ø; with 500 mm cable; red


Installation Notes

Installation




Snapping individual modules together to assemble a multi-pole test plug module.

Testing



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 … 40 mm!



Testing after the conductors have been terminated.