Data Sheet | Item Number: 249-138

Test plug module; without locking device; modular; for 4-conductor terminal blocks; gray

https://www.wago.com/249-138



Color: gray

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	500 V

Ratings per IEC/EN – Notes

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)

Ratings per IEC/EN 2

Ratings (note)	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)

General information

Test voltage	500 V
Test current	0.5 A

Physical data

Width	8 mm / 0.315 inches
Height	12 mm / 0.472 inches
Depth	25.1 mm / 0.988 inches
Module width	8 mm / 0.315 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.02 MJ
Weight	1.3 g

Commercial data

Product Group	2 (Terminal Block Accessories)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454359973
Customs tariff number	85366990990

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 9.0	EC002555
ETIM 10.0	EC002555
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	49b6921b-e745-4d6a-8ddb-6b3f340417a1
SCIP notification number (Belgium)	50c873aa-ce13-4e30-ab4e-9adb59d94ded
SCIP notification number (Bulgaria)	c516e619-ab32-4af6-940d-597525c3081d
SCIP notification number (Czech Republic)	0865b9d0-1564-4972-816f-d53032665ef1
SCIP notification number (Denmark)	7bc54153-d8e9-452c-9d7a-687d508ee438
SCIP notification number (Finland)	6be4f7a4-129f-484a-a4b0-103da2af6b83
SCIP notification number (France)	0bd316cb-03d1-4234-bcf8-45f5572ec581
SCIP notification number (Germany)	6f2ba8d9-c1e3-4349-afac-95220f391089
SCIP notification number (Hungary)	4af9e7b7-693d-402c-a686-b557b400b255
SCIP notification number (Italy)	17fe9b05-3091-4a41-8cdf-4ed7e1c170fe
SCIP notification number (Netherlands)	1bf7fd6f-5723-455d-824b-90caf37ff4aa
SCIP notification number (Poland)	3df95b8e-68af-4906-8d33-889a86169935
SCIP notification number (Romania)	9dbfa58c-c2e9-47aa-98d1-3fc3489cff4e
SCIP notification number (Sweden)	ade9cabc-dde1-4c62-b145-15b12ab45ec9

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-138

 Continued on next page

Documentation

Bid Text

249-138	19.02.2019	xml 3.14 KB
249-138	18.08.2017	doc 24.00 KB

CAD/CAE-Data

CAD data

2D/3D Models 249-138

CAE data

WSCAD Universe
249-138

1 Compatible Products

1.1 Optional Accessories

1.1.1 Test and measurement


1.1.1.1 Testing accessories



Item No.: 210-136
Test plug; 2 mm Ø; with 500 mm cable; red


Installation Notes

Installation




Snapping individual modules together to assemble a multi-pole test plug module.

Testing



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 … 40 mm!



Testing after the conductors have been terminated.